

### Microwave Networks, Inc. (MNI) Microwave Equipment

Choose from the following Microwave Networks microwave equipment.

VENDOR	BRAND/MODEL	MSRP
	<b>MICROWAVE NETWORKS, INC. MICROWAVE</b>	
Communications International	MICROWAVE NETWORKS /J06NC2-155F-YN0-OXBL-C - Proteus MX, 06 GHz Gigabit Ethernet Radio, Non Protected, Split Mount, w/ GigE SFP, ACM, Licensed for 155 Mbps in 30 MHz Channel - High Power	\$10,013.00
Communications International	MICROWAVE NETWORKS /J06NC3-155F-YN0-OXBL-C - Proteus MX, 06 GHz Gigabit Ethernet Radio, Non Protected, Split Mount, w/ GigE SFP, ACM, Licensed for 155 Mbps in 30 MHz Channel - Ultra High Power	\$13,971.00
Communications International	MICROWAVE NETWORKS /J06PC2-155F-YN0-OXBL-C -Proteus MX, 06 GHz Gigabit Ethernet Radio, Hot Standby Protected, Split Mount, w/ GigE SFP, ACM, Licensed for 155 Mbps in 30 MHz Channel - High Power	\$20,473.00
Communications International	MICROWAVE NETWORKS /J06PC3-155F-YN0-OXBL-C -Proteus MX, 06 GHz Gigabit Ethernet Radio, Hot Standby Protected, Split Mount, w/ GigE SFP, ACM, Licensed for 155 Mbps in 30 MHz Channel - Ultra High Power	\$25,743.00
Communications International	MICROWAVE NETWORKS /J11NC2-155F-YN0-OXBL-C-Proteus MX, 11 GHz Gigabit Ethernet Radio, Non Protected, Split Mount, w/ GigE SFP, ACM, Licensed for 155 Mbps in 30 MHz Channel - High Power	\$9,664.00
Communications International	MICROWAVE NETWORKS /J11NC3-155F-YN0-OXBL-C- Proteus MX, 11 GHz Gigabit Ethernet Radio, Non Protected, Split Mount, w/ GigE SFP, ACM, Licensed for 155 Mbps in 30 MHz Channel - Ultra High Power	\$13,496.00
Communications International	MICROWAVE NETWORKS /J11PC2-155F-YN0-OXBL-C - Proteus MX, 11 GHz Gigabit Ethernet Radio, Hot Standby Protected, Split Mount, w/ GigE SFP, ACM, Licensed for 155 Mbps in 30 MHz Channel - High Power	\$19,710.00
Communications International	MICROWAVE NETWORKS /J11PC3-155F-YN0-OXBL-C -Proteus MX, 11 GHz Gigabit Ethernet Radio, Hot Standby Protected, Split Mount, w/ GigE SFP, ACM, Licensed for 155 Mbps in 30 MHz Channel - Ultra High Power	\$25,675.00
Communications International	MICROWAVE NETWORKS /J06NE2-155F-YN0-OXBL-C - Proteus MX, 06 GHz Gigabit Ethernet Radio, Non Protected, All Indoor, w/ GigE SFP, ACM, Licensed for 155 Mbps in 30 MHz Channel - High Power	\$17,881.00
Communications International	MICROWAVE NETWORKS /J06NE3-155F-YN0-OXBL-C - Proteus MX, 06 GHz Gigabit Ethernet Radio, Non Protected, All Indoor, w/ GigE SFP, ACM, Licensed for 155 Mbps in 30 MHz Channel - Ultra High Power	\$20,190.00
Communications International	MICROWAVE NETWORKS /J06PE2-155F-YN0-OXBL-C- Proteus MX, 06 GHz Gigabit Ethernet Radio, Hot Standby, All Indoor, w/ GigE SFP, ACM, Licensed for 155 Mbps in 30 MHz Channel - High Power	\$32,739.00
Communications International	MICROWAVE NETWORKS /J06PE3-155F-YN0-OXBL-C - Proteus MX, 06 GHz Gigabit Ethernet Radio, Hot Standby, All Indoor, w/ GigE SFP, ACM, Licensed for 155 Mbps in 30 MHz Channel - Ultra High Power	\$36,145.00

4450 US Highway 1  
Vero Beach, FL 32967  
888.275.4244 | ask4ci.com

*Authorized Microwave Networks, Inc. Reseller*

Communications International	MICROWAVE NETWORKS /J11NE2-155F-YN0-OXBL-C - Proteus MX, 11 GHz Gigabit Ethernet Radio, Non Protected, All Indoor, w/ GigE SFP, ACM, Licensed for 155 Mbps in 30 MHz Channel - High Power	\$18,175.00
Communications International	MICROWAVE NETWORKS /J11NE3-155F-YN0-OXBL-C - Proteus MX, 11 GHz Gigabit Ethernet Radio, Non Protected, All Indoor, w/ GigE SFP, ACM, Licensed for 155 Mbps in 30 MHz Channel - Ultra High Power	\$21,234.00
Communications International	MICROWAVE NETWORKS /J11PE2-155F-YN0-OXBL-C- Proteus MX, 11 GHz Gigabit Ethernet Radio, Hot Standby, All Indoor, w/ GigE SFP, ACM, Licensed for 155 Mbps in 30 MHz Channel - High Power	\$33,335.00
Communications International	MICROWAVE NETWORKS /J11PE3-155F-YN0-OXBL-C - Proteus MX, 11 GHz Gigabit Ethernet Radio, Hot Standby, All Indoor, w/ GigE SFP, ACM, Licensed for 155 Mbps in 30 MHz Channel - Ultra High Power	\$36,868.00

**Microwave**  
NETWORKS

# Proteus MX



MADE IN



U.S.A

4000 Greenbriar Dr., Stafford | Texas | USA 77477

☎ 1.281.263.6500 | 📞 1.281.263.6400 | Toll Free 1.888.225.6429 | [www.microwavenetworks.com](http://www.microwavenetworks.com)



## Intelligent Bandwidth for Evolving Networks

The Proteus MX is Microwave Networks' fourth generation TDM/ Ethernet hybrid backhaul radio. Microwave Networks designed the Proteus MX specifically for mission critical applications. It is available in two basic configurations.

- **The Proteus MX features** a robust design with total redundancy of all traffic and overhead channels with automatic switchover for the highest possible path reliability.
- **The Proteus MXD** is configured in a back-to-back repeater configuration for use in loop or route diversity networks where redundancy is provided through the use of multiple paths.

Together, there is an appropriate Proteus MX radio to fit almost any mission critical backhaul application.

Proteus MX offers mission critical carrier-class Ethernet along with native TDM in a single, feature rich, and flexible platform, allowing easy and cost effective migration from legacy TDM to Ethernet/IP networks.

Proteus MX features set it apart from other radios. Its flexible functionality offers high speed native Ethernet with Rapid Ring Protection, native TDM with native DS1 loop protection, and Adaptive Code and Modulation that optimizes throughput while protecting critical traffic. When configured for hot standby, the Proteus MX point-to-point radios incorporate active circuit redundancy of all data and overhead channels. An optional feature is AES encryption and FIPS 140-2 Level 2 module protection. Whether you're keeping pace with growing traffic demands, reconfiguring radio-link payload for new services, or adding cyber security and networking features, the Proteus MX is designed to adapt to your needs.

The convergence of voice, data, and video networks is transforming telecommunications systems. Microwave Networks is ready to help you with mission critical microwave and integrated cyber security and networking solutions.

- **True 1+1 Mission Critical redundancy in a Licensed Band backhaul radio**
- **Native TDM and Native Ethernet**
- **Easy Network Migration**
- **MPLS Compatible Native Ethernet**

# Effortless Migration from TDM to Ethernet/IP Networks

Available in a range of frequencies from 6 - 38 GHz, the Proteus MX radio supports mission critical reliability requirements in public safety, government, critical infrastructure, utilities, and mobile operator networks, including P25, DMR, and LTE networks.

Featuring native TDM and native Ethernet, the Proteus MX simplifies network migration, delivering new Ethernet/IP services while supporting TDM legacy equipment. Using the Proteus MX, native TDM has lower latency than encapsulated TDM over Ethernet, given the same path conditions. Low latency is essential for time sensitive applications.

In spur topologies using hot standby mode, the Proteus MX active circuit redundancy ensures mission critical network reliability. In ring network topologies the Proteus MXD back-to-back repeater configuration simplifies installation and reduces rack space requirements while providing self healing DS1 loop protection and Ethernet Rapid Ethernet Ring Protection for best network reliability and availability. The Proteus MX and Proteus MXD are available for indoor or split mount installation.

## Supporting Mission Critical Legacy, P25, DMR, and LTE Networks

### Features

- Native Ethernet and Native TDM
- 6,7,8,11,13,15,18,23,26, 38 GHz
- 6 to 350 Mbps throughput
- 10/100/1000 BaseT Ethernet
- 4 to 128 DS1; 1 to 4 DS3; OC-4/STM-1
- 1+0, 1+1, 1+0 Repeater, Space Diversity
- Hot Standby with redundancy of all active components
- Back-to-back Repeater Configuration
- SHARP loop protected DS1
- RRP+ loop protected Ethernet
- All Indoor or Split Mount configurations
- VLAN, IEEE 802.1p & 802.1Q
- Hitless Adaptive Code Modulation (ACM)
- Software selected bandwidth, modulation, capacity, frequency, and output power
- Chart recorder, spectrum analyzer, and constellation viewer for link monitoring and diagnostics
- AES 128, 196, and 256 bit Encryption
- FIPS 140-2 Level 2 validation
- CyberShield cyber security integration
- Native TDM and MPLS compatible Native Ethernet

## Signal Processing Unit (SPU)

<b>Data Line Interface</b>	32xDS1 (2 x 64-pin Telco) ; 4xDS3 (8 x 75-ohm BNC) ; 155 Mbps (optical LC; SM or MM)
<b>Gigabit Ethernet</b>	4 x 10/100/1000 BaseT Gigabit Ethernet ports or 3 x 10/100/1000BaseT + 1 x 1000BaseT Optical (SFP)
<b>FEC &amp; Coding</b>	Low Density Parity Check (LDPC)
<b>Digital Engineering Orderwire</b>	Integrated Digital or External RS-422 Digital O/W; 2 x RJ-45 jacks for daisy chain/external connection
<b>Auxiliary Data Channels</b>	2 x RS-232 up to 19.2 kbps async; 1 x RS-422 at 64 kbps async (not available if EOW configured)
<b>Relay Alarm Outputs</b>	4 x Form-C relays, NO & NC contacts (software mapped)
<b>External Inputs</b>	6 x TTL floating inputs
<b>Configuration Memory</b>	Removable SD FLASH memory card (store link/terminal data & performance history)
<b>Dimensions (h x w x d)</b>	Dimensions (h x w x d) 3.5 in. x 19 in. x 11.2 in. (2RU)
<b>Weight</b>	18 lbs.
<b>Temperature</b>	+23° F to +122° F (-5° C to +50° C)
<b>Humidity</b>	Up to 95% non-condensing
<b>Input Power</b>	+/- 19 to +/- 60 volts DC

## Management

<b>Protocol</b>	SNMPv3 (also supports SNMP v1 and v2)
<b>Authentication</b>	RADIUS (client)
<b>Element Manager (EM)</b>	Java based management software; access radio through any local/remote management
<b>NMS Interface</b>	2 x RJ-45; 10/100/1000 BaseT; for access and bridging, configurable for in-band or out-of-band operation
<b>Command Line Interface</b>	RS-232 serial DB-9; for local VT-100 type interface or TELNET access
<b>Modem (PPP)</b>	RS-232 serial DB9; for dial-up access
<b>Management IP Routing</b>	RIP2 dynamic routing or static route maps
<b>NMS Compatibility</b>	OpenView™, NetView™, SNMPc™ or other SNMP-based NMS; Motorola MOSCAD; Motorola UEM

## Standards Compliance

<b>Safety</b>	EN 60950
<b>EMI/EMC</b>	EN 301 489; EN 300 385
<b>RF</b>	EN 302 217-2
<b>MAC QoS</b>	IEEE P802.1p
<b>VLAN</b>	IEEE 802.1Q
<b>Power Supply</b>	EN 300 132-2
<b>Storage</b>	ETS 300 019-1-1 (Class 1.1E)
<b>Transport</b>	ETS 300 019-1-2 (Class 2.1E)
<b>Environmental - SPU</b>	ETS 300 019-1-3 (Class 3.1E)

## System Specification

Operating Frequencies (GHz)	T/R Spacing (MHz)	
5.925 - 7.125	All FCC, ETSI and ITU spacings	
7.125 - 7.900	154, 160, 161, 168, 196, 245, 300	
7.900 - 8.500	119, 126, 151.614, 208, 266, 311.32	
10.70 - 11.70	490, 500, 530	
12.75 - 13.25	200, 225, 266	
14.40 - 15.35	315, 322, 420, 475, 490, 640, 644, 728	
17.70 - 19.70	1008, 1010, 1092.5, 1120, 1560	
21.20 - 23.60	1008, 1200, 1232	
24.20 - 26.50	800, 1008	
37.00 - 40.00	700, 812, 1260	
<b>Frequency Stability</b>	+/- 10 ppm (.001 %)	
<b>RX overload</b>	- 20 dBm for < 10 <sup>-6</sup> BER	
<b>Residual BER</b>	Better than 10 <sup>-12</sup>	
<b>Altitude</b>	15,000 ft.	
<b>Power Consumption (max.)</b>	Split-mount: 80 W non-protected, 166 W protected	All-indoor: 120 W non-protected, 250 W protected

## RF Unit and Antenna

	Split Mount Outdoor Unit (ODU)	All Indoor RF Unit
<b>Frequencies</b>	6, 7, 8, 11, 13, 15, 18, 23, 26 and 38 GHz	6, 7, 8, and 11 GHz
<b>Configuration</b>	Split-mount; SPU inside / ODU outside	All indoor rack mounted
<b>Dimensions</b>	10.2 in. diameter; 5.9 in. deep	7.0 in. x 19 in. x 11.5 in. (4RU)
<b>Weight</b>	11 lbs.	27 lbs.
<b>Temperature</b>		
<b>Full Performance</b>	-27°F to 131°F (-33° C to +55° C)	+23° F to +122° F (-5° C to +50°
<b>Operational</b>	-67°F to 131°F (-55° C to +55° C)	
<b>Humidity</b>	Up to 100%	95 % (no condensation)
<b>Output Power Control</b>	-4 dBm to Max	+8 dBm to Max
<b>SPU to ODU Interface</b>	TNC female (SPU); N-type female (ODU)	
<b>Recommended Cable</b>	RG-8A/U equivalent; 50 Ohms	Elliptical Waveguide
<b>Max. SPU to ODU distance</b>	850 feet using RG-8A/U	
<b>Intermediate Frequencies</b>	SPU to ODU - 350 MHz; ODU to SPU - 140 MHz	
<b>Antenna Diameter (ft.)</b>	Category A - 1,2,3,4,6,8,10, 12	
<b>Antenna Connection Options</b>	Integrated push-fit or remote mounting	6 GHz: CMR-137F, CPR-137F; 7/8 GHz: UG-51/U; 11 GHz: CPR-90, UG-39/U

Specifications are subject to change without notice.