



# 301MD RUGGED 2-IN-1 MEDICAL TABLETS

#### Slim, Antimicrobial, UL60601-1 Certified Tablet for Efficient Operations

The DT Research Rugged 2-in-1 Medical Tablets feature the integration of brilliant capacitive touch screens and high performance, energy-efficient Intel® Core™ i series processors within slim, lightweight, durable packages. With built-in front and back cameras, Wi-Fi, Bluetooth as well as optional data capture modules, these medical tablets offer health professionals effective tools to monitor, record and retrieve patient information.





#### **Features**

- 10.1" inch multi-touch screen, 1000 nits, digital pen support
- Intel® 8<sup>th</sup> or 10<sup>th</sup> Generation Core™ i processor
- Microsoft® Windows® 10 IoT Enterprise or Ubuntu operating system
- Docking keyboard option for 2-in-1 (tablet/ laptop) applications
- UL60601-1 certified with antimicrobial enclosure
- IP65 and MIL-STD-810G certified
- NIST compliant BIOS available
- Hot swappable battery pack
- Built-in front and backcameras
- Built-in smart card/CAC reader

### **Major Options**

- Barcode scanner
- Single/dual frequency NFC/RFID reader
- 4G LTE/AWS

## **Specifications**



Model	301MD
System	
СРИ	Intel® Core™ i5-8250U, Quad-Core, 1.6GHz (up to 3.4GHz) Intel® Core™ i7-8550U, Quad-Core, 1.8GHz (up to 4.0GHz) Intel® Core™ i7-10710U, Hexa-Core, 1.1GHz (up to 4.7GHz)
RAM	8GB to 16GB
Storage	256GB to 512GB Flash
Operating System	Microsoft® Windows® 10 IoT Enterprise or Ubuntu
NIST Compliance	NIST compliant BIOS available
Display	10.1" LED-backlight, high-brightness (1000 nits) screen with capacitive touch, outdoor viewable
Display Resolution	1920 x 1200
Buttons	1 power button, 2 brightness control buttons, 5 programmable buttons
Speaker	Built-in speaker
Camera	Full-HD front camera and 8 megapixel back camera
Network Interface	
WLAN	Wi-Fi 802.11ac, 2.4GHz/ 5GHz dual band
Bluetooth	Bluetooth 4.2 LE
I/O Ports	
USB Ports	USB 3.0 x 1, USB Type C x 1 (data transmitting and charging)
Headset Jack	1 (3.5mm)
Ethernet Port	Ethernet 10/ 100/ 1000MB Base-TLAN
Smart Card/ CAC Reader	Full-slot, reads ISO 7816 T=0, T=1; 1.8/3/5V smart card
Mechanical and Environmental	
AC/DC Adapter	Input: 100-240V AC; Output: 20V DC,3A
Battery Pack	Hot swappable battery, 11.4V, 5400mAh
Enclosure	ABS + PC plastics and magnesium-aluminum alloy; antimicrobial enclosure
Dimensions (H x W x D)	7.8 x 11 x 0.86 in/ 198 x 280 x 21.9 mm
Weight	3.1 lbs/ 1.4 kg
Durability	IP65 and MIL-STD-810G certified
Regulatory	FCC Class B, UL60601-1, CE, RoHS compliant
Temperature	Operation: -10°C to 60°C (-14°F to 140°F), optional -30°C to 60°C (-22°F to 140°F) Storage: -55°C to 70°C (-67°F to 158°F)
Humidity	0% – 90% non-condensing
<b>Major Options</b>	
Barcode Scanner	2D scanner, reads 1D also

Barcode Scanner	2D scanner, reads 1D also
NFC/RFID Reader	HF 13.56MHz, ISO standard 15693, 14443A(B) & 18000-3 mode-1

4G LTE/AWS **Mobile Broadband** 

Accessories
- Digital Pen - Docking Keyboard - Desktop Charging Cradle - Wall/Vehicle Mount Cradle

<sup>\*</sup> Specifications subject to change without notice.

3-SlotBattery Holster















