

Axis Communications

Product Name	Product Number US	Product Description	MSRP
2N AC - BOX PC	01672-001	The 2N® Access Commander Box is an ultra compact computer with pre-installed 2N® Access Commander – software designed for access control configuration and 2N devices management. It is ready to use, plug and play solution which requires only a power supply and an Ethernet cable to be connected to the computer. It is perfectly optimised for small and medium-size installations with up to 50 2N IP intercoms/Access Units and 1000 users. Free license 01372-001 for +5 devices (to be requested at the TechSupport) is included in the product price.	\$ 515.00
2N AU - RFID 125kHz	01365-001	2N Access Unit - RFID 125kHz. Comes without frame and/or flush box - those are from IP Verso.	\$ 400.00
2N AU - RFID 13.56MHz NFC READY	01366-001	2N Access Unit - RFID 13.56MHz NFC ready. Comes without frame and/or flush box - those are from IP Verso.	\$ 400.00
2N AU - FINGERPRINT	01367-001	2N Access Unit - Fingerprint (9137423E USB reader needed for user enrollment) Comes without frame and/or flush box - those are from IP Verso.	\$ 640.00
2N AU - BLUETOOTH	01368-001	2N Access Unit - Bluetooth. Comes without frame and/or flush box - those are from IP Verso.	\$ 440.00
2N AU - TOUCH KEYPAD	01370-001	2N Access Unit - Touch keypad Comes without frame and/or flush box - those are from IP Verso.	\$ 320.00
2N AU - RJ45 CONNECTOR CABLE	01371-001	2N Access Unit - RJ45 connector cable	\$ 10.00
2N AU 2.0 COMBI BLUETOOTH RFID NFC SEC	01851-001	2N Access Unit 2.0 – Bluetooth & RFID 125kHz, 13.56MHz secured card reader, reading PACS ID + UID, NFC ready, support of HID iClass secured. The unit is equipped with the RJ45 connector, no need to use 01371-001 2N AU - RJ45 CONNECTOR CABLE accessories anymore.	\$ 811.00
2N AU 2.0 COMBI KEYPAD RFID NFC SEC	01852-001	2N Access Unit 2.0 – Touch keypad & RFID 125kHz, 13.56MHz secured card reader, reading PACS ID + UID, NFC ready, support of HID iClass secured. The unit is equipped with the RJ45 connector, no need to use 01371-001 2N AU - RJ45 CONNECTOR CABLE accessories anymore.	\$ 696.00
2N AU 2.0 COMBI RFID 125kHz 13MHz NFC SEC	01850-001	2N Access Unit 2.0 - RFID 125kHz, 13.56MHz secured card reader, reading PACS ID + UID, NFC ready, support of HID iClass secured. The unit is equipped with the RJ45 connector, no need to use 01371-001 2N AU - RJ45 CONNECTOR CABLE accessories anymore.	\$ 582.00
2N AU - RFID 125kHz 2G	02137-001	2N Access Uni 2.0 - RFID 125kHz, second generation with better reading distance/time	\$ 410.00
2N AU 2.0 RFID 125k/13M NFC SEC 2G	02146-001	2N Access Unit - RFID 125kHz/13.56MHz NFC, second generation with better reading distance/time, reads PACS ID	\$ 582.00
2N AU 2.0 - 13.56MHz NFC SEC, 2G	02142-001	2N Access Unit - RFID 13,56MHz NFC secured (reads PACS ID), second generation with better reading distance/time	\$ 450.00

2N AU 2.0 - RFID 13.56MHz NFC,2G	02143-001	2N Access Uni 2.0 - RFID 13.56MHz, second generation with better reading distance/time	\$ 400.00
2N AU 2.0 Touch keypad	02262-001	2N Access Unit 2.0 touch keypad	\$ 320.00
2N AU 2.0 Fingerprint reader	02263-001	2N Access Unit 2.0 Fingerprint reader	\$ 640.00
2N IP AUDIO KIT - MIC & SPK SET	01478-001	2N IP Audio Kit - microphone & speaker set	\$ 40.00
2N IP AUDIO KIT - BUTTON	01479-001	2N IP Audio Kit - stainless steel backlit button	\$ 30.00
2N IP AUDIO KIT	01526-001	2N IP Audio Kit – SIP module for embedded installation	\$ 322.00
2N IP BASE - CAM BLACK	01357-001	2N IP Base - camera, black frame	\$ 665.00
2N IP BASE - 125kHz RFID	01358-001	2N IP Base - 125kHz RFID card reader	\$ 90.00
2N IP BASE - 13.56MHz RFID	01359-001	2N IP Base - 13.56MHz RFID card reader, reads UID	\$ 135.00
2N IP BASE - BACKPLATE	01360-001	2N IP Base - backplate for easier surface installation	\$ 60.00
2N IP BASE DOUBLE BUTTON	02017-001	2N IP Base double button spare part	\$ 25.00
2N IP Base Single button	02228-001	2N IP Base - single button spare part	\$ 23.00
2N IP FORCE - 1 BTN, HD CAM, PICT.	01334-001	2N IP Force - 1 button + HD camera + pictograms + 10W speaker, card reader ready	\$ 1,335.00
2N IP FORCE - 1 BTN, PICT.	01335-001	2N IP Force - 1 button + pictograms + 10W speaker, card reader ready	\$ 990.00
2N IP FORCE - 1 BTN	01336-001	2N IP Force - 1 button + 10W speaker	\$ 940.00
2N IP FORCE - 1 BTN + HD CAM	01337-001	2N IP Force - 1 button + HD camera + 10W speaker	\$ 1,300.00
2N IP FORCE - 1 BTN + KEYPAD	01338-001	2N IP Force - 1 button + keypad + 10W speaker	\$ 1,050.00
2N IP FORCE - 1 BTN + HD CAM + KPD	01339-001	2N IP Force - 1 button + HD camera + keypad + 10W speaker	\$ 1,310.00
2N IP FORCE - 2 BTN + HD CAM	01340-001	2N IP Force - 2 buttons + HD camera + 10W speaker, card reader ready	\$ 1,315.00
2N IP FORCE - 2 BTN	01341-001	2N IP Force - 2 buttons + 10W speaker, card reader ready	\$ 960.00
2N IP FORCE - 4 BTN	01342-001	2N IP Force - 4 buttons + 10W speaker	\$ 1,040.00
2N IP FORCE - 4 BTN + HD CAM	01343-001	2N IP Force - 4 button + HD camera + 10W speaker	\$ 1,325.00
2N IP FORCE - 125kHz RFID	01344-001	2N IP Force - 125kHz card reader. Includes Wiegand interface, 2 logical inputs, 2 output relays and tamper switch.	\$ 127.00
2N IP FORCE - SAFETY SCREWS	01345-001	2N IP Force - safety screws, torx with pin	\$ 12.00
2N IP FORCE - 13.56MHZ SEC RFID	01730-001	2N IP Force - 13.56MHz secured card reader, NFC ready, Reads UID + PACS ID, support of HID iClass secured. Includes Wiegand interface, 2 logical inputs, 2 output relays and tamper switch	\$ 295.00
2N IP FORCE TORX SCREW BLACK	01735-001	2N IP Force Torx 4 screws black for the front panel - 5 packages of screws	\$ 21.00
2N IP FORCE FRAME	01734-001	2N IP Force Frame for the main unit - 1 pc	\$ 30.00
2N IP FORCE PANEL4 BUTTONS	01736-001	2N IP Force front panel with 4 buttons - 1pc	\$ 130.00
2N IP FORCE PANEL 1 BUTTON	01737-001	2N IP Force front panel with 1 button - 1pc	\$ 92.00
2N IP FORCE PANEL 1 BTN PICTOGRAMS	01738-001	2N IP Force front panel with 1 button and pictograms -	\$ 112.00
2N IP FORCE PANEL 1 BTN KEYPAD READY	01739-001	2N IP Force front panel with 1 button ready for keypad - 1pc	\$ 95.00

2N IP FORCE PANEL 2 BTN CARD READER	01740-001	2N IP Force front panel with 2 buttons ready for card reader - 1pc	\$ 120.00
2N IP FORCE/SAFETY - FLUSH BOX	01348-001	2N IP Force and Safety - Brick flush mounting box	\$ 95.00
2N IP FORCE/SAFETY - PLASTER BOX	01349-001	2N IP Force and Safety - Plasterboard flush mounting box	\$ 85.00
2N IP FORCE/SAFETY - ADD.SWITCH	01350-001	2N IP Force and Safety - Additional switch + Tamper switch.	\$ 55.00
2N IP FORCE/SAFETY - GOOSENECK	01351-001	2N IP Force and Safety - Gooseneck stand, height 120cm/47in	\$ 253.00
2N IP FORCE/SAFETY - INST. ADAPTER	01352-001	2N IP Force and Safety - Installation adapter for Code Blue and Talkaphone	\$ 120.00
2N IP FORCE /SAFETY - DBL GOOSENECK	01550-001	2N IP Force and Safety - Gooseneck stand double, 45" / 80"	\$ 550.00
2N IP FORCE SAFETY SET OF BUSHINGS	01733-001	2N IP Force and Safety set of bushing for ethernet cable -5 pcs	\$ 62.00
2N IP FORCE SECURE DOOR	01976-001	2N IP Force Secure Door set - contains additional switch + tamper (01350-001) and Security Relay (01386-001)	\$ 110.00
2N IP FORCE KEYPAD	01873-001	2N IP Force keypad - 1pc	\$ 90.00
2N IP SAFETY - 1 BTN	01353-001	2N IP Safety - 1 button + 10W speaker	\$ 975.00
2N IP SAFETY - 2 BTN	01354-001	2N IP Safety - 2 buttons + 10W speaker	\$ 1,000.00
2N IP SAFETY - RED BTN	01355-001	2N IP Safety - red emergency button + 10W speaker	\$ 975.00
2N IP SAFETY - FRAME	01356-001	2N IP Safety - metal frame (orange color)	\$ 35.00
2N IP SAFETY PANEL 1 BUTTON	01870-001		\$ 38.00
2N IP SAFETY PANEL INFO/SOS	01871-001		\$ 43.00
2N IP SAFETY TORX SCREWS	01872-001		\$ 15.00
2N IP SAFETY BLUE BUTTON	01869-001	2N IP Safety quick dial button with blue backlight - 5pcs	\$ 220.00
2N IP SOLO - FLUSH MOUNT	01300-001	2N IP Solo - flush mount	\$ 1,031.00
2N IP SOLO - SURFACE MOUNT	01301-001	2N IP Solo - surface mount	\$ 1,010.00
2N IP SOLO - SURFACE MOUNT BLACK	01302-001	2N IP Solo - surface mount, black	\$ 1,010.00
2N IP SOLO - FLUSH MOUNT BLACK	01303-001	2N IP Solo - flush mount, black	\$ 1,031.00
2N IP SOLO - FLUSH BACKBOX	01304-001	2N IP Solo - backbox for flush installation	\$ 25.00
2N IP SOLO - BACKPLATE	01305-001	2N IP Solo - backplate for easier surface installation	\$ 51.00
2N IP SOLO GLASS MOUNT	02078-001	Backplate for glass mount, has to be shipped together with 01305-001 backplate	\$ 20.00
2N IP SOLO SURFACE BLACK WO CAMERA	02202-001	2N IP Solo black without camera for surface mount. The intercom is suitable for residential and commercial installation where camera is not required and IP Verso without camera has too big footprint, usually indoor (however intercom has IP54 rating and its perfectly suitable for outdoor installation).	\$ 500.00
2N IP SOLO SURFACE WO CAMERA	02203-001	2N IP Solo without camera for surface mount. The intercom is suitable for residential and commercial installation where camera is not required and IP Verso without camera has too big footprint, usually indoor (however intercom has IP54 rating and its perfectly suitable for outdoor installation).	\$ 500.00

2N IP SOLO FLUSH BLACK WO CAMERA	02204-001	2N IP Solo black without camera for flush mount. The intercom is suitable for residential and commercial installation where camera is not required and IP Verso without camera has too big footprint, usually indoor (however intercom has IP54 rating and its perfectly suitable for outdoor installation).	\$ 530.00
2N IP SOLO FLUSH WO CAMERA	02205-001	2N IP Solo without camera for flush mount. The intercom is suitable for residential and commercial installation where camera is not required and IP Verso without camera has too big footprint, usually indoor (however intercom has IP54 rating and its perfectly suitable for outdoor installation).	\$ 530.00
2N IP UNI - 1 BTN	01361-001	2N IP Uni - 1 button	\$ 405.00
2N IP UNI - 2 BTN	01362-001	2N IP Uni - 2 buttons	\$ 420.00
2N IP UNI - 1 BTN, PICTOGRAMS	01363-001	2N IP Uni - 1 button, pictograms	\$ 425.00
2N IP UNI - SURFACE MOUNT BOX	01364-001	2N IP Uni - surface mount box	\$ 80.00
2N IP UNI MIC GASKET	01862-001		\$ 23.00
2N IP UNI FRONT PANEL 1 BUTTON	01864-001		\$ 40.00
2N IP UNI PANEL 2 BUTTON	01865-001		\$ 42.00
2N IP UNI PANEL 1 BUTTON	01866-001		\$ 41.00
2N IP UNI FRONT SCREWS	01867-001		\$ 25.00
2N IP UNI SPEAKER CABLE	01861-001	2N IP Uni speaker with cable, 4 pcs	\$ 42.00
2N IP UNI MICROPHONE	01863-001	2N IP Uni microphone with cable, 10 pcs	\$ 45.00
2N IP UNI FLUSH BOX	01868-001	2N IP Uni flush box for in-wall installation, 1 pc	\$ 27.00
2N IP VARIO - SPARE SINGLE BUTTON	01329-001	2N IP Vario - spare single button	\$ 4.00
2N IP VARIO - SPARE DOUBLE BUTTON	01330-001	2N IP Vario - spare double button	\$ 4.00
2N IP VARIO - SPARE INFO COVER	01331-001	2N IP Vario - spare info cover	\$ 10.00
2N IP VARIO - ADDITIONAL SWITCH	01332-001	2N IP Vario - Additional switch including one NO/NC output relay	\$ 30.00
2N IP VARIO - 125kHz RFID	01333-001	2N IP Vario - 125kHz RFID card reader. Includes Wiegand interface, 2 logical inputs, 2 output relays.	\$ 100.00
YEALINK SIP-T58A BUTTON EXTENDER	01741-001	Button extedern for Yealink T-58A SIP phone	\$ 250.00
2N IP VARIO TUBE	01882-001		\$ 15.00
2N IP VARIO TUBE SEALING	01883-001		\$ 12.00
2N IP VARIO COVER 1 BUTTON	01884-001		\$ 40.00
2N IP VARIO COVER 1 BUTTON/KEYPAD	01885-001		\$ 40.00
2N IP VARIO COVER 3 BUTTON/READER	01886-001		\$ 42.00
2N IP VARIO COVER 3 BUTTON/KEYPAD	01887-001		\$ 42.00
2N IP VARIO COVER 6 BUTTON/READER	01888-001		\$ 44.00
2N IP VARIO COVER 6 BUTTON/KEYPAD	01889-001		\$ 44.00

2N IP VARIO MICROPHONE	01879-001	2N IP Vario microphone with cable, 5 pcs	\$ 15.00
2N IP VARIO WAGO TERMINAL	01880-001	2N IP Vario wago terminal for ethernet and lock connection, 5 pcs	\$ 20.00
2N IP VARIO KEYPAD	01881-001	2N IP Vario keypad, 1 pc	\$ 20.00
2N IP VARIO SPEAKER	01878-001	2N IP Vario speaker with holder and sealing, 5 pcs	\$ 25.00
2N IP VARIO COVER 6 BUTTON/DISPLAY	01890-001	2N IP Vario front metal cover with 6 button and display cut-out, 1 pc	\$ 44.00
2N IP VARIO COVER 8 BTN EXTENDER	01891-001	2N IP Vario front metal cover for 8 button extender, 1 pc	\$ 44.00
2N IP VARIO COVER 16 BTN EXTENDER	01892-001	2N IP Vario front metal cover for 16 button extender, 1 pc	\$ 44.00
2N IP VARIO BACK PANEL	01893-001	2N IP Vario backbox, black plastic chassis, 5 pcs	\$ 25.00
2N IP VARIO FRONT 1 BUTTON COVER	01894-001	2N IP Vario plastic front cover for 1 button, 1 pc	\$ 30.00
2N IP VARIO FRONT 1 BUTTON KEYPAD	01895-001	2N IP Vario plastic front cover for 1 button and keypad, 1 pc	\$ 75.00
2N IP VARIO FRONT 3 BUTTON COVER	01896-001	2N IP Vario front plastic cover for 3 buttons, 1 pc	\$ 30.00
2N IP VARIO FRONT 3 BUTTON KEYPAD	01897-001	2N IP Vario front plastic cover for 3 buttons and keypad	\$ 75.00
2N IP VARIO FRONT 6 BUTTON COVER	01898-001	2N IP Vario front plastic panel for 6 buttons, 1 pc	\$ 45.00
2N IP VARIO FRONT 6 BUTTON KEYPAD	01899-001	2N IP Vario plastic front cover with 6 buttons and keypad	\$ 90.00
2N IP VARIO CAMERA SUPPORT	01900-001	2N IP Vario plastic camera support, 5 pcs	\$ 8.00
2N IP VARIO CAMERA HOLDER	01901-001	2N IP Vario plastic camera holder, 5 pcs	\$ 8.00
2N IP VARIO CAMERA COVER	01902-001	2N IP Vario camera cover, 5 pcs	\$ 10.00
2N IP VARIO CAMERA BLIND COVER	01903-001	2N IP Vario cover for w/o camera version, 5 pcs	\$ 10.00
2N IP VARIO - EXTENDER 8 BTN	01320-001	2N IP Vario - extender 8 single buttons	\$ 160.00
2N IP VARIO - EXTENDER 8 DBTN	01321-001	2N IP Vario - extender 8 double buttons	\$ 190.00
2N IP VARIO - INFOPANEL	01322-001	2N IP Vario - infopanel	\$ 130.00
2N IP VARIO - 1M ROOF	01323-001	2N IP Vario - 1 module roof	\$ 65.00
2N IP VARIO - 2M ROOF	01324-001	2N IP Vario - 2 modules roof	\$ 75.00
2N IP VARIO - 1M FLUSH BOX	01325-001	2N IP Vario - 1 module flush box	\$ 70.00
2N IP VARIO - 2M FLUSH BOX	01326-001	2N IP Vario - 2 modules flush box	\$ 75.00
2N IP VARIO - 1M FLUSH BOX + ROOF	01327-001	2N IP Vario - 1 modules flush box and roof	\$ 120.00
2N IP VARIO - 2M FLUSH BOX + ROOF	01328-001	2N IP Vario - 2 modules flush box and roof	\$ 140.00
2N IP VARIO - 1 BTN + CAMERA	01313-001	2N IP Vario - 1 button + camera	\$ 880.00
2N IP VARIO - 3 BTN + CAMERA	01314-001	2N IP Vario - 3 buttons + camera	\$ 890.00
2N IP VARIO - 3x2 BTN + CAMERA	01315-001	2N IP Vario - 3x2 buttons + camera	\$ 910.00
2N IP VARIO - 1 BTN + KPD + CAMERA	01316-001	2N IP Vario - 1 button + keypad + camera	\$ 950.00
2N IP VARIO - 3x2 BTN + KPD + CAM	01318-001	2N IP Vario - 3x2 buttons + keypad + camera	\$ 980.00
2N IP VARIO - 3x2BTN+ KPD+DISP+CAM	01319-001	2N IP Vario - 3x2 buttons + keypad + display + camera	\$ 1,450.00
2N IP VARIO - 3 BTN + KPD + CAMERA	01317-001	2N IP Vario - 3 buttons + keypad + camera	\$ 960.00

2N IP VARIO - 1 BTN	01306-001	2N IP Vario - 1 button	\$ 555.00
2N IP VARIO - 3 BTN	01307-001	2N IP Vario - 3 buttons	\$ 570.00
2N IP VARIO - 3X2 BTN	01308-001	2N IP Vario - 3x2 buttons	\$ 585.00
2N IP VARIO - 1 BTN + KEYPAD	01309-001	2N IP Vario - 1 button + keypad	\$ 600.00
2N IP VARIO - 3 BTN + KEYPAD	01310-001	2N IP Vario - 3 buttons + keypad	\$ 615.00
2N IP VARIO - 3X2 BTN + KEYPAD	01311-001	2N IP Vario - 3x2 buttons + keypad	\$ 630.00
2N IP VARIO - 3X2 BTN + KPD + DISP	01312-001	2N IP Vario - 3x2 buttons + keypad + display	\$ 1,165.00
2N IP VERSO - INFOPANEL	01252-001	2N IP Verso - Infopanel	\$ 100.00
2N IP VERSO - KEYPAD	01253-001	2N IP Verso - Keypad	\$ 239.00
2N IP VERSO - KEYPAD BLACK	01254-001	2N IP Verso - Keypad, black	\$ 239.00
2N IP VERSO - RFID 125kHz	01255-001	2N IP Verso - RFID 125kHz card reader	\$ 132.00
2N IP VERSO - I/O	01257-001	2N IP Verso - 2 inputs and 2 output relays. This module is installed beneath other modules.	\$ 60.00
2N IP VERSO - 5 BUTTONS	01258-001	2N IP Verso - 5 buttons	\$ 130.00
2N IP VERSO - WIEGAND	01259-001	2N IP Verso - Wiegand. This module is installed beneath other modules.	\$ 90.00
2N IP VERSO - TAMPER SWITCH	01260-001	2N IP Verso - Tamper switch. This module is installed beneath other modules.	\$ 39.00
2N IP VERSO - BLIND PANEL	01261-001	2N IP Verso - Blind panel	\$ 24.00
2N IP VERSO - RFID 13MHz NFC	01262-001	2N IP Verso - RFID 13MHz card reader NFC ready	\$ 207.00
2N IP VERSO - INDUCTION LOOP	01263-001	2N IP Verso - Induction loop	\$ 225.00
2N IP VERSO - BLUETOOTH	01266-001	2N IP Verso - Bluetooth	\$ 310.00
2N IP VERSO - EXTENSION CABLE 1M	01267-001	2N IP Verso - Extension cable 1m	\$ 19.00
2N IP VERSO - EXTENSION CABLE 3M	01268-001	2N IP Verso - Extension cable 3m	\$ 20.00
2N IP VERSO - BLIND BUTTON	01270-001	2N IP Verso - Blind button. Covers one button, on the main unit or 5 button module.	\$ 22.00
2N IP VERSO - MAIN WO CAMERA	01271-001	2N IP Verso - Main unit without camera	\$ 528.00
2N IP VERSO - MAIN WO CAMERA BLACK	01272-001	2N IP Verso - Main unit without camera, black	\$ 528.00
2N IP VERSO - MAIN W CAMERA	01273-001	2N IP Verso - Main unit with camera	\$ 995.00
2N IP VERSO - MAIN W CAMERA BLACK	01274-001	2N IP Verso - Main unit with camera, black	\$ 995.00
2N IP VERSO - TOUCH DISPLAY	01275-001	2N IP Verso - Touch display	\$ 770.00
2N IP VERSO - TOUCH KEYPAD	01277-001	2N IP Verso - Touch keypad	\$ 168.00
2N IP VERSO - FINGERPRINT	01276-001	2N IP Verso - Fingerprint	\$ 532.00
2N IP VERSO - EXTENSION CABLE 5M	01269-001	2N IP Verso - Extension cable 5m	\$ 26.00
2N IP VERSO - IND.LOOP ANTENNA	01265-001	2N IP Verso - Induction loop external antenna for wider coverage area	\$ 95.00
2N IP VERSO BLIND BUTTON BLACK	01523-001	2N IP Verso - Blind button. Covers one button, on the main unit or 5 button module. Black	\$ 22.00

2N IP VERSO COMBI BLUETOOTH RFID SEC.	01639-001	2N IP Verso – Bluetooth & RFID reader (125kHz, secured 13.56MHz UID+PACS ID, NFC), support of HID iClass secured.	\$ 644.00
2N IP VERSO COMBI KEYPAD RFID SEC.	01638-001	2N IP Verso – Touch keypad & RFID reader (125kHz, secured 13.56MHz UID+PACS ID, NFC), support of HID iClass secured.	\$ 548.00
2N IP VERSO - RFID 13MHz NFC SEC	01712-001	2N IP Verso - RFID 13.56MHz secured card reader, reading PACS ID + UID, NFC ready, support of HID iClass secured.	\$ 300.00
2N LTE VERSO - MAIN W CAMERA	01792-001	LTE intercom - no wired data connection, connects to the network via LTE. Requires data LTE SIM card (MicroSIM size) and external power supply such as 01435-001. The internal antenna occupies position of one module, if you intend to use additional modules with the main unit, use the external antenna 01943-001.	\$ 1,165.00
2N LTE VERSO - MAIN W CAMERA BLACK	01791-001	LTE intercom - no wired data connection, connects to the network via LTE. Requires data LTE SIM card (MicroSIM size) and external power supply such as 01435-001. The internal antenna occupies position of one module, if you intend to use additional modules with the main unit, use the external antenna 01943-001.	\$ 1,165.00
2N LTE VERSO EXTERNAL ANTENNA	01943-001	Accessories for 2N LTE Verso for places with poor LTE coverage.	\$ 25.00
2N IP VERSO SECURE DOOR	01975-001	2N IP Verso Secure Door set - contains I/O module (01257-001), tamper switch (01260-001) and Security Relay (01386-001)	\$ 151.00
2N IP VERSO WEDGE FOR 2 MODULES	01940-001	2N IP Verso and LTE Verso 2 module wedge backplate, 25°, helps to cover blind spots of the camera	\$ 32.00
2N IP VERSO - BLIND MODULE COVER	02043-001	Plastic blind module cover for IP Verso, 5 pcs	\$ 50.00
2N IP VERSO AND SOLO - REFLECTOR	02058-001	2N IP Verso and Solo – Reflector with 2N logo black, 5 pcs	\$ 76.00
2N IP SOLO WEDGE BACKPLATE	02077-001	25° gradient mounting backplate	\$ 20.00
2N IP VERSO - SPEAKER COVER BLACK	02055-001	Speaker cover, black, 5 pcs	\$ 85.00
2N IP VERSO - RFID READER COVER	02056-001	Front plastic cover of Verso RFID reader, 5pcs	\$ 70.00
2N IP VERSO - CLAMP BETWEEN MODULES	02057-001	Metal clamps for connection of Verso modules backboxes together, 20pcs	\$ 45.00
2N IP VERSO BLUETOOTH READER COVER	02063-001	Plastic bluetooth reader cover	\$ 71.00
2N VERSO/SOLO TERMINAL 2 PIN 10X	02093-001	2N IP Verso/Solo - green 2 PIN terminal for input/output, 10 pcs	\$ 18.00
2N VERSO/SOLO TERMINAL 3 PIN 10X	02092-001	2N IP Verso/Solo - green 3 PIN terminal for relay and 12V input, 10 pcs	\$ 20.00
2N IP Verso - RFID 125kHz 2G	02140-001	2N IP Verso - RFID 125kHz, second generation with better reading distance/time.	\$ 150.00
2N IP Verso - RFID 13MHz NFC SEC 2G	02141-001	2N IP Verso - RFID 13.56MHz NFC, second generation with better reading distance/time, reads PACS ID	\$ 300.00
2N IP VERSO - 1M FLUSH FRAME	01278-001	2N IP Verso - 1 module flush frame	\$ 75.00
2N IP VERSO - 1M FLUSH FRAME BLACK	01279-001	2N IP Verso - 1 module flush frame, black	\$ 75.00
2N IP VERSO - 2M FLUSH FRAME	01280-001	2N IP Verso - 2 modules flush frame	\$ 85.00
2N IP VERSO - 2M FLUSH FRAME BLACK	01281-001	2N IP Verso - 2 modules flush frame, black	\$ 85.00

2N IP VERSO - 3M FLUSH FRAME	01282-001	2N IP Verso - 3 modules flush frame	\$ 85.00
2N IP VERSO - 3M FLUSH FRAME BLACK	01283-001	2N IP Verso - 3 modules flush frame, black	\$ 85.00
2N IP VERSO - 1M FLUSH BOX	01284-001	2N IP Verso - 1 module flush box	\$ 25.00
2N IP VERSO - 2M FLUSH BOX	01285-001	2N IP Verso - 2 modules flush box	\$ 30.00
2N IP VERSO - 3M FLUSH BOX	01286-001	2N IP Verso - 3 modules flush box	\$ 32.00
2N IP VERSO - 1M SURFACE FRAME	01287-001	2N IP Verso - 1 module surface frame	\$ 55.00
2N IP VERSO - 1M SURFACE FRAME BL.	01288-001	2N IP Verso - 1 module surface frame, black	\$ 55.00
2N IP VERSO - 2M SURFACE FRAME	01289-001	2N IP Verso - 2 modules surface frame	\$ 70.00
2N IP VERSO - 2M SURFACE FRAME BL.	01290-001	2N IP Verso - 2 modules surface frame, black	\$ 70.00
2N IP VERSO - 3M SURFACE FRAME	01291-001	2N IP Verso - 3 modules surface frame	\$ 110.00
2N IP VERSO - 3M SURFACE FRAME BL.	01292-001	2N IP Verso - 3 modules surface frame, black	\$ 110.00
2N IP VERSO - 1M BACKPLATE	01293-001	2N IP Verso - 1 module backplate for surface installation	\$ 48.00
2N IP VERSO - 2M BACKPLATE	01294-001	2N IP Verso - 2 modules backplate for surface installation	\$ 56.00
2N IP VERSO - 3M BACKPLATE	01295-001	2N IP Verso - 3 modules backplate for surface installation	\$ 65.00
2N IP VERSO - 2x2M BACKPLATE	01296-001	2N IP Verso - 2x2 modules backplate for surface installation	\$ 81.00
2N IP VERSO - 3x2M BACKPLATE	01297-001	2N IP Verso - 3x2 modules backplate for surface installation	\$ 104.00
2N IP VERSO - 2x3M BACKPLATE	01298-001	2N IP Verso - 2x3 modules backplate for surface installation	\$ 98.00
2N IP VERSO - 3x3M BACKPLATE	01299-001	2N IP Verso - 3x3 modules backplate for surface installation	\$ 140.00
2N IP VERSO - 1M GANG PLATE	01524-001	2N IP Verso - 1 module backplate for surface installation on a 2-gang backbox	\$ 48.00
2N IP VERSO - 2M GANG PLATE	01525-001	2N IP Verso - 2 modules backplate for surface installation on a 2-gang backbox	\$ 56.00
2N AC - LIC +5 DEVICES	01372-001	2N Access Commander - license for adding 5 devices (block of 5 licenses)	\$ 70.00
2N IP INTERCOM AND SIP AUDIO- INFORMACAST	01381-001	2N IP Intercom and SIP AudioLicense - Informacast License	\$ 85.00
2N AC - LIC +25 USERS	01373-001	2N Access Commander - license for adding 25 users (block of 25 licenses)	\$ 245.00
2N IP INTERCOM AND SIP AUDIO - G729 LIC	01375-001	2N IP Intercom and SIP Audio - license for G.729 audio codec	\$ 37.00
2N AC - INTEGRATION LICENSE	01374-001	2N Access Commander - LDAP license	\$ 231.00
2N IP INTERCOM ENHANCED AUDIO LIC	01376-001	2N IP Intercom License - Enhanced Audio	\$ 63.00
2N IP INTERCOM ENHANCED VIDEO LIC	01377-001	2N IP Intercom Enhanced Video lic	\$ 98.00
2N IP INTERCOM ENHANCED INTEGRATION LIC	01378-001	2N IP Intercom Enhanced Integration lic	\$ 63.00
2N IP INTERCOM ENHANCED SECURITY LIC	01379-001	2N IP Intercom License - Enhanced Security	\$ 98.00

2N IP INTERCOM LIFT MODULE LICENSE	02001-001	The Lift license enables the capability to integrate the 2N IP Intercom (Verso, Force, Vario) with the Axis A9188 module for the 2N Lift access control solution. The Lift license is NOT included in the Gold license.	\$ 225.00
2N AU - NFC LICENSE	01369-001	2N Access Unit - NFC license for 916010 NFC ready type	\$ 25.00
2N AU - LIFT MODULE LICENSE	02000-001	The Lift license enables the capability to integrate the 2N Access Unit with the Axis A9188 module for the 2N Lift access control solution.	\$ 225.00
2N IP INTERCOM GOLD LICENSE	01380-001	2N IP Intercom License - Gold License	\$ 225.00
2N IP INTERCOM - NFC LICENSE	01382-001	2N IP Intercom - NFC License	\$ 24.00
2N IDT 2.0 - MEETING ROOM LICENSE	02171-001	License key for the 2N® INDOOR TOUCH 2.0 enabling the 2N® MEETING ROOM app feature.	\$ 349.00
2N IDT - UNLOCKING LICENSE	01418-001	2N Indoor Touch - unlocking license for uploading apps	\$ 65.00
2N IDT - HTTP API LICENSE	01424-001	2N Indoor Touch HTTP API license	\$ 75.00
MIFARE RFID SMART CARD 13.56MHz	01384-001	Mifare RFID smart card 13.56MHz	\$ 5.00
MIFARE RFID SMART KEY FOB 13.56MHz	01385-001	Mifare RFID smart key fob 13.56MHz	\$ 5.00
2N SECURITY RELAY	01386-001	2N Security Relay	\$ 110.00
2N WIEGAND ISOLATOR	01387-001	2N Wiegand Isolator	\$ 150.00
2N MAGNETIC DOOR CONTACT	01388-001	2N Magnetic door contact	\$ 20.00
WIEGAND 125 kHz RFID CARD READER	01389-001	External 125 kHz EMarine RFID card reader, Wiegand	\$ 95.00
WIEGAND 13.56 MHz RFID CARD READER	01390-001	External 13.56MHz Mifare RFID card reader, Wiegand	\$ 95.00
2N INDUCTION LOOP	01391-001	2N External induction loop for IP Intercom	\$ 170.00
2N IND. LOOP EXT. ANTENNA	01392-001	2N External antenna for the induction loop	\$ 90.00
2N INDUCTION LOOP - POWER SUPPLY	01393-001	2N Power supply for the induction loop	\$ 40.00
PoE INJECTOR WITHOUT CABLE	01394-001	PoE injector PSA16U-480(POE), external PoE; 1port 15.4W ACDC - without cable	\$ 55.00
EMARINE RFID PROX CARD 125kHz	01395-001	Proximity Card Emarine 125kHz	\$ 5.00
EMARINE RFID PROX KEY FOB 125kHz	01396-001	Proximity Key Fob Emarine 125kHz	\$ 5.00
WEB RELAY - 1 OUTPUT, 1 INPUT	01397-001	Web IP Relay - 1 output, 1 input	\$ 260.00
WEB RELAY - 4 OUTPUTS, 0 INPUT, PoE	01398-001		\$ 330.00
USB RFID READER 125kHz	01399-001	External RFID Reader 125kHz EMarine (USB interface)	\$ 65.00
USB RFID READER 13MHz & 125kHz	01400-001	External RFID Reader 13.56MHz + 125kHz (USB interface)	\$ 335.00
USB FINGERPRINT READER	01401-001	External fingerprint reader (USB interface)	\$ 250.00
USB BLUETOOTH READER	01402-001	External Bluetooth reader (USB interface)	\$ 28.00
PoE INJECTOR WITH CABLE	01403-001	PoE injector PSA16U-480(POE), external PoE; 1port 15.4W ACDC - with US cable	\$ 65.00
2N 2WIRE - SET WITH US PLUG	01404-001	2N 2Wire - set of 2 adaptors and power source for the US plug	\$ 340.00
USB SEC RFID READER 13MHz & 125kHz	01527-001	External RFID secured reader 13.56MHz + 125kHz (USB interface)	\$ 430.00

VERSO/SOLO SPEAKER COVER,5x	01640-001	2N IP Verso and Solo speaker cover - plastic cover of speaker on the main unit - 5pcs	\$ 68.00
VERSO/SOLO CAMERA WINDOW,5x	01641-001	2N IP Verso and Solo camera window- camera version -plastic cover on the main unit - 5pcs	\$ 45.00
VERSO WINDOW NON-CAMERA,5x	01642-001	2N IP Verso camera window- non-camera version -plastic cover on the main unit - 5pcs	\$ 50.00
VERSO/SOLO REFLECTOR,2N LOGO,5x	01643-001	2N IP Verso and Solo Reflector with 2N logo - plastic part under the camera - 5pcs	\$ 62.00
VERSO/SOLO BUTTON NAMETAG,10x	01644-001	2N IP Verso and Solo button nametag - plastic button with nametag - 10pcs	\$ 90.00
VERSO FLUSH/SURFACE LOWER FIX,5x	01645-001	2N IP Verso Flush and surface bottom fixture - metal fixture to hold the frame - 5pcs	\$ 45.00
SOLO FLUSH/SURFACE LOWER FIX,5x	01646-001	2N IP Solo Flush and surface bottom fixture - metal fixture to hold the frame - 5pcs	\$ 40.00
VERSO/SOLO FLUSH TOP FIX,5x	01647-001	2N IP Verso and Solo Flush mount upper fixtrue - metal part to hold the frame - 5pcs	\$ 40.00
VERSO/SOLO SURFACE TOP FIX,5x	01648-001	2N IP Verso and Solo Surface mount upper fixture - metal part to hold the frame - 5pcs	\$ 35.00
VERSO BUS SHORT,80MM,10x	01649-001	2N IP Verso bus short, 80mm - vbus cabel to connect the modules - 10pcs	\$ 45.00
VERSO BUS SHORT,220MM,10x	01650-001	2N IP Verso bus short, 220mm - vbus cabel to connect the modules - 10pcs	\$ 55.00
VERSO MICROPHONE SET,10x	01651-001	2N IP Verso microphone set - microphone with cable to 3 module extension - 10pcs	\$ 70.00
FORCE/SAFETY SPEAKER 1W	01652-001	2N IP Force and Safety Speaker 1W, 16 Ohm, 77mm - 1pc	\$ 30.00
FORCE/SAFETY GASKET FOR MIC,5x	01654-001	2N IP Force and Safety Gasket for microphone - 5pcs	\$ 16.00
FORCE/SAFETY MIC WITH CABLE,5x	01655-001	2N IP Force and Safety microphone with cable - 10pcs	\$ 152.00
FORCE BUTTON NAMETAG,5x	01656-001	2N IP Force and analog Force Button namateg to plastic part - 5pcs	\$ 25.00
FORCE PLASTIC BUTTON ON PCB,5x	01657-001	2N IP Force and analog Force Plastic clear button on the PCB board - 10pcs	\$ 22.00
FORCE 1 BUTTON BOARD,1x	01658-001	2N IP Force and analog Force 1 button board - 1pc	\$ 30.00
FORCE 1 BUTTON BOARD, PICTOGRAM,5x	01659-001	2N IP Force and analog Force 1 button board, pictograms - 1pc	\$ 30.00
FORCE 2 BUTTONS BOARD,1x	01660-001	2N IP Force and analog Force 2 buttons board - 1pc	\$ 35.00
FORCE 4 BUTTON BOARD,1x	01661-001	2N IP Force and analog Force 4 buttons board - 1pc	\$ 40.00
FORCE/SAFETY SPEAKER10W 4pcs	01653-001	2N IP Force and Safety Speaker 10W, 4 Ohm, 76mm - 4pcs	\$ 65.00
2N U-SHAPED FRAME IP BASE BLACK	02041-001	U-shaped black front frame for 2N IP Base	\$ 60.00
2N IDT 2.0 POE BLACK	01668-001	2N® Indoor Touch 2.0 - PoE Black	\$ 755.00
2N IDT 2.0 POE WHITE	01669-001	2N® Indoor Touch 2.0 - PoE White	\$ 755.00
2N IDT 2.0 POE WIFI BLACK	01670-001	2N® Indoor Touch 2.0 - PoE Wi-Fi Black	\$ 820.00
2N IDT 2.0 POE WIFI WHITE	01671-001	2N® Indoor Touch 2.0 - PoE Wi-Fi White	\$ 820.00

2N INDOOR VIEW BLACK	02087-001	7" touchscreen answering unit with a wide viewing angle. The tempered glass surface and award-winning design are the perfect choices for any luxury residential project. The 2N Indoor View requires the 2N Indoor Flush Box (01700-001) or the 2N Indoor Desk Stand (02039-001) for an installation.	\$ 549.00
2N INDOOR VIEW WHITE	02088-001	7" touchscreen answering unit with a wide viewing angle. The tempered glass surface and award-winning design are the perfect choices for any luxury residential project. The 2N Indoor View requires the 2N Indoor Flush Box (01700-001) or the 2N Indoor Desk Stand (02039-001) for an installation.	\$ 549.00
2N INDOOR COMPACT BLACK	01935-001	The 2N® Indoor Compact is an indoor answering unit designed especially for the residential market. Installation by connecting a single UTP cable and configuration via a web interface guarantees that integrators can put the unit into operation quickly and easily. Users will be impressed by the minimalist design, tempered glass surface, 4.3" colour display, sound in HD quality and intuitive controls. A simply elegant solution for video communication.	\$ 425.00
2N INDOOR COMPACT WHITE	01936-001	The 2N® Indoor Compact is an indoor answering unit designed especially for the residential market. Installation by connecting a single UTP cable and configuration via a web interface guarantees that integrators can put the unit into operation quickly and easily. Users will be impressed by the minimalist design, tempered glass surface, 4.3" colour display, sound in HD quality and intuitive controls. A simply elegant solution for video communication.	\$ 425.00
2N INDOOR TALK BLACK	01698-001	2N Indoor Talk PoE – Black Elegant answering unit with HD sound. The design of the 2N® Indoor Talk answering unit will suit every flat or home. The aesthetic appearance of this product was achieved by using a glass surface and striking backlighting of its icons. However, we placed particular emphasis on selecting the highest-quality audio components in order to achieve a high-quality sound. This means you can talk to visitors outside as if they were standing right next to you. Invite them in and press the icon to open the door from the comfort of your home. The 2N Indoor Talk Black requires the 2N Indoor Flush Box (01700-001) for installation.	\$ 293.00

2N INDOOR TALK WHITE	01699-001	2N Indoor Talk PoE – White Elegant answering unit with HD sound. The design of the 2N® Indoor Talk answering unit will suit every flat or home. The aesthetic appearance of this product was achieved by using a glass surface and striking backlighting of its icons. However, we placed particular emphasis on selecting the highest-quality audio components in order to achieve a high-quality sound. This means you can talk to visitors outside as if they were standing right next to you. Invite them in and press the icon to open the door from the comfort of your home. The 2N Indoor Talk White requires the 2N Indoor Flush Box (01700-001) for installation.	\$ 293.00
2N INDOOR FLUSH BOX	01700-001	2N Indoor answering unit flush installation box, required for the 2N® Indoor Compact (01935-001 or 01936-001) and 2N® Indoor Talk (01698-001 or 01699-001).	\$ 22.00
2N INDOOR DESK STAND	02039-001	2N Indoor desk stand is intended for the 2N® Indoor Compact (01935-001 or 01936-001) or the 2N® Indoor Talk (01698-001 or 01699-001) answering units. There is no need to use the flush box (01700-001).	\$ 48.00
2N IDT - DESK STAND BLACK	01425-001	2N Indoor Touch - Desk stand black	\$ 80.00
2N IDT - DESK STAND WHITE	01426-001	2N Indoor Touch - Desk stand white	\$ 80.00
2N IDT - POWER SUPPLY FLUSH	01423-001	2N Indoor Touch External power supply, 12V 2A DC, flush mounted	\$ 100.00
GXV3370 IP PHONE	01695-001	Grandstream GXV 3370 Multimedia IP phone with 7” touch screen, Android, Wifi, PoE	\$ 590.00
GXV3240 IP PHONE	01422-001	Grandstream GXV 3240 Multimedia IP phone with 4.3” digital color LCD, Android, Wifi, PoE	\$ 370.00
YEALINK SIP T58A	01586-001	The Yealink SIP-T58A is a simple-to-use smart media phone that provides an enriched HD audio and video calling experience for business professionals. This all-new smart media phone enables productivity-enhancing visual communication with the ease of a standard phone.	\$ 650.00
2N IDT - PoE, BLACK	01416-001	2N Indoor Touch PoE - Black	\$ 755.00
2N IDT - PoE, WHITE	01417-001	2N Indoor Touch PoE - White	\$ 755.00
2N IDT - PoE, WIFI, BLACK	01419-001	2N Indoor Touch - PoE, WiFi, black	\$ 820.00
2N IDT - PoE, WIFI, WHITE	01420-001	2N Indoor Touch - PoE, WiFi, white	\$ 820.00
2N Grandstream GXV-3350 - VoIP	02240-001	Grandstream GXV 3350 Multimedia IP phone with 5” digital color LCD (1280x720), Android, Wifi, PoE, tiltable camera Peripherals: HDMI- out, USB, headset jack, EHS	\$ 430.00

2N SIP MIC	01208-001	2N SIP Mic allows paging to several zones with a simple push of a button. It is ideal for live or pre-recorded announcements. It has a built-in audio-management server for configuration, which means less equipment as well as flexible, easy and cost-efficient installation. The network microphone console has 12 buttons that can be configured with actions of your choice. 2N SIP Mic's 12 buttons give you a smart paging solution for up to 12 zones, and if your system grows you can easily connect the microphone console to a PBX system thanks to support for SIP. The microphone is based on open standards and connects to standard networks using PoE.	\$ 1,099.00
2N SIP SPEAKER - HORN	01433-001	2N SIP Speaker - Horn (outdoor SIP based active hornspeaker)	\$ 518.00
2N SIP SPEAKER - WALL MOUNTED, W	01432-001	2N SIP Speaker - Loudspeaker Set, wall mounted (SIP based active speaker)	\$ 460.00
2N SIP SPEAKER - WALL MOUNTED, B	01431-001	2N SIP Speaker - Loudspeaker Set, wall mounted (SIP based active speaker)	\$ 460.00
2N IP AUDIO POWER SUPPLY - US PLUG	01435-001	2N IP Audio Power Supply - US plug	\$ 75.00
AXIS A8004 JUNCTION BOX	5801-131	AXIS A8004 Junction box offers neat and easy recessed installations of the AXIS A8004-VE Network video door station. Multiple mounting and wiring options along with a robust steel construction makes it suitable for most situations and wall types.	\$ 69.00
AXIS A9801 SECURITY RELAY	5801-141	AXIS A9801 Security relay box offer an easy and cost efficient way to improve security for doors controlled by an Axis network video door station. The product bridges the connection between door station and door lock and is placed on the secure side of the door. If an intruder attempt to tamper with the door station to access the door lock wires, AXIS A9801 Security relay will cut the connection and ensure that the door remains securely locked.	\$ 119.00
MOUNT KIT CODEBLUE/A8004	5507-471	Stainless steel adapter plate for mounting AXIS A8004-VE Network Video Door Station in Code Blue emergency stanchions and call boxes, combining intelligent video surveillance with emergency communication in a single device. The adapter plate is compatible with all Code Blue help points, suitable for new deployments and retrofitting existing installations.	\$ 119.00
AXIS ACCESS CARD 1K, WHITE 200 pcs	5506-831	AXIS Access Card is a contactless Mifare 1K smart card that uses advanced radio frequency identification (RFID) technology to deliver secure and reliable physical access to premises. It is robust and IP68-rated, comes in a pack of 200 pcs.	\$ 359.00
AXIS A8105-E FLUSH MOUNT	5801-481	Nice and easy recessed mount of AXIS A8105-E Network video door station suitable for most wall types.	\$ 69.00

AXIS A8004-VE ACCESSIBILITY KIT	5801-671	AXIS A8004-VE Accessibility kit is an easy way to improve access to your building and comply with regulations on barrier-free accessibility. It's designed as a new front plate that mounts on and connects directly to any AXIS A8004-E Network Video Door Station. The product includes an inductive loop for hearing aids, illuminated pictograms for user feedback and a tactile dot for the call button, all of which help to simplify interaction for people with impaired hearing or vision.	\$ 199.00
AXIS TA8201 RECESSED MOUNT	01762-001	Recessed mount offering neat and easy installation of the AXIS A8207-VE Network Video Door Station. Multiple mounting and wiring options along with a robust construction makes it suitable for most situations and wall types.	\$ 119.00
AXIS TA8601 CONDUIT ADAPTER 3/4 NPS	01763-001	Cable protection attachment bracket for AXIS A8207-VE Network Video Door Station Compatible with 3/4" Conduits	\$ 79.00
AXIS TA8501 PHYSICAL TAMPERING SW	01962-001	AXIS TA8501 Physical Tampering Switch is an accessory to be used when the AXIS A8105-E Network Video Door Station is combined with the AXIS A9801 Security Relay. This accessory is a fix to the known issue of the integrated accelerometer showing false tampering alerts.	\$ 15.00
AXIS A1001 Network Door Controller	0540-001	AXIS A1001 Network Door Controller is an open, non-proprietary platform for access management. The controller is installed by each door and data is automatically synchronized between the controllers in the system. The controller supports most Wiegand and RS 485 OSDP readers. The unit comes with a built-in software for basic access management for up to 33 controllers as well as an open API to meet the requirements for larger and more advanced installations. The plenum rated controller is designed for wall or ceiling mount indoors and supports Power over Ethernet IEEE 802.3af Class 3. It is fitted with 14 configurable input/outputs and 5 power outputs for door accessories including fault/tamper detection and support for Uninterruptible Power Supply (UPS).	\$ 599.00
AXIS A1001 BULK 10PCS Network Door Controller	0540-021	AXIS A1001 Network Door Controller is an open, non-proprietary platform for access management. The controller is installed by each door and data is automatically synchronized between the controllers in the system. The controller supports most Wiegand and RS 485 OSDP readers. The unit comes with a built-in software for basic access management for up to 33 controllers as well as an open API to meet the requirements for larger and more advanced installations. The plenum rated controller is designed for wall or ceiling mount indoors and supports Power over Ethernet IEEE 802.3af Class 3. It is fitted with 14 configurable input/outputs and 5 power outputs for door accessories including fault/tamper detection and support for Uninterruptible Power Supply (UPS).	\$ 5,990.00

AXIS A1601	01507-001	With door controllers from Axis, you install one smart, independent device by each door to create a scalable access control system. The open platform allows you to mix and match best-of-breed software and hardware, and enables easy integration with other systems such as video surveillance, intrusion detection, and time and attendance. AXIS A1601 Network Door Controller is ideal for advanced access management in mid-sized and large, multi-site installations using third-party software (no embedded Entry Manager software). It has a powerful processor, expanded storage and memory, relays, and I/O ports. AXIS A1601 is powered by PoE+ and can also power connected equipment.	\$ 699.00
AXIS A9188 NETWORK I/O RELAY MODULE	0820-001	AXIS A9188 Network I/O Relay Module is an intelligent module with 8 configurable I/Os and 8 form C relays and supports supervised inputs. Open API, including VAPIX, for software integration. High level of integration with AXIS A1001 Network Door Controller for elevator control for floor management etc. Supported by AXIS Video Hosting System, AXIS Camera Station and third party partner software. The module provides 12 and 24 V DC output to I/O devices and can extend the functionality of any Axis product where you need additional I/Os or relays. Powered by PoE+ or 12 and 24 V DC input	\$ 499.00
AXIS A9161 NETWORK I/O RELAY MODULE	0821-001	AXIS A9161 Network I/O Relay Module has 6 configurable I/Os with supervised inputs and a relay. The module reacts on inputs, such as signals from PIR motion detectors or switches, to trigger actions. Supplying power to I/O devices, it can extend the functionality of Axis products where additional I/Os or relays are needed. Its enclosure makes installation easy and flexible. -6 I/Os and 1 form C relays -12 and 24 V DC output/input or PoE+ -Based on Axis open platforms, VAPIX and ACAP -Used with AXIS Camera station or third-party software	\$ 249.00
AXIS A9188-VE NETWORK I/O RELAY MODULE	0831-001	AXIS A9188-VE Network I/O Relay Module comes with AXIS T98A15-VE Surveillance Cabinet making it outdoor-ready, vandal-resistant, and UL294-approved. With its 8 configurable I/Os and relays, its open platform enables a high level of integration with AXIS A1001 Network Door Controller and other facility systems. -8 I/Os with supervised inputs and 8 form C relays -UL294-approved with cabinet AXIS T98A15-VE Surveillance Cabinet -12 and 24 V DC output/input or PoE+ -Open API, support for VAPIX, ACAP -Used with AXIS Camera station or third-party software	\$ 799.00

AXIS A8004-VE	0673-001	AXIS A8004-VE Network Video Door Station is an open, IP-based door station for two-way communication, video and remote entry control. By combining exceptional audio capabilities, including a high performing solution for echo cancellation and noise suppression, with an integrated HDTV camera with WDR and excellent low-light performance, the unit offers reliable 24/7 identification and remote entry control also in the most demanding situations. Based on open IP standards and interfaces such as Onvif, PoE and SIP, AXIS A8004-VE Network Video Door Station offers great integration possibilities and is a perfect complement to any video surveillance system.	\$ 1,249.00
AXIS A8105-E	0871-001	AXIS A8105-E is a small and powerful network video door station. It operates as a communication device and full-fledged security camera at the same time, providing HDTV video, audiovisual identification, two-way communication and remote entry control as an intrinsic part of video surveillance. Open standards such as ONVIF and Session Initiation Protocol (SIP) in combination with its small size, give unique opportunities for system design, integration and installation. Wide Dynamic Range (WDR) and efficient noise cancellation ensure uncompromised performance in demanding situations, such as strong backlight or surrounding noise. Axis' Digital Corridor Format easily adjusts the viewing area to the location.	\$ 799.00
AXIS A8207-VE MKII	02026-001	AXIS A8207-VE Network Video Door Station combines a fully featured 6MP security camera with high-quality, two-way audio communication and remote entry control. It also has an integrated RFID access control reader. By providing both surveillance, visitor management, and employee accessibility, AXIS A8207-VE increases the efficiency while keeping down the number of devices at the door. Analytics, such as motion or sound-based detection, is supported. Based on open standards and with several hardware interfaces, AXIS A8207-VE easily integrates with other systems and solutions and is prepared for future needs. Interaction is intuitive and accessible, with an inductive loop for hearing aid.	\$ 1,499.00
AXIS I8016-LVE	01995-001	AXIS I8016-LVE Network Video Intercom is a compact and highly robust network intercom for two-way communication, video and remote entry control. with exceptional audio quality, including echo and noise cancellation, and a 5MP camera with invisible IR night vision and 140° FOV, the unit offers reliable 24/7 identification and remote entry control also in the most demanding situations. Based on open IP standards and interfaces such as ONVIF, PoE and SIP, AXIS I8016-LVE Network Video Intercom offers great integration possibilities and is a perfect complement to any video surveillance system.	\$ 1,099.00
AXIS A4011-E READER	0745-001	AXIS A4011-E Reader is a generic touch-free reader with keypad and illuminated symbols. It is a perfect match to the Network Door Controller A1001. The reader is intended for both indoor and outdoor use and it supports most smart card formats with 13.56 MHz. The reader is certified according to UL294	\$ 369.00

AXIS A4010-E READER WITHOUT KEYPAD	01023-001	AXIS A4010-E Reader is a generic touch-free reader without keypad and 2 LED feedback. It is a perfect match to the Network Door Controller A1001. The reader has a small form factor, intended for both indoor and outdoor use. It uses RS485 OSDP communication and supports most smart card formats with 13.56 MHz. This reader is a Mark II for 0946-001 with same functionality but no visible differences.	\$ 199.00
AXIS 4IN1 SECURITY SCREWDRIVER	5507-711	The AXIS 4-in-1 Security Screwdriver Kit is a great tool for installing Axis products. The kit features two double-sided insert bits type that match Axis products using tamper resistant torx and standard philips head. The kit comes with a quick-release, non-slip rubber handle, and a velcro-sealed polyester pouch with belt clip. Insert bits material in chrome vanadium (TR10+PH1) and in stainless steel (TR20+TR30).	\$ 24.00
AXIS Q17 FRONT WINDOW KIT B	01687-001	Accessory front window assembly in polycarbonate for AXIS Q1785/86-LE, IK10 rated. Not recommended for installation that requires more than 22x optical zoom.	\$ 49.00
GASKET A CABLE 3,5-7MM 10PCS	5503-741	M20 Gasket for cable diameter 3,5mm to 7mm. 10 pcs.	\$ 19.00
ACC TOOL STEEL STRAP	21776	Tool for steel strap tensioning. For use with 21764 and AXIS T91A67	\$ 145.00
AXIS GASKET M16 5-8 MM 10PCS	01785-001	IP66 cable gasket for M16 holes (max 17mm). By using the included CONNECTOR GUARD A over the RJ45 connector, you do not need to re-terminate the network cable which gives a much faster and more secure installation. Suitable for cable diameters between 5-8mm. Black color. 10 pieces (bulk pack).	\$ 19.00
GASKET B M20 CABLE 6-13MM 10PCS	5503-751	M20 Gasket for cable diameter 6-13mm, 10 pcs.	\$ 19.00
GASKET C M25 CABLE 8-17MM 10PCS	5503-791	M20 Gasket for cable 8-17mm, 10 pcs.	\$ 19.00
CABLE GLAND A M20 5PCS	5503-761	M20 cable gland, 5 pcs.	\$ 9.00
LENS TOOL KIT AXIS M311X 2MM 4PCS	5503-561	Tool kit for simplifying adjustment of viewing direction and focus setting. Compatible with AXIS M311X cameras with 2mm lens. Content: Lens tool and Opening tool 4 pcs of each.	\$ 24.00
GASKET C M20 10PCS	5505-941	This gasket is specially made for flexible and easy installation. By using the included CONNECTOR GUARD A over the RJ45 connector, you do not need to re-terminate the network cable which gives a much faster and more secure installation. Made for M20 holes and cables from 5 to 15mm in outer diameter. 10 pcs.	\$ 19.00
LENS TOOL AXIS M311X 4PCS	5502-771	Tool kit for simplifying adjustment of viewing direction and focus setting. Compatible with AXIS M311X (except 2mm lens version). Content: Lens tool and Opening tool 4 pcs of each.	\$ 24.00
CABLE GASKET M20 3MM 10PCS	5506-421	M20 gasket for small cables like I/O and audio cables. 10 pcs	\$ 19.00
LENS TOOLKIT P39XX-R 4 PCS	5506-441	Tool kit for simplifying adjustment of viewing direction and focus setting. Compatible with AXIS P39xx-R cameras with the standard lens and the 2.8 mm accessory lens. Content: Lens tool, Allen key and Opening tool. 4 pcs of each.	\$ 19.00
CABLE GLAND A M25 5PCS	5503-831	M25 Cable gland, 5 pcs.	\$ 19.00

CABLE GLAND M20x1.5 RJ45 5PCS	5503-951	M20 cable gland for RJ45. Ease of installation, no need of cutting the cable.	\$ 19.00
CABLE SEALING IP65 FOR Q8108-R	5502-711	Accessory cable sealing to meet IP65 rating for Q8108-R.	\$ 249.00
AXIS M3004-V/05-V LENS M12 6MM	5503-651	Optional lens, 6mm for M3004-V/M3005-V	\$ 49.00
AXIS M3025-VE LENS M12 6MM	5504-551	Optional lens for AXIS M3025-VE, 6mm. Including focus ring.	\$ 49.00
LENS M12 6MM F1.9 4PCS	01960-001	Accessory lens 6 mm, F1.9 with M12 thread and built in IR-cut filter for AXIS F1005-E and FA1105. Tool for removing the standard lens is included. 4 Pcs.	\$ 79.00
LENS M12 16MM F1.8 4PCS	01961-001	Accessory lens 16 mm, F1.8 with M12 thread and built in IR-cut filter for AXIS F1005-E and FA1105. Tool for removing the standard lens is included. 4 Pcs.	\$ 79.00
LENS M12 12MM F1.6 4P	01780-001	LENS M12 12MM F1.6 Q6100-E, Q6010-E	\$ 99.00
LENS M12 25MM F2.4 4P	01781-001	LENS M12 25MM F2.4 4P Q6100-E	\$ 99.00
LENS M12 16MM F1.8 4P	01812-001	LENS M12 16MM F1.8 Q6010-E Q6100-E	\$ 99.00
LENS M12 6MM F2.0 4P	01813-001	LENS M12 6MM F2.0 Q6010-E Q6100-E	\$ 99.00
ACC LENS M12 MEGAPIXEL 16MM 10PCS	5502-161	Megapixel lens 16mm with M12 thread for AXIS M3113-R, AXIS M3114-R, AXIS 209FD, AXIS 209MFD, AXIS M3011, AXIS 3014. With IR filter. 10pcs	\$ 149.00
ACC LENS M12 MEGAPIXEL 2.8MM 10PCS	5502-101	Megapixel lens 2.8mm with M12 thread for AXIS M3113-R, AXIS M3114-R, AXIS 209FD, AXIS 209MFD, AXIS M3011, AXIS 3014. With IR filter. 10pcs	\$ 199.00
ACC LENS M12 MEGAPIXEL 3.6MM 10PCS	5502-151	Megapixel lens 3.6mm with M12 thread for AXIS M3113-R, AXIS M3114-R, AXIS 209FD, AXIS 209MFD, AXIS M3011, AXIS 3014. With IR filter 10pcs	\$ 149.00
AXIS WEATHERSHIELD K	5507-121	Weathershield for AXIS P14 Series designed for use in rainy and windy environments.	\$ 29.00
LENS M12 6MM 5PCS	5801-771	Accessory M12 6mm lens for AXIS Q6000-E MkII 5pcs	\$ 99.00
ACC LENS M12 MEGAPIXEL 6MM 10PCS	5502-111	Megapixel lens 6mm lens with M12 thread for AXIS M3113-R, AXIS M3114-R, AXIS 209FD, AXIS 209MFD, AXIS M3011, AXIS 3014. With IR filter 10pcs	\$ 149.00
LENS M12 2.8 MM F1.2 10P	01860-001	Megapixel lens 2.8 mm, F1.2 with M12 thread for AXIS P39-R Series that provides 110° horizontal FOV and excellent low light performance. Coated with IR-cut filter. 10 pieces bulk pack.	\$ 199.00
ACC LENS M12 2.8MM F2.0 10 PCS	5504-951	Megapixel lens 2.8 mm, F2.0 with M12 thread for AXIS P39-R Series that provides 115° horizontal FOV with these cameras. With IR filter. 10 pieces.	\$ 199.00
ACC LENS M12 6MM F1.6 10 PCS	5504-961	Megapixel lens 6 mm, F1.6 with M12 thread for AXIS P39-R Series that provides 52° horizontal FOV with these cameras. With IR filter. 10 pieces.	\$ 199.00
ACC LENS M12 8MM F1.6 10 PCS	5504-971	Megapixel lens 8 mm, F1.6 with M12 thread for AXIS P39-R Series that provides 40° horizontal FOV with these cameras. With IR filter. 10 pieces.	\$ 199.00
ACC LENS M12 3.6MM F2.0 10PCS	5506-011	Megapixel lens 3.6 mm, F2.0 with M12 thread for AXIS P39-R Series that provides 87° horizontal FOV with these cameras. With IR filter. 10 pieces. Can be used as a spare part for AXIS P39-R or as a wider FOV option for P3905-RE.	\$ 199.00

AXIS LENS M12 2.1MM F2.2 10PCS	5901-371	Megapixel lens 2.1mm, F2.2 with M12 thread for AXIS P39-R Series that provides 147° horizontal FOV with these cameras. With IR filter. 10 pieces. Lens tool included.	\$ 199.00
AXIS LENS M12 2.1 MM F1.8 IR 10P	02006-001	2.1 mm accessory lens, F1.8 with M12 thread, without IR-cut filter for day/night cameras with removable IR cut filter. Compatible with AXIS P3925-R and AXIS P3935-LR. 10 pcs. Lens tool included.	\$ 199.00
AXIS LENS M12 3.6 MM F1.8 IR 10P	02007-001	3.6 mm accessory lens, F1.8 with M12 thread, without IR-cut filter for day/night cameras with removable IR cut filter. Compatible with AXIS P3925-R and AXIS P3935-LR. 10 pcs. Lens tool included.	\$ 199.00
AXIS LENS M12 6.0 MM F1.9 IR 10P	02008-001	6.0 mm accessory lens, F1.9 with M12 thread, without IR-cut filter for day/night cameras with removable IR cut filter. Compatible with AXIS P3925-R and AXIS P3935-LR. 10 pcs. Lens tool included.	\$ 199.00
AXIS LENS M12 8.0 MM F1.8 IR 10P	02009-001	8.0 mm accessory lens, F1.8 with M12 thread, without IR-cut filter for day/night cameras with removable IR cut filter. Compatible with AXIS P3925-R and AXIS P3935-LR. 10 pcs. Lens tool included.	\$ 199.00
LENS M12 16MM 5PCS	5801-781	Accessory M12 16mm lens for AXIS Q6000-E MkII 5pcs	\$ 99.00
ACC LENS M12 MEGAPIXEL 6PCS	5506-431	2 pieces each of 2.8 mm (F2.0), 6 mm (F1.6) and 8 mm (F1.6) Megapixel lenses with M12 thread. For use with AXIS P39-R cameras. Includes lens tools.	\$ 149.00
ACC LENS M12 MEGAPIXEL 8MM 10PCS	5502-411	Megapixel lens 8mm with M12 thread for AXIS M3113-R, AXIS M3114-R, AXIS 209FD, AXIS 209MFD, AXIS M3011, AXIS 3014. With IR filter. 10pcs	\$ 149.00
LENS M12 MEGAPIXEL 10PCS	5502-421	Mixed pack of M12 Megapixel lenses. Focal length: 2.8mm, 3.6mm, 6mm, 8mm and 16mm for AXIS M3113-R, AXIS M3114-R, AXIS 209FD, AXIS 209MFD, AXIS M3011, AXIS 3014. With IR filter. 10pcs=2 pcs of each lens.	\$ 149.00
THEIA LENS CS VARIF 1.8-3MM DC-IRIS	5503-161	Barrel distortion corrected and IR corrected wideangle lens for cameras up to 5 mega pixel resolution. Compatible with e.g. AXIS M1114/-E, AXIS P1353/-E, P1354/-E, P1355/-E, P1357/-E, AXIS Q1602/-E, Q1604/-E, Q1614/-E, Q1615/-E.	\$ 289.00
LENS CS VF 2.2-6MM F1.3 DC-I MP	5502-751	Varifocal 2.2-6mm DC-Iris Megapixel Lens, F1.3, CS mount for AXIS M1113/4	\$ 149.00
LENS CS 2.4-6MM MANUAL IRIS	5503-181	Manual iris lens, varifocal 2.4-6MM compatible with AXIS M1103 and M1104.	\$ 79.00
LENS FUJINON CS 2.2-6MM DC-IRIS B	5800-781	Varifocal IR-corrected lens with DC-Iris. Compatible with e.g. AXIS P1353/-E, P1354/-E, P1355/-E, P1357/-E, AXIS Q1602/-E, Q1604/-E.	\$ 149.00
LENS CS 3-10.5MM DC-IRIS	5506-961	Standard lens for AXIS M1124/-E, M1125/-E.	\$ 99.00
LENS CS VARIF 9-40MM DC-IRIS D/N	5503-171	Varifocal IR-corrected lens for cameras up to 5 mega pixel resolution. Compatible with e.g. AXIS M1114/-E, P1354/-E, P1355/-E, P1357/-E, Q1602/-E, Q1604/-E.	\$ 259.00
LENS CS VARIF 9-40MM P-IRIS D/N	5504-901	Varifocal IR-corrected P-iris tele lens compatible with AXIS P1355/-E, P1357/-E, AXIS Q1602/-E, Q1604/-E, Q1614/-E, Q1615/-E.	\$ 259.00
LENS COMPUTAR CS 12.5-50MM DC-IRIS	5800-791	Varifocal IR-corrected lens with DC-Iris. Compatible with e.g. AXIS P1353/-E, P1354/-E, Axis Q1602/-E, Q1604/-E.	\$ 249.00
LENS COMPUTAR CS 12.5-50MM P-IRIS	5800-801	Varifocal IR-corrected lens with P-Iris. Compatible with e.g. AXIS Q1602/-E, Q1604/-E, Q1614/-E, Q1615/-E, AXIS P1355/-E, P1357/-E.	\$ 249.00

LENS COMPUTAR i-CS 2.8-8.5MM	5901-101	Standard lens for AXIS Q1615 MkII with remote zoom based on the new standard i-CS.	\$ 229.00
LENS CS VF 15-50MM F1.5 DC-I MP	5502-761	Varifocal Mega Pixel DC-Iris Lens 15-50mm, F1.5, CS mount, for AXIS M1113/14	\$ 199.00
LENS CS 15-50MM F1.5 DC-I MP D/N	5503-421	Varifocal Megapixel DC-Iris Lens 15-50mm, F1.5, CS mount, Day/Night for AXIS Q1602.	\$ 199.00
LENS FUJINON C CS 8-80MM DC	5506-991	Varifocal IR-corrected lens with DC-Iris. For use with both C-mount and CS-mount cameras thanks to the included adapter. Compatible with e.g. AXIS Q1635.	\$ 349.00
RICOM 2MP LENS DC-IRIS 8-26MM F0.9	01577-001	Lens RICOM 2 MP DC-iris CS-Mount Varifocal 8-26MM F0.9. Recommended for AXIS Q1645/-LE.	\$ 549.00
LENS CS 12-50 MM F1.4 P-IRIS 8MP	01690-001	Varifocal IR-corrected 12-50 mm P-Iris lens for cameras up to 8 megapixel resolution and 1/1.8" sensor . Compatible with e.g. AXIS Q1645/-LE, AXIS Q1647/-LE, AXIS P1367/-E and P1368-E.	\$ 449.00
LENS I-CS 9-50 MM F1.5 8MP	01727-001	Varifocal IR-corrected 9-50 mm i-CS lens for cameras up to 8 megapixel resolution and 1/1.8" sensor. Motorized zoom, focus and P-iris. Compatible with e.g. AXIS Q1645/-LE, AXIS Q1647/-LE, AXIS P1377/-LE and P1378/-LE.	\$ 449.00
LENS I-CS 3.9-10 MM F1.5 5MP	01576-001	Spare varifocal i-CS lens for AXIS Q1645/-LE and AXIS Q1647/-LE.	\$ 299.00
Lens CS 2.8 - 13 mm F1.4 DC-Iris 5 MP	01775-001	Tamron varifocal CS mount lens with DC-Iris and focal length 2.8 – 13 mm F1.4. It supports cameras up to 5 megapixels and is compatible with selected cameras from AXIS M11 Network Camera Series.	\$ 79.00
LENS CS 3-10.5 MM DC-IRIS 2 MP	01774-001	Ricom varifocal CS mount lens with DC-Iris and focal length 3 - 10.5 mm F1.4. It supports cameras up to 2 megapixels and is compatible with selected cameras from AXIS M11 Network Camera Series.	\$ 69.00
AXIS LENS CLOTH 10PCS	5502-661	Axis accessory lens cloth. 10 pack	\$ 39.00
AXIS LENS CLOTH 50PCS	5502-721	Axis accessory lens cloth. 50 pack	\$ 169.00
SURVEILLANCE STICKER ENG 10PCS	5502-811	Axis branded sticker showing a Camera. Text: Video surveillance in operation	\$ 8.00
SURVEILLANCE STICKER ENG 50PCS	5502-821	Axis branded sticker showing a Camera. Text: Video surveillance in operation	\$ 50.00
RADAR DETECTION STICKER EN 10PCS	01551-001	Axis branded sticker showing a radar detection illustration. Text: Radar detection in operation	\$ 8.00
AXIS WEATHERSHIELD KIT C	5504-881	Heavy duty outdoor weathershield for wall mounted AXIS fixed dome cameras. Designed to protect the dome from rain, snow and sun. The underside of the cover is coated with matte black anti-reflective coating, for suitable use with camera's built-in IR LEDs.	\$ 59.00
AXIS PT IR ILLUMINATOR KIT C	5801-901	850nm IR LED illuminator kit compatible with AXIS T99A Positioning Units for visual cameras. Kit includes one pair of IR illuminators, one metal mounting bracket, and three different diverging lenses. Note: this is the same illuminator kit as used in AXIS Q8685-LE PTZ Network Camera.	\$ 1,799.00

AXIS T99 ILLUMINATOR BRACKET KIT A	01181-001	Bracket kit for installing a pair of compatible illuminators to Axis positioning cameras and positioning units. Designed for use with AXIS Q8685-E and AXIS T99A10. Compatible with selected T90 white-LED and IR-LED illuminators. Includes fitting brackets, illuminator connectors, screws, washers, cable glands and cable ties. Illuminators sold separately.	\$ 199.00
AXIS WASHER KIT B	5507-701	Washer kit for spraying cleaning fluid on the windows of AXIS positioning cameras and positioning units. The kit contains a 23 litre tank, pump for delivery up to 11m (36ft), tube, nozzle and custom-made mounting bracket for the nozzle.	\$ 999.00
AXIS TQ6905-E WASHER KIT	02241-001	Washer kit for spraying cleaning fluid on the windows of AXIS positioning cameras and positioning units. The kit contains a 23 litre tank, pump for delivery up to 11m (36ft), tube, nozzle and custom-made mounting bracket for the nozzle. This washer kit compatible with Q6215 and as well requires seperate ordering of T6101 I/O since Q6215 does not have I/O.	\$ 1,099.00
AXIS WASHER KIT A	5505-921	Washer kit for spraying cleaning fluid on the windows of AXIS Q8631-E/Q8632-E and AXIS Q8665-E/Q8665-LE. The kit contains a 23 liter tank, pump for delivery up to 11m (36ft), tube, nozzle and mounting bracket for attaching the nozzle to the PT-head.	\$ 999.00
AXIS BIRD CONTROL SPIKE 10P	5801-121	Bird control spikes made of flexible UV-resistant polymer preventing birds from landing on cameras or mounts. Each module has five spikes and can be mounted on flat or curved surfaces using the pre-mounted adhesive or cable ties (not included). The modules can be connected lengthwise and/or widthwise to cover a larger area. 10 pcs.	\$ 24.00
AXIS SAFETY WIRE 3M 5P	5801-971	Stainless steel safety wire 3 m (10 ft) long, with a fixed loop in one end and an adjustable loop with a plated brass wire lock in the other. Suitable for both indoor and outdoor use.	\$ 34.00
AXIS F7301 CABLE BLACK 1M 4PCS	01552-001	Black cable with RJ12 and micro USB connectors for indoor Sensor Units. Length 1 m (39 in.) 4 pcs.	\$ 29.00
AXIS F7315 CABLE WHITE 15M 4PCS	5506-821	AXIS F7315 comes in packs of four. 15-m (49 ft.) white cable with an RJ12 contact for connection to an AXIS F1004 Sensor Unit.	\$ 99.00
AXIS P13 WEATHERSHIELD EXTENSION A	01692-001	AXIS P13 Weathershield Extension A for AXIS P1375-E. For mounting on AXIS P13 Series camera providing additional protection against rain, snow and sunlight.	\$ 49.00
M12(F)-RJ45(M) CABLE 0.5M (1.6FT)	01793-001	M12 D-Code 4-pin (Female) to RJ45 (Male) Ethernet cable, CAT5E. Length: 0.5m (1.6ft). Cable outer diameter: 6.2mm (0.25"). Color: Black. Outdoor UV and sunlight resistant. Tested operational for shock and vibration according to requirements for rolling stock and ground vehicle installations. Compatible with all Axis network video products with female RJ45 Ethernet port 802.3af and 802.3at (up to 30W).	\$ 35.00
AXIS TM1803 WEATHERSHIELD EXTENSION	02061-001	weathershield extension over M1135/37-E where entire top cover kit not wanted (TM1802)	\$ 39.00

AXIS TV5901 Control Board Adapter	02256-001	AXIS TV5901 Control Board Adapter is a cable to connect AXIS V5925 and AXIS V5938 to joystick, keypad and other controllers supporting VISCA protocol.	\$ 39.00
AXIS T92E05 PROTECTIVE HOUSING	0344-001	Protective camera housing for P13XX, M11XX, Q16XX and Q1755. Die cast aluminum casing and wallbracket, polycarbonate sunshield. The housing is IP66-, Nema 4X rated and IK10 impact-resistant. Sunshield, wallbracket and screwdriver included.	\$ 199.00
AXIS T92E20 OUTDOOR HOUSING	0433-001	Outdoor PoE camera housing with window-/camera heaters and fan for P13XX, M11XX, Q16XX and Q1755. Die cast aluminum casing and wallbracket, polycarbonate sunshield. The housing is IP66-, Nema 4X-, Vibration 4M3 rated and IK10 impact-resistant. Sunshield, wallbracket and screwdriver included.	\$ 329.00
AXIS T92G20 OUTDOOR HOUSING	01085-001	Outdoor PoE+ camera housing with IR illumination, window & camera heaters, and fan. Compatible with AXIS Q1645 and AXIS Q1647. Polycarbonate sunshield, aluminum wall mount and torx screwdriver included.	\$ 479.00
AXIS T93C10 OUTDOOR HOUSING	5507-681	Outdoor camera housing for Axis cameras with EF lenses (e.g.: AXIS Q1659). Made of IK10 impact resistant thermoplastic with dual-layer UV protection. IP66, NEMA 4X rated and UL listed. Powered by 24 VDC (power supply not included). Heavy duty wall mount included.	\$ 1,299.00
AXIS T93C EXTENSION KIT	5901-471	Extension kit to allow mounting of longer lenses in AXIS T93C10 Outdoor Housing (e.g.: compatible with AXIS Q1659 55-250 mm). Includes built-in sunshield and front window. The extension kit provides an extra space of 80mm in length within the housing, giving a total length of 380mm for the camera and lens. The part of the lens within the extension kit can have maximum diameter of 75mm.	\$ 99.00
AXIS T93F05 PROTECTIVE HOUSING	5900-261	Fixed box protective camera housing made of IK10 impact resistant and UV resistant polymer. IP66, NEMA 4X rated and UL listed. Compatible with AXIS P13 Series and AXIS Q16 Series. AXIS T94Q01A Wall mount included.	\$ 159.00
AXIS T93F10 OUTDOOR HOUSING 24VAC/12-24VDC	5900-271	Fixed box outdoor camera housing made of IK10 impact resistant and UV resistant polymer. IP66, NEMA 4X rated and UL listed. Powered by 24 V AC or 12-24 V DC. Compatible with AXIS P13 Series, AXIS Q16 Series, and M11 Series. AXIS T94Q01A Wall mount included. AXIS P1353/P1354/P1355/P1357 and AXIS Q1604/Q1614: -40 °C to 50 °C (-40 °F to 122 °F) AXIS P1365 and AXIS Q1615/Q1635: -40 °C to 55 °C (-40 °F to 131 °F). AXIS Q1645/Q1647: -40 °C to 40 °C (-40 °F to 104 °F) AXIS M1124/M1125: -40 °C to 55 °C (-40 °F to 131 °F)	\$ 239.00
AXIS T93F20 OUTDOOR HOUSING POE	5900-281	Fixed box outdoor camera housing made of IK10 impact resistant and UV resistant polymer. IP66, NEMA 4X rated and UL listed. Powered by PoE IEEE802.3af. Compatible with AXIS P13 Series, AXIS Q16 Series and M11 Series. AXIS T94Q01A Wall mount included. Temperature range: AXIS P1353/P1354/P1355/P1357 and AXIS Q1604/Q1614: -40 °C to 50 °C (-40 °F to 122 °F), AXIS P1365 and AXIS Q1615/Q1635: -40 °C to 55 °C (-40 °F to 131 °F), AXIS Q1645/Q1647: -40 °C to 40 °C (-40 °F to 104 °F), AXIS M1124/M1125: -40 °C to 55 °C (-40 °F to 131 °F).	\$ 239.00

AXIS T93G05 PROTECTIVE HOUSING	5506-491	Tailor-made light weight IP66- and IK10-rated housing for AXIS M1124/M1125. Operating temperature: -20 °C to 50 °C (-4 °F to 122 °F). Material: IK10 impact-resistant polymer. Wallmount included.	\$ 119.00
AXIS SUNSHIELD A	5504-941	Accessory sunshield and weather protection for AXIS T93F Housing Series	\$ 34.00
AXIS T96B05 OUTDOOR HOUSING	5505-911	Outdoor housing for selected AXIS P39 cameras. Enables the cameras to be mounted outside vehicles such as buses, trams, trucks and emergency vehicles. Includes lens tool and top cover tool.	\$ 99.00
AXIS T98A15-VE SURVEILLANCE CABINET	5900-151	IP66, IK10 and NEMA 4X rated outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, midspan and fuse from tough weather and vandalism. Mounting bracket for wall, DIN-rail, device mounting bracket and Electrical safety cover is included.	\$ 269.00
AXIS T98A16-VE SURVEILLANCE CABINET	5900-161	IP66, IK10 and NEMA 4X rated outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, midspan and fuse from tough weather and vandalism. The camera is mounted on the door of the cabinet. Mounting bracket for wall, DIN-rail, device mounting bracket and Electrical safety cover is included. Compatible cameras: AXIS M111X-E, P13XX-E, Q16XX-E, Q1755-E, Q191X-E Q192X-E.	\$ 269.00
AXIS T98A17-VE SURVEILLANCE CABINET	5900-171	IP66, IK10 and NEMA 4X rated outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, midspan and fuse from tough weather and vandalism. The camera is mounted on the door of the cabinet. Mounting bracket for wall, DIN-rail, device mounting bracket and Electrical safety cover is included. Compatible cameras: AXIS P33-VE/-LVE.	\$ 269.00
AXIS T98A18-VE SURVEILLANCE CABINET	5900-181	IP66, IK10 and NEMA 4X rated outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, midspan and fuse from tough weather and vandalism. The camera is mounted on the door of the cabinet. Mounting bracket for wall, DIN-rail, device mounting bracket and Electrical safety cover is included. Compatible products: AXIS T91B61 Wall bracket for use with AXIS P55, P56, Q60 and Q61-series or fixed dome pendant kits.	\$ 269.00
AXIS T98A19-VE SURVEILLANCE CABINET	5900-321	IP66, IK10 and NEMA 4X rated outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, midspan and fuse from tough weather and vandalism. The camera is mounted on the door of the cabinet. Mounting bracket for wall, DIN-rail, device mounting bracket and Electrical safety cover is included. Compatible products: AXIS P5414-E/15-E.	\$ 269.00
AXIS T98A SUNSHIELD	5503-551	Metal sunshield for AXIS T98A-VE Surveillance Cabinet series. Reduces the temperature inside the cabinet, caused by sun radiation, with up to 15°C (27°F).	\$ 74.00
AXIS CABINET LOCK A	5505-651	Door lock for AXIS T98A surveillance cabinet. Uses a generic key but it is possible to change locking cylinder to a unique key solution (not supplied from Axis)	\$ 59.00

CORRIDOR FORMAT BRACKET A	5504-931	The corridor format bracket makes it possible to mount a camera rotated 90 degrees inside the AXIS T93F05 and AXIS T93F20 housings to enable a vertically oriented, "portrait"-shaped video stream from the camera. Includes built-in camera heater (only applicable when mounted in AXIS T93F20).	\$ 39.00
CORRIDOR FORMAT BRACKET B	5506-381	The corridor format bracket makes it possible to mount a camera rotated 90 degrees inside the AXIS T93F10 housing to enable a vertically oriented, "portrait"-shaped video stream from the camera. Included with built-in camera heater.	\$ 39.00
AXIS T92E CAMERA HOLDER PLATE C	5505-331	Camera holder plate for mounting an AXIS Q1614 in a AXIS T92E05 and AXIS T92E20 housing. Or change the camera unit inside an AXIS P135X-E outdoor camera.	\$ 19.00
AXIS T92E CAMERA CHANGE KIT A	5505-341	Kit for mounting an AXIS Q1614 in a AXIS T92E05/AXIS T92E20 housing produced before 2014. Or change the camera unit inside an AXIS P134X-E outdoor camera.	\$ 39.00
AXIS M3004-V/05-V BLACK COVER 10PCS	5503-591	Clip on black cover for AXIS M3004-V and AXIS M3005-V.	\$ 99.00
AXIS M3004-V/05-V WHITE COVER 10PCS	5503-601	Clip on white cover for AXIS M3004-V and AXIS M3005-V.	\$ 99.00
AXIS M3006-V/07-PV COVER WHITE 10PCS	5503-621	Clip on white cover for AXIS M3006-V and AXIS M3007-PV. 10 pcs.	\$ 99.00
AXIS M3044-V/45-V/46-V VIEW PROT 5P	5507-441	Viewing protector that makes it harder to see where the camera is aiming. For use when the camera is used without dome. 5 pcs.	\$ 39.00
ACC CVER DME AXIS M301X MIX 10PCS	5502-341	Mixed covers with clear bubble for AXIS M3011 and AXIS M3014 Network Cameras. Includes 3 black, 3 silver, 3 gold and 1 white cover.	\$ 149.00
ACC CVER DME AXIS M301X BLCK 10PCS	5502-181	Black cover with clear bubble for AXIS M3011 and AXIS M3014. 10 pack	\$ 149.00
ACC CVER DME AXIS M301X SIL 10PCS	5502-191	Silver cover with clear bubble for AXIS M3011 and AXIS M3014 Network Cameras. 10 pack.	\$ 149.00
ACC CVER DME AXIS M301X GOLD 10PCS	5502-201	Gold cover with clear bubble for AXIS M3011 and AXIS M3014 Network Cameras. 10 pack.	\$ 149.00
AXIS M3024/25/26/27 COVER WHT 10PCS	5504-071	White cover skins compatible with AXIS M3024/M3025/M3026/M3027 for covering screws or simplify the painting process.	\$ 129.00
AXIS M3024/25/26/27 COVER BLK 10PCS	5504-061	Black cover skins compatible with AXIS M3024/M3025/M3026/M3027 for covering screws or simplify the painting process.	\$ 129.00
AXIS M30 SKIN COVER A BLACK 4P	01463-001	4-pack. Outdoor-ready skin covers compatible with AXIS M3057/58-PLVE cameras for changing the appearance of the camera, simplify re-painting and covering screws. Black color.	\$ 79.00
AXIS M30 CASING A BLACK 5P	5507-431	Black accessory casing for AXIS M3044-V/45-V/46-V. Replaces the white original casing. 5 pcs.	\$ 79.00
AXIS M30 VANDAL CASING A 5P	5901-131	Vandal-resistant (IK 08-rated) white casing with clear dome for M3047/48-P. 5 pcs.	\$ 99.00
AXIS M30 SM DETECT CASING A 5P	5901-151	Highly discreet white casing with smoke-detector look for AXIS M3047/48-P. 5 pcs.	\$ 79.00
AXIS M30 CASING B BLACK 5P	5901-121	Black accessory casing for AXIS M3047/48-P. Replaces the white original casing. 5 pcs.	\$ 79.00

AXIS M30 COVER RING A BLACK 4P	01492-001	4-pack of black accessory cover ring for AXIS M3015-V/16-V. Magnetic attachment. Replaces the original white cover ring. Dome not included.	\$ 59.00
AXIS M42 CASING A BLACK 4P	01245-001	Black accessory casings for AXIS M42 series. Replaces the original white casings. 4-piece bulk pack.	\$ 59.00
AXIS M42 SMOKED DOME A 4P	01608-001	Smoked dome with anti-scratch hard coating. Compatible with AXIS M42 series. 4x domes per pack.	\$ 79.00
AXIS M55 SMOKED DOME A	01607-001	Smoked dome in polycarbonate. IK09 vandal resistant. Compatible with AXISM5525-E. Single pack.	\$ 39.00
AXIS P32 SKIN COVER C BLACK 5P	5506-031	5-pack. Skin covers compatible with AXIS P32-V cameras for changing the appearance of the camera, simplify re-painting or covering screws. Black color.	\$ 79.00
AXIS TP3804-E Metal Casing White 4P	02236-001	A white metal casing for indoor/outdoor use that is compatible with: M3205-LVE, M3206-LVE, P3245-LVE, P3245-VE, P3247-LVE, AXIS P3248-LVE. It is IK 10/IP66, has a 3/4 conduit entry and is easy to install. This casing targeted for corrections and other segments that require a tough metal casing.	\$ 199.00
AXIS P56 SKIN COVER D	5506-161	Spare part skin covers for the AXIS P56 Series. Both the camera cover and the ring around the dome are included. 5 pcs.	\$ 129.00
AXIS P39-R SKIN COVER WHITE 10P	5505-991	Skin covers compatible with AXIS P39-R cameras for changing the appearance of the camera, simplify re-painting or covering screws. White color. 10 pcs.	\$ 149.00
AXIS P39-R SKIN COVER BLACK 10P	5506-001	Skin covers compatible with AXIS P39-R cameras for changing the appearance of the camera, simplify re-painting or covering screws. Black color. 10 pcs.	\$ 149.00
AXIS F8214 DOME ACC 4PCS	5506-501	AXIS F8214 Dome Accessory (4 pieces). Dome accessory for use with AXIS F1004 Sensor Unit. Can be mounted on walls and ceilings. Can be used with or without bubble.	\$ 59.00
AXIS SMOKED DOME M3004/05 5PCS	5504-031	Smoked domes for AXIS M3004-V and and M3005-V. 5pcs.	\$ 229.00
AXIS M3006 SMOKED DOME 5PCS	5504-011	Original white top cover with smoked dome for AXIS M3006, 5pcs.	\$ 249.00
AXIS M3025/26 SMOKED DOME 5PCS	5505-861	Smoked domes for AXIS M3025-VE, M3026-VE. 5 pcs.	\$ 249.00
AXIS M3044-V/45-V/46-V SM DOME 5P	5507-421	Smoked dome for AXIS M3044-V/45-V/46-V SM DOME. 5 pcs.	\$ 99.00
AXIS M3104/5/6-L BLACK CASING 5P	5801-401	Black accessory casing for AXIS M3104-L/05-L/06-L. Replaces the white original casing. 5 pcs.	\$ 79.00
AXIS M3104/5/6-LVE BLACK CASING 5P	5801-411	Black accessory casing for AXIS M3104-LV/5-LV/6-LV. Replaces the white original casing. 5 pcs.	\$ 89.00
AXIS P32 CASING A BLACK 5PCS	5901-461	Black accessory casing for AXIS P32-VE and P32-LVE outdoor cameras. Replaces the white original casing. Includes anti-loss screws, conduit side covers. 5 pcs per pack.	\$ 129.00
AXIS P32-V SMOKED DOME A 5P	5506-021	Smoked domes for AXIS P32-V Series, 5 pcs	\$ 169.00
AXIS P32-VE SMOKED DOME A 5P	5506-461	Smoked dome for AXIS P32-VE Series, 5 pcs	\$ 169.00
AXIS P3346 DOME KIT CL BLACK	5503-151	Black cover with clear dome for AXIS P3346.	\$ 29.00

AXIS P33 CASING A BLACK	01546-001	Black accessory casing for AXIS P33-V/-LV indoor cameras. Replaces the white original casing. Includes anti-loss screws, conduit side covers. Domes sold separately.	\$ 49.00
AXIS P33 SMOKED DOME A 4PCS	01547-001	Smoked dome with anti-scratch hard coating for indoor and outdoor AXIS P337X cameras. 4x domes per pack.	\$ 119.00
AXIS P37 SMOKED DOME KIT A	01715-001	Smoked dome kit for AXIS P3717-PLE and AXIS P3719-PLE. The dome is pre-mounted in the standard white top cover casing.	\$ 99.00
AXIS P54 SMOKED DOME	5800-761	Smoked dome for AXIS P54-series.	\$ 49.00
AXIS TP5801-E Smoked Dome	5506-151	Smoked dome for AXIS P56 Series cameras.	\$ 49.00
TOP COVER AXIS M311X-R BL 10PCS	5700-661	Black top cover including dome and screws for AXIS M311X-R. 10 pcs. Approved for use in buses and trams. Not for trains.	\$ 249.00
AXIS P3364-LV DOME KIT BLACK	5504-401	Dome kit for AXIS P3364-LV. The dome is pre-mounted in a black top cover casing.	\$ 49.00
AXIS Q35-LV SKIN COVER A BLACK 5P	01157-001	Skin covers in black, compatible with AXIS Q35-LV indoor cameras. Simple to repaint in other colours, and prevents unwanted access to the cameras' screws. Black in color. 5 pieces per pack.	\$ 79.00
AXIS Q35-LVE SKIN COVER A BLACK 2P	01529-001	2-pack of skin covers in black, compatible with AXIS Q35-VE/-LVE outdoor cameras. Simple to repaint in other colors, and prevents unwanted access to the cameras' screws. Black in color. 2 pieces per pack.	\$ 79.00
AXIS Q35 SMOKED DOME A 5PCS	01183-001	Smoked dome with anti-scratch hard coating. Compatible with AXIS Q3517-LV/-LVE. 5x domes per pack.	\$ 199.00
AXIS Q3517-SLVE NYLON DOME 2P	01585-001	Accessory clear dome in a special nylon blend with anti-scratch hard coating. IK10+ vandal-resistant with superior chemical resistance. Compatible with AXIS Q3517-SLVE but not recommended to use with IR illumination. 2x domes per pack.	\$ 159.00
AXIS Q36-VE SMOKED DOME	5801-501	Smoked dome with anti-scratch hard coating. Compatible with AXIS P38 and AXIS Q36 series.	\$ 49.00
AXIS Q37 SMOKED DOME A	5901-431	Smoked dome with anti-scratch hard coating. Compatible with AXIS Q3708-PVE and Q3709-PVE. Single pack.	\$ 59.00
AXIS Q60-S SMOKED DOME A	5504-791	Smoked dome in a special nylon blend with superior stress and chemical resistance. Compatible with AXIS Q604x-S and Q6055-S cameras. Single-pack.	\$ 79.00
AXIS Q6114-E/15-E CLEAR DOME	5507-281	Standard clear dome for AXIS Q6114-E/Q6115-E.	\$ 59.00
AXIS Q6114-E/15-E CLEAR DOME 5P	5506-521	Standard clear dome for AXIS Q61 Series, 5 pcs	\$ 269.00
AXIS Q6128 HARD-COATED CLEAR DOME	5801-791	Hard coated scratch resistant clear dome for AXIS Q6128-E	\$ 89.00
AXIS Q8414-LVS IR WINDOW B 5P	5506-371	Accessory IR window without microphone hole. 5 pcs.	\$ 119.00
AXIS Q8414-LVS SMOKED DOME 5P	5506-301	Smoked dome for hiding the direction of the camera. Compatible with AXIS Q8414-LVS. 5 pcs.	\$ 99.00
ACC DOME AXIS 212PTZ-V GLASS CLEAR	5502-091	Vandal-resistant casing with clear transparent cover as a spare part for AXIS 212PTZ-V.	\$ 69.00
ACC DOME AXIS 216FD-V GLASS CLEAR	5005-051	Vandal-resistant casing with clear transparent cover. Can also upgrade an AXIS 216FD/216MFD/P330X/M320X to an AXIS 216FD-V/216MFD-V/P330X-V/M320X-V.	\$ 69.00

AXIS TM3801 BLACK CASING 4P	01854-001	4 Pack black casing to change the appearance of the product.	\$ 59.00
AXIS TM3801 WHITE CASING 4P	02024-001	4 pack white casing changing the appearance of the camera.	\$ 59.00
AXIS TM3803 BLACK CASING 4P	01744-001	Cover top black casing for M3067/68 4P.	\$ 59.00
AXIS TM3804 SM DETECT CASING C 4P	01745-001	SMOKE DETECTOR CASING - COVER TOP ASS SMOKE M3067/68	\$ 59.00
AXIS TM3805 VANDAL CASING C 4P	01746-001	Vandal Casing COVER TOP ASS DOME M304X-PV.	\$ 79.00
AXIS TM3807 BLACK CASING 4P	01918-001	4P Black casing for M3115/6 LVE. Black accessory casing that replaces the white original casing for changing the appearance of the camera.	\$ 79.00
AXIS TP3801 BLACK CASING 4P	01623-001	Accessory black casing for selected AXIS P32 indoor cameras. 4pcs bulk pack.	\$ 79.00
AXIS TP3801-E BLACK CASING 4P	01626-001	Accessory black casing for selected AXIS M32 and P32 outdoor cameras. Pre-assembled with anti-loss screws. 4pcs bulk pack.	\$ 99.00
AXIS TP3802 SMOKED DOME 4P	01624-001	Smoked dome with anti-scratch hard coating. Compatible with selected AXIS P32 indoor cameras. 4pcs bulk pack.	\$ 99.00
AXIS TP3802-E SMOKED DOME 4P	01627-001	Smoked dome with anti-scratch hard coating. Compatible with selected AXIS M32 and P32 outdoor cameras. 4pcs bulk pack.	\$ 119.00
AXIS TP3806 DOME COVER BLACK 4P	02005-001	4 pack black dome cover for AXIS P3925-R. Replaces the standard white dome cover.	\$ 199.00
AXIS TP3808 DOME COVER BLACK 4P	02004-001	4 pack black dome cover for AXIS P3935-LR. Replaces the standard white dome cover.	\$ 199.00
AXIS TQ3801 HYDROPHILIC CLEAR DOME	01820-001	Accessory clear dome with special hydrophilic coating. Helps to prevent water droplets from covering the dome in rainy conditions. The coating also provides a self-cleaning effect that helps carry away dirt and dust by rain-wash. Compatible with AXIS P3807-PLE, AXIS Q3615-VE and AXIS Q3617-VE. Single pack	\$ 99.00
AXIS TQ6801 HYDROPHILIC CLEAR DOME	01816-001	Accessory clear dome with special hydrophilic coating. Helps to prevent water droplets from covering the dome in rainy conditions. The coating also provides a self-cleaning effect that helps carry away dirt and dust by rain-wash. Compatible with selected cameras from AXIS Q61 series, e.g.: AXIS Q6124-E, AXIS Q6128-E, AXIS Q6155-E. Single pack.	\$ 149.00
AXIS TQ6802 HYDROPHILIC CLEAR DOME	01817-001	Accessory clear dome with special hydrophilic coating. Helps to prevent water droplets from covering the dome in rainy conditions. The coating also provides a self-cleaning effect that helps carry away dirt and dust by rain-wash. Compatible with selected cameras from AXIS Q61 series that support IR illumination, e.g.: AXIS Q6125-LE. Single pack.	\$ 149.00
AXIS TQ6807 SMOKED DOME COVER	01947-001	Smoked dome cover including dome cover ring. Compatible with legacy AXIS Q60-E/-C cameras. See axis.com for updated compatibility list.	\$ 149.00
ACC DOME AXIS 23XD+ SMOKED COVER	5500-201	Smoked plastic dome for AXIS 231/232D+ dome cameras	\$ 28.00
ACC DOME UPGR KIT AXIS 233D CL/SM	5500-601	Clear and Smoked plastic dome for AXIS 233D dome cameras	\$ 69.00
CLEAR BUBBLE FUSIONDOMES	25741	Clear Bubble for AXIS Pendant Fusion Dome (Spare Part)	\$ 69.00
SMOKED BUBBLE FUSIONDOMES	25740	Smoked Bubble for AXIS Pendant Fusion Domes (Spare Part)	\$ 69.00

ECP081208 PS 24V UL	5801-931	The power supply is UL certified and made of epoxy powder coated copper free aluminum with stainless steel cover bolts and hinges. It is pre-mounted with fuses, terminals, RJ45 coupler and 115/230 V AC transformer, which provides 24 V AC for Explosion Protected Cameras. The cabinet has 3 open ¾"NPT cable entries and a fourth plugged entry and is Class I, Div 1 & 2, Class II, Div 1 & 2, Class 3, cUL to CSA C22.2 No. 30, No. 25 and NEMA 3 & 4 certified for temperatures between -40°C and +55°C. Weight is 67.3 lb (30.5 kg).	\$ 7,199.00
EX POLE BRACKET XF40	5507-191	The Electro-polished 316L stainless steel pole bracket is specifically designed for top mounting installations of XF40 and suitable for onshore, offshore, marine and heavy industrial applications. It features a swivel movement of pan ±90° and tilt ±45° and its weight is 1.1kg.	\$ 449.00
EX WALL MOUNT XF40	5507-201	Electro-polished 316L stainless steel wall mount for XF40, designed for onshore, offshore, marine and heavy industrial applications. Can also be used in conjunction with Bracket Pole Clamp Adaptor XF40 EX for pole mounting. It features a swivel movement of pan ±90° and tilt ±45° and its weight is 2.5 kg.	\$ 899.00
EX WALL MOUNT XF60	01171-001	Electro-polished 316L stainless steel wall mount for XF60, designed for onshore, offshore, marine and heavy industrial applications. Can also be used in conjunction with Ex pole mount XF40, for pole mounting. It features a swivel movement of pan ±90° and tilt 60° down.	\$ 999.00
EX WALL MOUNT XP40	5507-211	Electro-polished 316L stainless steel wall mount for XP40, designed for onshore, offshore, marine and heavy industrial applications. Weight 14 kg.	\$ 799.00
EX POLE MOUNT XF40	5507-221	Pole mounting explosion protected fixed network cameras is made simple using this electro-polished 316L stainless steel Ex Pole mount XF40, accompanied by the requisite Ex Wall Mount XF40. The Ex Pole Mount XF40 is specifically designed to mount Ex Wall Mount XF40 to poles of a diameter from 90mm to 120mm. Weight 4.2 kg.	\$ 599.00
WALL MOUNT D201-S XPT	01521-001	316L Stainless steel wall mount for use with D201-S AXIS Q6055 explosion-protected camera.	\$ 449.00
POLE MOUNT D201-S XPT	01522-001	316L Stainless steel pole mount adapter for the D201-S AXIS Q6055 explosion-protected camera. To be used together with Wall Mount D201-S.	\$ 749.00
CORNER MOUNT D201-S XPT	01571-001	316L Stainless steel corner mount adapter for the D201-S AXIS Q6055 explosion-protected camera. To be used together with Wall Mount D201-S.	\$ 999.00
WALL MOUNT F101 XF	01721-001	Stainless steel (316L) wall mount for F101-A XF explosion-protected cameras. Compatible with Pole Mount D201-S XPT and Corner Mount D201-S XPT.	\$ 749.00
EXCAM XF WIPER BLADE 10 PACK	01930-001	Replacement wiper blade for ExCam XF Q1785. Natural black rubber, 54mm, 10-pack.	\$ 189.00

WALL MOUNT D101-A XF	01969-001	316L Stainless steel wall mount for horizontal mounting of D101-A XF P3807. Can also be used as ceiling mount for D101-A XF P3807 and D201-S XPT Q6055.	\$ 749.00
FRONT GLASS PROTECTIVE FILM F101-A	02029-001	Plastic protective film for the front glass of the F101-A explosion-protected cameras. For use in highly corrosive atmospheres like hydrogen fluoride (HF) gas. Set of 5.	\$ 149.00
AXIS 1.5" NPS/NPT MALE COUPLER	01706-001	1.5" NPT Male-to-Male coupler used to connect any AXIS Pendant Kit (e.g.: AXIS T94A01D) to a legacy mount with Female NPT or NPS thread (e.g.: 3rd party wall mount). Useful in retrofitting legacy cameras in existing installations. Lock nut included. Material:Aluminum with black anodizing. Note: The National Pipe Taper (NPT) is a U.S. standard for tapered threads used on threaded pipes and fittings. The National Pipe Straight (NPS) threads are straight (parallel). Both NPT and NPS have the same thread angle, shape, and pitch (threads per inch).	\$ 35.00
M10 STAND EXTENSION 10CM 10PCS	5502-701	AXIS M10-series 10 cm stand extension. 10 pcs. Cable clip included.	\$ 29.00
ACC RACK HOLDER 2400/2401 EUR	19273	19" Rack mount holder for up to 8 2401/2400 Video Servers.	\$ 449.00
AXIS T8640 WALL MOUNT BRACKET	5026-411	Wall mount bracket for AXIS T8640 Ethernet over Coax adapter base or device unit.	\$ 25.00
AXIS T8640 DIN RAIL CLIP	5026-431	DIN rail clip for AXIS 8640 Ethernet over Coax adapter.	\$ 22.00
AXIS T8642 MOUNTING KIT A	5506-291	Kit for mounting an AXIS T8642 e.g. inside an AXIS Q8414-LVS. Kit contents: cable tie 432mm (17 in) long, BNC male to female angled adapter and network cable 135 mm (5.3 in) long.	\$ 14.00
AXIS T8640 RACK MOUNT BRACKET	5026-421	Rack mount bracket for AXIS T8640 Ethernet over Coax adapter (8 units in 1U).	\$ 62.00
AXIS T91A02 DIN RAIL CLIP 77MM	5017-027	DIN rail clip for AXIS Q7401, AXIS P8221 and AXIS 7701.	\$ 12.00
AXIS T91A02 DIN RAIL CLIP 86MM	5017-028	DIN rail clip for AXIS M7014 and AXIS P7214	\$ 12.00
AXIS T91A03 DIN RAIL MOUNT	5503-194	DIN rail clip for AXIS Q7424-R.	\$ 19.00
AXIS T91A04 CAMERA HOLDER ¾" NPS	5017-041	Holding device for pendant mounted cameras. For use with ¾" pipes with NPS or NPT threading. Compatible with all cameras with standard tripod threading.	\$ 29.00
AXIS T91A05 CAMERA HOLDER 1.5" NPS	5017-051	Holding device for pendant mounted cameras. For use with 1,5" pipes with NPS or NPT threading. Compatible with all cameras with standard tripod threading.	\$ 29.00
AXIS T91A06 PIPE ADAPTER 3/4-1.5"	5503-091	Pipe adapter step up from ¾" NPT thread to 1.5" NPS thread. Compatible with all pendant kits that are made for the AXIS T91A range of brackets.	\$ 12.00
AXIS T91A10 MOUNTING KIT	5507-331	Plastic mounting kit with stand and clamp for flexible mouting of Axis products with tripod thread.	\$ 19.00
AXIS T91A11 STAND WHITE	5017-111	Plastic camera stand. Original stand for the AXIS M11-series.	\$ 15.00

AXIS T91A13 THREADED CEIL MOUNT 10P	01464-001	10-pack threaded ceiling mount for quick installation under ceiling tiles. Compatible with cameras with standard 1/4"-20 UNC tripod thread. Total length 80mm (3") with thread length 65mm (2.5"). Threaded rod in nylon, counter nut with friction pad. 10-piece bulk pack.	\$ 39.00
AXIS T91A23 TILE GRID CEIL MNT 4P	01612-001	4-pack of ceiling mount accessory for mounting Axis cameras and stands on a variety of drop-ceiling tile grid system. Compatible with Axis Safety Wire. Color: Axis white. Bulk pack. Suitable tile grid (T-bar) dimensions: 15mm(0.6in)/24mm(0.9in)/35mm(1.4in). Suitable ceiling tiles type: square-edge, tegular edge.	\$ 79.00
AXIS T91A33 LIGHT TRACK MNT 4P	01467-001	4-pack of lighting track mounts. Color: white. Compatible with universal 3-circuit lighting track systems and selected linear trunking systems. Compatible with a wide range of Axis cameras and camera stands.	\$ 79.00
AXIS T91A33 LIGHT TRACK MNT BLK 4P	01474-001	4-pack of lighting track mounts. Color: black. Compatible with universal 3-circuit lighting track systems and selected linear trunking systems. Compatible with a wide range of Axis cameras and camera stands.	\$ 79.00
AXIS T85 RACK MOUNT KIT A	01232-001	Rack mount kit for AXIS T8508 PoE+ Network Switch	\$ 29.00
AXIS T91B21 STAND BLACK	5506-621	Black aluminum stand for wall or hard ceiling mount. A cable hole in the base of the stand makes it possible to hide the hole in the wall out of which the cable is routed. A snap on cover gives a clean look without visible screws. Compatible with all standard tripod thread cameras e.g. AXIS M11, P13, Q16 series.	\$ 29.00
AXIS T91B21 STAND WHITE	5506-611	White aluminum stand for wall or hard ceiling mount. A cable hole in the base of the stand makes it possible to hide the hole in the wall out of which the cable is routed. A snap on cover gives a clean look without visible screws. Compatible with all standard tripod thread cameras e.g. AXIS M11, P13, Q16 series.	\$ 29.00
AXIS T91A27 POLE MOUNT 10PCS	5503-971	Pole mount bracket compatible with all cameras with standard tripod threading (1/4"-20 UNC)	\$ 29.00
AXIS T91B47 100-410MM	01164-001	AXIS T91B47 Pole Mount for indoor and outdoor installations, for poles with diameter between 100-410 mm (4"-16"). Includes 1 pair of AXIS Stainless Steel Straps 1450mm (57") with TX30 screw interface for ease-of-installation. AXIS T91B47 is directly compatible with a wide range of Axis cameras.	\$ 85.00
AXIS T91B47 50-150MM	01165-001	AXIS T91B47 Pole Mount for indoor and outdoor installations, for poles with diameter between 50-150mm (2"-6"). Includes 1 pair of AXIS Stainless Steel Straps 570mm (22.5") with TX30 screw interface for ease-of-installation. AXIS T91B47 is directly compatible with a wide range of Axis cameras.	\$ 75.00

AXIS T91B57 POLE MOUNT 100-410MM	01470-001	Aluminum Pole Mount for indoor and outdoor installations, for poles with diameter between 100-410 mm (4"-16"). Includes 1 pair of AXIS Stainless Steel Straps 1450mm (57") with TX30 screw interface for ease-of-installation. AXIS T91B57 is compatible with mounts such as AXIS T91G61, T91H61, and AXIS T98A Surveillance Cabinet series. Color: Axis white.	\$ 115.00
AXIS T91B57 POLE MOUNT GREY	01446-001	Aluminum Pole Mount in Urban Grey color. For indoor and outdoor installations. Suitable for poles diameters between 100-410 mm (4"-16"). Includes 1 pair of AXIS Stainless Steel Straps 1450mm (57") with TX30 screw interface for ease-of-installation. AXIS T91B57 is compatible with mounts such as AXIS T91G61, T91H61, and AXIS T98A Surveillance Cabinet series.	\$ 139.00
AXIS T91B67 POLE MOUNT 65-165MM	01473-001	Outdoor-ready, powder-coated aluminum pole mount with 1.5" NPS thread for fixed dome pendant kits. Includes insect-proof cable gasket and 1 pair of stainless steel straps (with TX30 screw) for pole diameter between 65-165mm (2.5"-6.5"). White in color.	\$ 95.00
AXIS T91M47 POLE MOUNT	01149-001	Pole mount for our outdoor midspans and switch.	\$ 59.00
AXIS TD9301 OUTDOOR MIDSPAN POLE MOUNT	01951-001	AXIS TD9301 Outdoor Midspan Pole Mount for outdoor midspans, like AXIS 30W Outdoor Midspan.	\$ 59.00
AXIS T91D61 WALL MOUNT	5504-821	Chromated and powder coated aluminum wall mount with 1.5" NPS thread for fixed dome pendant kits. Cable routing from behind or through 3/4" conduit hole on the side. Includes mounting plate, pipe seal and conduit hole cover. Color: White	\$ 84.00
AXIS T91E61 WALL MOUNT	5506-481	Wall mount with internal cable canal for dome cameras with 1.5" NPS thread, compatible with Axis pendant kits. IK10 and NEMA 4X rated. Powder coated aluminum for indoor and outdoor installations.	\$ 39.00
AXIS T91G61 WALL MOUNT	5506-951	Aluminum wall mount with IP66 compartment to safely accommodate power and connectivity accessories (e.g. PoE midspan). IK10 and NEMA 4X rated in Axis white color. Includes a pre-terminated IP66 rated RJ45 connector. Compatible with wide range of Axis cameras, incl. AXIS M55, P56, Q37, Q60, Q61 Series.	\$ 199.00
AXIS T91G61 WALL MOUNT GREY	01444-001	Aluminum wall mount with IP66 compartment to safely accommodate power and connectivity accessories (e.g. PoE midspan). IK10 and NEMA 4X rated in Urban Grey color to match AXIS Q62 series. Includes a pre-terminated IP66 rated RJ45 connector. Compatible with wide range of Axis cameras.	\$ 229.00
AXIS TS2901 APPLIANCE STAND	02035-001	AXIS TS2901 Appliance Stand is a stand compatible with AXIS S2208 and AXIS S2212 Appliances which allows the unit to be mounted vertically, on a table or shelf. The appliance is secured to the stand with the 4 included screws. Mounted vertically, the appliance will take even less space than it usually does, leaving more space for other activities. The stand itself can be screwed to the table/shelf, which is a simple way to secure the appliance against light thefts and from falling. It can also lie on the table, when using the included rubber feet.	\$ 39.00

AXIS T91H61 WALL MOUNT	5507-641	AXIS T91H61 Wall Mount is designed with a built-in RJ45 cable and connection to, and spacious compartment for connectivity accessories such as midspans and media converters. The wall mount is impact-resistant (IK10) and weather-resistant (IP66, NEMA 4X) for indoor and outdoor use. The 1.5" NPS thread mount ensures compatibility with all pendant kits for Axis fixed dome cameras.	\$ 175.00
AXIS T91F61 WALL MOUNT STAINLESS STEEL	5506-681	Wall mount for AXIS Q3505-SVE, made of stainless steel.	\$ 399.00
AXIS T91L61 WALL-AND-POLE MOUNT	5801-721	Wall-and-Pole Mount for Axis PTZ and multi-sensor cameras. Built-in Ethernet cable with an IP66 RJ45 connector for quick installation with protection against dust and water. Connect PoE via either RJ45 or IDC (insulation-displacement contact) connectors. Suitable for both indoor and outdoor environments. Separate stainless steel straps required for pole installation.	\$ 99.00
AXIS T91K61 WALL MOUNT	5901-401	Marine-grade stainless steel wall mount for AXIS Q6055-S PTZ Network Camera. Compatible with stainless steel pole mount (sold separately).	\$ 399.00
AXIS T94J01A WALL MOUNT	5901-331	Aluminum wall mount for Axis positioning cameras and positioning units. Robust and impact-resistant. Compatible with Axis ACI 3/4" conduit adapters, and offers multiple cable entries. Cables can be routed through the back or, by using a conduit connection, from each side or from the bottom. Suitable for indoor and outdoor use.	\$ 199.00
AXIS T94J01A WALL MOUNT GREY	01445-001	Robust and impact-resistant aluminum wall mount for selected Axis PTZ and positioning cameras. Multiple cable entry points for 3/4" (M25) conduit pipes. Suitable for indoor and outdoor use. Color: Urban Grey.	\$ 229.00
AXIS T91D62 TELESCOPIC PARAPET MNT	5507-271	Made for parapet and wall installations. Telescopic arm with adjustable length between 783 mm (30.1 in) to 1033 mm (40.7 in) for compensating different parapet thicknesses or obstructive elements on the facade of the building. It can Swivel round its own axis 180 degrees, allowing mounting/maintain the camera easily and safely from the rooftop. The mount is intended for outdoor fixed and PTZ dome cameras supporting 1.5" NPS thread. A retrofit mounting bracket (optional accessory) makes it possible to reuse holes drilled for Pelco's PTZ dome parapet mount.	\$ 349.00
AXIS T91D62 ADAPTER MOUNTING BRACKET	5507-501	Retrofit adapter mount bracket for re-using holes drilled from Pelco's PTZ dome parapet mount, or for increasing the attachment area towards the parapet.	\$ 59.00
AXIS T91B62 PARAPET MOUNT	5504-631	Chromated and powder coated aluminum parapet mount compatible with fixed dome pendant kits and AXIS P55-series and AXIS Q60-series PTZ dome cameras. Cable routing from behind or through 3/4" conduit hole on the side. Includes mounting plate, pipe seal, conduit hole cover and AXIS T94A01D Pendant Kit for PTZ dome cameras. Color: White	\$ 189.00

AXIS T91B50 TELESCOPIC CEIL MNT	5507-451	Indoor/outdoor telescopic ceiling mount. Expands between 1 m (39") and 2 m (79"). Features a swivel action to prevent breaking if hit by forklifts or high vehicles. Can be mounted on a sloped ceiling. Accessory extension pipes (Not included) for a maximum length of 5 m (197"). Compatible with all Axis pendant kits featuring a 1,5" NPS thread and the AXIS T91A05 Camera holder for fixed cameras.	\$ 199.00
AXIS T91B51 CEILING MOUNT	5507-461	The indoor/outdoor ceiling mount is ideal for low ceiling installations such as parking houses, with swivel action to prevent breaking if hit. Can be mounted in a sloped ceilings/soffits to compensate angles up to 45 degrees. Available accessory extension pipes (Not included) of 30 cm (12") or 1 meter (39") to enable correct camera height for the specific environment. Compatible with all Axis pendant kits featuring a 1,5" NPS thread and the AXIS T91A05 Camera holder for fixed cameras.	\$ 119.00
AXIS T91B52 EXTENSION PIPE 30 CM	5507-491	Extension pipe for AXIS T91B50 and AXIS T91B51. Length 30 cm (12").	\$ 34.00
AXIS T91B52 EXTENSION PIPE 100 CM	5507-481	Extension pipe for AXIS T91B50 and AXIS T91B51. Length 100 cm (39").	\$ 49.00
AXIS T91B53 TELESCOPIC CEIL MNT 2P	01189-001	Twin-pack (bulk). Includes 2x indoor telescopic ceiling mounts, extendable between 1m to 1.8m (3.2 to 6ft) at 10cm (4") intervals. Compatible with Axis pendant kits and camera holder with 3/4" conduit interface. Suitable for vertical and horizontal mounting.	\$ 169.00
AXIS T91B63 CEILING MOUNT	5504-641	Chromated and powder coated aluminum ceiling mount 75 cm / 29.5 inch compatible with fixed dome pendant kits and AXIS P55-series and AXIS Q60-series PTZ dome cameras. Cable routing from behind or through 3/4" conduit hole on the side. Includes mounting plate, pipe seal, conduit hole cover and AXIS T94A01D Pendant Kit for PTZ dome cameras. Color: White	\$ 119.00
AXIS T91A64 BRACKET CORNER	5017-641	Corner Bracket. Requires AXIS T91A61 Wall Bracket. AXIS P55-series, AXIS Q60-series PTZ Dome Network Cameras, AXIS P33 Series Pendant kit, AXIS P33-VE Series Pendant kit, AXIS 225 Pendant kit and AXIS 216/P3301 Pendant kit. White.	\$ 79.00
AXIS T91F67 POLE MOUNT STAINLESS STEEL	5506-691	Pole mount bracket for AXIS Q35-SLVE stainless steel cameras. Compatible with AXIS T91F61 Wall mount. Made of marine-grade stainless steel. Includes 1 pair marine-grade (SS316L) stainless steel straps with TX30 screw interface for ease-of-installation. Straps length 1450mm (57"), suitable for pole diameter range 100-410mm (4"-16").	\$ 139.00
AXIS T91A6 PIPE SEAL 1PCS	5503-781	Pipe seal for AXIS T91A6, to protect from dust, water and bugs.	\$ 11.00
AXIS T93C WALL-POLE CONDUIT BACKBOX	5901-421	Aluminum conduit back box for wall or pole mount. Space for outdoor power supply, and electrical connection boxes. Steel straps for pole mount are sold separately. Recommended to use with POWER SUPPLY PS24 240W (not included).	\$ 199.00
AXIS T94A01C ATTACHMENT KIT	5901-301	For attaching AXIS Q61 PTZ network camera to AXIS Q6000-E MkII PTZ network camera.	\$ 99.00

AXIS T94A01D PENDANT KIT	5502-431	Pendant kit for the AXIS Q60-series and AXIS P55-series PTZ Network Cameras, enables mount on standard '1,5" NPT threaded brackets. White.	\$ 49.00
AXIS T94A02D PENDANT KIT	5901-411	Marine-grade stainless steel pendant kit for AXIS Q60-S with 1.5" NPT male thread.	\$ 129.00
AXIS T94A01F CEILING BRACKET	5506-181	Bracket for mounting an AXIS P56 Series camera in a hard ceiling. For indoor and outdoor installations. 3/4" conduit hole, compatible with ACI adapters.	\$ 29.00
AXIS T94A02F CEILING BRACKET	5801-601	Aluminum ceiling bracket for Axis PTZ cameras and AXSI Q37 Series for indoor or outdoor use. 3/4" conduit hole on the side.	\$ 49.00
AXIS T94A01L RECESSED MOUNT	5505-721	Outdoor recessed mount for AXIS Q60-E cameras. Can be mounted in panels, wood or pre-made holes solid concrete. The mount is very sturdy and made of aluminum and stainless steel. It supports the IK10 impact rating of the camera and has two 3/4" conduit holes for a plenum rated and rodent safe installation.	\$ 249.00
AXIS T94A02L RECESSED MOUNT	5506-171	Outdoor recessed mount for AXIS P56 cameras. Also suitable indoor for recessed camera installations in plenum as the back box is made of metal and has a 3/4" hole for cable protection conduits.	\$ 139.00
AXIS T94A03L RECESSED MOUNT	5506-841	Recessed mount for AXIS P5514/-E and P5515/-E cameras. Also suitable indoor for recessed camera installations in plenum as the back box is made of metal and has a 3/4" hole for cable protection conduits.	\$ 139.00
AXIS T94A04L RECESSED MOUNT	5801-611	Indoor and outdoor recessed mount for AXIS Q61 Series. Suitable indoor for recessed camera installations in air handling spaces as the back box is made of metal and has a 3/4" hole for cable protection conduits.	\$ 139.00
AXIS T94B02D PENDANT KIT 10PCS	01159-001	Pendant kit for wall mount or ceiling mount. Compatible with Axis mounting accessories with 1.5" NPS thread. 3/4" threaded pipes can also be used with a nut for securing. Compatible with the small form factor of AXIS M20, M31-LV/-LVE, M30-V/-WV and Companion dome cameras. 10-pack.	\$ 199.00
AXIS T94B02D PENDANT KIT	5507-361	Pendant kit for wall mount or ceiling mount. Compatible with Axis mounting accessories with 1.5" NPS thread. 3/4" threaded pipes can also be used with a nut for securing. Compatible with the small form factor of AXIS M20, M31-LV/-LVE, M30-V/-WV and Companion dome cameras. Single pack.	\$ 29.00
AXIS T94B02D PENDANT KIT BLACK	01185-001	Pendant kit for wall mount or ceiling mount in black. Compatible with Axis mounting accessories with 1.5" NPS thread. 3/4" threaded pipes can also be used with a nut for securing. Compatible with the small form factor of AXIS M20, M31-LV/-LVE, M30-V/-WV and Companion dome cameras. Single pack.	\$ 29.00
AXIS T94B05L RECESSED MOUNT	01150-001	Indoor recessed mount for drop ceiling installation. The aluminum casing makes it suitable for use in air handling spaces. Compatible with AXIS M3044-V/M3045-V/M3046-V/M3047-V/M3048-V.	\$ 69.00

AXIS T94B03L RECESSED MOUNT	5801-861	Indoor recessed mount for drop ceiling installations. The aluminum casing makes it suitable for use in air handling spaces. Compatible with AXIS M2025/26 and AXIS Companion Bullet.	\$ 69.00
AXIS T94B02M J-BOX/GANG BOX PLATE	5801-421	Bracket for mounting a camera on a 4" square, 4" octagon, single or double-gang junction box. Compatible with AXIS M3044-V/M3045-V/M3046-V.	\$ 24.00
AXIS T94B01P CONDUIT BACK BOX	5507-401	Conduit back box for 1/2" or M20 pipes. Features the 1/2" ACI interface to enable use of ACI adapters. There is an integrated female tripod thread for use of standard camera stands or holders. Compatible with AXIS M3044-V/M3045-V/M3046-V.	\$ 19.00
AXIS T94B01S MNT BRACKET BLACK 10PCS	5504-531	Black mount bracket for mounting on standard tripod threading (1/4"-20 UNC) or single-gang junction box. Compatible with AXIS M3004-V/5-V.	\$ 49.00
AXIS T94B01S MNT BRACKET WHITE 10PCS	5503-911	White mount bracket for mounting on standard tripod threading (1/4"-20 UNC) or single-gang junction box. Compatible with AXIS M3004-V/5-V.	\$ 49.00
AXIS T94C01L RECESSED MOUNT	01242-001	Indoor recessed mount for drop ceiling installations. Single-screw ceiling attachment for quick and easy installation. Not suitable for air-handling (plenum) spaces. Compatible with AXIS M42 series and AXIS Companion Dome mini LE.	\$ 39.00
AXIS T94C01M J-BOX/GANG BOX PLATE	01243-001	Bracket for mounting camera on 4" square, 4" octagon, single or double-gang junction box. Compatible with AXIS M42 Series and AXIS Companion Dome mini LE.	\$ 29.00
AXIS T94C01U UNIVERSAL MOUNT	01244-001	Versatile 4-in-1 mount accessory for use as either a pendant kit with 3/4" (M25) conduit interface, conduit back box with 1/2" (M20) conduit side entry, pole mount, or standard camera thread. Compatible with AXIS M42 series and AXIS Companion Dome mini LE. Pole mounting straps available separately.	\$ 29.00
AXIS T94D01S MT BRACKET FL WT 10PCS	5504-911	White plastic adapter for mounting AXIS P3904-R and AXIS P3905-R on flat surfaces. Does not fit with AXIS P3915-R. Used when the cable must enter from the side. 10 pack.	\$ 29.00
AXIS T94D02S MT BRACKET CU WT 10PCS	5504-921	White plastic adapter for mounting AXIS P3904-R, AXIS P3905-R and AXIS P3915-R on curved surfaces. 10 pack.	\$ 29.00
AXIS T94F01D PENDANT KIT	5503-881	Indoor pendant kit for AXIS M3006/7, AXIS M3024-LVE/3025-VE/3026-VE. to enable use of AXIS T91A Brackets or 1.5"(NPT or NPS threaded) pipes. The camera network cable fits into the product and a RJ45 network cable coupler is included.	\$ 39.00
AXIS T94F02D PENDANT KIT	5900-021	Outdoor pendant kit for M3024-LVE/M3025-VE, P14 Series, to enable use of AXIS T91A Brackets or 1.5"(NPT or NPS threaded) pipes.	\$ 39.00
AXIS T94F01L RECESSED MOUNT	5503-901	Indoor recessed mount for drop ceiling installations. RJ45 network cable coupler included. Compatible with AXIS M3006-V/M3007-PV,AXIS M3024-LVE/M3025-VE/M3026-VE.	\$ 89.00

AXIS T94F01M J-BOX/GANG BOX PLATE	5503-921	Bracket for mounting on 4" square, 4" octagon, single or double-gang junction box. RJ45 network cable coupler included. Compatible with. Compatible with AXIS M3006/7, AXIS M3024-LVE/3025-VE/3026-VE, P14 Series.	\$ 29.00
AXIS T94F01P CONDUIT BACK BOX	5504-041	Backbox for AXIS M3006-V, AXIS M3007-P/-PV, AXIS M3024-LVE/3025-VE/3026-VE/3027-PVE, P14 Series, which enables safe cabling through 1/2" (M20) conduits.	\$ 29.00
AXIS T94G01P CONDUIT BACK BOX	5505-181	Back box for 3/4" (M25) conduits/cable protection pipes. Compatible with AXIS Q1765-LE and AXIS Q1931-E.	\$ 29.00
AXIS T94H01P CONDUIT BACKBOX	5034-111	Vandal resistant aluminum back box accessory for AXIS P33-/V series indoor cameras (except P3301/04) which enables safe cabling through 3/4" conduits.	\$ 39.00
AXIS T94K01D PENDANT KIT	5505-081	Indoor pendant kit for AXIS P32-V Series- AXIS P33-/V and AXIS Q3505-V, compatible with Axis ceiling-/wall mounts, AXIS T91A67 Pole mount and 1.5" NPS threaded pipes.	\$ 39.00
AXIS T94M01D PENDANT KIT	5505-091	Outdoor pendant kit for AXIS Q3505-VE compatible with Axis ceiling-/wall mounts, AXIS T91A67 Pole mount and 1.5" NPS threaded pipes.	\$ 59.00
AXIS T94M02L RECESSED MOUNT	01156-001	Outdoor recessed mount for mid-size outdoor dome cameras such as: AXIS P32-VE/-LVE, P33-VE/-LVE and Q35-VE/-LVE series. Suitable for outdoor installations in roof overhangs and soffits. Also suitable for indoor installations in plenum spaces.	\$ 109.00
AXIS T94M02D PENDANT KIT	5507-511	AXIS T94M02D comprises a weather shield and a mounting adapter for AXIS P3707-PE Network Camera. The mounting adapter is compatible with 1.5-inch NPS thread. The kit enables AXIS P3707-PE to be mounted on poles, parapets and outer corners using many AXIS T91 mounting accessories.	\$ 99.00
AXIS T94N01D PENDANT KIT	01513-001	AXIS T94N01D Pendant Kit comprises a weathershield and a mounting adapter for AXIS P3717-PLE Network Camera. The mounting adapter is compatible with 1.5-inch NPS thread. The kit enables AXIS P3717-PLE to be mounted on walls, poles, parapets and outer corners using AXIS T91 mounting accessories.	\$ 89.00
AXIS T94N02D Pendant Kit	02076-001	AXIS T94N02D Pendant Kit comprises a weathershield and a mounting adapter for AXIS P3715-PLVE Network Camera. The mounting adapter is compatible with 1.5-inch NPS thread. The kit enables AXIS P3715-PLVE to be mounted on walls, poles, parapets and outer corners using AXIS T91 mounting accessories.	\$ 69.00
AXIS T94N01G POLE MOUNT	5901-341	Stainless steel pole mount designed for use with heavier Axis products such as positioning cameras and positioning units. IK10. Includes 3pcs stainless steel straps included for pole diameter 60-400mm (2.4-15.7in) and sealing gaskets for multiple cable entries with protection against insect infestation.	\$ 199.00
AXIS T94N01L RECESSED MOUNT	01514-001	Indoor and outdoor recessed mount for discreet installations in drop ceilings, roof overhangs/soffits of AXIS P37 network camera series. Also suitable for installations in plenum space, as the back box is made of metal with a 3/4" hole for cable protection conduits.	\$ 119.00

AXIS T94P01B CORNER BRACKET	5504-711	Corner mount for AXIS P5414-E/15-E, AXIS Q1765-LE, AXIS Q1931-E and AXIS P33-VE series.	\$ 79.00
AXIS T94P01L RECESSED MOUNT	01172-001	Indoor and outdoor recessed mount for AXIS M55 Series. Suitable for air-handling spaces in indoor installations as the enclosure is made of metal and has a 3/4" (M25) conduit hole for protected cable-routing. UL-approved.	\$ 99.00
AXIS T94Q01A WALL MOUNT	5505-241	Wall mount compatible with all Axis outdoor fixed box cameras and housings. Corrosion tested according to NEMA 4X, UL listed and IK10 rated.	\$ 44.00
AXIS T94Q01F CEILING AND COLUMN MNT	5507-591	The powder-coated aluminum AXIS T94Q01F for AXIS fixed box outdoor ready cameras and housings, can be used for both ceiling/soffit and column/parapet installations. This allows Axis' fixed camera housings to be mounted under hard surfaces such as ceilings, beams, soffits and canopies. It can also be mounted on pole or column tops, parapets and other horizontal building structures. Re-direction and maintenance of the camera is easy thanks to the swivel arm feature. The cable is routed through the pipe, and is never exposed to weather or potential vandalism. Cable conduits and Axis' conduit adapters (3/4" dimension) are used for cable protection when routed from the side.	\$ 109.00
AXIS T94R01B CORNER BRACKET	5507-601	The powder-coated aluminum AXIS T94R01B Corner Bracket is used for attaching the wall mount of Axis' camera housing to the outer corners of a building. AXIS T94R01B Corner Bracket is compatible with AXIS T91E61 Wall Mount for fixed dome cameras. Small-size fixed dome and bullet-style cameras can also be mounted, thanks to the included and commonly used hole pattern of a single gang junction box.	\$ 59.00
AXIS T94R01P CONDUIT BACK BOX	5505-141	Back box to enable external cable entry or use of cable protection equipment. Hole for 3/4 inch conduits or M25 cable protection pipes. Compatible with AXIS T94Q01A Wall mount, all AXIS M11-E/P13-E/Q16-E/Q1755-E/Q1910-E/21-E/22-E outdoor fixed box camera wall mounts and AXIS T92E Series and AXIS T93E05 Fixed camera housings.	\$ 34.00
AXIS T94S01L RECESSED MOUNT	5507-671	Indoor recessed mount for drop ceiling installations. Single-screw ceiling attachment for quick and easy installation. Not suitable for air-handling (plenum) spaces. Compatible with AXIS P32-V/-LV series.	\$ 42.00
AXIS T94S01L RECESSED MOUNT 10P	5901-361	Indoor recessed mount for drop ceiling installations. Single-screw ceiling attachment for quick and easy installation. Not suitable for air-handling (plenum) spaces. Compatible with AXIS P32-V/-LV series. 10-pack.	\$ 399.00
AXIS T94S02L RECESSED MOUNT	01462-001	Indoor recessed mount for ceiling/wall installations. Compatible with AXIS M3057/58-PLVE cameras. Single-screw ceiling attachment for quick and easy installation. Not suitable for air-handling (plenum) spaces.	\$ 49.00

AXIS T94S01P CONDUIT BACK BOX	01190-001	Outdoor-ready, impact resistant (IK10+) back box with sealed compartment (IP66/67) for secure storage of connectivity devices. 3/4" / M25 conduit interface from both side and back. Can be mounted directly behind a wide range of Axis network cameras. Includes a network cable and extra gaskets.	\$ 119.00
AXIS T94T01D PENDANT KIT	5505-871	Outdoor pendant kit for AXIS P32-VE Series, compatible with Axis ceiling-/wall mounts, AXIS T91A67 Pole mount and 1.5" NPS threaded pipes.	\$ 49.00
AXIS T94T02D PENDANT KIT	01461-001	Outdoor pendant kit for AXIS M30-PLVE Series. Weathershield made from impact-, UV-, and heat-resistant polymer. Compatible with wide range of Axis mounts with 1.5" NPS threaded interface.	\$ 49.00
AXIS T94U01D PENDANT KIT	5506-651	Pendant kit for AXIS Q3505-SVE, without weather shield, mainly for indoor use made of stainless steel.	\$ 379.00
AXIS T94U02D PENDANT KIT	5506-661	Outdoor pendant kit with weather shield for AXIS Q3505-SVE, made of stainless steel.	\$ 419.00
AXIS T94V01C DUAL CAMERA MOUNT	01457-001	AXIS T94V01C Dual Camera Mount allows back-to-back installation of two Axis cameras for panoramic coverage. Compatible with a wide range of Axis dome cameras, box cameras, and bullet cameras. Compatible with Axis mounting accessories with 1.5" NPS threaded interface, for mounting on walls, poles, and under ceilings. AXIS T94V01C is IK10 rated for impact resistance, which safeguards it against vandalism. Suitable for both indoor and outdoor use. Note: To ensure physical stability, do not use AXIS T94V01C for single camera installations.	\$ 99.00
AXIS T94V02D PENDANT KIT	01505-001	Outdoor pendant kit for AXIS P38-PVE and Q36-VE series. Weathershield made from impact-, UV-, and heat-resistant polymer. Compatible with wide range of Axis mounts with 1.5" NPS threaded interface.	\$ 89.00
AXIS T94V01D PENDANT KIT	5801-431	Pendant kit for indoor and outdoor use for the AXIS Q36-VE Series compatible with Axis ceiling-/wall-/pole mounts with 1.5" NPS thread.	\$ 89.00
AXIS T94V01L RECESSED MOUNT	5801-441	Recessed mount for indoor and outdoor use for the AXIS Q36-VE and AXIS P38 Series. It has a metal back box with 3/4" (M25) conduit hole (for protected cable runs) and is suitable for installation in plenum (air-handling) spaces.	\$ 109.00
AXIS T95A64 BRACKET CORNER	5010-641	Corner bracket for AXIS T98A-VE Surveillance Cabinet and AXIS Positioning Cameras. When used with AXIS Positioning Cameras, AXIS T94J01A Wall Mount is required.	\$ 89.00
AXIS T95A67 BRACKET POLE	5010-671	Pole bracket for AXIS T98A-VE Surveillance Cabinet. No straps required.	\$ 129.00
ADAPTER CURV L GREY M311X 10PCS	5503-061	Optional light grey adapter for mounting AXIS M311X on curved surfaces. 10 pack	\$ 29.00
WALL MOUNT AXIS PS24	5000-011	Metal box to mount AXIS PS24 to a wall.	\$ 79.00
AXIS PS-24 Pole bracket	21764	Outdoor pole mount bracket for PS-24 and AXIS T97A10. Requires the Wall Mount AXIS PS-24 (5000-011) and a mounting tool for straps (21776 or similar).	\$ 45.00

AXIS T91A03 DIN RAIL CLIP 5PCS	5800-511	The clip, made of steel, enables mounting on a standard 35mm DIN rail. It includes 2 cable ties. Compatible with AXIS T8120/T8133 midspans and AXIS T8604 / T8605 converters. Weight: 17 g (0.6 oz.). 5-pack.	\$ 19.00
AXIS MIDSPAN DIN CLIP A	5503-931	Din clip for AXIS midspan T8123, T8124 and T8125	\$ 19.00
P1214/-E MOUNT KIT INC HOUS 5-P	5800-431	Original mounting kit for AXIS P1214/-E. Kit contents: sensor unit housing, flush wall mount bracket. 5 pack.	\$ 99.00
P1214/-E MOUNT KIT EXC HOUS 5-P	5800-461	Mounting kit for AXIS P1204/E. Kit contents: Flush mount wall bracket. 5 pack.	\$ 29.00
STAND M10 SERIES 7CM	5700-481	Plastic stand for the AXIS M10-series	\$ 13.00
AXIS P33 MOUNTING BRACKET	5502-401	Mounting bracket for AXIS P33-V/-LV indoor cameras. For mounting cameras on junction boxes (4" square, 4" octagon, single-gang, or double-gang), and other Axis mounting accessories. Also compatible with selected AXIS M30 and P32 cameras.	\$ 29.00
AXIS P33XX-VE 3/4" NPS CONDUIT ADAPTER	5503-711	Aluminum cable cover with stainless steel adapter used for mounting 3/4" NPS or NPT pipes to AXIS P33XX-VE cameras for cable protection.	\$ 39.00
AXIS P33XX-VE 3/4" NPS COND ADPT 4P	5503-721	Aluminum cable cover with stainless steel adapter used for mounting 3/4" NPS or NPT pipes to AXIS P33XX-VE cameras for cable protection. Four complete units.	\$ 144.00
AXIS P33XX-VE 3/4" NPS ADAPT	5503-131	Stainless steel adapter used for mounting 3/4" NPS or NPT pipes to AXIS P33XX-VE cameras for cable protection.	\$ 29.00
AXIS RETROFIT KIT FOR T94S01L 4P	01982-001	Cover ring and holder for installing selected AXIS P32 cameras with legacy AXIS T94S01L Recessed Mount. Bulk pack with 4 sets of rings and clips to retrofit 4 cameras.	\$ 39.00
AXIS RETROFIT KIT T94K01L/02L 4P	02002-001	Retrofit into T94K01L or T94K02L. Mic hole for -LV cameras. Includes 4 sets of lid ring cover, gaskets, screws.	\$ 79.00
AXIS P33-VE Pendant Kit	5502-321	Pendant kit for selected AXIS P33-VE Fixed Dome Network Cameras, compatible with mounts with 1.5" NPT/NPS threaded interface. Color: Axis white	\$ 49.00
ADAPTER AXIS 209 TO M31/P39 50 PCS	5503-192	Adapter plate for mounting an AXIS M31 using the same foot print as the AXIS 209. 50 PCS	\$ 249.00
AXIS P33XX-VE CABLE COVER 4 PCS	5503-731	Aluminum cable cover for AXIS P33XX-VE cameras. 4 pcs.	\$ 59.00
AXIS ACI COND ADAP 3/4" U-SHAPE 30MM 5PCS	5505-191	Mechanical adapter that provides a U-shaped 30mm wide cable entry for use when a U-shape cable protection is required. The adapter is compatible with AXIS P54-series, AXIS P32-VE Series (requires AXIS ACI Mounting Bracket A), AXIS Q3505-VE, AXIS T91B6X mounts and AXIS AXIS T94R01P Conduit Back Box. 5 pcs.	\$ 24.00
AXIS ACI CONDUIT BRACKET A 5P	5505-971	Cable protection attachment bracket for AXIS P32-VE Series. Compatible with 3/4" Conduits, M25 pipes and AXIS ACI adapters. 5pcs.	\$ 39.00

AXIS ACI CONDUIT BRACKET B 5P	5506-041	Cable protection attachment bracket for AXIS P32-V Series. Compatible with 1/2" Conduits, M20 pipes and AXIS ACI adapters. 5pcs.	\$ 19.00
AXIS ACI CONDUIT ADAPTER 1/2"-3/4" A 2P	5505-541	Step up ACI adapter for attaching 3/4" conduits or M25 pipes to AXIS products with a 1/2" conduit interface such as AXIS P32-V series (requires AXIS ACI conduit bracket B) and AXIS Q3505-V. 2 pcs	\$ 39.00
AXIS ACI COND ADAP 1/2 " U-SHAPE 20MM 5P	5505-521	Mechanical adapter that provides a U-shaped 20mm wide cable entry for use when a U-shape cable protection is required. The adapter is compatible with AXIS products with a 1/2" conduit interface such as AXIS P32-V series (requires AXIS ACI conduit bracket B) and AXIS Q3505-V. 5 pcs	\$ 19.00
AXIS ACI COND ADAP 1/2"-3/4" NPS 2P	5505-591	Threaded stainless steel step up ACI adapter for attaching 3/4" NPS conduits to AXIS products with a 1/2" conduit interface such as AXIS Q35-V series. 2 pcs	\$ 69.00
AXIS ACI CONDUIT ADAPTER 3/4" NPS 2P	5505-641	Threaded stainless steel ACI adapter for attaching 3/4" NPS conduits to AXIS products with a 3/4" conduit interface such as AXIS Q35-VE series. 2 pcs	\$ 99.00
AXIS F8001 SURFACE MOUNT	5505-791	Bracket to mount and secure an F Series main unit onto a surface. Withstands vibrations and secures all cables to/from the main unit.	\$ 39.00
ACC PL ADAPTER CURVED AXIS M311X 10PCS	5502-551	Optional adapter for mounting AXIS M311X on curved surfaces. 10 pack	\$ 29.00
AXIS RACK SLIDE RAILS A	5504-781	Rack slides for AXIS Q7920 Video Encoder Chassis	\$ 69.00
AXIS F7308 CABLE BLACK 8M 4PCS	5506-921	AXIS F7308 comes in packs of four. 8-m (26 ft.) black cable with an RJ12 contact for connection to an AXIS F1004 Sensor Unit. Used as a spare part for the original cable that comes with AXIS F1004 Sensor Unit.	\$ 39.00
AXIS F8002 DIN RAIL CLIP	5505-801	DIN clip + angled mounting bracket. Allows an AXIS F Series main unit to be mounted on a DIN rail with the short side against the rail to minimize used space. Main unit can be mounted with cables going in any of three directions (up, down or out from the rail).	\$ 39.00
AXIS F8401 CLEAR LENS PROTECTOR 5PCS	5505-841	Lens protection for AXIS F1005-E. The lens protector is screwed onto the threaded front part of the sensor unit to protect the lens. Comes in pack of 5 units.	\$ 79.00
AXIS F8201 VARI-ANGLE MT BRACK 5PCS	5505-811	Mounting bracket for AXIS F1005-E, AXIS F1015 and AXIS 1035-E. Allows the sensor unit to be fixed and angled into various directions to get the desired view. Comes in pack of 5 pcs.	\$ 29.00
AXIS F8202 STRAIGHT MT BRACKET 5PCS	5505-821	Mounting bracket that allows the pinhole sensor unit of AXIS F1025 to be mounted onto a flat surface with the cone being flush with opposite surface. Comes in pack of 5 pcs.	\$ 29.00
AXIS F8203 FIXED MT BRACKET 5PCS	5505-831	Metal bracket for stable mounting of AXIS F1005-E, F1015 and F1035-E. Variety of holes for screws for flexible mounting. Comes in pack of 5 units.	\$ 149.00

AXIS F8204 MOUNTING BAND 10 PCS	5506-571	Stainless steel band for flexible mounting of AXIS F Series Sensor units and AXIS P12 sensor units. Sold in 10-pack. 10 x M20 x 1.5 nuts to lock the band to the sensor unit are included. Works with all AXIS P12 Sensor Units and all AXIS F Series Sensor units except AXIS F1015.	\$ 39.00
AXIS F8206 PINHOLE MT BRACKET 5PCS	5507-621	Mounting bracket that allows AXIS F1004 Pinhole Sensor Unit and the sensor unit for AXIS P1264 to be mounted behind a thin metal/plastic/glass panel. Comes in pack of 5 pcs.	\$ 29.00
AXIS F8211 PINHOLE TRIM RING 10PCS	5507-101	Trim ring for discreet mounting of AXIS F1025 Sensor Unit behind a thin surface. 10 PCS.	\$ 59.00
AXIS F8212 TRIM RING 10PCS	5507-111	Trim ring for discreet mounting of AXIS F1005-E, F1035-E, P1214-E and P1224-E behind a surface. 10 PCS.	\$ 99.00
AXIS F8224 RECESSED MOUNT 4PCS	5506-511	AXIS F8224 Recessed Mount (4 pieces). Recessed mount accessory for use with AXIS F1004 Sensor Unit. Can be mounted in a ceiling.	\$ 59.00
AXIS F8205 BULLET ACCESSORY	5506-211	Bullet-style camera accessory for AXIS F1005-E. AXIS F1005-E provides 113° horizontal FOV. Comes with c-clamp and a stand.	\$ 24.00
AXIS F8215 VARIFOCAL BULLET ACC	5506-221	Varifocal bullet-style camera accessory for AXIS F1015. AXIS F1015 provides 58-108° horizontal FOV. Comes with c-clamp and a stand.	\$ 24.00
AXIS F8225 PINHOLE ACCESSORY	5506-531	Discreet accessory for ceiling mount of AXIS F1025 (pinhole). AXIS F1025 provides 92° horizontal FOV. Used to get overview of rooms or of a door. Can easily be repainted to fit ceiling color.	\$ 39.00
AXIS F8235 FISHEYE ACCESSORY	5506-541	Discreet accessory to mount a AXIS F1035-E in a ceiling. Perfect for overview in small rooms or in parts of a larger room. Can easily be repainted to fit ceiling color.	\$ 39.00
AXIS F92A01 BLACK HEIGHT S. HOUSING	01630-001	Height strip housing for discrete mounting of a pin hole sensor unit, for capturing eye-level images e.g. of people leaving a store. It is compatible with AXIS F1025, FA1125, F1004 Pin hole, AXIS P1264 and P1265. Comes with both a metric and an imperial height strip. Black aluminium housing.	\$ 99.00
AXIS F92A01 SILVER HEIGHT S. HOUSI~	01631-001	Height strip housing for discrete mounting of a pin hole sensor unit, for capturing eye-level images e.g. of people leaving a store. It is compatible with AXIS F1025, FA1125, F1004 Pin hole, AXIS P1264 and P1265. Comes with both a metric and an imperial height strip. Silver aluminium housing.	\$ 99.00
AXIS T91R61 WALL MOUNT	01516-001	Tiltable wall-mount for AXIS D2050-VE Network Radar Detector. Includes arm, AXIS T94R01P CONDUIT BACK BOX and conduit 260 mm (10 inch) cable kit.	\$ 129.00
AXIS TM3001 TILT MOUNT	01748-001	Tilt Mount Plastic, 15deg tilt, 1/2" (M20) conduit. BRACKET MOUNT ASSEMBLY M3067.	\$ 29.00
AXIS TM3101 PENDANT WALL MOUNT	01742-001	Elegant mount for indoor mounting of Axis mini dome cameras in pendant style. Concealed mounting with no visible screws. Room for microphone and connectivity devices (e.g.: AXIS T6101, AXIS T8643). Compatible with wide range of cameras, incl. AXIS M20/M30/M31/M42, etc. Made from strengthened eco-friendly plastic.	\$ 39.00

AXIS TM3101 PENDANT WALL MNT BLACK	01917-001	Elegant mount in black for indoor mounting of Axis mini dome cameras in pendant style. Concealed mounting with no visible screws. Room for microphone and connectivity devices (e.g.: AXIS T6101, AXIS T8643). Compatible with wide range of cameras, incl. AXIS M30, AXIS M31, AXIS M42, etc. Made from strengthened eco-friendly plastic.	\$ 39.00
AXIS TM3201 RECESSED MOUNT	01856-001	Recessed mount for selected AXIS M30 cameras. Includes covers for fixed mini dome and panoramic cameras.	\$ 39.00
AXIS TP1601 ADAPTER PLATE	02083-001	Adapter plate for mounting on conduit back box TP3603 or T94S01P. Plate is for P14 series and M42 series that allows for the cameras to look aesthetically pleasing when mounted onto a conduit back box.	\$ 29.00
AXIS TP3101 PENDANT WALL MOUNT	01783-001	Elegant mount for indoor mounting of Axis dome cameras in pendant style. Concealed mounting with no visible screws. Room for microphone and connectivity devices (e.g.: AXIS T6101, T8643) and AXIS I/O Indication LED. Compatible with AXIS M32-LVE and AXIS P32-V/-LV cameras. Made from strengthened eco-friendly plastic.	\$ 49.00
AXIS TP3201 RECESSED MOUNT	01757-001	Indoor recessed mount for drop ceiling installation. Supports the optional use of an internal microphone. Metal enclosure with conduit entries, suitable for installation in air handling / plenum spaces. Compatible with: AXIS M32-LVE, AXIS P32-V/-LV, AXIS P33/-V and AXIS Q35-V/-LV series; and AXIS Device Microphone A and B.	\$ 79.00
AXIS TP3202 RECESSED MOUNT	01983-001	Indoor recessed mount for drop ceiling installations. Single-screw ceiling attachment for quick and easy installation. Not suitable for air-handling (plenum) spaces. Compatible with selected AXIS M32 and AXIS P32 cameras.	\$ 42.00
AXIS TP3601 3/4" CONDUIT ADAPTER 4P	01804-001	Adapters for protected cable routing in 3/4" conduit (M25 pipe). Compatible with selected AXIS M32 and P32 cameras. 4pcs bulk pack.	\$ 29.00
AXIS TP3603 CONDUIT BACK BOX	02025-001	TP3603 indoor conduit back box a complement to T94S01P at a lower price point for large indoor installations (eg data centers). Compatible with P32/M32 indoor versions as well as indoor versions of Q17/19/29, P33, Q35, and P14/M42(plate needed TP1601). TP3603 has two separate conduit entries (1/2" & 3/4") and has space for connectors (e.g. T86 Media Converters & T6101 I/O interface).	\$ 49.00
AXIS TP3701 J-BOX & POLE ADAPTER	01743-001	Optional accessory for mounting over junction boxes or on poles. Plastic straps (two) are included. Compatible with AXIS TM3101 and TP3101 Pendant Wall Mount.	\$ 29.00
AXIS TP8101 PENDANT KIT	02019-001	An indoor metal pendant kit for mounting AXIS P8815-2 3D People Counter. Compatible AXIS ceiling mounts and 1.5" and 3/4" conduits.	\$ 39.00
AXIS TP8201 RECESSED MOUNT	02020-001	A plenum rated recessed mount for P8815-2 3D People Counter	\$ 99.00
AXIS TP3602 1/2" CONDUIT ADAPTER 4P	01805-001	Adapters for protected cable routing in 1/2" conduit (M20 pipe). Compatible with selected AXIS M32 and P32 cameras. 4pcs bulk pack.	\$ 29.00
AXIS TP3902 RETROFIT KIT 4P	01807-001	Metal bracket with snap-on features for replacing legacy AXIS P3214/15/24/25/35-VE/-LVE outdoor fixed dome cameras with the new AXIS P324x-VE/-LVE cameras. Bulk pack for retrofitting 4 cameras.	\$ 39.00

AXIS TQ6501-E PARAPET MOUNT	02110-001	Parapet Mount is an outdoor-ready mount. The round base of the mount makes it easy to install as well as suitable for installations on poles. Cables can be routed through the bottom, or from the side by using a conduit connection. Chromated and powder coated aluminum parapet mount compatible with fixed dome pendant kits and AXIS P55-series and AXIS Q60-series PTZ dome cameras. Includes mounting plate, pipe seal, conduit hole cover. Color: White	\$ 199.00
AXIS TQ9601 CONDUIT TOP BOX	01818-001	CONDUIT TOP BOX for Q9216-SLV.	\$ 99.00
AXIS TQ6901-E ADAPTER BRACKET 4P	02111-001	AXIS TQ6901-E is a useful adapter for retrofitting AXIS Q6215-LE in camera installations that have 3rd party competitor mounts. AXIS TQ6901-E is made of powder coated aluminum and is sold in packs of four.	\$ 199.00
AXIS TS3001 Recorder Mount	02081-001	AXIS TS3001 Recorder Mount ensures that the AXIS S3008 Recorder is in a fixed position either if it is mounted on walls, shelves, or under tables. Its design and shape allows the recorder to be mounted in two opposite directions.	\$ 19.00
AXIS T99A10 24V AC/DC	01226-001	High accuracy outdoor positioning unit with AXIS T93F10 camera housing. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IK10, IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC. Recommended for AXIS P13 and Q16 network camera series. Optional wall mount and pole mount accessories available separately.	\$ 1,799.00
AXIS T99A11 24V AC/DC	01227-001	High accuracy outdoor positioning unit to be used with PT Mount models in AXIS Q19 and Q29 series. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IK10, IP66, NEMA 4X rated and UL listed. Ready for column-mount. Optional wall mount and pole mount accessories available separately. Powered by 24 V AC/DC.	\$ 1,799.00
AXIS AUDIO MANAGER PRO C7050 MK II	02071-004	AXIS Audio Manager Pro provides easy, remote management of large IP audio installations. Take control of your complete audio system from one single user interface which handles, for example, system setup of audio devices, zone management, audio content management, and audio scheduling. Especially useful in retail or in schools, AXIS Audio Manager Pro helps you broadcast music, live or scheduled announcements, emergency messages, and more, either individually in separate zones or centrally to all devices. With quick installation, intuitive operation, and online device status monitoring, AXIS Audio Manager realizes the benefits of network audio.	\$ 2,995.00

<p>AXIS AUDIO MANAGER PRO C7050</p>	<p>01519-004</p>	<p>AXIS Audio Manager provides easy, remote management of large IP audio installations. Take control of your complete audio system from one single user interface which handles, for example, system setup of audio devices, zone management, audio content management, and audio scheduling. Especially useful in retail or in schools, AXIS Audio Manager helps you broadcast music, live or scheduled announcements, emergency messages, and more, either individually in separate zones or centrally to all devices. With quick installation, intuitive operation, and online device status monitoring, AXIS Audio Manager realizes the benefits of network audio.</p>	<p>\$ 2,995.00</p>
<p>AXIS AUDIO MANAGER PRO - E-LICENSE</p>	<p>02062-001</p>	<p>AXIS Audio Manager Pro provides easy, remote management of large IP audio installations.</p> <p>The AXIS AUDIO MANAGER PRO - E-LICENSE is used to when installing AXIS Audio Manager Pro on your own custom hardware or virtual machine (VMWare, Microsoft Hyper-V, Microsoft Windows Datacenter)</p>	<p>\$ 2,495.00</p>
<p>AXIS C1310-E NETWORK HORN SPEAKER</p>	<p>01796-001</p>	<p>AXIS C1310-E Network Horn Speaker is perfect for outdoor environments in most climates. The speaker is a complete audio system in a single unit. It connects to the standard existing network so there is no need for a separate audio network. Further it is simple to install with PoE for both power and connectivity. AXIS C1310-E allows users to remotely warn off intruders before they commit a crime, to deliver instructions during an emergency or to make general voice messages. Built-in memory supports pre-recorded messages, or security personal can respond to notifications with live speak. Digital signal processing (DSP) ensures clear sound. Open standards support easy integration with network video, access control, analytics, and VoIP (supporting SIP). AXIS C1310-E is a standalone unit that can be placed anywhere, which supports a flexible, scalable and cost-effective approach to system design.</p>	<p>\$ 499.00</p>
<p>AXIS C1004-E NETW CAB SPEAKER BLACK</p>	<p>0923-001</p>	<p>AXIS C1004-E Network Cabinet Speaker (black) is an all-in-one speaker system connected with a single network cable. It delivers out-of-the-box-ready high-quality sound without any need for fine-tuning. Background music can be played via the preinstalled AXIS Audio Player application. You can create and schedule your own playlists from an onboard SD card or from audio streaming services. AXIS C1004-E is also perfect for voice announcements (scheduled or live calls). The speakers can be zoned together thanks to built-in audio synchronization technology.</p>	<p>\$ 549.00</p>

AXIS C1004-E NETW CAB SPEAKER WHITE	0833-001	AXIS C1004-E Network Cabinet Speaker (white) is an all-in-one speaker system connected with a single network cable. It delivers out-of-the-box-ready high-quality sound without any need for fine-tuning. Background music can be played via the preinstalled AXIS Audio Player application. You can create and schedule your own playlists from an onboard SD card or from audio streaming services. AXIS C1004-E is also perfect for voice announcements (scheduled or live calls). The speakers can be zoned together thanks to built-in audio synchronization technology.	\$ 549.00
AXIS C2005 NETW CEILING SPEAK WHITE	0834-001	AXIS C2005 Network Ceiling Speaker (white) is an all-in-one speaker system connected with a single network cable. It delivers out-of-the-box-ready high-quality sound without any need for fine-tuning. Background music can be played via the preinstalled AXIS Audio Player application. You can create and schedule your own playlists from an onboard SD card or from audio streaming services. AXIS C2005 is also perfect for voice announcements (scheduled or live calls). The speakers can be zoned together thanks to built-in audio synchronization technology.	\$ 399.00
AXIS C1410 NETWORK MINI SPEAKER	01916-001	AXIS C1410 Network Mini Speaker is a discrete and affordable speaker that fits into smaller spaces and provides wide-area audio coverage. The speaker is a complete audio system in a single unit. It connects to the standard existing network so there is no need for a separate audio network. Further it is simple to install with PoE for both power and connectivity. AXIS C1410 allows users to remotely warn off intruders before they commit a crime, to deliver instructions during an emergency or to make general announcements. Built-in memory supports pre-recorded messages, or personnel can respond to notifications with live speak. Digital signal processing (DSP) ensures clear sound and with remote health testing you know that it is working. Open standards support easy integration with network video, access control, analytics, and VoIP. AXIS C1410 is a standalone unit that can be placed anywhere, which supports a flexible, scalable and cost-effective approach to system design. It also has a built-in PIR sensor for motion detection.	\$ 299.00
AXIS C8033 NETWORK AUDIO BRIDGE	01025-001	AXIS C8033 Network Audio Bridge is a smart solution for connecting and combining analog and digital audio systems. With this scalable and cost-efficient product, you can connect analog audio sources to Axis network speaker system, connect digital audio sources to an analog speaker system, or combine analog and digital speaker systems to act as one. Based on open standards, the audio bridge is easily integrated with other systems. It is small, easy to place, and easy to connect using Power over Ethernet.	\$ 199.00

AXIS C8210 NETWORK AUDIO AMP	01558-001	AXIS C8210 Network Audio Amplifier is a smart migration tool for transforming any passive speaker, independent of brand or formfactor, into a network speaker. This gives you all the benefits of network audio including less components. AXIS C8210 enables scalable and cost-effective solutions and can power up to eight speakers with a total power output of 15 W. Based on open standards, the amplifier is easily integrated with other systems. It is small, easy to place, and easy to connect using Power over Ethernet.	\$ 399.00
XF40-Q1765 -60C INMETRO	0835-031	Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to INMETRO. Certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	\$ 7,599.00
XF40-Q1765 CSA	0835-041	Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to CSA. Certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif,WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -40°C to +60°C (-40°F to +140°F). Powered by 24 V AC(Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	\$ 6,999.00
XF40-Q1765 -60C CSA	0835-051	Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to CSA. Certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. WDR- dynamic contrast. It supports Onvif, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshieldand AXIS Surveillance microSDXC™ Card 64 GB.	\$ 7,599.00

XF40-Q1765 -50C UL	01111-001	Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to UL. Certification part code Oxalis-UL1410-15. Oxalis explosion-protected housing with three 3/4" NPT cable entries, Axis 1080p HDTV camera inside with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -58°F to +158°F (-50°C to +70°C). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	\$ 7,899.00
XF60-Q1765 -50C 110V UL	01124-001	Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to UL. Certification part code Oxalis-UL2410-02. Oxalis explosion-protected housing with three 3/4" NPT cable entries, Axis 1080p HDTV camera inside with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps.It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -58°F to +158°F (-50°C to +70°C). Powered by 110V AC. Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	\$ 8,399.00
XP40-Q1765 -50C UL	01113-001	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to UL. Certification part code Oxalis-UL1410-25/UL2420-01. Oxalis explosion-protected housing with 3/4" NPT cable entries, Axis 1080p HDTV camera inside with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -58°F to +158°F (-50°C to +70°C). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	\$20,699.00
XP40-Q1765 -50C 110V UL	01126-001	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to UL. Certification part code Oxalis-UL1410-25/UL2420-01. Oxalis explosion-protected housing with 3/4" NPT cable entries, Axis 1080p HDTV camera inside with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67 rated and operating temperature in -58°F to +158°F (-50°C to +70°C). Powered by 110VAC. Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	\$20,999.00

XP40-Q1765 CSA	0836-041	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to CSA. Certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -40°C to +60°C (-40°F to +140°F). Powered by 24 V AC(Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	\$17,499.00
XP40-Q1765 -60C CSA	0836-051	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to CSA. Certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	\$18,499.00
XF40-Q2901 UL 8.3FPS 19MM -50C	01133-001	Explosion-protected 316L stainless steel Temperature Alarm Camera certified for hazardous areas according to UL. Certification part code OXALIS-UL1410-TI-50. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations. Oxalis explosion-protected housing with three 3/4" NPT cable entries and Axis Temperature Alarm camera inside with 336x256 resolution and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. 3 individual streams in H.264 and Motion JPEG: simultaneous, individually configured streams in max. resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -58°F to +158°F (-50°C to +70°C). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	\$20,999.00

XF40-Q2901 CSA 8.3FPS 19MM -40C	01092-001	Explosion-protected 316L stainless steel Temperature Alarm Camera certified for hazardous areas according to CSA. Certification part code 1410-TI-50. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations. Oxalis explosion-protected housing with three M20 cable entries and Axis Temperature Alarm camera inside with 336x256 resolution and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -40°C to +60°C (-40°F to +140°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	\$18,999.00
XF40-Q2901 CSA 8.3FPS 19MM -60C	01128-001	Explosion-protected 316L stainless steel Temperature Alarm Camera certified for hazardous areas according to CSA. Certification part code 1410-TI-50. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations. Oxalis explosion-protected housing with three M20 cable entries and Axis Temperature Alarm camera inside with 336x256 resolution and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	\$19,599.00
XP40-Q1942 UL 8.3FPS 19MM -50C	01142-001	Explosion-protected 316L stainless steel PT Thermal Network camera certified for hazardous areas according to UL. Certification part code UL1410-10-TI-50/UL2420-01. Oxalis explosion-protected housing with two 3/4" NPT cable entries and Axis Thermal Network Camera inside with 640x480 resolution and 32° angle of view. Continuous 360° pan, ±90° tilt and 64 preset positions. At least 3 individual streams in H.264 and Motion JPEG: simultaneous, individually configured streams in maximum resolution at 8.3 fps. It supports Electronic Image Stabilization, Zipstream, ONVIF, Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -58°F to +158°F (-50°C to +70°C). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	\$29,499.00

XP40-Q1942 UL 8.3FPS 19MM -50C 110V	01144-001	Explosion-protected 316L stainless steel PT Thermal Network Camera certified for hazardous areas according to UL. Certification part code OXALIS-UL2410-TI-50. Oxalis explosion-protected housing with two 3/4" NPT cable entries and Axis Thermal Network Camera inside with 640x480 resolution and 32° angle of view. Continuous 360° pan, ±90° tilt and 64 preset positions. At least 3 individual streams in H.264 and Motion JPEG: simultaneous, individually configured streams in maximum resolution at 8.3 fps. It supports Electronic Image Stabilization, Zipstream, ONVIF, Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -58°F to +158°F (-50°C to +70°C). Powered by 110 V AC. Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	\$29,999.00
XP40-Q1942 CSA 8.3FPS 19MM -40C	01101-001	Explosion-protected 316L stainless steel PT Thermal Network Camera certified for hazardous areas according to CSA. Certification part code 1410-10-TI-50/2420-01. Oxalis explosion-protected housing with one M20 cable entry and Axis Thermal Network Camera inside with 640x480 resolution and 32° angle of view. Continuous 360° pan, ±90° tilt and 64 preset positions. At least 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -40°C to +60°C (-40°F to +140°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	\$24,999.00
XP40-Q1942 CSA 8.3FPS 19MM -60C	01137-001	Explosion-protected 316L stainless steel PT Thermal Network Camera certified for hazardous areas according to CSA. Certification part code 1410-10-TI-50/2420-01. Oxalis explosion-protected housing with one M20 cable entry and Axis Thermal Network Camera inside with 640x480 resolution and 32° angle of view. Continuous 360° pan, ±90° tilt and 64 preset positions. At least 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. It supports Electronic Image Stabilization, Zipstream, ONVIF, Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	\$25,999.00
F101-A XF P1367	01703-001	Explosion-protected, PoE powered, 5 MP fixed network camera, FM listed for hazardous locations Class I/II/III Division 1, Groups B, C, D, E, F, G, T6; Class I Zone 1 IIB + H2 AEx d IIB+H2 T6, Class II Zone 21, AEx d IIIC T6 Db, -20°C ≤ Ta ≤ +60°C. Powder coated aluminum housing (RAL 3017). i-CS mount lens, 2.8 - 8mm, F1.2. Lightfinder, Zipstream, WDR - forensic capture. AXIS Surveillance SD Card 64GB, sunshield included.	\$ 3,999.00

F101-A XF Q1785	01587-001	Explosion-protected, PoE powered, HDTV 1080p 32x optical zoom, FM listed for hazardous locations Class I/II/III Division 1, Groups B, C, D, E, F, G, T6; Class I Zone 1 IIB + H2 AEx d IIB+H2 T6, Class II Zone 21, AEx d IIIC T6 Db, ATEX/IECEX, -40°C <= Ta <= +60°C. Powder coated aluminum housing (RAL 3017). Lightfinder, Zipstream, forensic WDR, electronic image stabilization. AXIS Surveillance SD Card 64GB.	\$ 4,999.00
D201-S XPT Q6055	01480-001	Explosion-protected, top performance, PoE powered HDTV 1080p PTZ dome network camera with 32x zoom, FM listed for hazardous locations Class I Division 1, Groups B, C, D, T6; Class 1 Zone 1 IIB + H2 T6, -20°C <= Ta <= +55°C (FM17US0156). Stainless Steel 316L housing. Auto day/night functionality, Zipstream, wide dynamic range, electronic image stabilization, highlight compensation. Continuous 360° rotation and 220° tilt with E-flip. HDTV 1080p@30 fps, 720@60 fps. High PoE midspan with fiber slot is included (for installation in safe area or Ex d enclosure), AXIS Surveillance SD Card 64GB. Optional accessories: Wall and pole mount.	\$14,999.00
D101-A XF P3807	01914-001	D101-A XF P3807 is an explosion-protected multi-sensor camera, providing an easy, reliable and cost-efficient one-camera installation – reducing installation time, cabling and VMS license costs. Thanks to its excellent image sensors, along with Forensic WDR and Lightfinder technology, it provides great video quality in any light conditions. Its four sensors give a seamless 180° panoramic overview, at up to 30 fps in 8 MP resolution. Enclosed in a red aluminum housing and FM listed for hazardous locations Class I/II/III Division 1, Groups B, C, D, E, F, G, T6; Class 1 Zone 1 IIB + H2 T6, -20°C <= Ta <= +55°C (FM17US0156). ATEX, IECEx II 2G Ex db IIB + H2, T6 GB, II 2 D Ex tb IIIC T85°C Db IP66.	\$ 9,999.00
XP40-Q1785 -60C 230V	02118-001	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas (IIC, IIIC, T4) according to ATEX, IECEx, EAC, CSA. Certification part code 1410-25/2420-01, by Eaton MEDC. AXIS Q1785 1080p HDTV camera inside with 32x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR, EIS and active tampering alarm. IP66 and IP67-rated, operating temperature in -60°C to +40°C). Powered by 230 V AC. Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 128 GB.	\$19,499.00

XP40-Q1785 UL -50C	02121-001	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas (IIC, IIIC, T4) according to ATEX, IECEx, EAC, CSA. Certification part code 1410-25/2420-01, by Eaton MEDC. AXIS Q1785 1080p HDTV camera inside with 32x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR, EIS and active tampering alarm. IP66 and IP67-rated, operating temperature -60°C to +40°C). Powered by 230 V AC. Fiber connectivity simplex singlemode 9/125um, SC connector, 10/100Mb. Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 128 GB	\$20,699.00
XP40-Q1785 UL 110V -50C	02122-001	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas (Class I/II/III Div 1, T4) according to UL. Certification part code Oxalis-UL1410-25/UL2420-01, by Eaton MEDC with 3/4" NPT cable entries, AXIS Q1785 1080p HDTV camera inside with 32x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR, EIS and active tampering alarm. IP66 and IP67-rated and operating temperature in -58°F to +158°F (-50°C to +70°C). Powered by 110 V AC. Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 128 GB.	\$20,999.00
XP40-Q1785 UL 110V FO -50C	02123-001	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas (Class I/II/III Div 1, T4) according to UL. Certification part code Oxalis-UL1410-25/UL2420-01, by Eaton MEDC with 3/4" NPT cable entries. AXIS Q1785 1080p HDTV camera inside with 32x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR, EIS and active tampering alarm. IP66 and IP67-rated and operating temperature in -58°F to +158°F (-50°C to +70°C). Powered by 230 V AC. Fiber connectivity simplex singlemode 9/125um, SC connector, 10/100Mb. Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 128 GB.	\$21,999.00
F101-A XF P1377	01927-001	Explosion-protected, PoE powered, 5 MP fixed network camera, FM listed for hazardous locations Class I/II/III Division 1, Groups B, C, D, E, F, G, T5; Class I Zone 1 IIB + H2 AEx/Ex d IIB+H2 T5, Zone 21, AEx/Ex d IIIC T85°C Db, Operating temp: -40°C (US Div)/-50°C (Zone, CAN Div) <= Ta <= +55°C. Powder coated aluminum housing (RAL 3017). i-CS mount lens, 3.9-10 mm, F1.2. Lightfinder, Zipstream, WDR - forensic capture. AXIS Surveillance SD Card 128GB, Sunshield included.	\$ 3,999.00

AXIS M1045-LW	0812-004	<p>Small, wireless indoor cube camera for day & night surveillance. 2.8mm fixed lens with 110° HFOV. Automatic IR cut filter. IR illumination up to 10 meters (33 feet) . Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 30 fps with WDR.</p> <p>Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Connects over wireless LAN (IEEE 802.11a/b/g/n) or wired Ethernet. Supports Wi-Fi Protected Setup™ PBC compatible. Includes wall, corner bracket and table top bracket for easy mounting. Power supply included.</p>	\$ 229.00
AXIS M1065-L	0811-001	<p>Small, full-featured indoor cube camera for day & night surveillance. 2.8mm fixed lens with 110° HFOV. Automatic IR cut filter. IR illumination up to 10 meters (33 feet) . Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 30 fps with WDR.</p> <p>Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Built-in microphone and mini-speaker, integrated PIR motion sensor. Powered over Ethernet (PoE) or by accessory power supply. Includes wall, corner bracket and table top bracket for easy mounting. Power supply not included.</p>	\$ 279.00
AXIS M1065-LW	0810-004	<p>Small, full-featured wireless indoor cube camera for day & night surveillance. 2.8mm fixed lens with 110° HFOV. Automatic IR cut filter. IR illumination up to 10 meters (33 feet) . Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 30 fps with WDR.</p> <p>Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Built-in microphone and mini-speaker, integrated PIR motion sensor. Connects over wireless LAN (IEEE 802.11a/b/g/n) or wired Ethernet. Supports Wi-Fi Protected Setup™ PBC compatible. Includes wall, corner bracket and table top bracket for easy mounting. Power supply included.</p>	\$ 299.00
AXIS M1134	01979-001	<p>HDTV 720p resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 3-10.5 mm F1.4 DC-iris lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; HDTV 720p at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Audio in and audio detection with either built-in microphone or optional analog microphone. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. PoE class 2 or 8-28VDC input. Includes stand for wall and ceiling mount. Midspan or power supply not included.</p>	\$ 349.00
AXIS M1134 BAREBONE	01979-041	AXIS M1134 Barebone in single pack. No lens. No power supply	\$ 329.00

AXIS M1135	01768-001	HDTV 1080p resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 3-10.5 mm F1.4 DC-iris lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Audio in and audio detection with either built-in microphone or optional analog microphone. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. PoE class 2 or 8-28VDC input. Includes stand for wall and ceiling mount. Midspan or power supply not included.	\$ 419.00
AXIS M1135 BAREBONE	01768-041	AXIS M1135 Barebone in single pack. No lens. No power supply.	\$ 399.00
AXIS M1135-E	01772-001	Outdoor, NEMA 4X, IP66 and IK10-rated, light weight HDTV 1080p resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 3-10.5 mm F1.4 DC-iris lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Audio in and audio detection with optional analog microphone. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Operation in -25°C to +50°C. PoE class 2 or 8-28VDC input. Includes removable sunshield, wall bracket, Torx T20 screw driver and IP66- rated cable glands. Midspan or power supply not included.	\$ 519.00
AXIS M1137	01769-001	5MP resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 2.8-13 mm F1.4 DC-iris lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 5MP at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Audio in and audio detection with either built-in microphone or optional analog microphone. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. PoE class 3 or 8-28VDC input. Includes stand for wall and ceiling mount. Midspan or power supply not included.	\$ 499.00
AXIS M1135 BULK 10PCS	01768-021	AXIS M1135 in 10-pack. Cannot be sold separately as single packs.	\$ 4,149.00
AXIS M1137 BAREBONE	01769-041	AXIS M1137 Barebone in single pack. No lens. No power supply	\$ 479.00

AXIS M1137-E	01773-001	Outdoor, NEMA 4X, IP66 and IK10-rated, light weight 5MP resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 2.8-13 mm F1.4 DC-iris lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 5MP at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Audio in and audio detection with optional analog microphone. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Operation in -25°C to +50°C. PoE class 3 or 8-28VDC input. Includes removable sunshield, wall bracket, Torx T20 screw driver and IP66- rated cable glands. Midspan or power supply not included.	\$ 599.00
AXIS M1145-L	0591-001	HDTV camera for day and night surveillance with varifocal 3-10.5mm P-iris lens. Remote 3.5 x optical zoom and focus with automatic IR cut filter. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p or 2MP resolution at 30 fps. Video motion detection and active tampering alarm and I/O ports. OptimizedIR, a power-efficient LED technology that provides an adaptable angle of IR illumination up to 15 meters (50 feet) MicroSD/SDHC memory card slot for edge storage. Includes stand for easy mounting. Power over Ethernet. Midspan not included.	\$ 499.00
AXIS M1145-L BULK 10PCS	0591-021	AXIS M1145-L in 10-pack/bulk. Cannot be sold separately as single packs.	\$ 4,949.00
AXIS M2025-LE	0911-001	Day/night, compact and outdoor-ready bullet style HDTV camera, IP66- and IK08-rated. Built-in IR illumination and WDR – Forensic Capture. Fixed lens with 115° HFOV. Automatic IR cut filter. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and corridor format. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F). Midspan not included.	\$ 329.00
AXIS M2025-LE BLACK	0988-001	Day/night, compact and outdoor-ready bullet style HDTV camera in black color, IP66- and IK08-rated Built-in IR illumination and WDR – Forensic Capture. Fixed lens with 115° HFOV. Automatic IR cut filter. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and corridor format. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F). Midspan not included.	\$ 329.00
AXIS M2025-LE BULK 10PCS	0911-021	AXIS M2025-LE in 10-pack/bulk. Cannot be sold separately as single packs.	\$ 3,249.00

AXIS M2026-LE MK II	01049-001	Day/night, compact and outdoor-ready bullet style HDTV camera, IP66- and IK08-rated. Built-in IR illumination and WDR. Fixed lens with 130° HFOV. Automatic IR cut filter. Multiple, individually configurable H.264/H.265 and Motion JPEG streams; max 4 MP / QuadHD resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and corridor format. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F). Midspan not included.	\$ 399.00
AXIS M2026-LE MK II BLACK	01050-001	Day/night, compact and outdoor-ready bullet style HDTV camera in black color, IP66- and IK08-rated. Built-in IR illumination and WDR. Fixed lens with 130° HFOV. Automatic IR cut filter. Multiple, individually configurable H.264/H.265 and Motion JPEG streams; max 4 MP / QuadHD resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and corridor format. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F). Midspan not included.	\$ 399.00
AXIS M2026-LE Mk II BULK 10PCS	01049-021	AXIS M2026-LE Mk II in 10-pack/bulk. Cannot be sold separately as single packs.	\$ 3,949.00
AXIS M2026-LE Mk II BLACK BULK 10PCS	01050-021	AXIS M2026-LE Mk II Black in 10-pack/bulk. Cannot be sold separately as single packs.	\$ 3,949.00
AXIS P1214	0532-001	Miniature HDTV pinhole camera for discreet surveillance. Cable from sensor unit going in the direction of the lens. Edge storage using microSD card or NAS. ACAP support, I/O port, multiple video streams in H.264 and Motion JPEG. 25/30 fps in all resolutions up to 720p. PoE and 8-28 VDC support.	\$ 499.00
AXIS P1214 BULK 10 PCS	0532-021	AXIS P1214 in pack of 10 units	\$ 4,949.00
AXIS P1214-E	0533-001	Miniature HDTV camera for discreet outdoor surveillance. Cable from sensor unit going in the direction of the lens. Edge storage using microSD card or NAS. ACAP support, I/O port, multiple video streams in H.264 and Motion JPEG. 25/30 fps in all resolutions up to 720p. PoE and 8-28 VDC support.	\$ 499.00
AXIS P1214-E BULK 10 PCS	0533-021	AXIS P1214-E in pack of 10 units	\$ 4,949.00
AXIS P1224-E	0654-001	Miniature HDTV camera for discreet indoor/outdoor surveillance with 145° horizontal field of view. Edge storage using microSD card or NAS. ACAP support, I/O port, multiple video streams in H.264 and Motion JPEG. 25/30 fps in all resolutions up to 720p. PoE and 8-28 VDC support.	\$ 499.00

AXIS P1244	0896-001	AXIS P1244 Network Camera is a modular camera based on a small-sized main unit (AXIS P12 Mk II) and AXIS F1004 Sensor Unit. The camera provides HDTV 720p resolution and 102° horizontal FoV. Supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, and edge storage using microSD card or NAS. The main unit is powered with PoE. The sensor unit has a pigtail with a detachable cable (8 m/26 ft.) for easy installation and maintenance. Comes with a kit for flush mount installation in ceiling/wall.	\$ 299.00
AXIS P1245	0926-001	AXIS P1245 Network Camera is a modular camera based on a small-sized main unit (AXIS P12 Mk II) and AXIS FA1105 Sensor Unit. The camera provides HDTV 1080p resolution, 111° horizontal FoV and WDR - Forensic Capture. Supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, and edge storage using microSD card. The main unit is powered with PoE. The sensor unit has a built in connector and a detachable cable (8 m/26 ft.) for easy installation and maintenance. Comes with a kit for flush mount installation in ceiling/wall.	\$ 339.00
AXIS P1254	0924-001	AXIS P1254 Network Camera is a modular camera based on a small-sized main unit (AXIS P12 Mk II) and AXIS F1004 Bullet Sensor Unit that enables easy mounting on walls or ceilings and with the ability to tilt and rotate. The camera provides HDTV 720p resolution and 102° horizontal FoV. Supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, and edge storage using microSD card or NAS. The main unit is powered with PoE. The sensor unit has a pigtail with a detachable cable (8 m/26 ft.) for easy installation and maintenance.	\$ 299.00
AXIS P1264	0925-001	AXIS P1264 Network Camera is a modular camera based on a small-sized main unit (AXIS P12 Mk II) and AXIS F1004 Pinhole Sensor Unit that is designed for extremely discreet indoor installations. The camera provides HDTV 720p resolution and 57° horizontal FoV. Supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, and edge storage using microSD card or NAS. The main unit is powered with PoE. The sensor unit has a pigtail with a detachable cable (8 m/26 ft.) for easy installation and maintenance. Bracket included for mounting behind thin metal, plastic or glass panel.	\$ 299.00

AXIS P1265	0927-001	AXIS P1265 Network Camera is a modular camera based on a small-sized main unit (AXIS P12 Mk II) and an AXIS FA1125 Pinhole Sensor Unit that is designed for extremely discreet indoor installations. The camera provides HDTV 1080p resolution, 91° horizontal FoV and WDR - Forensic Capture. Supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, and edge storage using microSD card. The main unit is powered with PoE. The sensor unit has a built in connector with a detachable cable (8 m/26 ft.) for easy installation and maintenance. Bracket included for mounting behind a thin metal, plastic or glass panel.	\$ 349.00
AXIS P1275	0928-001	AXIS P1275 Network Camera is a modular camera based on a small-sized main unit (AXIS P12 Mk II) and an AXIS FA4115 Dome Sensor Unit with a varifocal lens that enables easy mounting on walls or ceilings. It can be manually directed with pan, tilt and rotate movements. The camera provides HDTV 1080p resolution, 53-99° horizontal FoV and WDR - Forensic Capture. Supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, and edge storage using microSD card. The main unit is powered with PoE. The sensor unit has a built in connector and a detachable cable (8 m/26 ft.) for easy installation and maintenance.	\$ 379.00
AXIS P1375	01532-001	HDTV 1080p resolution, day/night, fixed box camera providing Forensic WDR and Lightfinder 2.0 technology. Includes an IR corrected varifocal 2.8-8 mm F1.2 P-Iris lens and remote back focus. Camera also supports CS-mount DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p at 50/60 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and security lock slot. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with either built-in microphone or optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Power over Ethernet or 12-28VDC input. Includes black stand for wall and ceiling mount with hole for easy cable management. Midspan or power supply not included.	\$ 649.00
AXIS P1375 BAREBONE	01532-031	AXIS P1375 Barebone in single pack. No lens. No power supply.	\$ 599.00

AXIS P1375-E	01533-001	Outdoor, NEMA 4X, IP66/67 and IK10-rated, light weight HDTV 1080p resolution, day/night, fixed box camera providing Forensic WDR and Lightfinder 2.0 technology. Includes an IR corrected varifocal 2.8-8 mm F1.2 P-Iris lens and remote back focus. Camera also supports CS-mount DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p at 50/60 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and open casing intrusion switch. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Support for optional AXIS Fixed Box IR Illuminator Kit A and AXIS P13 Weathershield Extension A. Serial port for RS422/485 communication. Operation in -40°C to +60°C. Power over Ethernet or 12-28VDC input. Includes removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included.	\$ 899.00
AXIS P1375-E BAREBONE	01533-031	AXIS P1375-E Barebone. No lens. Midspan not included	\$ 849.00
AXIS P1367	0762-001	5MP resolution, day/night, fixed box camera providing Forensic WDR and Lightfinder technology for demanding light conditions. Includes an IR corrected varifocal 2.8-8.5 mm F1.2 P-iris lens and remote back focus (camera also supports i-CS and DC-iris lenses with CS Mount). Multiple, individually configurable H.264 and Motion JPEG streams; max 5MP at 25/30 fps in in 16:9 format. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling, Memory card slot for optional local video storage. Serial port for RS422/485 communication. Power over Ethernet or 8-28 V DC input. Includes black metal stand with hole for easy cable management. Midspan not included.	\$ 799.00
AXIS P1367 BAREBONE	0762-031	AXIS P1367 Barebone. No lens. No power supply.	\$ 699.00

AXIS P1367-E	0763-001	<p>Outdoor, 5MP resolution, day/night, fixed box camera providing Forensic WDR and Lightfinder for demanding light conditions Includes an IR corrected varifocal 2.8-8.5 mm F1.2 P-iris lens and remote back focus (camera also supports i-CS and DC-iris lenses with CS Mount).</p> <p>Multiple, individually configurable H.264 and Motion JPEG streams; max 5MP at 25/30 fps in 16:9 format. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Two-way audio. I/O for alarm/event handling, Memory card slot for optional local video storage. Serial port for RS422/485 communication. Corridor format.</p> <p>NEMA 4X, IP66/67 and IK10-rated for operation in -40°C to +55°C and intermittent up to +60°C. Powered by IEEE 802.3af Type 1 Class 3 midspan. Includes a removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan not included.</p>	\$ 999.00
AXIS P1367-E BAREBONE	0763-031	AXIS P1367-E Barebone. No lens. Midspan not included	\$ 899.00
AXIS P1377	01808-001	<p>5MP resolution, day/night, fixed box camera providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 2.8-10 mm F1.2 P-Iris lens and remote back focus. Camera also supports CS-mount DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 5MP at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and security lock slot. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with either built-in microphone or optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. PoE class 3 or 12-28VDC input. Includes black stand for wall and ceiling mount with hole for easy cable management. Midspan or power supply not included</p>	\$ 749.00
AXIS P1377 BAREBONE	01808-031	AXIS P1377 Barebone in single pack. No lens. No power supply.	\$ 699.00

AXIS P1377-LE	01809-001	Outdoor, NEMA 4X, IP66/67 and IK10-rated, 5MP resolution, day/night, fixed box camera providing providing Forensic WDR and Lightfinder technology. OptimizedIR, a power-efficient 850nm IR LED technology covering 50 meters (130 feet).Includes an IR corrected varifocal 2.8-10 mm F1.2 P-Iris lens and remote back focus. Camera also supports CS-mount DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 5MP at 50/60 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and open casing intrusion switch. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Operation in -40°C to +60°C. PoE+ class4 or 12-28VDC input. Support for optional AXIS P13 Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included.	\$ 999.00
AXIS P1377-LE BAREBONE	01809-031	AXIS P1377-LE Barebone. No lens. Midspan not included	\$ 949.00
AXIS P1368-E	01109-001	Outdoor, 4K Ultra HD (8MP) camera, day/night, fixed box camera providing Forensic WDR and Lightfinder for demanding light conditions. Includes an IR corrected varifocal 2.8-8.5 mm F1.2 i-CS lens with P-Iris, remote zoom and focus for installation (camera also supports P-Iris and DC-iris lenses with CS Mount). Multiple, individually configurable H.264 and Motion JPEG streams; max 4K Ultra HD/8MP at 25/30 fps in 16:9 format. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Two-way audio. I/O for alarm/event handling, Memory card slot for optional local video storage. Serial port for RS422/485 communication NEMA 4X, IP66/67 and IK10-rated for operation in -40°C to +55°. Powered by IEEE 802.3af Type 1 Class 3 midspan. Includes a removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan not included.	\$ 1,099.00
AXIS P1368-E BAREBONE	01109-031	AXIS P1368-E Barebone. No lens. Midspan not included	\$ 999.00

AXIS P1378	01810-001	4K resolution, day/night, fixed box camera providing Forensic WDR and Lightfinder technology. Features a 1/1.8" image sensor. Includes an IR corrected varifocal 3.9-10 mm F1.5 P-Iris lens and remote back focus. Camera also supports CS-mount DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 4K at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and security lock slot. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with either built-in microphone or optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. PoE class 3 or 12-28VDC input. Includes black stand for wall and ceiling mount with hole for easy cable management. Midspan or power supply not included.	\$ 849.00
AXIS P1378 BAREBONE	01810-031	AXIS P1378 Barebone in single pack. No lens. No power supply.	\$ 799.00
AXIS P1378-LE	01811-001	Outdoor, NEMA 4X, IP66/67 and IK10-rated, 4K resolution, day/night, fixed box camera providing providing Forensic WDR and Lightfinder technology. Features a 1/1.8" image sensor. OptimizedIR, a power-efficient 850nm IR LED technology covering 40 meters (130 feet).Includes an IR corrected varifocal 3.9-10 mm F1.5 P-Iris lens and remote back focus. Camera also supports CS-mount DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 4K at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and open casing intrusion switch. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Operation in -40°C to +60°C. PoE+ class4 or 12-28VDC input. Support for optional AXIS P13 Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included.	\$ 1,099.00
AXIS P1378-LE BAREBONE	01811-031	AXIS P1378-LE Barebone. No lens. Midspan not included	\$ 1,049.00

<p>AXIS P1435-LE</p>	<p>0777-001</p>	<p>Compact and outdoor-ready HDTV camera for day and night surveillance, IP66-rated, varifocal 3-10.5 mm P-iris lens . Remote 3.5 x optical zoom and focus. Automatic IR cut filter. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Video motion detection, active tampering alarm, corridor format, Lightfinder, Zipstream technology and WDR – Forensic Capture. I/O ports, microSD/SDHC memory card slot for edge storage. OptimizedIR, a power-efficient LED technology with adaptable angle of IR illumination up to 30 meters (100 feet). Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 60 °C (-22 °F to 140 °F).</p>	<p>\$ 599.00</p>
<p>AXIS P1435-LE 22MM</p>	<p>0890-001</p>	<p>Compact and outdoor-ready HDTV camera for day and night surveillance, IP66-rated, varifocal 10-22 mm P-iris lens . Remote 2 x optical zoom and focus. Automatic IR cut filter. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Video motion detection, active tampering alarm, corridor format, Lightfinder, Zipstream technology and WDR – Forensic Capture. I/O ports, microSD/SDHC memory card slot for edge storage. OptimizedIR, a power-efficient LED technology with adaptable angle of IR illumination up to 50 meters (164 feet). Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 60 °C (-22 °F to 140 °F).</p>	<p>\$ 649.00</p>
<p>AXIS P1445-LE</p>	<p>01506-001</p>	<p>Compact outdoor, HDTV, day/night, fixed bullet camera providing Forensic WDR and Lightfinder for demanding light conditions. IR corrected varifocal 2.8-8.5 mm F1.2 P-iris lens with remote 3x optical zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps.. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, active tampering alarm, shock detection and corridor format. Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology covering 40 meters (131 feet). Integrated bracket for easy mounting on wall and ceiling. NEMA 4X, IP66/67 and IK10-rated for operation in -40°C to +60°C(-40 °F to 140 °F). Powered by IEEE 802.3af Type 1 Class 3 midspan (PoE). Midspan not included.</p>	<p>\$ 699.00</p>

<p>AXIS P1455-LE</p>	<p>01997-001</p>	<p>Compact and outdoor-ready HDTV camera for day and night surveillance. NEMA 4X, IP66/67 and IK10-rated, light weight HDTV 1080p resolution fixed bullet camera providing Forensic WDR and Lightfinder 2.0. Varifocal 3-9 mm F1.6 lens with remote 3 x optical zoom and focus with automatic IR cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p at 50/60 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection and active tampering alarm, defogging and corridor format. Audio in and I/O port, microSD/SDHC memory card slot for edge storage. OptimizedIR, a power-efficient LED technology with adaptable angle of IR illumination up to 40 meters (131 feet). Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -40 °C to 60 °C (-40 °F to 140 °F). Includes removable sunshield, mounting bracket, Torx L-key, and IP66/67- rated cable glands. Midspan not included.</p>	<p>\$ 599.00</p>
<p>AXIS P1447-LE</p>	<p>01054-001</p>	<p>Compact outdoor, 5MP resolution, day/night, fixed bullet camera providing Forensic WDR and Lightfinder for demanding light conditions. IR corrected varifocal 2.8-8.5 mm F1.2 P-iris lens with remote 3x optical zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams; max 5MP at 25/30 fps in 16:9 format. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, active tampering alarm, shock detection and corridor format. Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology covering 30 meters (98 feet). Integrated bracket for easy mounting on wall and ceiling. NEMA 4X, IP66/67 and IK10-rated for operation in -40°C to +60°C(-40 °F to 140 °F). Powered by IEEE 802.3af Type 1 Class 3 midspan (PoE). Midspan not included.</p>	<p>\$ 749.00</p>

AXIS P1448-LE	01055-001	<p>Compact outdoor, 4K Ultra HD (8MP) resolution, day/night, fixed bullet camera providing Forensic WDR and Lightfinder for demanding light conditions. IR corrected varifocal 2.8-9.8 mm F1.6 P-iris lens with remote 3.5x optical zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams; max 4K Ultra HD/8MP at 25/30 fps in 16:9 format. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, active tampering alarm, shock detection and corridor format. Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology covering 25 meters (82 feet). Integrated bracket for easy mounting on wall and ceiling. NEMA 4X, IP66/67 and IK10-rated for operation in -40°C to +60°C (-40 °F to 140 °F). Powered by IEEE 802.3af Type 1 Class 3 midspan (PoE). Midspan not included.</p>	\$ 949.00
AXIS Q1615 Mk II	0883-001	<p>HDTV, Day/night fixed camera providing WDR – Forensic Capture and Lightfinder for demanding light conditions. Varifocal 2.8-8.5 mm i-CS lens with remote zoom and focus for installation. Support for P-Iris and DC-iris lenses, multiple, individually configurable H.264 and Motion JPEG streams; full HDTV 1080p/2MP resolution at up to 60 fps second and 720p/1MP resolution at 120 fps. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Electronic image stabilization. Scene profiles. Two-way audio and audio detection. I/O for alarm/event handling. Memory card slot for optional local video storage. Serial port for RS485/RS422 communication. Power over Ethernet or 8-28 V DC input. Includes stand for wall and ceiling mount. Power supply not included.</p>	\$ 999.00
AXIS Q1615 Mk II BAREBONE	0883-041	<p>AXIS Q1615 Mk II Barebone in single pack. No lens. No power supply.</p>	\$ 899.00
AXIS Q1615-E Mk II	0884-001	<p>Outdoor, NEMA 4X, IP66 and IK10-rated, HDTV, Day/night fixed camera providing WDR – Forensic Capture and Lightfinder for demanding light conditions. Varifocal 2.8-8.5 mm i-CS lens with remote zoom and focus for installation. Support for P-Iris and DC-iris lenses, multiple, individually configurable H.264 and Motion JPEG streams; full HDTV 1080p/2MP resolution at up to 60 fps second and 720p/1MP resolution at 120 fps. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Electronic image stabilization. Scene profiles. Two-way audio and audio detection. I/O for alarm/event handling. Memory card slot for optional local video storage. Serial port for RS485/RS422 communication. Arctic Temperature Control, operation in -30°C to 60°C (-22 °F to 140 °F) when powered by IEEE 802.3af midspan or -40°C to 60°C (-40 °F to 140 °F) with PoE+ Midspan. Includes a removable sunshield and wall bracket. Midspan not included.</p>	\$ 1,299.00

<p>AXIS Q1615 Mk III</p>	<p>02051-001</p>	<p>HDTV 1080p resolution, day/night, fixed box camera providing Forensic WDR and Lightfinder 2.0. Includes an IR corrected varifocal 2.8-8.5 mm F1.2 i-CS lens with remote zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p/2MP resolution up to 60 fps with Forensic WDR and up to 120 fps without. Axis Zipstream technology for reduced bandwidth and storage needs. Deep learning processing unit, shock detection, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with either built-in microphone or optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Power over Ethernet or 12-28VDC input. Includes black stand for wall and ceiling mount with hole for easy cable management. Midspan or power supply not included.</p>	<p>\$ 999.00</p>
<p>AXIS Q1615-LE Mk III</p>	<p>02064-001</p>	<p>Outdoor, NEMA 4X, IP66/67 and IK10-rated, light weight HDTV 1080p resolution, day/night, fixed box camera providing OptimizedIR, Forensic WDR and Lightfinder 2.0. Includes an IR corrected varifocal 2.8-8.5 mm F1.2 i-CS lens with remote zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p/2MP resolution up to 60 fps with Forensic WDR and up to 120 fps without. Axis Zipstream technology for reduced bandwidth and storage needs. Deep learning processing unit, shock detection, intrusion alarm. Barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by IEEE 802.3at Type 2 Class 4 (PoE+). Built-in heaters and fan, Arctic Temperature Control for start-up in -40°C to 60°C (-40 °F to 140 °F). Includes removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included.</p>	<p>\$ 1,299.00</p>
<p>AXIS Q1615 Mk III BAREBONE</p>	<p>02051-041</p>	<p>AXIS Q1615 MK III Barebone in single pack. No lens. No power supply.</p>	<p>\$ 899.00</p>

AXIS Q1645	01222-001	1/2" image sensor, HDTV, Day/night fixed camera providing Forensic WDR and Lightfinder for demanding light conditions. Varifocal 3.9-10 mm i-CS lens with remote zoom and focus for installation. Support for P-Iris and DC-iris lenses, multiple, individually configurable H.264 and Motion JPEG streams; full HDTV 1080p/2MP resolution up to 60 fps with Forensic WDR and up to 120 fps without. Zipstream for reduced bandwidth and storage. Fence Guard, Motion Guard, Video motion detection, shock detection and active tampering alarm. Barrel distortion correction, Defog and Electronic image stabilization. Scene profiles. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling. Memory card slot for optional local video storage. Serial port for RS485/RS422 communication. Power over Ethernet or 8-28 V DC input. Includes stand for wall and ceiling mount. Midspan or power supply not included	\$ 1,199.00
AXIS Q1645 BARE BONE	01222-041	AXIS Q1645 Barebone in single pack. No lens. No power supply.	\$ 999.00
AXIS Q1645-LE	01223-001	1/2" image sensor, outdoor, NEMA 4X, IP66 and IK10-rated HDTV, day/night fixed camera providing OptimizedIR, Forensic WDR and Lightfinder. Varifocal 3.9-10 mm i-CS lens with remote zoom and focus. Support for CS-mount P-Iris and DC-iris lenses, multiple, individually configurable H.264 and Motion JPEG streams; full HDTV 1080p/2MP resolution up to 60 fps with Forensic WDR and up to 120 fps without. Zipstream for reduced bandwidth and storage. Includes analytics AXIS Guard Suite, shock detection and active tampering alarm. Barrel distortion correction, Defog and Electronic image stabilization. Scene profiles. Two-way audio and I/O for alarm/event handling. Memory card slot for optional local video storage. Serial port for RS485/RS422 communication. Powered by IEEE 802.3at Type 2 Class 4 (PoE+). Built-in heaters and fan, Arctic Temperature Control for start up in -40°C to 60°C (-40 °F to 140 °F). Includes a removable sunshield and wall bracket. Midspan not included.	\$ 1,499.00
AXIS Q1647	01051-001	1/2" sensor, 5 MP, Day/night fixed camera providing Forensic WDR and Lightfinder for demanding light conditions. Varifocal 3.9-10 mm i-CS lens with remote zoom and focus for installation. Support for P-Iris and DC-iris lenses, multiple, individually configurable H.264 and Motion JPEG streams; 5 MP at 30 fps with Forensic WDR, and 4 MP at up to 60 fps without Forensic WDR. Zipstream for reduced bandwidth and storage. Fence Guard, Motion Guard, Video motion detection, shock detection and active tampering alarm. Barrel distortion correction, Defog and Electronic image stabilization. Scene profiles. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling. Memory card slot for optional local video storage. Serial port for RS485/RS422 communication. Power over Ethernet or 8-28 V DC input. Includes stand for wall and ceiling mount. Midspan or power supply not included	\$ 1,399.00
AXIS Q1647 BARE BONE	01051-041	AXIS Q1647 Barebone in single pack. No lens. No power supply.	\$ 1,199.00

<p>AXIS Q1647-LE</p>	<p>01052-001</p>	<p>1/2" sensor, outdoor, NEMA 4X, IP66 and IK10-rated, 5 MP, Day/night fixed camera providing OptimizedIR, Forensic WDR and Lightfinder. Varifocal 3.9-10 mm i-CS lens with remote zoom and focus. Support for CS-mount P-Iris and DC-iris lenses, multiple, individually configurable H.264 and Motion JPEG streams; 5 MP at 30 fps with Forensic WDR, and 4 MP at up to 60 fps without Forensic WDR. Zipstream for reduced bandwidth and storage. Includes analytics AXIS Guard Suite, shock detection and active tampering alarm and shock detection. Barrel distortion correction, Defog and Electronic image stabilization. Scene profiles. Two-way audio and I/O for alarm/event handling. Memory card slot for optional local video storage. Serial port for RS485/RS422 communication. Powered by IEEE 802.3at Type 2 Class 4 (PoE+). Built-in heaters and fan, Arctic Temperature Control for start up in -40°C to 60°C (-40 °F to 140 °F). Includes a removable sunshield and wall bracket. Midspan not included.</p>	<p>\$ 1,699.00</p>
<p>AXIS Q1659 BAREBONE</p>	<p>01568-031</p>	<p>Note: Before the order is processed, this product requires an End User Information statement to be submitted to order@axis.com</p> <p>Professional photography meets video surveillance</p> <p>AXIS Q1659 Network Camera offers ultra-high image resolution for surveillance in superb detail at 8 frames per second, achieving unprecedented levels of detail for observing open spaces and across long distances.</p> <p>It features digital single-lens reflex (DSLR) imaging technology and offers a choice of Canon EF/EF-S lenses, depending on individual user needs. Equipped with an EF lens mount, the camera enables easy lens changes.</p> <p>AXIS Q1659 is compatible with a broad number of video management systems, and it supports Zipstream that significantly reduces bandwidth and storage requirements.</p> <ul style="list-style-type: none"> > 20 MP resolution > Canon EF mount and EF/EF-S lenses > Axis' Zipstream technology > PoE and SFP slot for optional fiber connectivity > Optional accessory housing 	<p>\$ 4,899.00</p>

<p>AXIS Q1659 10-22MM F/3.5-4.5</p>	<p>0967-001</p>	<p>Professional photography meets video surveillance</p> <p>AXIS Q1659 Network Camera offers ultra-high image resolution for surveillance in superb detail at 8 frames per second, achieving unprecedented levels of detail for observing open spaces and across long distances.</p> <p>It features digital single-lens reflex (DSLR) imaging technology and offers a choice of Canon EF/EF-S lenses, depending on individual user needs. Equipped with an EF lens mount, the camera enables easy lens changes.</p> <p>AXIS Q1659 is compatible with a broad number of video management systems, and it supports Zipstream that significantly reduces bandwidth and storage requirements.</p> <ul style="list-style-type: none"> > 20 MP resolution > Canon EF mount and EF/EF-S lenses > Axis' Zipstream technology > PoE and SFP slot for optional fiber connectivity > Optional accessory housing 	<p>\$ 5,899.00</p>
<p>AXIS Q1659 24MM F/2.8</p>	<p>0962-001</p>	<p>Professional photography meets video surveillance</p> <p>AXIS Q1659 Network Camera offers ultra-high image resolution for surveillance in superb detail at 8 frames per second, achieving unprecedented levels of detail for observing open spaces and across long distances.</p> <p>It features digital single-lens reflex (DSLR) imaging technology and offers a choice of Canon EF/EF-S lenses, depending on individual user needs. Equipped with an EF lens mount, the camera enables easy lens changes.</p> <p>AXIS Q1659 is compatible with a broad number of video management systems, and it supports Zipstream that significantly reduces bandwidth and storage requirements.</p> <ul style="list-style-type: none"> > 20 MP resolution > Canon EF mount and EF/EF-S lenses > Axis' Zipstream technology > PoE and SFP slot for optional fiber connectivity > Optional accessory housing 	<p>\$ 4,999.00</p>

<p>AXIS Q1659 35MM F/2</p>	<p>0963-001</p>	<p>Professional photography meets video surveillance</p> <p>AXIS Q1659 Network Camera offers ultra-high image resolution for surveillance in superb detail at 8 frames per second, achieving unprecedented levels of detail for observing open spaces and across long distances.</p> <p>It features digital single-lens reflex (DSLR) imaging technology and offers a choice of Canon EF/EF-S lenses, depending on individual user needs. Equipped with an EF lens mount, the camera enables easy lens changes.</p> <p>AXIS Q1659 is compatible with a broad number of video management systems, and it supports Zipstream that significantly reduces bandwidth and storage requirements.</p> <ul style="list-style-type: none"> > 20 MP resolution > Canon EF mount and EF/EF-S lenses > Axis' Zipstream technology > PoE and SFP slot for optional fiber connectivity > Optional accessory housing 	<p>\$ 5,899.00</p>
<p>AXIS Q1659 50MM F/1.4</p>	<p>0964-001</p>	<p>Professional photography meets video surveillance</p> <p>AXIS Q1659 Network Camera offers ultra-high image resolution for surveillance in superb detail at 8 frames per second, achieving unprecedented levels of detail for observing open spaces and across long distances.</p> <p>It features digital single-lens reflex (DSLR) imaging technology and offers a choice of Canon EF/EF-S lenses, depending on individual user needs. Equipped with an EF lens mount, the camera enables easy lens changes.</p> <p>AXIS Q1659 is compatible with a broad number of video management systems, and it supports Zipstream that significantly reduces bandwidth and storage requirements.</p> <ul style="list-style-type: none"> > 20 MP resolution > Canon EF mount and EF/EF-S lenses > Axis' Zipstream technology > PoE and SFP slot for optional fiber connectivity > Optional accessory housing 	<p>\$ 5,399.00</p>

<p>AXIS Q1659 85MM F/1.2</p>	<p>0965-001</p>	<p>Professional photography meets video surveillance</p> <p>AXIS Q1659 Network Camera offers ultra-high image resolution for surveillance in superb detail at 8 frames per second, achieving unprecedented levels of detail for observing open spaces and across long distances.</p> <p>It features digital single-lens reflex (DSLR) imaging technology and offers a choice of Canon EF/EF-S lenses, depending on individual user needs. Equipped with an EF lens mount, the camera enables easy lens changes.</p> <p>AXIS Q1659 is compatible with a broad number of video management systems, and it supports Zipstream that significantly reduces bandwidth and storage requirements.</p> <ul style="list-style-type: none"> > 20 MP resolution > Canon EF mount and EF/EF-S lenses > Axis' Zipstream technology > PoE and SFP slot for optional fiber connectivity > Optional accessory housing 	<p>\$ 8,149.00</p>
<p>AXIS Q1659 100MM F/2.8</p>	<p>0966-001</p>	<p>Professional photography meets video surveillance</p> <p>AXIS Q1659 Network Camera offers ultra-high image resolution for surveillance in superb detail at 8 frames per second, achieving unprecedented levels of detail for observing open spaces and across long distances.</p> <p>It features digital single-lens reflex (DSLR) imaging technology and offers a choice of Canon EF/EF-S lenses, depending on individual user needs. Equipped with an EF lens mount, the camera enables easy lens changes.</p> <p>AXIS Q1659 is compatible with a broad number of video management systems, and it supports Zipstream that significantly reduces bandwidth and storage requirements.</p> <ul style="list-style-type: none"> > 20 MP resolution > Canon EF mount and EF/EF-S lenses > Axis' Zipstream technology > PoE and SFP slot for optional fiber connectivity > Optional accessory housing 	<p>\$ 6,499.00</p>

<p>AXIS Q1659 70-200MM F/2.8</p>	<p>0968-001</p>	<p>Professional photography meets video surveillance</p> <p>AXIS Q1659 Network Camera offers ultra-high image resolution for surveillance in superb detail at 8 frames per second, achieving unprecedented levels of detail for observing open spaces and across long distances.</p> <p>It features digital single-lens reflex (DSLR) imaging technology and offers a choice of Canon EF/EF-S lenses, depending on individual user needs. Equipped with an EF lens mount, the camera enables easy lens changes.</p> <p>AXIS Q1659 is compatible with a broad number of video management systems, and it supports Zipstream that significantly reduces bandwidth and storage requirements.</p> <ul style="list-style-type: none"> > 20 MP resolution > Canon EF mount and EF/EF-S lenses > Axis' Zipstream technology > PoE and SFP slot for optional fiber connectivity > Optional accessory housing 	<p>\$ 8,399.00</p>
<p>AXIS Q1700-LE</p>	<p>01782-001</p>	<p>Robust outdoor, color 2 MP/1080p HDTV license plate camera for sharp license plate images day and night. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p / 2MP resolution at up to 50/60 fps. Varifocal 18–137 mm, 8x optical zoom lens, 16°-2.3° HFOV, F2.9 with remote zoom and installation focus. License plate capture range 20-50 meter at night with built-in OptimizedIR at speeds up to 130 km/h (81 mph)</p> <p>Includes license plate capture assistant for easy setup, pixel counter, shock detection, active tampering alarm, defogging and electronic image stabilization. Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage.</p> <p>Integrated bracket for easy mounting on wall and ceiling. Dark grey (NCS S5502-B) casing, black fixed metal weather shield with anti-glare coating.</p> <p>NEMA 4X, IP66/67 and impact resistant in -40°C to +60°C(-40 °F to 140 °F).</p> <p>Powered by PoE (IEEE 802-3af), RJ45 or IDC punchdown connector, 20-28 V DC or 20-24 V AC. License plate recognition software, power supply or midspan not included.</p>	<p>\$ 1,299.00</p>

AXIS Q1765-LE PTMOUNT	0644-001	Outdoor, IP66 and NEMA 4X-rated, 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Integrated IR LED illumination. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. WDR- dynamic contrast. Video motion detection and active tampering alarm. Serial port supporting RS422/485 communication for connection to a pan-tilt motor. MicroSD/MicroSDHC memory card slot for optional local video storage. Operation in -40°C to +50°C. Powered by PoE (IEEE 802-3af), 8-28 V DC or 20-24 V AC. Includes a removable sunshield. Power supply, midspan or pan-tilt motor not included.	\$ 1,399.00
AXIS Q1775	0751-001	1080p HDTV camera with 10x zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max. HDTV 1080p resolution at 50/60 fps. WDR-Dynamic Capture (130dB@ 30 fps and 90dB@ 60 fps). Video motion detection, Gatekeeper functionality and active tampering alarm. Two way audio in 48KHz, I/O and serial port for RS485/RS422 communication. SDHC/SDXC memory card slot for optional local video storage. Operation in 0 °C to +50 °C. Powered by PoE (IEEE 802-3af), 8-28 V DC or 20-24 V AC. Includes stand for wall or ceiling mount. Power supply not included.	\$ 1,299.00
AXIS Q1775-E	0752-001	Outdoor, IP66- and NEMA 4X-rated, 1080p HDTV camera with 10x zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max. HDTV 1080p resolution at 50/60 fps. WDR-Dynamic Capture (130dB@ 30 fps and 90dB@ 60 fps). Video motion detection, Gatekeeper functionality and active tampering alarm. Two way audio in 48KHz, I/O and serial port for RS485/RS422 communication. SD/SDHC/SDXC memory card slot for optional local video storage. Arctic Temperature Control, operation in -30°C to 50°C (-22 °F to 122 °F) when powered by IEEE 802.3af midspan or -40 °C to 50 °C (-40 °F to 122 °F) with PoE+ Midspan. Includes a removable sunshield and wall bracket. Midspan not included.	\$ 1,599.00

<p>AXIS Q1785-LE</p>	<p>01161-001</p>	<p>Robust outdoor, 2 MP/HDTV, day/night fixed bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Forensic WDR and Lightfinder for demanding light conditions and Axis Zipstream technology for reduced bandwidth and storage needs.</p> <p>Varifocal 4.3–137 mm, F1.4 with remote zoom and autofocus.</p> <p>Includes analytics AXIS Guard Suite, shock detection and active tampering alarm. Corridor format, Barrel distortion correction, Defog, Electronic image stabilization and Scene profiles</p> <p>Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage.</p> <p>OptimizedIR, a power-efficient IR LED technology.</p> <p>Integrated bracket for easy mounting on wall and ceiling.</p> <p>NEMA 4X, IP66/67 and impact resistant in -40°C to +60°C(-40 °F to 140 °F). Powered by PoE (IEEE 802-3af), 20-28 V DC or 20-24 V AC. Includes a removable sunshield. Power supply or midspan not included.</p>	<p>\$ 1,199.00</p>
<p>AXIS Q1786-LE</p>	<p>01162-001</p>	<p>Robust outdoor, 4 MP/Quad HD1440p, day/night fixed bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1440p /4MP resolution at 50/60 fps. Forensic WDR and Lightfinder for demanding light conditions and Axis Zipstream technology for reduced bandwidth and storage needs.</p> <p>Varifocal 4.3–137 mm, F1.4 with remote zoom and autofocus.</p> <p>Includes analytics AXIS Guard Suite, shock detection and active tampering alarm. Corridor format, Barrel distortion correction, Defog, Electronic image stabilization and Scene profiles</p> <p>Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage.</p> <p>OptimizedIR, a power-efficient IR LED technology.</p> <p>Integrated bracket for easy mounting on wall and ceiling.</p> <p>NEMA 4X, IP66/67 and impact resistant in -40°C to +60°C(-40 °F to 140 °F). Powered by PoE (IEEE 802-3af), 20-28 V DC or 20-24 V AC. Includes a removable sunshield. Power supply or midspan not included.</p>	<p>\$ 1,399.00</p>

AXIS Q1798-LE	01702-001	<p>Robust outdoor, NEMA 4X, IP66/67 and IK10-rated 10 MP/ 4K, day/night, fixed bullet camera providing Forensic WDR and Lightfinder 2.0 technology. Features a 4/3" type image sensor, built-in varifocal 12–48 mm, 4 x optical Canon zoom lens, 90°-21° HFOV, F1.7 with remote zoom and autofocus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 4K at 30 fps /10MP resolution at 20 fps.</p> <p>Axis Zipstream technology for reduced bandwidth and storage needs.</p> <p>Includes analytics AXIS Guard Suite, Video motion detection, shock detection and active tampering alarm. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Audio mic/line in, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling. MicroSD/MicroSDHC memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology.</p> <p>Integrated bracket for easy mounting on wall and ceiling.</p> <p>Operation in -40°C to +60°C (-40 °F to 140 °F). Powered by PoE class 4 (IEEE 802-3at), 20-28 V DC or 20-24 V AC. Includes a removable sunshield, Torx T20 allen key, IP66/67- rated cable glands and optional IDC punch connector.</p> <p>Power supply or midspan not included.</p>	\$ 1,799.00
AXIS F34 MAIN UNIT	0778-001	<p>AXIS F34 Main Unit. 4-channel main unit to be used with any of AXIS F Sensor Units. Supports 1080p in 15/12.5 fps or 720p in full frame rate. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Supports edge storage through NAS or SD cards (optional). Two SD card slots. Power over Ethernet or 8-28 V DC input. Power supply not included.</p>	\$ 399.00
AXIS F41 MAIN UNIT	0658-001	<p>AXIS F41 Main Unit. To be used with any of AXIS F Series Sensor Units. Supports full HDTV 1080p and WDR - Forensic Capture. Two way audio, 4 configurable I/Os with 12 V output and RS232. Supports Edge Storage through NAS or SD card (optional). PoE and 8-28 V DC support.</p>	\$ 449.00
AXIS F44 DUAL AUDIO INPUT	0936-001	<p>AXIS F44 Dual Audio Input Main Unit. 4-channel main unit to be used with any of AXIS F Series Sensor Units. Supports 1080p in 15/12.5 fps or 720p in full frame rate. Two way audio, 4 configurable I/Os with 12 V output and RS232. Supports Edge Storage through NAS or SD cards (optional). Two SD card slots. PoE and 8-28 V DC support. Comes with a stereo-to-mono adapter cable that allows two audio inputs. This article replaces AXIS F44 Main Unit (0659-00x) and the US version of AXIS F44 Dual Audio Input (0936-004).</p>	\$ 549.00
AXIS F1004 SENSOR UNIT	0765-001	<p>AXIS F1004 Sensor Unit with a fixed lens. Provides HDTV 720p and 102° horizontal FOV. Pigtail for a detachable 8-m (26-ft.) cable for connecting to an AXIS F Main Unit. A flush ceiling/wall mount kit is included.</p>	\$ 99.00

AXIS F1004 BULLET SENSOR UNIT	0935-001	AXIS F1004 Bullet Sensor Unit with a fixed lens. Bullet-style mechanics enabling easy mounting on walls or ceilings and with the ability to tilt and rotate. Provides HDTV 720p and 102° horizontal FOV. Pigtail for a detachable 8-m (26-ft.) cable for connecting to an AXIS F Main Unit.	\$ 119.00
AXIS F1004 PINHOLE SENSOR UNIT	01003-001	AXIS F1004 Pinhole Sensor Unit. Pinhole lens for extremely discreet surveillance. Provides HDTV 720p and 57° horizontal FOV. Pigtail for a detachable 8-m (26-ft.) cable for connecting to an AXIS F Main Unit. Comes with a mounting bracket for the sensor unit.	\$ 119.00
AXIS F34 SURVEILLANCE SYSTEM	0779-004	AXIS F34 Surveillance System. Includes one AXIS F34 Main Unit, 4 x AXIS F1004 Sensor Units, 4 x AXIS F8214 Dome Accessory, 4 x AXIS F8224 Recessed Mount, 4 x AXIS F7315 Cable White 15 m (49 ft) for connecting sensor units to the main unit and 2 x AXIS Surveillance microSDXC card 64 GB. Comes with a power supply.	\$ 799.00
AXIS F1005-E SENSOR UNIT 3M	0675-001	AXIS F1005-E Sensor Unit with a 3 meter cable to the main unit. IP66 rated. To be used with AXIS F Series Main Units. Fixed lens that provides 113° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8201 Vari-angle Mounting Bracket.	\$ 249.00
AXIS F1005-E SENSOR UNIT 12M	0676-001	AXIS F1005-E Sensor Unit with a 12 meter cable to the main unit. IP66 rated. To be used with AXIS F Series Main Units. Fixed lens that provides 113° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8201 Vari-angle Mounting Bracket.	\$ 269.00
AXIS F1015 SENSOR UNIT 3M	0677-001	AXIS F1015 Sensor Unit with a 3 meter cable to the main unit. To be used with AXIS F Series Main Units. Vari-focal lens that provides 53° - 108° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8201 Vari-angle Mounting Bracket.	\$ 279.00
AXIS F1015 SENSOR UNIT 12M	0678-001	AXIS F1015 Sensor Unit with a 12 meter cable to the main unit. To be used with AXIS F Series Main Units. Vari-focal lens that provides 53° - 108° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8201 Vari-angle Mounting Bracket.	\$ 299.00
AXIS F1025 SENSOR UNIT 3M	0735-001	AXIS F1025 Sensor Unit with a 3 meter cable to the main unit. To be used with AXIS F Series Main Units. Pinhole lens that provides 92° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8202 Straight Mounting Bracket.	\$ 249.00
AXIS F1025 SENSOR UNIT 12M	0734-001	AXIS F1025 Sensor Unit with a 12 meter cable to the main unit. To be used with AXIS F Series Main Units. Pinhole lens that provides 92° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8202 Straight Mounting Bracket.	\$ 269.00

AXIS F1035-E SENSOR UNIT 3M	0737-001	AXIS F1035-E Sensor Unit with a 3 meter cable to the main unit. IP66 rated. To be used with AXIS F Series Main Units. Fisheye lens that provides 194° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8201 Vari-angle Mounting Bracket.	\$ 249.00
AXIS F1035-E SENSOR UNIT 12M	0736-001	AXIS F1035-E Sensor Unit with a 12 meter cable to the main unit. IP66 rated. To be used with AXIS F Series Main Units. Fisheye lens that provides 194° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8201 Vari-angle Mounting Bracket.	\$ 269.00
AXIS F4005-E DOME SENSOR UNIT	0775-001	AXIS F4005-E Dome Sensor Unit with a 12-meter (39-feet) cable to an AXIS F Series Main Unit. Comes with a clear dome cover and damask at the back that makes it IK09 and IP66 rated. Fixed lens that provides 110° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit.	\$ 289.00
AXIS F4005 DOME SENSOR UNIT	0798-001	AXIS F4005 Dome Sensor Unit with a 12-meter (39-feet) cable to an AXIS F Series Main Unit. Recessed dome without a clear dome cover. Fixed lens that provides 113° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit.	\$ 279.00
AXIS FA1105 SENSOR UNIT	0913-001	AXIS FA1105 is a discreet indoor sensor unit with 111° horizontal field of view, for use with an AXIS FA Main Unit. It can be installed in tight places and flush-mounted in a wall, ceiling or metal panel with only a small hole visible for the lens. AXIS FA1105 provides a 1080p resolution and Forensic WDR (wide dynamic range) that is optimized for low light and motion. The unit comes with a mounting bracket and an 8 m (26 ft.) cable for connection to a main unit.	\$ 139.00
AXIS FA1125 SENSOR UNIT	0914-001	AXIS FA1125 is an extremely discreet indoor, pin hole lens, Sensor Unit with a 91° horizontal field of view, for use with an AXIS FA Main Unit. It can be installed in tight places and flush-mounted in a wall, ceiling or metal panel with only a pinhole visible for the lens. AXIS FA1125 provides a 1080p resolution and Forensic WDR (wide dynamic range) that is optimized for low light and motion. The unit comes with a mounting bracket and an 8 m (26 ft.) cable for connection to a main unit.	\$ 149.00
AXIS FA3105-L EYEBALL SENSOR UNIT	01026-001	AXIS FA3105-L is a compact eyeball sensor unit with built in IR illumination (15 m / 49 ft range of reach) for use with AXIS FA Main Unit. It has 103° horizontal field of view and 1080p HDTV resolution with Forensic WDR (wide dynamic range) that is optimized for low light and motion. The unit comes with a mounting bracket and an 8 m (26 ft.) cable for connection to the main unit.	\$ 149.00

AXIS FA4115 SENSOR UNIT	01001-001	AXIS FA4115 is a compact varifocal dome sensor unit with 53° to 99° horizontal field of view for use with an AXIS FA Main Unit. AXIS FA4115 provides a 1080p resolution a Forensic WDR (wide dynamic range) that is optimized for low light and motion. The unit comes with a mounting bracket and an 8-m (26 ft.) cable for connection to a main unit.	\$ 179.00
AXIS FA54 MAIN UNIT	0878-004	AXIS FA54 is a modular camera Main Unit and can stream full frame rate HDTV 1080p videos from four sensor units simultaneously using one IP address. It has an HDMI port for connection to a surveillance or public view monitor, Forensic WDR (wide dynamic range) that is optimized for low light and motion, Axis Zipstream, two microphone inputs and one audio out, I/O port and two micro SD card slots for local storage.	\$ 449.00
AXIS Q1659 55-250MM F/4-5.6	01118-001	Professional photography meets video surveillance AXIS Q1659 Network Camera offers ultra-high image resolution for surveillance in superb detail at 8 frames per second, achieving unprecedented levels of detail for observing open spaces and across long distances. It features digital single-lens reflex (DSLR) imaging technology and offers a choice of Canon EF/EF-S lenses, depending on individual user needs. Equipped with an EF lens mount, the camera enables easy lens changes. AXIS Q1659 is compatible with a broad number of video management systems, and it supports Zipstream that significantly reduces bandwidth and storage requirements. > 20 MP resolution > Canon EF mount and EF/EF-S lenses > Axis' Zipstream technology > PoE and SFP slot for optional fiber connectivity > Optional accessory housing	\$ 5,199.00
AXIS P8815-2 3D Ppl Counter BK	01787-001	AXIS P8815-2 3D People Counter is a custom-designed stereo camera designed for people counting. The people counter functionality is included; no need to purchase and install a separately licensed product. Main features include: Accurate and reliable 3D people counting. All-in-one solution with reliable hardware. Optimized for challenging conditions. Flexible counting zones. Easy integration in AXIS Store Reporter or 3rd party reporting system. This version comes with a black casing.	\$ 799.00

AXIS P8815-2 3D Ppl Counter WH	01786-001	AXIS P8815-2 3D People Counter is a custom-designed stereo camera designed for people counting. The people counter functionality is included; no need to purchase and install a separately licensed product. Main features include: Accurate and reliable 3D people counting. All-in-one solution with reliable hardware. Optimized for challenging conditions. Flexible counting zones. Easy integration in AXIS Store Reporter or 3rd party reporting system. This version comes with a white casing.	\$ 799.00
AXIS M3015	01151-001	Ultra-discreet, indoor fixed mini dome for recessed mounting in ceiling or wall. Fixed lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max HDTV 1080p at 30 fps with WDR. Axis Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	\$ 269.00
AXIS M3016	01152-001	Ultra-discreet, indoor fixed mini dome for recessed mounting in ceiling or wall. Fixed lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 3 MP at 30 fps with WDR. Axis Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	\$ 369.00
AXIS M3044-V	0802-001	Ultra-compact, indoor fixed mini dome with dust- and vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p resolution at 30 fps with WDR. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	\$ 199.00
AXIS M3044-WV	0803-004	Ultra-compact, indoor fixed mini dome with dust- and vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p at 30 fps with WDR. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Connects over wireless LAN (IEEE 802.11b/g/n) or wired Ethernet. Power supply included.	\$ 229.00
AXIS M3045-V	0804-001	Ultra-compact, indoor fixed mini dome with dust- and vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 30 fps with WDR. HDMI output (micro). Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	\$ 269.00

AXIS M3045-WV	0805-004	Ultra-compact, indoor fixed mini dome with dust- and vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 30 fps with WDR. HDMI output (micro). Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Connects over wireless LAN (IEEE 802.11b/g/n) or wired Ethernet. Power supply included.	\$ 299.00
AXIS M3046-V 1.8MM	01116-001	Ultra-compact, indoor fixed mini dome with dust- and vandal-resistant casing for easy mounting on wall or ceiling. Fixed 1.8mm lens. Multiple, individually configurable H.264 and Motion JPEG streams; max 3 MP at 30 fps with WDR. HDMI output (micro). Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	\$ 369.00
AXIS M3046-V 2.4mm	0806-001	Ultra-compact, indoor fixed mini dome with dust- and vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max 4 MP at 30 fps with WDR. HDMI output (micro). Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	\$ 369.00
AXIS M3064-V	01716-001	AXIS M3064-V is an ultra-compact, indoor fixed mini dome with dust- and IK08 vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens, horizontal/vertical field of view 83°/45°. D/N functionality with automatically removable IR cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max HDTV 720p resolution at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet.	\$ 199.00
AXIS M3065-V	01707-001	AXIS M3065-V is an ultra-compact, indoor fixed mini dome with dust- and IK08 vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens, horizontal/vertical field of view 102°/55°. D/N functionality with automatically removable IR-cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max HDTV 1080p at 30 fps with WDR. HDMI output (micro). Zipstream for reduced bandwidth and storage. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet.	\$ 269.00

AXIS M3075-V	01709-001	AXIS M3075-V is an ultra-compact, indoor fixed mini dome with dust- and IK08 vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens, horizontal/vertical field of view 102°/55°. D/N functionality with automatically removable IR-cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max HDTV 1080p at 30 fps with WDR. HDMI output (micro). Zipstream for reduced bandwidth and storage. Audio detection and capture with built-in microphone. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet.	\$ 299.00
AXIS M3066-V	01708-001	AXIS M3066-V is an ultra-compact, indoor fixed mini dome with dust- and IK08 vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens, horizontal/vertical field of view 131°/97°. D/N functionality with automatically removable IR-cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 4 MP at 30 fps with WDR. HDMI output (micro). Zipstream for reduced bandwidth and storage. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet.	\$ 369.00
AXIS M3047-P	0808-001	Ultra-compact, indoor fixed mini dome with 6 MP sensor, fixed lens and and tamper-resistant casing for easy mounting on wall or ceiling. Provides 360°/180° overview and dewarped panorama, quad, corner, corridor or digital PTZ views in up to 30 fps. Multiple, individually configurable H.264 and Motion JPEG streams. Client dewarping also supported. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. HDMI output (micro). Memory card slot for optional local video storage. Environment-friendly, PVC-free with recycled plastics. Power over Ethernet. Midspan not included.	\$ 469.00
AXIS M3048-P	01004-001	Ultra-compact, indoor fixed mini dome with 12 MP sensor, fixed lens and and tamper-resistant casing for easy mounting on wall or ceiling. Provides 360°/180° overview in up to 30 fps and dewarped panorama, quad, corner, corridor or digital PTZ views in up to 15 fps. Multiple, individually configurable H.264 and Motion JPEG streams. Client dewarping also supported. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. HDMI output (micro). Memory card slot for optional local video storage. Environment-friendly, PVC-free with recycled plastics. Power over Ethernet. Midspan not included.	\$ 669.00

AXIS M3067-P	01731-001	AXIS M3067-P is an ultra-compact, indoor fixed mini dome with 6 MP sensor, fixed lens and tamper-resistant casing for easy mounting on wall or ceiling. Forensic WDR, Lightfinder and D/N functionality with automatically removable IR cut filter. Provides 360°/180° overview and dewarped panorama, quad, corner, corridor or digital PTZ views in up to 30 fps with WDR, up to 60 fps without. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Signed firmware and secure boot ensure firmware authenticity. Environment-friendly, PVC-free with recycled plastics. Power over Ethernet.	\$ 469.00
AXIS M3068-P	01732-001	AXIS M3068-P is an ultra-compact, indoor fixed mini dome with 12 MP sensor, fixed lens and tamper-resistant casing for easy mounting on wall or ceiling. Forensic WDR and D/N functionality with automatically removable IR cut filter. Provides 360°/180° overview and dewarped panorama, quad, corner, corridor or digital PTZ views in up to 15 fps with WDR, up to 30 fps without. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Signed firmware and secure boot ensure firmware authenticity. Environment-friendly, PVC-free with recycled plastics. Power over Ethernet.	\$ 669.00
AXIS M3025-VE	0536-001	Compact, day/night fixed mini dome in a vandal-resistant casing for outdoor or indoor installation. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and I/O for alarm/event handling. Comes with a 2 m (6.6 ft.) network cable and is powered using Power over Ethernet. Midspan not included.	\$ 549.00
AXIS M3026-VE	0547-001	Compact, day/night fixed mini dome in a vandal-resistant casing for outdoor or indoor installation. Fixed, 106° lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps or 3 MP resolution at 20 fps. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and I/O for alarm/event handling. Comes with a 2 m (6.6 ft.) network cable and is powered using Power over Ethernet. Midspan not included.	\$ 649.00
AXIS M3027-PVE	0556-001	Compact, day/night fixed mini dome in a vandal-resistant casing for outdoor or indoor installation, offering 360°/180° panoramic views as well as quad and digital PTZ views. Multiple, individually configurable H.264 and Motion JPEG streams in up to 5MP resolution at 12 fps. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and I/O for alarm/event handling. Comes with a 2 m (6.6 ft.) cable with a male RJ-45 network connector and is powered using Power over Ethernet. Midspan not included.	\$ 749.00

<p>AXIS M3037-PVE</p>	<p>0548-001</p>	<p>Compact, day/night fixed mini dome in a vandal-resistant casing for outdoor or indoor installation, offering 360°/270°/180° panoramic views as well as quad and digital PTZ views. Multiple, individually configurable H.264 and Motion JPEG streams in up to 5MP resolution at 12 fps. Two-way, echo-free audio communication with built-in microphone and speaker. SIP support for IP phone system integration. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and I/O for alarm/event handling. Comes with a 2 m (6.6 ft.) cable with a male RJ-45 network connector and is powered using Power over Ethernet. Midspan not included.</p>	<p>\$ 799.00</p>
<p>AXIS M3057-PLVE</p>	<p>01177-001</p>	<p>360°/180° fixed dome with 6 MP sensor and support for Forensic WDR, Lightfinder and OptimizedIR illumination. Vandal-resistant casing in flat design, for outdoor or indoor installation. Provides complete 360° overview in up to 30 fps with WDR and 60 fps with WDR disabled. Dewarped panorama, quad, corner, corridor and up to four digital PTZ views. Client-side dewarping also supported. Multiple, individually configurable H.264 and Motion JPEG streams, Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall or junction boxes. Midspan not included.</p>	<p>\$ 649.00</p>
<p>AXIS M3058-PLVE</p>	<p>01178-001</p>	<p>360°/180° fixed dome with 12 MP sensor and support for Forensic WDR, Lightfinder and OptimizedIR illumination. Vandal-resistant casing in flat design, for outdoor or indoor installation. Provides complete 360° overview in up to 20 fps with WDR and 30 fps with WDR disabled. Dewarped panorama, quad, corner, corridor and up to four digital PTZ views. Client-side dewarping also supported. Multiple, individually configurable H.264 and Motion JPEG streams, Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall or junction boxes. Midspan not included.</p>	<p>\$ 849.00</p>
<p>AXIS M3104-L</p>	<p>0865-001</p>	<p>Day/night, compact mini dome with flat-faced design for indoor use. Built-in IR illumination and WDR – Forensic Capture. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.</p>	<p>\$ 249.00</p>

AXIS M3104-LVE	0866-001	Day/night, compact mini dome in a vandal-resistant, outdoor-ready, flat-faced design. Built-in IR illumination and WDR – Forensic Capture. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	\$ 299.00
AXIS M3105-L	0867-001	Day/night, compact mini dome with flat-faced design for indoor use. Built-in IR illumination and WDR – Forensic Capture. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	\$ 319.00
AXIS M3105-LVE	0868-001	Day/night, compact mini dome in a vandal-resistant, outdoor-ready, flat-faced design. Built-in IR illumination and WDR – Forensic Capture. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	\$ 369.00
AXIS M3106-L MK II	01036-001	Day/night, compact mini dome with flat-faced design for indoor use. Built-in IR illumination and fixed lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 4MP resolution at 30 fps with WDR. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	\$ 419.00
AXIS M3106-LVE MK II	01037-001	Day/night, compact mini dome in a vandal-resistant, outdoor-ready, flat-faced design. Built-in IR illumination and fixed lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 4 MP resolution at 30 fps with WDR. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	\$ 469.00
AXIS M3115-LVE	01604-001	AXIS M3115-LVE is a compact mini dome in a flat-faced, outdoor-ready, IK08 impact-resistant design with built-in IR illumination. Fixed lens, 105° field of view. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; HDTV 1080p at up to 30 fps with Forensic WDR and Lightfinder. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet.	\$ 319.00

AXIS M3116-LVE	01605-001	AXIS M3116-LVE is a compact mini dome in a flat-faced, outdoor-ready, IK08 impact-resistant design with built-in IR illumination. Fixed lens, 130° field of view. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 4 MP at up to 30 fps with Forensic WDR and Lightfinder. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet.	\$ 419.00
AXIS M3205-LVE	01517-001	Fixed dome with built-in IR illumination and IK10 vandal-resistant casing, designed for easy outdoor or indoor installation. Fixed lens, 100° field of view. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; HDTV 1080p at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection, tampering alarm and supervised digital input / digital output for alarm/event handling. HDMI output (micro). Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.	\$ 499.00
AXIS M3206-LVE	01518-001	Fixed dome with built-in IR illumination and IK10 vandal-resistant casing, designed for easy outdoor or indoor installation. Fixed lens, wide 105°/79° horizontal/vertical field of view. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 4 MP at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection, tampering alarm and supervised digital input / digital output for alarm/event handling. HDMI output (micro). Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.	\$ 599.00
AXIS M4206-V	01240-001	Ultra-compact, varifocal, D/N mini dome with dust- and vandal-resistant casing for easy indoor mounting on wall or ceiling. 3-6 mm lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 3MP for wide 4:3 view, 1080p for 16:9, max 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. HDMI output (micro). Memory card slot for optional local video storage. Power over Ethernet. Midspan not included.	\$ 419.00

AXIS M4206-LV	01241-001	Ultra-compact, varifocal, D/N mini dome with built-in IR illumination and dust- and vandal-resistant casing for easy indoor mounting on wall or ceiling. 3-6 mm lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 3MP for wide 4:3 view, 1080p for 16:9, max 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. HDMI output (micro). Memory card slot for optional local video storage. Power over Ethernet. Midspan not included.	\$ 469.00
AXIS P3224-LV MKII	0990-001	Day/night fixed dome with support for WDR – Forensic Capture, Lightfinder and OptimizedIR with built-in IR illumination. Discreet, dust and IK08 vandal-resistant indoor casing. Varifocal 2.8-10 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 720p at 30 fps with WDR, and up to 60 fps with WDR disabled. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	\$ 499.00
AXIS P3225-V MKII	0952-001	Day/night fixed dome with support for WDR – Forensic Capture and Lightfinder. Discreet, dust and IK08 vandal-resistant indoor casing. Varifocal 3-10.5 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	\$ 499.00
AXIS P3225-VE MKII	0953-001	Day/night fixed dome with support for WDR – Forensic Capture and Lightfinder. IK10 vandal-resistant outdoor casing. Varifocal 3-10.5 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	\$ 619.00

<p>AXIS P3225-LV MKII</p>	<p>0954-001</p>	<p>Day/night fixed dome with support for WDR – Forensic Capture, Lightfinder and OptimizedIR with built-in IR illumination. Discreet, dust and IK08 vandal-resistant indoor casing. Varifocal 3-10.5 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.</p>	<p>\$ 579.00</p>
<p>AXIS P3225-LVE MKII</p>	<p>0955-001</p>	<p>Day/night fixed dome with support for WDR – Forensic Capture, Lightfinder and OptimizedIR with built-in IR illumination. IK10 vandal-resistant outdoor casing. Varifocal 3-10.5 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes and weather shield against sun, rain or snow.</p>	<p>\$ 699.00</p>
<p>AXIS P3227-LV</p>	<p>0885-001</p>	<p>Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR with built-in IR illumination. Discreet, dust- and IK08 vandal-resistant indoor casing. Varifocal 3.5-10 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264 and Motion JPEG streams. 5 MP at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.</p>	<p>\$ 779.00</p>
<p>AXIS P3227-LVE</p>	<p>0886-001</p>	<p>Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR with built-in IR illumination. IK10 vandal-resistant outdoor casing. Varifocal 3.5-10 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264 and Motion JPEG streams. 5 MP at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.</p>	<p>\$ 899.00</p>

AXIS P3228-LV	0887-001	Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR with built-in IR illumination. Discreet, dust- and IK08 vandal-resistant indoor casing. Varifocal 3.5-10 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264 and Motion JPEG streams. 4K (8MP) at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	\$ 979.00
AXIS P3228-LVE	0888-001	Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR with built-in IR illumination. IK10 vandal-resistant outdoor casing. Varifocal 3.5-10 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264 and Motion JPEG streams. 4K (8MP) at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.	\$ 1,099.00
AXIS P3235-LVE	01199-001	Day/night fixed dome with support for WDR – Forensic Capture, Lightfinder and OptimizedIR with built-in IR illumination. IK10 vandal-resistant outdoor casing. Varifocal 3-10 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	\$ 749.00
AXIS P3245-V	01591-001	Fixed dome with support for Forensic WDR and Lightfinder 2.0. Discreet, dust- and IK10 vandal-resistant indoor casing. Varifocal 3.4-8.9 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.	\$ 499.00

<p>AXIS P3245-LV</p>	<p>01592-001</p>	<p>Fixed dome with support for Forensic WDR, Lightfinder 2.0 and OptimizedIR illumination. Discreet, dust- and IK10 vandal-resistant indoor casing. Varifocal 3.4-8.9 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.</p>	<p>\$ 579.00</p>
<p>AXIS P3245-VE</p>	<p>01594-001</p>	<p>Fixed dome with support for Forensic WDR and Lightfinder 2.0. Discreet, dust- and IK10 vandal-resistant outdoor-ready casing. Varifocal 3.4-8.9 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.</p>	<p>\$ 619.00</p>

<p>AXIS P3245-LVE</p>	<p>01593-001</p>	<p>Fixed dome with support for Forensic WDR, Lightfinder 2.0 and OptimizedIR illumination. Discreet, dust- and IK10 vandal-resistant outdoor-ready casing. Varifocal 3.4-8.9 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.</p>	<p>\$ 699.00</p>
<p>AXIS P3247-LV</p>	<p>01595-001</p>	<p>AXIS P3247-LV is a day/night fixed dome with discreet, dust- and IK10 vandal-resistant indoor casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 3-8mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 5 MP at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware, secure boot and AXIS Edge Vault ensure firmware authenticity and device identity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.</p>	<p>\$ 779.00</p>
<p>AXIS P3247-LVE</p>	<p>01596-001</p>	<p>AXIS P3247-LVE is a day/night fixed dome with IK10 vandal-resistant outdoor casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 3-8 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 5 MP at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware, secure boot and AXIS Edge Vault ensure firmware authenticity and device identity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.</p>	<p>\$ 899.00</p>

<p>AXIS P3248-LV</p>	<p>01597-001</p>	<p>AXIS P3248-LV is a day/night fixed dome with discreet, dust- and IK10 vandal-resistant indoor casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 4.3-8.6 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 4K (8MP) at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware, secure boot and AXIS Edge Vault ensure firmware authenticity and device identity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.</p>	<p>\$ 979.00</p>
<p>AXIS P3248-LVE</p>	<p>01598-001</p>	<p>AXIS P3248-LVE is a day/night fixed dome with IK10 vandal-resistant outdoor casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 4.3-8.6 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 4K (8MP) at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware, secure boot and AXIS Edge Vault ensure firmware authenticity and device identity. Memory card slot for optional local video storage. Power over Ethernet.</p>	<p>\$ 1,099.00</p>
<p>AXIS P3255-LVE</p>	<p>02099-001</p>	<p>Fixed dome with Deep Learning Processing Unit. Support for Forensic WDR, Lightfinder 2.0 and OptimizedIR illumination. Discreet, dust- and IK10 vandal-resistant outdoor-ready casing. Varifocal 3.4-8.9 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. HDTV 1080p up to 60 fps, 30fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware, secure boot and AXIS Edge Vault ensure firmware authenticity and device identity. Memory card slot for optional local video storage. Powered by IEEE 802.3at Type 2 Class 4 (PoE+). Includes mounting bracket for wall/ceiling or junction boxes.</p>	<p>\$ 799.00</p>

AXIS P3367-V	0406-001	5MP, day/night, fixed dome with discreet, vandal-resistant indoor casing. Varifocal 3-9 mm P-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max 5MP resolution at 12 fps or HDTV 1080p at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling, SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers.	\$ 999.00
AXIS P3367-VE	0407-001	5MP, day/night, fixed dome with vandal-resistant, IP66-rated outdoor casing. Varifocal 3-9 mm P-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max 5MP resolution at 12 fps or HDTV 1080p at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling, SD/SDHC memory card slot for optional local video storage. Operation in -40°C to +55°C powered by standard Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers, weather shield against sun, rain or snow, and 5m Ethernet cable with mounted gasket.	\$ 1,199.00
AXIS P3374-V	01056-001	Day/night fixed dome with support for WDR-Forensic Capture and Lightfinder. Discreet, IK10 vandal-resistant indoor casing. Varifocal 3 – 10 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 720p at 30 fps with WDR, and up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Two-way audio and audio detection. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Power over Ethernet, midspan not included.	\$ 599.00
AXIS P3374-LV	01058-001	Day/night fixed dome with support for WDR-Forensic Capture, Lightfinder and OptimizedIR with built-in IR illumination. Discreet, IK10 vandal-resistant indoor casing. Varifocal 3 – 10 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 720p at 30 fps with WDR, and up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Two-way audio and audio detection. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Power over Ethernet, midspan not included.	\$ 699.00

AXIS P3375-V	01060-001	Day/night fixed dome with support for WDR-Forensic Capture and Lightfinder. Discreet, IK10 vandal-resistant indoor casing. Varifocal 3 – 10 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Two-way audio and audio detection. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Power over Ethernet, midspan not included.	\$ 699.00
AXIS P3375-LV	01062-001	Day/night fixed dome with support for WDR-Forensic Capture, Lightfinder and OptimizedIR with built-in IR illumination. Discreet, IK10 vandal-resistant indoor casing. Varifocal 3 – 10 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Two-way audio and audio detection. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Power over Ethernet, midspan not included.	\$ 799.00
AXIS P3375-VE	01061-001	Day/night fixed dome with support for WDR-Forensic Capture and Lightfinder. IK10 vandal-resistant outdoor casing. Varifocal 3 – 10 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Two-way audio and audio detection. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Operation in -40 °C to 55 °C (-40 °F to 131 °F) powered by standard Power over Ethernet. Midspan not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.	\$ 899.00
AXIS P3375-LVE	01063-001	Day/night fixed dome with support for WDR-Forensic Capture, Lightfinder and OptimizedIR with built-in IR illumination. IK10 vandal-resistant outdoor casing. Varifocal 3 – 10 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Two-way audio and audio detection. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Operation in -40 °C to 55 °C (-40 °F to 131 °F) powered by standard Power over Ethernet. Midspan not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.	\$ 999.00

AXIS P3707-PE	0815-001	Flexible multisensor fixed camera with four 1080p sensors. The lenses can be adjusted to provide a 108° to 54° horizontal field of view for either a wide, panoramic view, or detailed, zoomed-in views. The lenses can be rotated to support vertically oriented scenes in Axis' Corridor Format. Supports individually configurable video streams from each camera head, as well as quad view streaming, enabling 4x 1080p resolution videos at 12.5/15 fps or 4x 720p resolution videos at full frame rate. Axis' Zipstream technology is supported to lower bandwidth and storage requirements. PoE Class 2.	\$ 1,199.00
AXIS P3715-PLVE	01970-001	AXIS P3715-PLVE offers two channels with 2MP per channel, at a frame rate of 30 fps. With its unique peanut-shaped dome design, this multidirectional camera offers cost-effective installation and flexible positioning of both varifocal camera heads. Each head can be controlled individually, so you can capture scenes in two directions in wide angle or zoomed-in views. It features Axis Lightfinder and Axis Forensic WDR for true colors and great details in challenging or poor light. And, remote zoom and focus capabilities ensures fast and accurate installation. Furthermore, Zipstream with support for H.264 significantly lowers bandwidth and storage requirements.	\$ 899.00
AXIS P3717-PLE	01504-001	AXIS P3717-PLE Network Camera is a compact 8-megapixel camera with four varifocal lenses enabling overview and detailed surveillance. With one IP address and one network cable, the four-camera-in-one unit provides a flexible, cost-effective solution for multidirectional surveillance. 360° IR illumination, Forensic WDR and Lightfinder technology provides excellent video quality in any light conditions. Each camera head can be individually positioned (pan, tilt, roll and twist) along a circular track. Remote zoom and focus makes it easy to install and the clear cover, with no sharp edges, ensures undistorted views in all directions. The camera comes with an integrated weathershield.	\$ 1,349.00
AXIS P3719-PLE	01500-001	AXIS P3719-PLE Network Camera is a compact 15-megapixel camera with four varifocal lenses (4 x Quad HD) enabling overview and detailed surveillance. With one IP address and one network cable, the four-cameras-in-one unit provides a flexible, cost-effective solution for multidirectional surveillance. 360° IR illumination, WDR and Lightfinder technology provides excellent video quality in any light conditions. Each camera head can be individually positioned (pan, tilt, roll, and twist) along a circular track. Remote zoom and focus makes it easy to install and the clear cover, with no sharp edges, ensures undistorted views in all directions. The camera has an integrated weathershield.	\$ 1,599.00

AXIS P3807-PVE	01048-001	<p>AXIS P3807-PVE Network Camera is a fixed dome camera with multiple sensors, providing an easy, reliable and cost-efficient one-camera installation – reducing installation time, cabling and VMS license costs. Thanks to its excellent image sensors, along with Forensic WDR and Lightfinder technology, it provides great video quality in any light conditions. Its four sensors give a seamless 180° panoramic overview, at up to 30 fps in 8 MP resolution. The camera is easy to install as recessed, flush, pendant, back-to-back, and comes with adjustable pre-set camera positions.</p> <ul style="list-style-type: none"> •Seamlessly stitched images •180° horizontal and 90° vertical coverage •8 MP resolution at full frame rate •Axis Lightfinder and Forensic WDR •Axis Zipstream for reduced bandwidth and storage needs 	\$ 1,349.00
AXIS P3904-R Mk II	01078-001	720p fixed dome onboard camera with male RJ-45 network connector. Equipped with 3.6mm, F2.0 lens in ruggedized IP66/67 casing. Includes lens tool, top cover tool, allen key, and drill template.	\$ 449.00
AXIS P3904-R MK II BULK 10PCS	01078-021	AXIS P3904-R MkII (RJ45) in bulk 10-pack. 720p fixed dome onboard camera with male RJ-45 network connector.	\$ 4,265.00
AXIS P3904-R MK II BULK 50 PCS	01078-031	AXIS P3904-R MkII (RJ45) in bulk 50-pack. 720p fixed dome onboard camera with male RJ-45 network connector.	\$21,299.00
AXIS P3904-R Mk II M12	01071-001	720p fixed dome onboard camera with female M12 D-coded connector. Equipped with 3.6mm, F2.0 lens in ruggedized IP66/67 casing. Includes lens tool, top cover tool, allen key, and drill template.	\$ 449.00
AXIS P3904-R MK II M12 BULK 10PCS	01071-021	AXIS P3904-R MkII (M12) in bulk 10-pack. 720p fixed dome onboard camera with female M12 D-coded connector.	\$ 4,265.00
AXIS P3904-R MK II M12 BULK 50PCS	01071-031	AXIS P3904-R MkII (M12) in bulk 50-pack. 720p fixed dome onboard camera with female M12 D-coded connector.	\$21,299.00
AXIS P3905-R Mk II	01072-001	1080p fixed dome onboard camera with male RJ-45 network connector. Equipped with 3.6mm, F2.0 lens in ruggedized IP66/67 casing. Includes lens tool, top cover tool, allen key, and drill template.	\$ 549.00
AXIS P3905-R MK II BULK 10PCS	01072-021	AXIS P3905-R MkII (RJ45) in bulk 10-pack. 1080p fixed dome onboard camera with male RJ-45 network connector.	\$ 5,215.00
AXIS P3905-R MK II BULK 50 PCS	01072-031	AXIS P3905-R MkII (RJ45) in bulk 50-pack. 1080p fixed dome onboard camera with male RJ-45 network connector.	\$25,999.00
AXIS P3905-R Mk II M12	01073-001	1080p fixed dome onboard camera with female M12 D-coded connector. Equipped with 3.6mm, F2.0 lens in ruggedized IP66/67 casing. Includes lens tool, top cover tool, allen key, and drill template.	\$ 549.00
AXIS P3905-R MK II M12 BULK 10 PCS	01073-021	AXIS P3905-R MkII (M12) in bulk 10-pack. 1080p fixed dome onboard camera with female M12 D-coded connector.	\$ 5,215.00
AXIS P3905-R MK II M12 BULK 50 PCS	01073-031	AXIS P3905-R MkII (M12) in bulk 50-pack. 1080p fixed dome onboard camera with female M12 D-coded connector.	\$25,999.00

AXIS P3905-R MK II BAREBONE 10P	01072-041	AXIS P3905-R Mk II (RJ45) with no lens in bulk 10-pack. 1080p fixed dome onboard camera with male RJ-45 network connector. Lenses sold separately. Note: Avoid installing lenses in dusty environments. To reduce the risk of dust falling into the sensor, hold the camera with the lens opening facing down.	\$ 5,025.00
AXIS P3915-R Mk II	01074-001	1080p fixed dome onboard camera with male RJ-45 network connector, and support for audio and I/O. Equipped with 3.6mm, F2.0 lens in ruggedized IP66/67 casing. Includes lens tool, top cover tool, allen key, and drill template.	\$ 599.00
AXIS P3915-R MK II BULK 10 PCS	01074-021	AXIS P3915-R MkII (RJ45) in bulk 10-pack. 1080p fixed dome onboard camera with male RJ-45 network connector, and support for audio and I/O. Accessory kit not included in 10-pack.	\$ 5,690.00
AXIS P3915-R MK II BULK 50 PCS	01074-031	AXIS P3915-R MkII (RJ45) in bulk 50-pack. 1080p fixed dome onboard camera with male RJ-45 network connector, and support for audio and I/O. Accessory kit not included in 50-pack.	\$28,399.00
AXIS P3915-R Mk II M12	01075-001	1080p fixed dome onboard camera with female M12 D-coded connector, and support for audio and I/O. Equipped with 3.6mm, F2.0 lens in ruggedized IP66/67 casing. Includes lens tool, top cover tool, allen key, and drill template.	\$ 599.00
AXIS P3915-R MK II M12 BULK 10 PCS	01075-021	AXIS P3915-R MkII (M12) in bulk 10-pack. 1080p fixed dome onboard camera with female M12 D-coded connector, and support for audio and I/O. Accessory kit not included in 10-pack.	\$ 5,690.00
AXIS P3915-R MK II M12 BULK 50 PCS	01075-031	AXIS P3915-R MkII (M12) in bulk 50-pack. 1080p fixed dome onboard camera with female M12 D-coded connector, and support for audio and I/O. Accessory kit not included in 50-pack.	\$28,399.00
AXIS P3905-R MK II M12 BAREBONE 10P	01073-041	AXIS P3905-R Mk II (M12) with no lens in bulk 10-pack. 1080p fixed dome onboard camera with female M12 D-coded connector. Lenses sold separately. Note: Avoid installing lenses in dusty environments. To reduce the risk of dust falling into the sensor, hold the camera with the lens opening facing down.	\$ 5,025.00
AXIS P3925-R	01920-001	Full HDTV 1080p fixed dome onboard camera with male RJ-45 network connector for rolling stock and vehicles. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage. Includes lens tool, L-key, and drill template.	\$ 549.00

AXIS P3925-R BULK 10P	01920-021	Bulk 10-pack of AXIS P3925-R. Full HDTV 1080p fixed dome onboard camera with male RJ-45 network connector for rolling stock and vehicles. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage	\$ 5,215.00
AXIS P3925-R M12	01933-001	Full HDTV 1080p fixed dome onboard camera for rolling stock and vehicles with female M12 D-coded connector. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage. Includes lens tool, L-key, and drill template.	\$ 549.00
AXIS P3925-R M12 BULK 10P	01933-021	Bulk 10-pack of AXIS P3925-R. Full HDTV 1080p fixed dome onboard camera with female M12 D-coded connector for rolling stock and vehicles. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage.	\$ 5,215.00
AXIS P3935-LR	01919-001	Full HDTV 1080p fixed dome onboard camera for rolling stock and vehicles with male RJ-45 network connector. Invisible 940-nm IR LEDs, I/O for alarm/event handling, built in microphone and external microphone input or line input. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage. Includes lens tool, L-key, and drill template.	\$ 599.00

AXIS P3935-LR BULK 10P	01919-021	Bulk 10-pack of AXIS P3935-RL. Full HDTV 1080p fixed dome onboard camera for rolling stock and vehicles with male RJ-45 network connector. Invisible 940-nm IR LEDs, I/O for alarm/event handling, built in microphone and external microphone input or line input. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage.	\$ 5,690.00
AXIS P3935-LR M12	01932-001	Full HDTV 1080p fixed dome onboard camera for rolling stock and vehicles with female M12 D-coded connector. Invisible 940-nm IR LEDs, I/O for alarm/event handling, built in microphone and external microphone input or line input. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage. Includes lens tool, L-key, and drill template.	\$ 599.00
AXIS P3935-LR M12 BULK 10P	01932-021	Bulk 10-pack of AXIS P3935-RL. Full HDTV 1080p fixed dome onboard camera for rolling stock and vehicles with female M12 D-coded connector. Invisible 940-nm IR LEDs, I/O for alarm/event handling, built in microphone and external microphone input or line input. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage.	\$ 5,690.00
AXIS P9106-V BRUSHED STEEL	01553-001	3MP compact and vandal-resistant (IK10) corner-mounted camera with 1.8mm lens for wide field of view without blind spots. Elegant brushed steel design with no visible screws. Dust- and waterproof (IP66) casing. WDR, Zipstream, SD card slot and support for portcast technology. Video motion detection and active tampering alarm. PoE Class 1. Color: Brushed stainless steel.	\$ 649.00
AXIS P9106-V WHITE	01620-001	3MP compact and vandal-resistant (IK10) corner-mounted camera with 1.8mm lens for wide field of view without blind spots. Ligation-resistant design with dust- and waterproof (IP66) casing. WDR, Zipstream, SD card slot and support for portcast technology. Video motion detection and active tampering alarm. PoE Class 1. White in color.	\$ 599.00

<p>AXIS Q3515-LV 9MM</p>	<p>01039-001</p>	<p>Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR illumination. Discreet, dust and IK10 vandal-resistant indoor casing. Varifocal 3-9 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. 1080p at 30 fps with WDR and Lightfinder and up to 120 fps without. Zipstream for reduced bandwidth and storage. Fence Guard, Motion Guard, Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. Supervised inputs / digital outputs for alarm / event handling. Electronic image stabilization. Memory card slot for optional local video storage. Power over Ethernet or 8-28V DC power with redundancy. Midspan and power supply not included. Includes mounting bracket for wall or junction boxes.</p>	<p>\$ 849.00</p>
<p>AXIS Q3515-LV 22MM</p>	<p>01044-001</p>	<p>Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR illumination. Discreet, dust and IK10 vandal-resistant indoor casing. Varifocal 9-22 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. 1080p at 30 fps with WDR and Lightfinder and up to 120 fps without. Zipstream for reduced bandwidth and storage. Fence Guard, Motion Guard, Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. Supervised inputs / digital outputs for alarm / event handling. Electronic image stabilization. Memory card slot for optional local video storage. Power over Ethernet or 8-28V DC power with redundancy. Midspan and power supply not included. Includes mounting bracket for wall or junction boxes.</p>	<p>\$ 899.00</p>
<p>AXIS Q3515-LVE 9MM</p>	<p>01041-001</p>	<p>Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR illumination. IK10+ vandal-resistant outdoor casing. Varifocal 3-9 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. 1080p at 30 fps with WDR and Lightfinder, and up to 120 fps without. Zipstream for reduced bandwidth and storage. Fence Guard, Motion Guard, Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. Supervised inputs / digital outputs for alarm / event handling. Electronic image stabilization. Memory card slot for optional local video storage. Operation in -50 °C to 60 °C (-58 °F to 140 °F) powered by standard Power over Ethernet or 8-28V DC power with redundancy. Midspan and power supply not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.</p>	<p>\$ 999.00</p>

<p>AXIS Q3515-LVE 22MM</p>	<p>01046-001</p>	<p>Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR illumination. IK10+ vandal-resistant outdoor casing. Varifocal 9-22 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. 1080p at 30 fps with WDR and Lightfinder, and up to 120 fps without. Zipstream for reduced bandwidth and storage. Fence Guard, Motion Guard, Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. Supervised inputs / digital outputs for alarm / event handling. Electronic image stabilization. Memory card slot for optional local video storage. Operation in -50 °C to 60 °C (-58 °F to 140 °F) powered by standard Power over Ethernet or 8-28V DC power with redundancy. Midspan and power supply not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.</p>	<p>\$ 1,049.00</p>
<p>AXIS Q3517-LV</p>	<p>01021-001</p>	<p>Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR with built-in IR illumination. Discreet, dust and IK10 vandal-resistant indoor casing. Varifocal 4.3 – 8.6 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. 5 MP at 30 fps with WDR, and 4 MP at up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. Supervised inputs / digital outputs for alarm / event handling. Electronic image stabilization. Memory card slot for optional local video storage. Power over Ethernet or 8-28V DC power with redundancy. Midspan and power supply not included. Includes mounting bracket for wall or junction boxes.</p>	<p>\$ 1,099.00</p>
<p>AXIS Q3517-LVE</p>	<p>01022-001</p>	<p>Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR with built-in IR illumination. IK10+ vandal-resistant outdoor casing. Varifocal 4.3 – 8.6 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. 5 MP at 30 fps with WDR, and 4 MP at up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. Supervised inputs / digital outputs for alarm / event handling. Electronic image stabilization. Memory card slot for optional local video storage. Operation in -50 °C to 60 °C (-58 °F to 140 °F) powered by standard Power over Ethernet or 8-28V DC power with redundancy. Midspan and power supply not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.</p>	<p>\$ 1,249.00</p>

<p>AXIS Q3517-SLVE</p>	<p>01237-001</p>	<p>Day/night fixed dome in a stainless steel (marine-grade SS 316L) outdoor casing, offering high corrosion resistance and IK10+ (50 joules) vandal resistance. Support for Forensic WDR, Lightfinder and OptimizedIR IR illumination. Varifocal 4.3 – 8.6 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. 5 MP at 30 fps with WDR, and 4 MP at up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. Supervised inputs / digital outputs for alarm / event handling. Electronic image stabilization. Memory card slot for optional local video storage. Operation in -50 °C to 60 °C (-58 °F to 140 °F) powered by standard Power over Ethernet or 8-28V DC power with redundancy. Midspan and power supply not included. Includes mounting bracket for wall/ceiling or junction boxes.</p>	<p>\$ 1,349.00</p>
<p>AXIS Q3527-LVE</p>	<p>01565-001</p>	<p>Fixed dome with enhanced security features: signed firmware and secure boot ensure firmware authenticity, and a Trusted Platform Module (TPM) secures certificates and cryptographic keys. Forensic WDR, Lightfinder and OptimizedIR illumination. IK10+ vandal-resistant outdoor casing. Varifocal 4.3 – 8.6 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. 5 MP at 30 fps with WDR, and 4 MP at up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. Supervised inputs / digital outputs for alarm / event handling. Electronic image stabilization. Memory card slot for local storage. Operation in -50 °C to 60 °C (-58 °F to 140 °F) powered by standard Power over Ethernet or 8-28V DC power with redundancy. Midspan and power supply not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.</p>	<p>\$ 1,349.00</p>
<p>AXIS Q3518-LVE</p>	<p>01493-001</p>	<p>Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR with built-in IR illumination. IK10+ vandal-resistant outdoor casing. Varifocal 4.3 – 8.6 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. Up to 4K/8MP at 30 fps. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. Supervised inputs / digital outputs for alarm / event handling. Electronic image stabilization. Memory card slot for optional local video storage. Operation in -50 °C to 60 °C (-58 °F to 140 °F) powered by standard Power over Ethernet or 8-28V DC power with redundancy. Midspan and power supply not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.</p>	<p>\$ 1,349.00</p>

AXIS Q3615-VE	0743-001	Day/night fixed dome with 1/2" sensor, providing WDR – Forensic Capture and Lightfinder for demanding light conditions. IK10 vandal-resistant outdoor casing. Pan/tilt/roll/zoom for remote installation and readjustment. Motorized varifocal 4.1-9 mm P-Iris lens. Multiple, individually configurable H.264 and Motion JPEG streams; HDTV 1080p at up to 60 fps. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Electronic image stabilization. Memory card slot for optional local video storage. Operation in wide temperature range powered by standard Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes and substantial weather shield against sun, rain or snow.	\$ 1,349.00
AXIS Q3617-VE	0744-001	Day/night fixed dome with 1/2" sensor, providing WDR – Forensic Capture and Lightfinder for demanding light conditions. IK10 vandal-resistant outdoor casing. Pan/tilt/roll/zoom for remote installation and readjustment. Motorized varifocal 4.1-9 mm P-Iris lens. Multiple, individually configurable H.264 and Motion JPEG streams; up to 4MP @ 30 fps with WDR, 6 MP @ 20 fps without WDR. Zipstream for reduced bandwidth and storage needs. Video motion detection, shock detection and active tampering alarm. Electronic image stabilization. Memory card slot for optional local video storage. Operation in wide temperature range powered by standard Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes and substantial weather shield against sun, rain or snow.	\$ 1,549.00
AXIS Q3708-PVE	0801-001	180° multi-sensor, day/night fixed dome in an IK10 vandal-resistant outdoor casing. Fixed focal, multi-megapixel lenses, focused from factory. 3 x QHD resolution, up to 15MP total in 4:3 format. WDR Forensic Capture, Zipstream and one single IP address. Operation in wide temperature range powered by standard Power over Ethernet Plus. Midspan not included. Designed for pendant or wall mount arm with same bayonet joint interface as Axis' PTZ domes. Includes weather shield against sun, rain or snow, easily repaintable to blend in with the environment.	\$ 1,999.00
AXIS Q3709-PVE	0664-001	Multi-sensor, day/night fixed dome in an IK10 vandal-resistant outdoor casing. Fixed focal, multi-megapixel lenses, focused from factory. Multiple, individually configurable H.264 and Motion JPEG streams; high-quality 4K video in 30 fps from each of 3 sensors and up to 33 MP resolution in total, together providing a 180° view. Video motion detection and active tampering alarm. Operation in wide temperature range powered by standard Power over Ethernet Plus. Midspan not included. Designed for pendant or wall mount arm with same bayonet joint interface as Axis' PTZ domes. Includes weather shield against sun, rain or snow, easily repaintable to blend in with the environment.	\$ 2,399.00

AXIS Q9216-SLV STEEL	01766-001	Robust stainless steel corner-mount camera replacing AXIS Q8414 (Trinity). Key features: <ul style="list-style-type: none"> • Anti-ligature, stainless steel, IK10+, IP66, • 4MP, >90° VFoV, >120° HFoV, • 940nm LEDs for invisible IR • H.264 + H.265 with Zipstream, • Built-in microphone, • I/O and optional line-in/out, • Option to further prevent screw-tampering 	\$ 1,149.00
AXIS Q9216-SLV WHITE	01767-001	Robust stainless steel corner-mount camera replacing AXIS Q8414 (Trinity). Key features: <ul style="list-style-type: none"> • Anti-ligature, stainless steel, IK10+, IP66, • 4MP, >90° VFoV, >120° HFoV, • 940nm LEDs for invisible IR • H.264 + H.265 with Zipstream, • Built-in microphone, • I/O and optional line-in/out, • Option to further prevent screw-tampering 	\$ 1,149.00
AXIS Q8414-LVS METAL	0709-001	AXIS Q8414-LVS Network Camera Metal is a brushed stainless steel indoor corner camera with an anti-grip/anti-ligature design to prevent self-harm. Ideal for correctional facilities and psychiatric wards. It supports IK10+ 50 joules impact rating. It is IP66- and NEMA 4X-rated for easy and safe cleaning. Superb images day and night with Lightfinder technology and has built-in invisible IR LED (940 nm). It delivers HDTV 720p or 1.3 Megapixel video, supporting a lens with: P-Iris, varifocal 2.5–6 mm, 105°–49° horizontal angle of view, F1.2. It offers 3 masks and I/O ports. Built-in surface mounted high quality microphone.	\$ 1,299.00
AXIS Q8414-LVS WHITE	0710-001	AXIS Q8414-LVS Network Camera White is a powder coated stainless steel indoor corner camera with an anti-grip/anti-ligature design to prevent self-harm. Ideal for correctional facilities and psychiatric wards. It supports IK10+ 50 joules impact rating. It is IP66- and NEMA 4X-rated for easy and safe cleaning. Superb images day and night with Lightfinder technology and has built-in invisible IR LED (940 nm). It delivers HDTV 720p or 1.3 Megapixel video, supporting a lens with: P-Iris, varifocal 2.5–6 mm, 105°–49° horizontal angle of view, F1.2. It offers 3 masks and I/O ports. Built-in surface mounted high quality microphone.	\$ 1,299.00
AXIS Q8685-E 24V AC/DC	0862-001	High accuracy outdoor PTZ positioning camera. HDTV 1080p video, 30x optical zoom, focus recall, extreme light sensitivity and Axis Zipstream. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated long-life silicone wiper for remote maintenance, and integrated SFP slot for long-distance fiber connection. IK10, IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included)	\$ 3,599.00

AXIS Q8685-LE 24V AC/DC	0864-001	High accuracy outdoor PTZ positioning camera with IR illuminators. HDTV 1080p video, 30x optical zoom, built-in IR pass filter for sharper images in mixed lighting conditions. IR range up to 500m. Integrated long-life silicone wiper for remote maintenance, and integrated SFP slot for long-distance fiber connection. IK10, IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included)	\$ 5,199.00
AXIS M5054	01079-001	Ceiling-mount mini PTZ dome camera with 5x Optical zoom and autofocus, HDTV 720p (1280x720) 25/30fps in H.264 with Zipstream and Motion JPEG. IP51 protection against dust and water. Basic analytics are included. Only PoE, midspan not included. Surface ceiling mounting brackets included	\$ 499.00
AXIS M5065 US	01107-004	Ceiling-mount mini PTZ dome camera with 5x Optical zoom and autofocus, HDTV 1080p (1920x1080) 30fps in H.264 with Zipstream and Motion JPEG. IP51 protection against dust and water. Basic analytics are included. Only PoE, midspan not included. Surface ceiling mounting brackets included 4 wireless I/O using Z-wave communication.	\$ 599.00
AXIS M5525-E 60HZ	01146-001	Discreet PTZ with HDTV 1080p, 1920x1080, 10x optical zoom, automatic day/night and autofocus. Continues 360° pan. WDR- Forensic Capture, IP66, PoE and 24V. 30fps in H.264 and Motion JPEG, Zipstream, Scene profiles, two-way audio, 4 I/O. Surface mount or Axis PTZ standard mount. Midspan not included.	\$ 999.00
AXIS P5414-E 60HZ	0588-001	Intelligent Direct Drive PTZ camera with HDTV 720p, day/night and 18x zoom, designed for mounting on a wall or building. No extra bracket are needed, build in junction box. Audio In/Out, full size SD card, 24 V DC, 4 configurable I/Os and Ethernet connector with PoE. Repaintable sunshield covering the entire unit. Power supply not included.	\$ 1,599.00
AXIS P5415-E 60HZ	0589-001	Intelligent Direct Drive PTZ camera with HDTV 1080p, day/night and 18x zoom, designed for mounting on a wall or building. No extra bracket are needed, build in junction box. Audio In/Out, full size SD card, 24 V DC, 4 configurable I/Os and Ethernet connector with PoE. Repaintable sunshield covering the entire unit. Power supply not included.	\$ 1,999.00
AXIS Q8665-E 120V AC	0717-001	High speed and precision PT-head design PTZ camera with integrated wiper. HDTV 1080p resolution and 18x optical zoom. Pan speed: 0.02°/s to 100°/s, tilt speed: 0.02°/s to 40°/s. Continuous pan rotation, 360° endless and +90° to -40° tilt. IP66-rated and NEMA 4X-rated, operating temperature -40 °C to 55 °C (-40 °F to 131 °F). Power input 120V AC.	\$ 4,999.00
AXIS Q8665-LE 24V AC	0718-001	High precision PT-head design PTZ camera with integrated wiper and IR illuminators enabling a viewing range in darkness up to 150m. HDTV 1080p resolution and 18x optical zoom. Pan speed: 0.02°/s to 40°/s, tilt speed: 0.02°/s to 30°/s. Continuous pan rotation, 360° endless and +90° to -40° tilt. IP66-rated and NEMA 4X-rated, operating temperature -40 °C to 55 °C (-40 °F to 131 °F). Power input 24V AC.	\$ 5,199.00

AXIS Q8665-LE 120V AC	0720-001	High precision PT-head design PTZ camera with integrated wiper and IR illuminators enabling a viewing range in darkness up to 150m. HDTV 1080p resolution and 18x optical zoom. Pan speed: 0.02°/s to 40°/s, tilt speed: 0.02°/s to 30°/s. Continuous pan rotation, 360° endless and +90° to -40° tilt. IP66-rated and NEMA 4X-rated, operating temperature -40 °C to 55 °C (-40 °F to 131 °F). External power supply with power input 120V AC and integrated light sensor for IR illuminator control included.	\$ 6,499.00
AXIS P5624-E MK II 60HZ	0932-001	PTZ camera with continuous 360° pan for both indoor and outdoor with 23x optical zoom. HDTV 720p @ 30fps (1280x720) in H.264, Motion JPEG and Axis Zipstream and Focus Recall, Day & Night, IP66 and NEMA 4X classification. Advanced Gatekeeper, full-size SD-card slot, smoked and clear dome. Mounting brackets and Midspan are not included.	\$ 1,599.00
AXIS P5635-E MK II 60HZ	0929-001	PTZ camera with continuous 360° pan for both indoor and outdoor with 30x optical zoom Autofocus and Focus Recall. HDTV 1080p @ 30fps (1920x1080) in H.264, Motion JPEG and Axis Zipstream. Two-way audio, 4xI/O, 24V and PoE, Day & Night, IP66 and NEMA 4X classification. Advanced Gatekeeper, full-size SD-card slot. Mounting brackets, Midspan/Power supply and connector or cable for audio, I/O and 24V are not included.	\$ 1,999.00
AXIS P5654-E 60HZ	01759-001	PTZ camera with 77° field of view, continuous 360° pan for both indoor and outdoor with 21x optical zoom. HDTV 720p @ 60fps (1280x720) in H.264/265, Motion JPEG, Axis Zipstream, Lightfinder 2 and Focus Recall, WDR, Day & Night, IP66, IK10 and NEMA 4X classification. Advanced Gatekeeper, full-size SD-card slot, smoked and clear dome. Mounting brackets and Midspan are not included.	\$ 1,599.00
AXIS P5655-E 60HZ	01682-001	PTZ camera with continuous 360° pan for both indoor and outdoor with 32x optical zoom, Lightfinder 2, Autofocus and Focus Recall. HDTV 1080p @ 30/60fps (1920x1080) in Motion JPEG, H.264, H.265, and Axis Zipstream. Two-way audio, 4xI/O, 24V and PoE, Day & Night, IP66, IK10 and NEMA 4X classification. Advanced Gatekeeper, full-size SD-card slot. Mounting brackets, Midspan/Power supply and connector or cable for audio, I/O and 24V are not included.	\$ 1,999.00
AXIS Q6000-E 60HZ MK II	01006-001	Outdoor-ready 360° situational awareness camera, comprising 4x2MP sensors @ 30fps in H.264 Zipstream and Motion JPEG. Tilttable sensors with exchangeable lenses. Designed to be integrated with any AXIS Q60-E series camera for large area coverage and simultaneous zoomed-in view, using the one-click PTZ control feature. Full size SD-card slot. No extra equipment required, as it uses the same brackets, power supply and network cable as the connected AXIS Q60-E.	\$ 1,599.00

AXIS Q6010-E 60HZ	01981-001	Outdoor-ready 360° situational awareness camera, comprising of 4x5MP sensors @ 20fps in H.264/H.265 Zipstream and Motion JPEG. Movable sensors with exchangeable lenses. Autofocus, D/N, Autopilot for tracking. Designed to be integrated with AXIS Q605x-E and AXIS Q607x-E series camera for large area coverage and simultaneous zoomed-in view, using the one-click PTZ control feature. Full size SD-card slot. No extra equipment required, as it uses the same brackets, power supply and network cable as the connected AXIS Q60-E.	\$ 1,599.00
AXIS Q6100-E 60HZ	01711-001	Outdoor-ready 360° situational awareness camera, comprising of 4x5MP sensors @ 20fps in H.264/H.265 Zipstream and Motion JPEG. Movable sensors with exchangeable lenses. Autofocus, D/N. Directional Audio Detection. Designed to be integrated with any AXIS Q61-series camera for large area coverage and simultaneous zoom-in view, using the one-click PTZ control feature. Full size SD-card slot. No extra equipment required, as it uses the same brackets, power supply and network cable as the connected AXIS Q61	\$ 1,599.00
AXIS Q6055-C 60HZ	0943-001	Actively cooled, outdoor-ready high-speed PTZ dome camera with 32x optical zoom. IP66-, MIL-, IK10 and NEMA 4X-rated. Temperature range -20 °C to +75 °C. Auto day/night functionality. Continuous 360° rotation and 220° tilt with E-flip. HDTV 1080p (1920x1080) @ 30 fps. 720P@60 fps. Shock detection, autotracking, tour recording and Active Gatekeeper. Highlight compensation. Basic built-in analytics: object removed, fence detector, object counter, enter/exit detection, video motion detection. Including 7m cable, media converter switch with 2xSFP slots for optical fiber modules, 2xRJ-45, 2xI/O and 24 V in. Power supply and brackets are not included. (several different accessories available).	\$ 4,099.00
AXIS Q6074 60HZ	01968-004	Top performance PTZ camera with HDTV 720p @60fps 30x optical zoom for indoor use. IP52 rated. Zipstream with H.264/ H.265. Auto day/night functionality. Continuous 360° rotation and 180° tilt with E-flip. Two-way audio, I/O and external power with multi-connector cable (not included). Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear and smoked transparent dome cover and High PoE midspan are included. Mounting kits for hard and drop ceilings	\$ 2,099.00

AXIS Q6074-E 60HZ	01974-004	<p>Top performance PTZ camera with HDTV 720p @60fps, 30x optical zoom, outdoor-ready, IP66, IK10 and NEMA 4x-rated. Zipstream with H.264/ H.265, Arctic Temperature Control enables operation and start up from -40 °C to +50 °C (-58 °F to 122 °F). Auto day/night functionality. Continuous 360° rotation and 220° tilt with E-flip. Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear transparent dome cover and High PoE midspan with fiber slot are included. No mounting bracket included (several different accessories available).</p>	\$ 2,599.00
AXIS Q6075 60HZ	01750-004	<p>Top performance PTZ camera with HDTV 1080p @60fps 40x optical zoom for indoor use. IP52 rated. Zipstream with H.264/ H.265. Auto day/night functionality. Continuous 360° rotation and 180° tilt with E-flip. Two-way audio, I/O and external power with multi-connector cable (not included). Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear and smoked transparent dome cover and High PoE midspan are included. Mounting kits for hard and drop ceilings</p>	\$ 2,549.00
AXIS Q6075-E 60HZ	01752-004	<p>Top performance PTZ camera with HDTV 1080p @60fps, 40x optical zoom, outdoor-ready, IP66, IK10 and NEMA 4x-rated. Zipstream with H.264/ H.265, Arctic Temperature Control enables operation and start up from -40 °C to +50 °C (-58 °F to 122 °F). Auto day/night functionality. Continuous 360° rotation and 220° tilt with E-flip. Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear transparent dome cover and High PoE midspan with fiber slot are included. No mounting bracket included (several different accessories available).</p>	\$ 3,099.00

AXIS Q6075-S 60HZ	01756-001	Stainless steel, (SS-316L) pressurized (5psi) Top performance HDTV 1080p compliant, outdoor-ready, IP66, IK10 and NEMA 4X-rated PTZ dome camera with 40x optical zoom. Auto day/night functionality. Continuous 360° rotation and 220° tilt. HDTV 1080p (1920x1080) @60fps. Zipstream with H.264/ H.265 Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear transparent dome cover. Including 7 m cable, media converter switch with 2xSFP slots for optical fiber modules, 2xRJ-45, 2xI/O and 24V in. Brackets and power adapter are not included (several different accessories available).	\$ 4,499.00
AXIS Q6124-E 60HZ	01070-004	Lightfinder HDTV PTZ for outdoor as well as indoor use. HDTV 720p resolution in 60fps with 30x zoom and top performance. Perfect image quality in all directions, without distortion. 130db WDR, EIS, automatic defog, Advanced gate keeper. With its compact size and repaintable surface, it will easily blend into the surroundings. Midspan with fiber slot included.	\$ 2,699.00
AXIS Q6125-LE 60HZ	01234-004	Top of the line PTZ with IR, HDTV 1080 and 30x optical zoom, H264/265 with Zipstream and Motion JPEG. IP66 for both indoor and outdoor use, WDR . Perfect image quality in all directions without distortion. WDR, EIS, Speed dry. Includes Advanced gate keeper analytics. With its compact size and repaintable surface, it will easily blend into the surroundings. Midspan with fiber slot and RJ45 input included.	\$ 2,999.00
AXIS Q6135-LE 60HZ	01959-004	PTZ camera with continues 360° pan and build in IR illumination (660ft) with 32x optical zoom, Autofocus and Focus Recall. HDTV 1080p @ 60fps (1920x1080) in Motion JPEG, H.264, H.265, and Axis Zipstream. Day & Night, IP66, NEMA 4X and NEMA TS2 classification. Full-size SD-card slot. Perfect image quality in all directions without distortion. WDR, EIS, Speed dry. Includes Advanced gate keeper and analytics. Repaintable surface. Midspan with fiber slot and RJ45 input included.	\$ 2,499.00
AXIS Q6128-E 60HZ	0799-004	Compact, top performance 4K Comparable with SMPTE 2036 3840x2160 resolution in 30fps, (8MP). With 12x optical zoom for outdoor as well as indoor use. Day/night, Automatic defog, DNR 2D/3D and EIS. IP66, Active gatekeeper, tour recording and autotracking. Perfect image quality in all directions, without distortion, repaintable surface. Mounting brackets are not included (several different accessories available). Midspan with fiber slot included.	\$ 3,199.00
AXIS Q6154-E 60 HZ	01511-004	Compact top performance HDTV PTZ for outdoor and indoor use with unique Laser Focus giving perfect focus. HDTV 720p resolution in 60fps, perfect image quality in all directions without distortion due to Axis' Sharpdome technology with hard coating. Repaintable surface, will easily blend into the surroundings. 30x zoom 120dbWDR, EIS, automatic defog, Advanced gate keeper and Lightfinder. Midspan with fiber slot included	\$ 2,699.00

AXIS Q6155-E 60HZ	0934-004	Compact top performance HDTV PTZ for outdoor and indoor use with unique Laser Focus giving perfect focus. HDTV 1080p resolution in 30fps, perfect image quality in all directions without distortion due to Axis' Sharpdome technology with hard coating. Repaintable surface, will easily blend into the surroundings. 30x zoom 120dbWDR, EIS, automatic defog, Advanced gate keeper and Lightfinder. Midspan with fiber included	\$ 2,999.00
AXIS Q6215-LE 60HZ	01442-004	PTZ for the toughest conditions. MIL specified, build in IR illumination 400M (1300ft), can be mounted face up or face down. IP66/67/68, IK10, MIL 8105 521. Camera part; 1/2" sensor with HDTV 1080p, 30x optical zoom, 60fps, H264 with Zipstream and Motion JPEG, WDR. Perfect image quality in all directions without distortion, window wiper. Advanced gate keeper analytics. 90W Midspan included. Color; Urban grey.	\$ 3,499.00
AXIS Q6215-LE 60HZ	01442-018	Product version for Canadian market. PTZ for the toughest conditions. MIL specified, build in IR illumination 400M (1300ft), can be mounted face up or face down. IP66/67/68, IK10, MIL 8105 521. Camera part; 1/2" sensor with HDTV 1080p, 30x optical zoom, 60fps, H264 with Zipstream and Motion JPEG, WDR. Perfect image quality in all directions without distortion, window wiper. Advanced gate keeper analytics. 90W Midspan included. Color; Urban grey.	\$ 3,499.00
AXIS V5925 60 Hz	01966-004	Generic PTZ camera with 30x zoom, autofocus and HDTV 1080p resolution at 60fps for live streaming of video and audio. "Video conference" design, smooth pan and tilt, EIS. HDMI, 3G-SDI, XLR-3 for studio connectivity. Studio quality in stereo. Power supply and wall mount bracket are included.	\$ 1,999.00
AXIS Q6075-SE 60 Hz	02239-001	Stainless steel, (SS-316L) top performance HDTV 1080p compliant, outdoor-ready, IP66, IK10 and NEMA 4X-rated PTZ dome camera with 40x optical zoom. Auto day/night functionality. Continuous 360° rotation and 220° tilt. HDTV 1080p (1920x1080) @60fps. Zipstream with H.264/ H.265 Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear transparent dome cover. Including 7 m cable, media converter switch with 2xSFP slots for optical fiber modules, 2xRJ-45, 2xI/O and 24V in. Brackets and power adapter are not included (several different accessories available).	\$ 4,499.00

<p>AXIS Q8752-E 35 MM 30 FPS</p>	<p>01838-001</p>	<p>High accuracy outdoor PTZ positioning Bispectral camera based on AXIS ARTPEC7 platform. Thermal sensor features a 640x480 resolution, 30 fps and 35 mm lens with 10.5° angle of view. Visual sensor have HDTV 1080p video resolution, 32x optical zoom, focus recall and is extremely light sensitive. EIS (Electronic Image Stabilization) on both channels ensures focused and stable video. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.265 and local storage. Included cybersecurity features are TPM module, Axis secure boot and comes with signed FW. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included).</p> <p>This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.</p>	<p>\$12,999.00</p>
<p>AXIS Q8752-E 35 MM 8.3 FPS</p>	<p>01839-001</p>	<p>High accuracy outdoor PTZ positioning Bispectral camera based on AXIS ARTPEC7 platform. Thermal sensor features a 640x480 resolution, 8.3 fps and 35 mm lens with 10.5° angle of view. Visual sensor have HDTV 1080p video resolution, 32x optical zoom, focus recall and is extremely light sensitive. EIS (Electronic Image Stabilization) on both channels ensures focused and stable video. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.265 and local storage. Included cybersecurity features are TPM module, Axis secure boot and comes with signed FW. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included).</p> <p>This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.</p>	<p>\$12,999.00</p>

<p>AXIS Q8752-E ZOOM 30 FPS</p>	<p>01841-001</p>	<p>High accuracy outdoor PTZ positioning Bispectral camera based on AXIS ARTPEC7 platform. Thermal sensor features a 640x480 resolution, 30 fps and 35-105 mm thermal zoom lens. Visual sensor have HDTV 1080p video resolution, 32x optical zoom, focus recall and is extremely light sensitive. EIS (Electronic Image Stabilization) on both channels ensures focused and stable video. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.265 and local storage. Included cybersecurity features are TPM module, Axis secure boot and comes with signed FW. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included).</p> <p>This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.</p>	<p>\$21,999.00</p>
<p>AXIS Q8752-E ZOOM 8.3 FPS</p>	<p>01840-001</p>	<p>High accuracy outdoor PTZ positioning Bispectral camera based on AXIS ARTPEC7 platform. Thermal sensor features a 640x480 resolution, 8.3 fps and 35-105 mm thermal zoom lens. Visual sensor have HDTV 1080p video resolution, 32x optical zoom, focus recall and is extremely light sensitive. EIS (Electronic Image Stabilization) on both channels ensures focused and stable video. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.265 and local storage. Included cybersecurity features are TPM module, Axis secure boot and comes with signed FW. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included).</p> <p>This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.</p>	<p>\$21,999.00</p>

<p>AXIS Q8641-E 35MM 30 FPS 24V</p>	<p>01119-001</p>	<p>High accuracy outdoor PT positioning thermal camera. 384x288 resolution, 30 fps and 35 mm lens with 10.5° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.</p>	<p>\$ 5,799.00</p>
<p>AXIS Q8641-E 35MM 8.3 FPS 24V</p>	<p>01120-001</p>	<p>High accuracy outdoor PT positioning thermal camera. 384x288 resolution, 8.3 fps and 35 mm lens with 10.5° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.</p>	<p>\$ 5,799.00</p>
<p>AXIS Q8642-E 60MM 30 FPS 24V</p>	<p>01121-001</p>	<p>High accuracy outdoor PT positioning thermal camera. 640x480 resolution, 30 fps and 60 mm lens with 10°angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.</p>	<p>\$ 9,499.00</p>

<p>AXIS Q8642-E 60MM 8.3 FPS 24V</p>	<p>01122-001</p>	<p>High accuracy outdoor PT positioning thermal camera. 640x480 resolution, 8.3 fps and 60 mm lens with 10°angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.</p>	<p>\$ 9,499.00</p>
<p>AXIS Q8741-E 35MM 30 FPS 24V</p>	<p>0824-001</p>	<p>High accuracy outdoor PTZ positioning bispectral camera. Thermal sensor features a 384x288 resolution, 30 fps and 35 mm lens with 10.5° angle of view. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, focus recall and are extremely light sensitive. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.</p>	<p>\$ 9,999.00</p>
<p>AXIS Q8741-LE 35MM 30 FPS 24V</p>	<p>01013-001</p>	<p>High accuracy outdoor PTZ positioning bispectral camera with IR illuminators. Thermal sensor features a 384x288 resolution, 30 fps and 35 mm lens with 10.5° angle of view. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, built-in IR pass filter for sharper images in mixed lighting conditions. IR range up to 500m. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.</p>	<p>\$11,599.00</p>

<p>AXIS Q8741-E 35MM 8.3 FPS 24V</p>	<p>0823-001</p>	<p>High accuracy outdoor PTZ positioning bispectral camera. Thermal sensor features a 384x288 resolution, 8.3 fps and 35 mm lens with 10.5° angle of view. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, focus recall and are extremely light sensitive. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.</p>	<p>\$ 9,999.00</p>
<p>AXIS Q8741-LE 35MM 8.3 FPS 24V</p>	<p>01012-001</p>	<p>High accuracy outdoor PTZ positioning bispectral camera with IR illuminators. Thermal sensor features a 384x288 resolution, 8.3 fps and 35 mm lens with 10.5° angle of view. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, built-in IR pass filter for sharper images in mixed lighting conditions. IR range up to 500m. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.</p>	<p>\$11,599.00</p>

<p>AXIS Q8742-E ZOOM 30 FPS 24V</p>	<p>0830-001</p>	<p>High accuracy outdoor PTZ positioning Bispectral camera. Thermal sensor features a 640x480 resolution, 30 fps and 35-105 mm thermal zoom lens. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, focus recall and are extremely light sensitive. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.</p>	<p>\$21,999.00</p>
<p>AXIS Q8742-E ZOOM 8.3 FPS 24V</p>	<p>0829-001</p>	<p>High accuracy outdoor PTZ positioning Bispectral camera. Thermal sensor features a 640x480 resolution, 8.3 fps and 35-105 mm thermal zoom lens. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, focus recall and are extremely light sensitive. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.</p>	<p>\$21,999.00</p>

<p>AXIS Q8742-E 35MM 30 FPS 24V</p>	<p>0828-001</p>	<p>High accuracy outdoor PTZ positioning Bispectral camera. Thermal sensor features a 640x480 resolution, 30 fps and 35 mm lens with 17° angle of view. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, focus recall and are extremely light sensitive. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.</p>	<p>\$12,999.00</p>
<p>AXIS Q8742-LE 35MM 30 FPS 24V</p>	<p>01017-001</p>	<p>High accuracy outdoor PTZ positioning bispectral camera with IR illuminators. Thermal sensor features a 640x480 resolution, 30 fps and 35 mm lens with 17° angle of view. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, built-in IR pass filter for sharper images in mixed lighting conditions. IR range up to 500m. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.</p>	<p>\$14,599.00</p>

<p>AXIS Q8742-E 35MM 8.3 FPS 24V</p>	<p>0827-001</p>	<p>High accuracy outdoor PTZ positioning bispectral camera. Thermal sensor features a 640x480 resolution, 8.3 fps and 35 mm lens with 17° angle of view. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, focus recall and are extremely light sensitive. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.</p>	<p>\$12,999.00</p>
<p>AXIS Q8742-LE 35MM 8.3 FPS 24V</p>	<p>01016-001</p>	<p>High accuracy outdoor PTZ positioning bispectral camera with IR illuminators. Thermal sensor features a 640x480 resolution, 8.3 fps and 35 mm lens with 17° angle of view. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, built-in IR pass filter for sharper images in mixed lighting conditions. IR range up to 500m. Integrated long-life silicone wiper for remote maintenance. The bispectral camera only need one IP address and supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.</p>	<p>\$14,599.00</p>

<p>AXIS Q8742-LE ZOOM 30 FPS 24V</p>	<p>01019-001</p>	<p>High accuracy outdoor PTZ positioning bispectral camera with IR illuminators. Thermal sensor features a 640x480 resolution, 30 fps and and 35-105 mm thermal zoom lens. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, built-in IR pass filter for sharper images in mixed lighting conditions. IR range up to 500m. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.</p>	<p>\$23,599.00</p>
<p>AXIS Q8742-LE ZOOM 8.3 FPS 24V</p>	<p>01018-001</p>	<p>High accuracy outdoor PTZ positioning bispectral camera with IR illuminators. Thermal sensor features a 640x480 resolution, 8.3 fps and and 35-105 mm thermal zoom lens. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, built-in IR pass filter for sharper images in mixed lighting conditions. IR range up to 500m. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.</p>	<p>\$23,599.00</p>

<p>AXIS P1280-E 2.2 MM 8.3 FPS</p>	<p>02114-001</p>	<p>AXIS P1280-E Thermal Network Camera is a modular thermal camera based on a small-sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/ 39.4ft cable. The camera provides 208x156 resolution, a 2.2 mm lens with 63° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, edge storage using microSD card and built-in analytics with support for AXIS Camera Application Platform, which enables the usage of a broad range of third-party applications. The flexible form factor allows it to be placed in locations with limited space and a wide range of mounting accessories enables wall, ceiling and recessed installations. The main unit is powered with PoE. The sensor unit has 12 m/39.4 ft cable.</p> <p>The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.</p>	<p>\$ 799.00</p>
<p>AXIS P1280-E 4MM 8.3 FPS</p>	<p>0940-001</p>	<p>AXIS P1280-E Thermal Network Camera is a modular thermal camera based on a small-sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/ 39.4ft cable. The camera provides 208x156 resolution, a 4 mm lens with 35.4° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, edge storage using microSD card and built-in analytics with support for AXIS Camera Application Platform, which enables the usage of a broad range of third-party applications. The flexible form factor allows it to be placed in locations with limited space and a wide range of mounting accessories enables wall, ceiling and recessed installations. The main unit is powered with PoE. The sensor unit has 12 m/39.4 ft cable.</p> <p>The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.</p>	<p>\$ 799.00</p>

<p>AXIS P1290-E 4 MM 8.3 FPS</p>	<p>01168-001</p>	<p>AXIS P1290-E Thermal Network Camera is a modular thermal camera based on a small-sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/ 39.4ft cable and dome casing.The camera provides 208x156 resolution, a 4 mm lens with 35.4° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, edge storage using microSD card and built-in analytics with support for AXIS Camera Application Platform, which enables the usage of a broad range of third-party applications. The main unit is powered with PoE. The sensor unit has 12 m/39.4 ft cable.</p> <p>The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.</p>	<p>\$ 849.00</p>
<p>AXIS Q1941-E 7MM 30 FPS</p>	<p>0786-001</p>	<p>Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 30 fps, and 7 mm lens with 55° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.</p>	<p>\$ 2,799.00</p>
<p>AXIS Q1941-E 13MM 30 FPS</p>	<p>0787-001</p>	<p>Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 30 fps, and 13 mm lens with 28° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.</p>	<p>\$ 2,799.00</p>

<p>AXIS Q1941-E 19MM 30 FPS</p>	<p>0877-001</p>	<p>Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 30 fps, and 19 mm lens with 19.4° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.</p>	<p>\$ 2,799.00</p>
<p>AXIS Q1941-E 35MM 30 FPS</p>	<p>0788-001</p>	<p>Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 30 fps, and 35 mm lens with 10.7° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.</p>	<p>\$ 3,799.00</p>
<p>AXIS Q1941-E 60MM 30 FPS</p>	<p>0789-001</p>	<p>Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 30 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.</p>	<p>\$ 5,299.00</p>

<p>AXIS Q1941-E PT MOUNT 7MM 30 FPS</p>	<p>0973-001</p>	<p>Outdoor Thermal Network Camera for positioning unit, 384x288 resolution, 30 fps, and 7 mm lens with 55° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed.</p> <p>This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.</p>	<p>\$ 2,799.00</p>
<p>AXIS Q1941-E PT MOUNT 13MM 30 FPS</p>	<p>0974-001</p>	<p>Outdoor Thermal Network Camera for positioning unit, 384x288 resolution, 30 fps, and 13 mm lens with 28° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed.</p> <p>This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.</p>	<p>\$ 2,799.00</p>
<p>AXIS Q1941-E PT MOUNT 19MM 30 FPS</p>	<p>0979-001</p>	<p>Outdoor Thermal Network Camera for positioning unit, 384x288 resolution, 30 fps, and 19 mm lens with 19.4° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed.</p> <p>This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.</p>	<p>\$ 2,799.00</p>

<p>AXIS Q1941-E PT MOUNT 35MM 30 FPS</p>	<p>0975-001</p>	<p>Outdoor Thermal Network Camera for positioning unit, 384x288 resolution, 30 fps, and 35 mm lens with 10.7° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed.</p> <p>This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.</p>	<p>\$ 3,799.00</p>
<p>AXIS Q1941-E PT MOUNT 60MM 30 FPS</p>	<p>0977-001</p>	<p>Outdoor Thermal Network Camera for positioning unit, 384x288 resolution, 30 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed.</p> <p>This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.</p>	<p>\$ 5,299.00</p>
<p>AXIS Q1942-E 10MM 30 FPS</p>	<p>0916-001</p>	<p>Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 30 fps, and 10mm lens with 63° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed.</p> <p>This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.</p>	<p>\$ 4,999.00</p>

<p>AXIS Q1942-E 19MM 30 FPS</p>	<p>0918-001</p>	<p>Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 30 fps, and 19 mm lens with 32° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.</p>	<p>\$ 4,999.00</p>
<p>AXIS Q1942-E 35MM 30 FPS</p>	<p>0920-001</p>	<p>Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 30 fps, and 35 mm lens with 17° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.</p>	<p>\$ 5,999.00</p>
<p>AXIS Q1942-E 60MM 30 FPS</p>	<p>0922-001</p>	<p>Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 30 fps, and 60 mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.</p>	<p>\$ 7,499.00</p>

<p>AXIS Q1942-E PT MOUNT 10MM 30 FPS</p>	<p>0981-001</p>	<p>Outdoor Thermal Network Camera for positioning unit. 640x480 resolution, 30 fps, and 10mm lens with 63° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed.</p> <p>This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.</p>	<p>\$ 4,999.00</p>
<p>AXIS Q1942-E PT MOUNT 19MM 30 FPS</p>	<p>0983-001</p>	<p>Q1942-E PT mount 19mm Outdoor Thermal Network Camera for positioning unit. 640x480 resolution, 30 fps, and 19mm lens with 32° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed.</p> <p>This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.</p>	<p>\$ 4,999.00</p>
<p>AXIS Q1942-E PT MOUNT 35MM 30 FPS</p>	<p>0985-001</p>	<p>Outdoor Thermal Network Camera for positioning unit. 640x480 resolution, 30 fps, and 35mm lens with 17° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed.</p> <p>This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.</p>	<p>\$ 5,999.00</p>

<p>AXIS Q1942-E PT MOUNT 60MM 30 FPS</p>	<p>0987-001</p>	<p>Outdoor Thermal Network Camera for positioning unit. 640x480 resolution, 30 fps, and 60mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed.</p> <p>This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.</p>	<p>\$ 7,499.00</p>
<p>AXIS Q2901-E 9MM 8.3 FPS</p>	<p>0645-001</p>	<p>AXIS Q2901-E Temperature alarm camera for wall and ceiling mount, IP66-rated, 336x256 resolution, 8.3 fps, and 35° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, audio, local storage, I/O, PoE, shock detection, AXIS Video Motion Detection 3.0, audio detection and AXIS Camera Application Platform.</p> <p>The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.</p>	<p>\$ 5,199.00</p>
<p>AXIS Q2901-E PTMOUNT 9MM 8.3 FPS</p>	<p>0646-001</p>	<p>AXIS Q2901-E PT Mount Temperature alarm camera ready for pan/tilt motor head, IP66-rated, 336x256 resolution, 8.3 fps, and 35° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, local storage, RS422/RS485, PoE, shock detection, AXIS Video Motion Detection 3.0, and AXIS Camera Application Platform.</p> <p>The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.</p>	<p>\$ 5,199.00</p>
<p>AXIS Q2901-E 19MM 8.3 FPS</p>	<p>0647-001</p>	<p>AXIS Q2901-E Temperature alarm camera for wall and ceiling mount, IP66-rated, 336x256 resolution, 8.3 fps, and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, audio, local storage, I/O, PoE, shock detection, AXIS Video Motion Detection 3.0, audio detection and AXIS Camera Application Platform.</p> <p>The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.</p>	<p>\$ 5,199.00</p>

<p>AXIS Q2901-E PTMOUNT 19MM 8.3 FPS</p>	<p>0648-001</p>	<p>AXIS Q2901-E PT Mount Temperature alarm camera ready for pan/tilt motor head, IP66-rated, 336x256 resolution, 8.3 fps, and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, local storage, RS422/RS485, PoE, shock detection, AXIS Video Motion Detection 3.0, and AXIS Camera Application Platform.</p> <p>The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.</p>	<p>\$ 5,199.00</p>
<p>AXIS FA1080-E 2.2MM 8.3 FPS</p>	<p>02089-001</p>	<p>AXIS FA1080-E 2.2M 8.3 FPS is a modular thermal sensor unit to be used together with AXIS FA54 Main Unit. The thermal sensor unit provides 208x156 resolution and includes a 2.2 mm lens with 63° horizontal FOV. The flexible form factor allows it to be placed in locations with limited space and can be used with a wide range of mounting accessories to enable wall, ceiling and recessed installations. The sensor unit is outdoor-ready and has 12 m/39.4 ft cable.</p> <p>This product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.</p>	<p>\$ 649.00</p>
<p>AXIS FA1080-E 4MM 8.3 FPS</p>	<p>01728-001</p>	<p>AXIS FA1080-E 4MM 8.3 FPS is a modular thermal sensor unit to be used together with AXIS FA54 Main Unit. The thermal sensor unit provides 208x156 resolution and includes a 4 mm lens with 35.4° horizontal FOV. The flexible form factor allows it to be placed in locations with limited space and can be used with a wide range of mounting accessories to enable wall, ceiling and recessed installations. The sensor unit is outdoor-ready and has 12 m/39.4 ft cable.</p> <p>This product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.</p>	<p>\$ 649.00</p>

AXIS FA4090-E 4MM 8.3 FPS	01729-001	<p>AXIS FA4090-E 4MM 8.3 FPS is a modular thermal sensor unit to be used together with AXIS FA54 Main Unit. The thermal sensor unit provides 208x156 resolution and includes a 4 mm lens with 35.4° horizontal FOV. The dome housing makes it easy to install and direct the sensor unit to cover your area of interests. The sensor unit is outdoor-ready and has 12 m/39.4 ft cable.</p> <p>This product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.</p>	\$ 699.00
CANON SUNSHADE COVER SC640-VB	0723C001	Sunshade cover for VB-H651LVE/VE outdoor Domes. Includes securing bolts for easy installation.	\$ 84.00
CANON SMOKED DOME UNIT DU10-S-VB	0721C001	Smoked dome cover for VB-R1xVE & VB-R1x PTZ Domes	\$ 81.00
CANON SMOKED DOME UNIT DU640-S-VB	0722C001	Smoked dome cover for VB-H651VE/V & VB-M64xVE/V domes	\$ 44.00
CANON WALL MOUNTING KIT WM10-VB	0720C001	Wall mount bracket for VB-R1xVE outdoor PTZ Domes. Consisting of heavy duty metal hinged cable box, right angle extender and PA10-15-VE bayonet camera fitting - 215mm stand-off.	\$ 456.00
CANON PLEN REC MOUNTKIT SR640-P-VB	0717C001	Indoor recessed ceiling mount kit for VB-H651V/M64xV domes. Comprising of in-ceiling cage and cover - Titanium White	\$ 350.00
CANON HEATER UNIT HU641-VB	0724C001	Optional heater element for VB-H651VE/M641VE outdoor Domes. Requires 24V AC power.	\$ 128.00
CANON PLE. REC MOUNT KIT SR30-P-VB	1065C001	Indoor plenum recessed ceiling mount kit for VB-S30D/S31D/S80xD mini-domes. Comprising of fire resistant in-ceiling cage and cover - Titanium White	\$ 121.00
CANON CEILIN MOUNT COV S SS40-S-VB	4962B001	Indoor surface mount ceiling cover (Silver) for VB-H43/M42 PTZ's Comprising of a metal mounting plate and "skirt" cover - Silver	\$ 62.00
CANON CEILING MOUNTING KIT CM10-VB	0711C001	Ceiling mount Back Box for VB-R1xVE outdoor PTZ Domes. Consisting of heavy duty metal hinged cable box and PA10-15-VE bayonet camera fitting - 342mm drop.	\$ 367.00
CANON 1.5 IN PIPE ADPT PA10-15-VB	0718C001	1.5inch Pipe Adaptor for VB-R1xVE outdoor PTZ Domes with standard NPSM screw thread and bayonet camera fitting - 100mm long.	\$ 86.00
CANON REC MOUNT KIT SR640-S-VB	0715C001	Indoor recessed ceiling mount kit for VB-H651V/M64xV domes. Comprising of in-ceiling cage and cover - Titanium White	\$ 276.00
CANON CONDUIT BOX CB740-VB	0712C001	Conduit box for VB-H76x/H751LE/M74x outdoor bullets.	\$ 118.00
CANON PENDANT MOUNTING KIT PC640-VB	0719C001	Indoor pendant mounting cap for VB-R13/11 indoor PTZ Domes, VB-H65x/M64x domes, and VB-H76x/H751LE/M74x bullets. Comprising of 1.5inch NPSM threaded pipe adaptor / cover - Titanium White.	\$ 89.00
CANON CONDUIT ADAPTER CA640-VB	0713C001	Conduit adaptor for VB-M64xVE outdoor Domes.	\$ 103.00
CANON REC MOUNT KIT SR11-S-VB	0714C001	Indoor recessed ceiling mount kit for VB-R13/R11 indoor PTZ Domes. Comprising of mounting template, in-ceiling cage and cover - Titanium White	\$ 328.00

CANON CEILIN MOUNT COV B SS40-B-VB	4962B002	Indoor surface mount ceiling cover (Black) for VB-H43B/M42B PTZ's. Comprising of a metal mounting plate and "skirt" cover - Black	\$ 62.00
CANON INDOOR DOME HOUSING DR41-C-VB	6816B001	Indoor recessed ceiling mount kit for VB-H43(/B) & VB-M42(/B) PTZ's. Comprising of in-ceiling cage and Clear Dome - Silver	\$ 215.00
CANON INDOOR DOME HOUSING DR41-S-VB	6816B002	Indoor recessed ceiling mount kit for VB-H43(/B) & VB-M42(/B) PTZ's. Comprising of in-ceiling cage and Smoked Dome - Silver	\$ 215.00
CANON SURFACE MOUNT SPACER SS30-VB	9920B001	Indoor surface mount wall/ceiling spacer for VB-S30D/S31D/S80xD mini-domes.	\$ 52.00
CANON A-BK3S(OW)	1381V106	Pole Mount Adapter and 59" length Non-Tool Stainless Clamp (Minimum Pole Diameter 4")	\$ 122.00
CANON A-SWD5VCHB	1381V120	A-SWD5VC with Heater & Blower	\$ 349.00
CANON A-SWD5ZWB600	2178V433	Wall bracket kit for VB-M641, VB-M640, VB-H630, VB-H610, VB-M620, and VB-M600	\$ 248.00
CANON A-SWD5WB3	2787V308	Wall bracket for VB-H43, VB-H41, VB-M42, VB-M40, VB-S30D, VB-S31D, VB-S800D, VB-S805D	\$ 104.00
CANON A-ODW7C12S(OW)	1923V398	A-ODW7C12(OW) with sunshield	\$ 618.00
CANON A-ODW7T12(OW)	1923V397	Wall mount 7" tinted vandal dome 12VDC with heater & blower (0.126" thickness polycarbonate capsule, IP66 or IPX4 selectable) for VB-H43, VB-H41, VB-M42, VB-M40, VB-C60, VB-C300, VB-C500D, VB-C50iR w/VB-EX50, and VC-C50iR	\$ 468.00
CANON A-CA15G	1381V127	Ceiling mount adapter	\$ 36.00
CANON A-SY15	1381V128	Sunshield	\$ 43.00
CANON A-SWD5ZWB	1968V994	Wall bracket for A-SWD5V & A-SWD5Z	\$ 205.00
CANON A-CM3	1381V107	Corner Mount Adapter	\$ 104.00
CANON A-VC50BRK	1381V108	Adapter bracket for VC-C50iR	\$ 31.00
CANON A-ODW5C12S(OW)	3067V203	A-ODW5C12(OW) with sunshield	\$ 511.00
CANON A-SWD5ZC	2064V111	Tough Dome Lite. Vandal surface mount dome 5" clear for VB-H43, VB-H41, VB-M42, VB-M40, VB-C60, VB-C300, VB-C500D, VB-C50iR, and VC-C50iR. (Capsule made of 0.118" thickness Polycarbonate)	\$ 205.00
CANON A-BK4	3063V605	Pole Mount Adapter and Stainless U-Bolt for 1 1/2" NPT (2x) (Pole Diameter 1.5" - 2.0")	\$ 102.00
CANON A-ODW5C12(OW)	3067V202	Wall mount 6" clear dome 12VDC with heater & blower (IP66 or IPX4 selectable) for VB-M50, VB-H43, VB-H41, VB-M42, VB-M40, VB-C60, VB-C300, VB-C500D, VB-C50iR, and VC-C50iR	\$ 406.00
CANON A-SWD5ZWB-2	2038V642	Attachment Plate for A-SWD5ZWB (Required if installing VB-M641, VB-M640, VB-H630, VB-H610, VB-M620, and VB-M600)	\$ 56.00
CANON A-ODW5T(OW)	3067V201	Wall mount 6" tinted dome 24VAC with heater & blower (IP66 or IPX4 selectable) for VB-M50, VB-H43, VB-H41, VB-M42, VB-M40, VB-C60, VB-C300, VB-C500D, VB-C50iR, and VC-C50iR	\$ 406.00

CANON A-ODW5TS(OW)	3067V212	A-ODW5T(OW) with sunshield	\$ 511.00
CANON A-ODW5T12S(OW)	3067V205	A-ODW5T12(OW) with sunshield	\$ 511.00
CANON A-H24	2038V640	Additional Heater for A-ODW	\$ 32.00
CANON A-OH15FBHSET-S(OW)	2038V641	Outdoor camera housing with heater & blower and Wall bracket in Stainless for VB-H730F, VB-H710F, VB-M720F, VB-M700F, and VB-C50FSi	\$ 287.00
CANON A-RCP5C	2030V463	Replacement capsule, 5" Clear (for A-ODW5 / A-ID5 / A-SWD5)	\$ 97.00
CANON A-ODW5C(OW)	3067V199	Wall mount 6" clear dome 24VAC with heater & blower (IP66 or IPX4 selectable) for VB-M50, VB-H43, VB-H41, VB-M42, VB-M40, VB-C60, VB-C300, VB-C500D, VB-C50iR, and VC-C50iR	\$ 406.00
CANON A-RCP7C	2030V464	Replacement capsule, 7" Clear (for A-ODW7 / A-ID7)	\$ 102.00
CANON A-CM100NPT	1381V101	Ceiling mount bracket for 1 1/2" NPT. Steel construction with powder coat finish	\$ 101.00
CANON A-SWD5ZT	2064V112	Tough Dome Lite. Vandal surface mount dome 5" tinted for VB-H43, VB-H41, VB-M42, VB-M40, VB-C60, VB-C300, VB-C500D, VB-C50iR, and VC-C50iR. (Capsule made of 0.118" thickness Polycarbonate)	\$ 205.00
CANON A-RCP5VT	2384V845	Replacement capsule, 5" Tinted (for A-SWD5V / A-SWD5Z)	\$ 97.00
CANON A-BK3(OW)	2120V066	Pole Mount Adapter and 59" length Non-Tool Aluminum Clamp (Minimum Pole Diameter 4")	\$ 75.00
CANON A-SWD5BH2	2120V067	Blower & Heater for A-SWD5, A-SWD5Z, A-SWD5V	\$ 90.00
CANON A-RCP5VC	2384V844	Replacement capsule, 5" Clear (for A-SWD5V / A-SWD5Z)	\$ 97.00
CANON A-ODW5CS(OW)	3067V200	A-ODW5C(OW) with sunshield	\$ 511.00
CANON A-CP100NPT	1381V102	Coupling for dome housing for 1 1/2" NPT. Steel construction with powder coat finish	\$ 64.00
CANON A-RCP5T	1381V103	Replacement capsule, 5" Tinted (for A-ODW5 / A-ID5 / A-SWD5)	\$ 95.00
CANON A-ID7TF	1381V112	Indoor tinted recessed 7" dome for VB-H43, VB-H41, VB-M42, VB-M40, VB-C60, VB-C300, VB-C500D, VB-C50FSi, VB-C50iR w/VB-EX50, and VC-C50iR	\$ 181.00
CANON A-ID7CF	1381V111	Indoor clear recessed 7" dome for VB-H43, VB-H41, VB-M42, VB-M40, VB-C60, VB-C300, VB-C500D, VB-C50FSi, VB-C50iR w/VB-EX50, and VC-C50iR	\$ 181.00
CANON A-ODW7C12(OW)	1923V396	Wall mount 7" clear vandal dome 12VDC with heater & blower (0.126" thickness polycarbonate capsule, IP66 or IPX4 selectable) for VB-H43, VB-H41, VB-M42, VB-M40, VB-C60, VB-C300, VB-C500D, VB-C50iR w/VB-EX50, and VC-C50iR	\$ 468.00
CANON A-OH15F	1588V039	Outdoor camera housing with Wall bracket for VB-H730F, VB-H710F, VB-M720F, VB-M700F, and VB-C50FSi	\$ 165.00

CANON A-SWD5VT	1381V119	Tough Dome. Vandal surface mount dome 5" tinted for VB-H43, VB-H41, VB-M42, VB-M40, VB-C60, VB-C300, VB-C500D, VB-C50iR, and VC-C50iR. (Capsule made of 0.118" thickness Polycarbonate with Cast Aluminum Body)	\$ 256.00
CANON A-SWD5VTHB	1381V121	A-SWD5VT with Heater & Blower	\$ 349.00
CANON A-ODW7T12S(OW)	1923V399	A-ODW7T12(OW) with sunshield	\$ 618.00
CANON A-RCP7T	1381V104	Replacement capsule, 7" Tinted (for A-ODW7 / A-ID7)	\$ 102.00
CANON A-VSM4TL	1381V125	Vandal Resistant M4 Screws & Tool Set; consists of 7 vandal resistant M4 screws and 1 tool	\$ 22.00
CANON A-OH15FBHSET(OW)	1381V126	Outdoor camera housing with heater & blower and Wall bracket in Steel for VB-H730F, VB-H710F, VB-M720F, VB-M700F, and VB-C50FSi	\$ 238.00
CANON A-ODW7C(OW)	1381V097	Wall mount 7" clear vandal dome 24VAC with heater & blower (0.126" thickness polycarbonate capsule, IP66 or IPX4 selectable) for VB-H43, VB-H41, VB-M42, VB-M40, VB-C60, VB-C300, VB-C500D, VB-C50iR w/VB-EX50, and VC-C50iR	\$ 468.00
CANON A-PS2412SWD5	1381V122	24VAC-12VDC Converter (for A-SWD5)	\$ 106.00
CANON A-PS2412	1381V105	24VAC-12VDC Converter (for A-ODW / A-ID / A-OH15)	\$ 106.00
CANON A-ODW7CS(OW)	1381V099	A-ODW7C(OW) with sunshield	\$ 618.00
CANON A-ODW7T(OW)	1586V919	Wall mount 7" tinted vandal dome 24VAC with heater & blower (0.126" thickness polycarbonate capsule, IP66 or IPX4 selectable) for VB-H43, VB-H41, VB-M42, VB-M40, VB-C60, VB-C300, VB-C500D, VB-C50iR w/VB-EX50, and VC-C50iR	\$ 468.00
CANON A-ODW7TS(OW)	1586V921	A-ODW7T(OW) with sunshield	\$ 618.00
CANON A-CM100	1381V100	Narrow ceiling mount bracket. Steel construction with powder coat finish	\$ 115.00
CANON A-ODW5T12(OW)	3067V204	Wall mount 6" tinted dome 12VDC with heater & blower (IP66 or IPX4 selectable) for VB-M50, VB-H43, VB-H41, VB-M42, VB-M40, VB-C60, VB-C300, VB-C500D, VB-C50iR, and VC-C50iR	\$ 401.00
CANON A-SWD5C	3067V206	Surface mount dome 6" clear for VB-M50, VB-H43, VB-H41, VB-M42, VB-M40, VB-C300, VB-C500D, VB-C50iR, and VC-C50iR	\$ 129.00
CANON A-SWD5T	3067V207	Surface mount dome 6" tinted for VB-M50, VB-H43, VB-H41, VB-M42, VB-M40, VB-C300, VB-C500D, VB-C50iR, and VC-C50iR	\$ 129.00
CANON A-SWD5CHB	3067V208	A-SWD5C w/ heater and blower for VB-M50, VB-H43, VB-H41, VB-M42, VB-M40, VB-C300, VB-C500D, VB-C50iR, and VC-C50iR	\$ 225.00
CANON A-SWD5THB	3067V209	A-SWD5T w/ heater and blower for VB-M50, VB-H43, VB-H41, VB-M42, VB-M40, VB-C300, VB-C500D, VB-C50iR, and VC-C50iR	\$ 225.00
CANON A-ID5T5	3067V210	Indoor tinted recessed 6" dome for VB-M50, VB-H43, VB-H41, VB-M42, VB-M40, VB-C60, VB-C300, VB-C500D, VB-C50iR, and VC-C50iR	\$ 137.00
CANON A-ID5C5	3067V211	Indoor clear recessed 6" dome for VB-M50, VB-H43, VB-H41, VB-M42, VB-M40, VB-C60, VB-C300, VB-C500D, VB-C50iR, and VC-C50iR	\$ 137.00

CANON A-SWD5VC	1381V118	Tough Dome. Vandal surface mount dome 5" clear for VB-H43, VB-H41, VB-M42, VB-M40, VB-C60, VB-C300, VB-C500D, VB-C50iR, and VC-C50iR. (Capsule made of 0.118" thickness Polycarbonate with Cast Aluminum Body)	\$ 256.00
CANON ITS-S-RK RECESSED KIT	2943V528	Recessed Mounting Kit for VB-S30D, VB-S31D, VB-S800D, VB-S805D	\$ 109.00
CANON PA-V18 US	8362B001	EAC certified encapsulated AC Adapter (12V DC Power supply) with US plug	\$ 115.00
CANON HEATER UNIT HU652-VB	1498C001	Optional heater element for VB-H652LVE outdoor Dome. Requires AC24V power	\$ 150.00
CANON SMOKED DOME UNIT DU652-S-VB	1497C001	Smoked Dome Unit for VB-H652LVE outdoor dome	\$ 65.00
CANON PENDANT CAP PC30VE-VB	1736C001	Indoor Pendant mounting Cap for VB-S30VE/S800VE mini-domes	\$ 67.00
CANON CONDUIT BOX CB30VE-VB	1735C001	Conduit Box for VB-S30VE/S800VE mini-domes	\$ 100.00
CANON A-SWD5WB2	3072V366	Indoor universal wall mount bracket suitable for VB-R13/R11 indoor PTZ Domes, and VB-H/M domes. 172mm standoff to centre	\$ 112.00
CANON A-SWD5CA2	3497V728	Ceiling adapter for A-SWD5 (Pipe is not provided)	\$ 172.00
CANON NETWORK CAMERA VB-M741LE (H2)	3746C001	Outdoor fixed box network camera with IR LED illumination up to 30m. 2.4x optical zoom, day/night switching. Hydrophilic Coating II for better visibility during / after rainfall and fouling resistance. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology. 8 in-built video & audio intelligent analytic functions, and linked events. IP66, NEMA250-rated and operating temperature in -50° C to +55° C (-58° F to +131° F). Powered by PoE+, PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Pigtail cable connection. Available in Titanium White.	\$ 1,226.22
CANON NETWORK CAMERA VB-M740E (H2)	3747C001	Outdoor fixed box network camera with IR LED illumination up to 30m. 2.4x optical zoom, day/night switching. Hydrophilic Coating II for better visibility during / after rainfall and fouling resistance. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology. 8 in-built video & audio intelligent analytic functions, and linked events. IP66, NEMA250-rated and operating temperature in -50° C to +55° C (-58° F to +131° F). Powered by PoE+, PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Pigtail cable connection. Available in Titanium White. Includes wall/ceiling plate for easy surface mounting. Includes wall/ceiling plate for easy surface mounting.	\$ 954.00

CANON NETWORK CAMERA VB-S910F	1389C001	Indoor compact fixed box network camera. 3.5x optical zoom, auto focus, digital night mode and built-in Omni-directional microphone. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast, ADSR - Area-specific Data Size Reduction technology. 7 in-built video & audio intelligent analytic functions and linked events. Powered by PoE (Power supply not included). Audio output port and in-built microphone, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Titanium White.	\$ 439.00
CANON NETWORK CAMERA VB-H761LVE (H2)	3749C001	Outdoor vandal resistant fixed box network camera with IR LED illumination up to 60m. 20x optical zoom, auto focus, day/night switching, Hydrophilic Coating II for better visibility during / after rainfall and fouling resistance. Enhanced Digital Zoom capabilities and Clear IR Mode. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology and Motion-Adaptive Noise Reduction. 8 in-built video & audio intelligent analytic functions, and linked events. IP66, NEMA250, IK09-rated and operating temperature in -50° C to +55° C (-58° F to +131° F). Powered by PoE+, PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Available in Titanium White. Includes wall/ceiling plate for easy surface mounting.	\$ 1,485.00
CANON NETWORK CAMERA VB-H760VE (H2)	3750C001	Outdoor vandal resistant fixed box network camera. 20x optical zoom, auto focus, day/night switching and Enhanced Digital Zoom capabilities. Hydrophilic Coating II for better visibility during / after rainfall and fouling resistance. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology and Motion-Adaptive Noise Reduction. 7 in-built video intelligent analytic functions. IP66, NEMA250, IK09-rated and operating temperature in -10° C to +55° C (-14° F to +131° F). Powered by PoE(Power supply not included) and SD/SDHC/SDHX Card slot for Edge storage. Available in Titanium White. Includes wall/ceiling plate for easy surface mounting.	\$ 1,338.00
CANON NETWORK CAMERA VB-H751LE(H2)	3748C001	Outdoor fixed box network camera with IR LED illumination up to 30m. 2.4x optical zoom, day/night switching. Hydrophilic Coating II for better visibility during / after rainfall and fouling resistance. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology and Motion-Adaptive Noise Reduction. 8 in-built video & audio intelligent analytic functions, and linked events. IP66, NEMA250-rated and operating temperature in -50° C to +55° C (-58° F to +131° F). Powered by PoE+, PoE, 24V AC	\$ 1,350.00

CANON NETWORK CAMERA VB-S905F MkII	2556C001	Indoor compact fixed box network camera. Fixed 2.7mm wide angle lens (96.0° AOV 16:9), digital night mode. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE. (Power supply not included). Two way audio, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.	\$ 349.48
CANON NETWORK CAMERA VB-H730F MkII	2551C001	Indoor fixed box network camera with remote Zoom configuration. 2.4x optical zoom and day/night switching. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports, and SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.	\$ 649.15
CANON NETWORK CAMERA VB-S900F MkII	2553C001	Indoor compact fixed box network camera. Fixed 2.7mm wide angle lens (96.0° AOV 16:9) and digital night mode. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE (Power supply not included). Two way audio, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.	\$ 429.31
CANON NETWORK CAMERA VB-M641VE	0308C001	Outdoor vandal resistant fixed dome network camera with remote PTRZ configuration. 2.4x optical zoom and day/night switching. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology. 8 in-built video & audio intelligent analytic functions, and linked events. IP66, NEMA250 and IK10-rated and operating temperature in -40° C to +55° C (-40° F to +131° F) with optional heater fitted. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Pigtail cable connection. Available in Titanium White. Includes wall/ceiling plate for easy surface mounting. Optional heater unit HU641-VB sold separately.	\$ 1,069.11
CANON NETWORK CAMERA VB-M641V	0309C001	Indoor vandal resistant fixed dome network camera with remote PTRZ configuration. 2.4x optical zoom, day/night switching. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology. 8 in-built video & audio intelligent analytic functions, and linked events. IK10-rated. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Titanium White. Includes wall/ceiling plate for easy surface mounting.	\$ 759.49

CANON NETWORK CAMERA VB-M640VE	0310C001	Outdoor vandal resistant fixed dome network camera with PTRZ configuration. 2.4x optical zoom, day/night switching. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology. 6 in-built video intelligent analytic functions. IP66, NEMA250 and IK10-rated and operating temperature in -10° C to +55° C (-14° F to +131° F). Powered by PoE (Power supply not included) and micro SD/SDHC/SDHX Card slot for Edge storage. Pigtail cable connection. Available in Titanium White. Includes wall/ceiling plate for easy surface mounting.	\$ 769.05
CANON NETWORK CAMERA VB-M640V	0311C001	Indoor vandal resistant fixed dome network camera with remote PTRZ configuration. 2.4x optical zoom, day/night switching. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology. 6 in-built video intelligent analytic functions. IK10-rated. Powered by PoE (Power supply not included) and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Titanium White. Supplied with wall/ceiling mounting plate.	\$ 619.46
CANON NETWORK CAMERA VB-H651V	1385C001	Indoor vandal resistant fixed dome network camera with remote PTRZ configuration. 2.4x optical zoom, day/night switching. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology and Motion-Adaptive Noise Reduction. 8 in-built video & audio intelligent analytic functions, and linked events. IK10-rated. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Titanium White. Includes wall/ceiling plate for easy surface mounting.	\$ 888.85
CANON NETWORK CAMERA VB-H651VE	1384C001	Outdoor vandal resistant fixed dome network camera with remote PTRZ configuration. 2.4x optical zoom, day/night switching. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology and Motion-Adaptive Noise Reduction. 8 in-built video & audio intelligent analytic functions, and linked events. IP66, NEMA250 and IK10-rated and operating temperature in -40° C to +55° C (-40° F to +131° F) with	\$ 1,231.00

CANON NETWORK CAMERA VB-S800VE	1388C001	Outdoor compact fixed dome network camera. Fixed 2.7mm wide-angle lens (93.8° AOV 16:9), digital night mode and built-in Omni-directional microphone. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast, ADSR - Area-specific Data Size Reduction technology. 7 in-built video & audio intelligent analytic functions and linked events. IP66, IK10-rated and operating temperature in -25° C to +50° C (-14° F to + 122° F). Powered by PoE (Power supply not included). Audio output port and in-built microphone, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. 1m pigtail cable connection. Available in Titanium White.	\$ 505.00
CANON NETWORK CAMERA VB-S805D MkII	2554C001	Indoor compact fixed dome network camera. Fixed 2.7mm wide-angle lens (95° AOV 16:9) and digital night mode. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE (Power supply not included). Two way audio, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.	\$ 349.06
CANON NETWORK CAMERA VB-S30D MkII	2545C001	Indoor compact network camera with lite-PTZ operation. 3.5x optical zoom, auto focus, and digital night mode. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE (Power supply not included). Two way audio, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.	\$ 598.78
CANON NETWORK CAMERA VB-S31D MkII	2546C001	Indoor compact network camera with lite-PT operation. Fixed 2.7mm wide angle lens (95.0° AOV 16:9) and digital night mode. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE (Power supply not included). Two way audio, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.	\$ 569.13
CANON NETWORK CAMERA VB-S800D MkII	2552C001	Indoor compact fixed dome network camera. Fixed 2.7mm wide-angle lens (95.0° AOV 16:9) and digital night mode. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE (Power supply not included). Two way audio, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.	\$ 398.75

CANON NETWORK CAMERA VB-R13VE (H2)	3753C001	Outdoor vandal resistant PTZ Dome network camera with 360° endless rotation, auto-flip, and auto-tracking capabilities. 30x optical zoom, auto focus, day/night switching and Enhanced Digital Zoom capabilities. Hydrophilic Coating II for better visibility during / after rainfall and fouling resistance. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology and Motion-Adaptive Noise Reduction. 9 in-built video & audio intelligent analytic functions, and linked events. IP66, NEMA250, IK10-rated and operating temperature in -50° C to +55° C (-58° F to +131° F). Powered by PoE+, PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. 12cm Pigtail cable connection. Available in Titanium White. Requires WM10-VB Wall mount, CM10-VB Ceiling mount, or PA10-15-VB Pipe mount - sold separately.	\$ 3,678.61
CANON NETWORK CAMERA VB-R13	1383C001	Indoor PTZ Dome network camera with 360° endless rotation, auto-flip, and auto-tracking capabilities. 30x optical zoom, auto focus, day/night switching and Enhanced Digital Zoom capabilities. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology and Motion-Adaptive Noise Reduction. 9 in-built video & audio intelligent analytic functions, and linked events. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Available in Titanium White. Includes ceiling plate for easy surface mounting.	\$ 2,918.76
CANON NETWORK CAMERA VB-R12VE (H2)	3754C001	Outdoor vandal resistant PTZ Dome network camera with 360° endless rotation, auto-flip, and auto-tracking capabilities. 30x optical zoom, auto focus, day/night switching and Enhanced Digital Zoom capabilities. Hydrophilic Coating II for better visibility during / after rainfall and fouling resistance. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology and Motion-Adaptive Noise Reduction. 7 in-built video intelligent analytic functions. IP66, NEMA250, IK10-rated and operating temperature in -50° C to +55° C (-58° F to +131° F). Powered by PoE+, PoE, 24V AC and 12V DC (Power supply not included). SD/SDHC/SDHX Card slot for Edge storage. Available in Titanium White. Requires WM10-VB Wall mount, CM10-VB Ceiling mount, or PA10-15-VB Pipe mount - sold separately.	\$ 3,399.40

CANON NETWORK CAMERA VB-R11VE (H2)	3751C001	Outdoor vandal resistant network PTZ Dome camera with 360° endless rotation, auto-flip, and auto-tracking capabilities. 30x optical zoom, auto focus, and day/night switching. Hydrophilic Coating II for better visibility during / after rainfall and fouling resistance. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology. 9 in-built video & audio intelligent analytic functions, and linked events. IP66, NEMA250, IK10-rated and operating temperature in -50° C to +55° C (-58° F to +131° F). Powered by PoE+, PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. 12cm Pigtail cable connection. Available in Titanium White. Requires WM10-VB Wall mount, CM10-VB Ceiling mount, or PA10-15-VB Pipe mount - sold separately.	\$ 2,855.75
CANON NETWORK CAMERA VB-R11	0306C001	Indoor PTZ Dome network camera with 360° endless rotation, auto-flip, and auto-tracking capabilities. 30x optical zoom, auto focus, and day/night switching. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology. 9 in-built video & audio intelligent analytic functions, and linked events. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Available in Titanium White. Includes ceiling plate for easy surface mounting.	\$ 2,689.44
CANON NETWORK CAMERA VB-R10VE (H2)	3752C001	Outdoor vandal resistant network PTZ Dome camera with 360° endless rotation, auto-flip, and auto-tracking capabilities. 30x optical zoom, auto focus and day/night switching. Hydrophilic Coating II for better visibility during / after rainfall and fouling resistance. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology. 7 in-built video intelligent analytic functions. IP66, NEMA250, IK10-rated and operating temperature in -50° C to +55° C (-58° F to +131° F). Powered by PoE+, PoE, 24V AC and 12V DC (Power supply not included). SD/SDHC/SDHX Card slot for Edge storage. Available in Titanium White. Requires WM10-VB Wall mount, CM10-VB Ceiling mount, or PA10-15-VB Pipe mount - sold separately.	\$ 2,914.00
CANON NETWORK CAMERA VB-M50B	1064C001	Indoor PTZ network camera with 348° rotation and large aperture lens ideal for low light applications. 5x optical zoom, auto focus, day/night switching and Clear IR Mode. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast, ADSR - Area-specific Data Size Reduction technology and Motion-Adaptive Noise Reduction. 9 in-built video & audio intelligent analytic functions and linked events. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Only available in Black.	\$ 3,399.35

CANON NETWORK CAMERA VB-H652LVE	1061C001	Outdoor vandal resistant fixed dome network camera with IR LED illumination up to 20m, and NTSC video out for manual PT configuration. 2.4x optical zoom, day/night switching. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology and Motion-Adaptive Noise Reduction. 8 in-built video & audio intelligent analytic functions, and linked events. IP66, NEMA250 and IK10-rated and operating temperature in -40° C to +55° C (-40° F to +131° F) with optional heater fitted. Powered by PoE+, PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Titanium White. Includes wall/ceiling plate for easy surface mounting. Optional heater unit HU652-VB sold separately.	\$ 1,439.36
CANON NETWORK CAMERA VB-S30VE	1387C001	Outdoor compact network camera with lite-PTZ operation. 3.5x optical zoom, auto focus, digital night mode and built-in Omni-directional microphone. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast, ADSR - Area-specific Data Size Reduction technology. 7 in-built video & audio intelligent analytic functions and linked events. IP66, IK10-rated and operating temperature in -25° C to +50° C (-14° F to + 122° F). Powered by PoE (Power supply not included). Audio output port and in-built microphone, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. 1m pigtail cable connection. Available in Titanium White.	\$ 736.00
CANON NETWORK CAMERA VB-M44B	2542C002	BLACK VERSION Indoor PTZ network camera with 340° rotation. 20x optical zoom, auto focus, and day/night switching. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Available in Black (/B).	\$ 1,509.00
CANON NETWORK CAMERA VB-M44S	2542C001	SILVER VERSION Indoor PTZ network camera with 340° rotation. 20x optical zoom, auto focus, and day/night switching. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.	\$ 1,509.00
CANON NETWORK CAMERA VB-H45B	2541C002	BLACK VERSION Indoor PTZ network camera with 340° rotation. 20x optical zoom, auto focus, and day/night switching. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Available in Black (/B).	\$ 2,349.35

CANON NETWORK CAMERA VB-H45S	2541C001	SILVER VERSION Indoor PTZ network camera with 340° rotation. 20x optical zoom, auto focus, and day/night switching. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.	\$ 2,349.35
AXIS P7701	0319-004	1 channel network video decoder. Decodes H.264 and MPEG-4 Part 2 in max. D1 resolution at 30/25 (NTSC/PAL) fps and 720p in Motion JPEG. Decodes AAC, G726 and G.711 audio streams in mono. Supports video source sequencing. Power over Ethernet enabled. Includes power supply.	\$ 499.00
AXIS P7701 VIDEO DEC BB BULK 20PCS	0319-051	AXIS P7701 BARE BOARD in 20-pack. Cannot be sold separately as single packs. No power supplies.	\$ 9,980.00
AXIS P7701 VIDEO DECODER BARE BONE	0319-041	Bare bone 1 channel video decoder (PCB without any mechanics). Decodes H.264 and MPEG-4 Part 2 in max. D1 resolution at 30/25 (NTSC/PAL) fps and 720p in Motion JPEG. Decodes AAC, G726 and G.711 audio streams in mono. Supports video source sequencing. Power over Ethernet enabled. No power supply.	\$ 499.00
AXIS T8705 VIDEO DECODER	01186-004	Network Video Decoder for easy display of video from IP cameras on big screens. With the 1080p HDMI output, Ethernet input and compact size, it is very easy to setup and use. It can display the video both as sequence or multimode and with the integrated VAPIX support, it automatically finds Axis cameras on the network for plug-and-play configuration.	\$ 299.00
AXIS M7011 Video Encoder	0764-001	Single channel video encoder with H.264 (High, Main and Base profile) and Motion JPEG support. Power over Ethernet (IEEE 802.3af). Edge storage using microSDHC card or NAS. AVHS and ACAP support. No midspan included.	\$ 199.00
AXIS M7016 VIDEO ENCODER	0541-004	Sixteen-channel video encoder. Dual streaming H.264 and Motion JPEG on all channels. Max D1 resolution at 30/25 (NTSC/PAL) fps on all streams. Video motion detection. Active tampering alarm. Unit includes 4 x micro SD card slots for edge storage. PTZ support. Unit has 4 x ARTPEC chips and 4 x IP addresses. Includes power supply.	\$ 999.00
AXIS M7104 VIDEO ENCODER	01679-001	Four channel video encoder supporting PAL/NTSC cameras. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Frame rate 25/30 fps in all resolutions. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Serial port for RS422/485 communication. Power over Ethernet or 12-20V DC input. MicroSD/MicroSDHC memory card slot for optional local video storage.	\$ 299.00

AXIS P7224 Video Encoder Blade	0418-001	AXIS P7224: Four-channel video encoder blade. Dual streaming H.264 and Motion JPEG on all channels. Max D1 resolution at 30/25 (NTSC/PAL) fps on all streams. Video motion detection. Active tampering alarm. Two-way audio with audio detection. PTZ support. COMPATIBLE WITH AXIS Q7900 RACK AND AXIS 291 1U VIDEO SERVER RACK.	\$ 399.00
AXIS P7216 VIDEO ENCODER	0542-004	Sixteen-channel video encoder. Dual streaming H.264 and Motion JPEG on all channels. Max D1 resolution at 30/25 (NTSC/PAL) fps on all streams. Video motion detection. Active tampering alarm. Two-way audio with audio detection. SFP slot for optional fiber connection and/or network redundancy. Unit includes 4 x micro SD card slots for edge storage. PTZ support. Unit has 4 x ARTPEC chips and 4 x IP addresses. Includes power supply.	\$ 1,299.00
AXIS P7224 VID ENC BLADE BULK 10PCS	0418-021	AXIS P7224 in 10-pack. Cannot be sold separately as single packs.	\$ 3,869.00
AXIS P7304 VIDEO ENCODER	01680-001	Four channel video encoder supporting PAL/NTSC and HD analog cameras. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Frame rate 25/30 fps in all resolutions up to 1080p. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, active tampering alarm and audio detection. I/O for alarm/event handling, serial port for RS422/485 communication. Power over Ethernet or 12-20V DC input. MicroSD/MicroSDHC memory card slot for optional local video storage. Two-way audio with analog or digital microphone.	\$ 399.00
AXIS Q7411 VIDEO ENCODER	0518-004	Video Encoder with H.264 (Main and Base profile) and Motion JPEG support. Supports 60/50 frames per second. Coax PTZ Control, video motion detection, two-way audio, configurable I/O connectors and ACAP support. 8-28 VD and Power over Ethernet (IEEE 802.3af). Edge storage using microSDHC card or NAS.	\$ 399.00
AXIS Q7411 VIDEO ENCODER BULK 10PCS	0518-021	AXIS Q7411 in 10-pack. Power supply not included. Cannot be sold separately as single packs.	\$ 3,869.00
AXIS Q7414 VIDEO ENCODER BLADE	0354-001	Four channel video encoder blade. Multiple, individually configurable H.264 and Motion JPEG streams; max. D1 resolution at 30/25 fps per channel. Four bi-directional audio channels with AAC encoding. Video motion detection. Active tampering alarm. COMPATIBLE WITH AXIS Q7900 RACK AND AXIS 291 1U VIDEO SERVER RACK.	\$ 999.00
AXIS Q7414 VIDEO ENCODER BULK 10PCS	0354-021	AXIS Q7414 in 10-pack. Cannot be sold separately as single packs.	\$ 9,491.00
AXIS Q7424-R MKII VIDEO ENCODER	0742-001	Rugged Video Encoder with H.264 and Motion JPEG support. 1-4 video channels. Video motion detection. Two-way audio with audio detection. ACAP support on one channel. Ethernet port and SFP slot for fiber connection. Support for Power over Ethernet (IEEE 802.3af) and Power Supply (optional). Edge storage using SDHC card or NAS. PTZ support and configurable I/O connectors. AXIS Q7424-R MkII is an update to the original AXIS Q7424-R. The addition of 100 Mbps on the SFP slot is the only difference. The original product only has support for 1 Gbps.	\$ 899.00

AXIS Q7424-R MKII VID ENC BULK 10P	0742-021	Rugged Video Encoder with H.264 and Motion JPEG support. 1-4 video channels. Video motion detection. Two-way audio with audio detection. ACAP support on one channel. Ethernet port and SFP slot for fiber connection. Support for Power over Ethernet (IEEE 802.3af) and Power Supply (optional). Edge storage using SDHC card or NAS. PTZ support and configurable I/O connectors. AXIS Q7424-R MkII is an update to the original AXIS Q7424-R. The addition of 100 Mbps on the SFP slot is the only difference. The original product only has support for 1 Gbps. 10 PCS.	\$ 8,541.00
AXIS Q7436 VIDEO ENCODER BLADE	0584-001	6 channel video encoder blade. Multiple, individually configurable H.264 (Base, Main and High profile) and Motion JPEG streams; max. D1 resolution at 60/50 fps per channel. Video motion detection. Active tampering alarm. Coax PTZ Control (Coaxitron). Compatible with the following video encoder chassis:AXIS Q7920, AXIS Q7900 and AXIS 291 1U	\$ 1,199.00
AXIS Q7436 VIDEO ENCODER BLADE BULK 10 PCS	0584-021	AXIS Q7436 in 10-pack. Cannot be sold separately as single packs.	\$11,399.00
AXIS Q7436/Q7920 KIT	0656-004	14 x AXIS Q7436 Video Encoder Blade mounted in an AXIS Q7920 Video Encoder Chassis. Country specific power cable.	\$18,599.00
AXIS 291 1U VIDEO SERV RACK	0267-004	1U 19" rack unit with three expansions slots, compatible with all Axis Blade video servers. Universal built-in power supply. One 10/100/1000Base-T output.	\$ 399.00
AXIS 291 1U VIDEO SERVER RACK < GENERIC >	0267-001	1U 19" rack unit with three expansions slots, compatible with all Axis Blade video servers. Universal built-in power supply. One 10/100/1000Base-T output. No power cable.	\$ 399.00
AXIS Q7920 VIDEO ENCODER CHASSIS	0575-004	5 U rack-mount video encoder chassis, providing an expandable solution for migrating large-scale analog installations to network video. Holds up to 14 hot-swappable video encoder blades supporting up to 84 analog cameras.	\$ 2,599.00
AXIS S2208	01580-004	AXIS Camera Station S2208 Appliance is an eight channel compact desktop Client/Server including an integrated managed PoE switch validated and tested with Axis products. Preloaded with AXIS Camera Station software with preconfigured AXIS Camera Station settings and all other necessary software e.g. Windows 10 IoT. Includes 4 TB storage, Core licenses for 8 devices, 5-year limited hardware warranty on the appliance and 3-year on the hard drive. Supports up to 4k ultra HD.	\$ 2,299.00
AXIS S1116 MT	01617-001	AXIS Camera Station S1116 Recorder is an out-of-the-box ready workstation tested and validated with Axis products for reliable surveillance up to 4K video streams. Preconfigured and preloaded with AXIS Camera Station video management software including licenses for 16 channels plus all necessary system software. Includes 5-year limited hardware warranty, on-site hardware replacement service, keep your hard drive and international keyboard and mouse.	\$ 3,299.00

AXIS S1116 RACKED	01618-001	AXIS Camera Station S1116 Recorder is an out-of-the-box ready rack-server tested and validated with Axis products for reliable surveillance up to 4K video streams. Preconfigured and preloaded with AXIS Camera Station video management software including licenses for 16 channels plus all necessary system software. Includes 5-year limited hardware warranty, on-site hardware replacement service and keep your hard drive.	\$ 3,799.00
AXIS S1132	01613-001	AXIS Camera Station S1132 Recorder is an out-of-the-box ready rack server tested and validated with Axis products for reliable surveillance up to 4K video streams. Preconfigured and preloaded with AXIS Camera Station video management software including licenses for 32 channels plus all necessary system software. Includes 5-year limited hardware warranty, on-site hardware replacement service and keep your hard drive.	\$ 5,499.00
AXIS S1148 24TB	01614-001	AXIS Camera Station S1148 Recorder is an out-of-the-box ready rack server tested and validated with Axis products for reliable surveillance up to 4K video streams. Preconfigured and preloaded with AXIS Camera Station video management software including licenses for 48 channels plus all necessary system software. Includes 5-year limited hardware warranty, on-site hardware replacement service and keep your hard drive.	\$ 8,499.00
AXIS S1148 64TB	01615-001	AXIS Camera Station S1148 Recorder is an out-of-the-box ready rack server tested and validated with Axis products for reliable surveillance up to 4K video streams. Preconfigured and preloaded with AXIS Camera Station video management software including licenses for 48 channels plus all necessary system software. Includes 5-year limited hardware warranty, on-site hardware replacement service and keep your hard drive.	\$11,499.00
AXIS S1148 140TB	01616-001	AXIS Camera Station S1148 Recorder is an out-of-the-box ready rack server tested and validated with Axis products for reliable surveillance up to 4K video streams. Preconfigured and preloaded with AXIS Camera Station video management software including licenses for 48 channels plus all necessary system software. Includes 5-year limited hardware warranty, on-site hardware replacement service and keep your hard drive.	\$16,999.00
AXIS S9201 MKII	01691-001	AXIS Camera Station S9201 Mk II Desktop Terminal is an all-in-one desktop terminal with a 22-inch monitor for system overview, to be used with Axis recorders. The terminal is preloaded with AXIS Camera Station software and all other necessary software. Includes 3-year hardware warranty, on-site hardware replacement service and international keyboard and mouse.	\$ 1,899.00

AXIS S9002 MK II	01619-001	AXIS Camera Station S9002 Mk II Desktop Terminal is a high-performance desktop terminal to be used with Axis recorders. Optimized for surveillance purposes with four monitors and supports up to three 4K video streams. The terminal is preloaded with AXIS Camera Station software and all other necessary software. Includes 5-year limited hardware warranty, on-site hardware replacement service and international keyboard and mouse.	\$ 2,499.00
AXIS S2212	01581-004	AXIS Camera Station S2212 Appliance is a twelve channel compact desktop Client/Server including an integrated managed PoE switch validated and tested with Axis products. Preloaded with AXIS Camera Station software with preconfigured AXIS Camera Station settings and all other necessary software e.g. Windows 10 IoT. Includes 6 TB storage, Core licenses for 12 devices, 5-year limited hardware warranty on the appliance and 3-year on the hard drive. Supports up to 4k ultra HD.	\$ 2,999.00
AXIS S2216	01582-004	AXIS Camera Station S2216 Appliance is a sixteen channel Client/Server for rack-mounting including an integrated managed PoE switch validated and tested with Axis products. Preloaded with AXIS Camera Station software with preconfigured AXIS Camera Station settings and all other necessary software e.g. Windows 10 IoT. Includes 8 TB storage, Core licenses for 16 devices, 5-year limited hardware warranty on the appliance and 3-year on the hard drives. Supports up to 4k ultra HD.	\$ 3,799.00
AXIS S2224	01583-004	AXIS Camera Station S2224 Appliance is a twenty four channel Client/Server for rack-mounting including an integrated managed PoE switch validated and tested with Axis products. Preloaded with AXIS Camera Station software with preconfigured AXIS Camera Station settings and all other necessary software e.g. Windows 10 IoT. Includes 12 TB storage, Core licenses for 24 devices, 5-year limited hardware warranty on the appliance and 3-year on the hard drives. Supports up to 4k ultra HD.	\$ 4,499.00
AXIS S9101 Mk II	01985-004	AXIS Camera Station S9101 Mk II Desktop Terminal is a complement to Axis recorders to enable quick set-up of a surveillance workstation. The terminal is preloaded with an AXIS Camera Station client and preconfigured to minimize installation time. AXIS S9101 Mk II has validated hardware and software components for optimal surveillance experience and includes 5-year limited hardware warranty.	\$ 1,199.00

AXIS S1132 TOWER 32 TB	02079-004	AXIS Camera Station S1132 Tower 32 TB is an out-of-the-box ready server and client validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1132 Tower 32 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 32 channels plus all necessary software. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard disks and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1132 Tower 32 TB provides high-performance and reliability for your system. Includes 5-year limited hardware warranty, on-site hardware replacement service and keep your hard drive.	\$ 7,599.00
AXIS S1132 TOWER 64 TB	02080-004	AXIS Camera Station S1132 Tower 64 TB is an out-of-the-box ready server and client validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1132 Tower 64 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 32 channels plus all necessary software. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard disks and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1132 Tower 64 TB provides high-performance and reliability for your system. Includes 5-year limited hardware warranty, on-site hardware replacement service and keep your hard drive.	\$ 9,499.00
AXIS S3008 4 TB	02046-004	AXIS S3008 4 TB Recorder is a compact recorder with 8 PoE ports and a gigabit uplink. Up to 8 devices can be connected to the recorder and recording is done on the internal hard drive. For an easy and intuitive surveillance, it is compatible with AXIS Companion VMS and a wide range of cameras. To increase reliability and security, the product supports disk encryption, contains a 4 TB surveillance class hard drive and includes 5-year limited hardware warranty on the recorder and 3-year on the hard drive.	\$ 799.00
AXIS S3008 2 TB	02105-004	AXIS S3008 2 TB Recorder is a compact recorder with 8 PoE ports and a gigabit uplink. Up to 8 devices can be connected to the recorder and recording is done on the internal hard drive. For an easy and intuitive surveillance, it is compatible with AXIS Companion VMS and a wide range of cameras. To increase reliability and security, the product supports disk encryption, contains a 2 TB surveillance class hard drive and includes 5-year limited hardware warranty on the recorder and 3-year on the hard drive.	\$ 599.00

AXIS S3008 8 TB	02135-004	AXIS S3008 8 TB Recorder is a compact recorder with 8 PoE ports and a gigabit uplink. Up to 8 devices can be connected to the recorder and recording is done on the internal hard drive. For an easy and intuitive surveillance, it is compatible with AXIS Companion VMS and a wide range of cameras. To increase reliability and security, the product supports disk encryption, contains a 8 TB surveillance class hard drive and includes 5-year limited hardware warranty on the recorder and 3-year on the hard drive.	\$ 1,099.00
ACAP AXIS PERIMETER DEFENDER 1 E-LICENSE	0333-608	Single unit e-license for AXIS Perimeter Defender, a scalable and flexible video analytics application for perimeter surveillance and protection. Visit www.axis.com for supported products and application download.	\$ 299.00
ACAP AXIS PERIMETER DEFENDER 10 E-LICENSE	0333-609	Ten (10) unit e-license for AXIS Perimeter Defender, a scalable and flexible video analytics application for perimeter surveillance and protection. Visit www.axis.com for supported products and application download.	\$ 2,989.00
AXIS PERIMETER DEFENDER PTZ 1P ELIC	01725-001	Single unit license for AXIS Perimeter Defender PTZ Autotracking. Together with a fixed camera running AXIS Perimeter defender this enable automatic control of a PTZ camera to zoom in on and follow detected objects. Please check the supported countries (https://www.axis.com/files/pods/axis_perimeter_defender_ptz_autotracking_supported_countries.pdf) before ordering. Visit www.axis.com for supported products and application download.	\$ 299.00
AXIS H. 264 50-user decoder license pack	0160-050	A license document that grants installation of AXIS AVC/H.264 decoder onto 50 separate computers. Applicable for all AXIS products that supports H.264 but does not have support for audio.	\$ 45.00
AXIS H.264 +AAC decoder 50-user decoder license pack	0160-060	A license document that grants installation of AXIS AVC/H.264 and ACC decoder onto 50 separate computers. Applicable for all AXIS products that supports H.264 that also have support for audio.	\$ 55.00
AXIS STORE DATA MANAGER 10CH BASE E-LICENSE	01147-101	AXIS Store Data Manager is a server side tool that is used to collect and arrange analytics data from retail analytics-enabled cameras.	\$ 499.00
AXIS STORE DATA MANAGER 1CH ADD-ON E-LICENSE	01147-111	AXIS Store Data Manager is a server side tool that is used to collect and arrange analytics data. This article is for additional channels to be added to AXIS Store Data Mgr 10P Core	\$ 29.00
AXIS PEOPLE COUNTER E-LICENSE	01147-011	AXIS People Counter is a cost-efficient and scalable video analytics application for people counting. This business-improving application, installed on a network camera, enables accurate monitoring and analysis of customer flows. It is ideal for e.g. quick evaluation of marketing efforts, improving staff and store planning, or evaluating conversion rate if combined with point-of-sale data.	\$ 249.00
AXIS QUEUE MONITOR E-LICENSE	01147-031	AXIS Queue Monitor is a cost-efficient and scalable video analytics application for queue measurement and analysis. This application, installed on a network camera, provides statistics about queue duration and queue fluctuations over the course of the day, facilitating both staff planning and the comparison between store locations.	\$ 299.00

AXIS OCCUPANCY ESTIMATOR E-LICENSE	01147-051	AXIS Occupancy Estimator is a cost-efficient and scalable video analytics application for gathering and analyzing occupancy data. This application, installed on a network camera, is a valuable tool for improving service planning in places like shopping malls or entertainment venues.	\$ 249.00
AXIS TAILGATING DETECTOR E-LICENSE	01147-071	AXIS Tailgating Detector is a cost-efficient video analytics application for ensuring that only one person at a time is entering in an automated access control system. Preventing unauthorized entering, the camera-integrated application is ideal for subways, gyms, or other places where access cards are used	\$ 249.00
AXIS DIRECTION DETECTOR E-LICENSE	01147-081	AXIS Direction Detector is a cost-efficient and scalable video analytics application for detecting people moving in the wrong direction. This camera-integrated application reduces the need for physical barriers or extra staff in for example retail stores or airports, where it registers the number of people passing by and in what direction	\$ 249.00
AXIS RANDOM SELECTOR E-LICENSE	01147-091	AXIS Random Selector is a camera-integrated video analytics application for randomly singling out individuals for inspection. The application eliminates any bias in the selection and inspection of, for instance, employees leaving a store, and may thereby reduce employees' discomfort.	\$ 249.00
ACAP AXIS PARKING VIO DETN 1 E-LIC	01939-001	Single unit e-license for AXIS Parking Violation Detection, a scalable and flexible video analytics solution to detect vehicles stopping in areas where vehicles should not park or stop.	\$ 649.00
AXIS LIVE PRIVACY SHIELD	01931-001	When you want video surveillance but still need to protect peoples privacy.	\$ 199.00
AXIS LIVE PRIVACY SHIELD 10PCS	01931-021	Ten (10) unit e-license for AXIS Live Privacy Shield, when you want video surveillance but still need to protect peoples privacy.	\$ 1,989.00
AXIS STORE REPORTER SUBSCRIPT 2021	02283-001	AXIS Store Reporter is a web-based tool that is used for graphical representation and reporting of statistical data gathered from Axis retail analytics applications. It is sold on a per channel basis as e-license. A license is valid until 31 Dec 2021. After this date the license will have to be renewed. AXIS Store Data Manager is included in AXIS Store Reporter.	\$ 99.00
ACS CORE DEVICE E-LICENSE	0879-010	One (1) AXIS Camera Station version 5.0 and up, Core Device license. Applicable for AXIS devices. AXIS Camera Station is a monitoring and recording system mid-size installations optimized to take full advantage of Axis leading network cameras and video encoders. It combines easy setup with an intuitive user interface for efficient operation, quick investigation and high definition identification. Delivered as eLicense key. Note: eLicenses are non-cancellable, non-changeable and non-returnable.	\$ 79.00

ACS UNIVERSAL DEVICE E-LICENSE	0879-020	<p>One (1) Universal Device license applicable for AXIS Camera Station version 5.0 and up.</p> <p>AXIS Camera Station is a monitoring and recording system mid-size installations optimized to take full advantage of Axis leading network cameras and video encoders. It combines easy setup with an intuitive user interface for efficient operation, quick investigation and high definition identification.</p> <p>Delivered as eLicense key. Note: eLicenses are non-cancellable, non-changeable and non-returnable.</p>	\$ 149.00
ACS 4 TO UNIVERSAL UPG E-LICENSE	0879-040	<p>One (1) upgrade license applicable for existing licenses of AXIS Camera Station, version 1,2,3, 4. Each existing license in combination with this upgrade license enables upgrade to a AXIS Camera Station version 5 Universal Device license.</p> <p>Delivered as eLicense key. Note: eLicenses are non-cancellable, non-changeable and non-returnable.</p>	\$ 19.00
ACS CORE TO UNIVERSAL UPG E-LICENSE	0879-030	<p>This license is primarily used for replacing AXIS devices with ONVIF devices. One (1) Upgrade license and one AXIS Camera Station version 5 Core Device license upgrades to one (1) Universal Device license.</p> <p>Delivered as eLicense key. Note: eLicenses are non-cancellable, non-changeable and non-returnable.</p>	\$ 79.00
AXIS D20 FRONT COVER KIT A	01438-001	Replacement front cover for AXIS D2050-VE. Includes anti-loss screws and sealing gaskets.	\$ 79.00
AXIS F4005-E CLEAR DOME 5PCS	5801-461	Standard clear dome for AXIS F4005-E, 5 pcs	\$ 79.00
ACC TOP COVER AXIS 209FD-R 10PCS	5500-301	Replaceable cover for AXIS 209FD-R, 10 pcs. Includes dry bags	\$ 249.00
SPR DOME CLEAR AXIS 215 PTZ-E	5700-291	Spare clear dome for AXIS 215-PTZ-E. Includes mounting ring, clear bubble, rubber gasket and 4 screws.	\$ 99.00
ACC DOME AXIS 216FD-V GLASS SMOKED	5005-061	Vandal-resistant casing with smoked transparent cover. Can also upgrade an AXIS 216FD/216MFD/P330X/M320X to an AXIS 216FD-V/216MFD-V/P330X-V/M320X-V	\$ 69.00
AXIS M3006 CLEAR DOME 5PCS	5800-731	Original white top cover with clear dome for AXIS M3006, 5pcs.	\$ 249.00
AXIS M3007 CLEAR DOME 5PCS	5800-741	Original white top cover with clear dome for AXIS M3007, 5pcs.	\$ 249.00
AXIS M3024 CLEAR DOME 5PCS	5800-711	Standard clear domes for AXIS M3024, 5 pcs	\$ 249.00
AXIS M3025/26 CLEAR DOME 5PCS	5800-721	Standard clear domes for AXIS M3025, M3026. 5 pcs	\$ 249.00
AXIS M3027 CLEAR DOME 5PCS	5800-751	Standard clear domes for AXIS M3027, 5 pcs	\$ 249.00
AXIS M3044-V/45-V/46-V CL DOME 5P	5801-841	Standard clear dome for AXIS M3044-V/45-V/46-V, 5 pcs	\$ 99.00
AXIS M30-PLVE CLEAR DOME A 4P	01567-001	Standard clear dome with anti-scratch hard coating. Rubber gaskets included. Compatible with AXISM3057/58-PLVE. 4-piece bulk pack.	\$ 59.00

AXIS M30 DOME COVER CASING A 5PCS	5901-241	Original white casing with clear dome for M3044/45/46-V/-WV and AXIS Companion Dome cameras. 5 pcs.	\$ 149.00
AXIS M30 CASING B WHITE 5P	01153-001	Original white casing for AXIS M3047/48-P. 5 pcs.	\$ 79.00
AXIS TM3803 WHITE CASING 4P	01950-001	Spare part white casing. Cover top replacement part for M3067/68.	\$ 59.00
AXIS M42 CASING A WHITE 4P	01922-001	Original white casings for AXIS M42 series. Easy to repaint. 4-piece bulk pack.	\$ 59.00
AXIS M42 CLEAR DOME A 4P	01923-001	Clear dome with anti-scratch hard coating. Compatible with AXIS M42 series. 4x domes per pack.	\$ 79.00
TOP COVER AXIS M311X-R 10PCS	5700-641	Original dark grey top cover including dome and screws for AXIS M311X-R. 10 pcs	\$ 249.00
TOP COVER M311X-VE NOCAP 10 PCS	5800-061	Original top cover including dome and screws for AXIS M311X-VE No Cap. 10 pcs.	\$ 249.00
AXIS M50 CLEAR DOME COVER A	01239-001	Spare part AXIS M50 dome casing cover in white. Included in AXIS M5054/55/65 cameras.	\$ 49.00
AXIS M501X DOME	5800-111	Spare part AXIS M501X dome, pre-mounted in the white top casing. Opening tool and gasket are included.	\$ 29.00
AXIS M55 CLEAR DOME A	01606-001	Spare part clear dome in polycarbonate. IK09 vandal resistant. Compatible with AXIS M5525-E. Single pack.	\$ 39.00
AXIS P32-V CLEAR DOME A 5P	5506-131	Standard clear dome for AXIS P32-V Series, 5 pcs	\$ 169.00
AXIS P32-VE CLEAR DOME A 5P	5506-121	Standard clear dome for AXIS P32-VE Series, 5 pcs	\$ 169.00
AXIS P32-LVE SEMI SMOKED DOME A 5P	5504-991	Semi smoked domes for AXIS P32-LVE Series, 5 pcs	\$ 169.00
SPR AXIS P3343 DOME KIT	5700-321	Dome Kit for AXIS P3343, AXIS P3344, AXIS P3353 and AXIS P3354 as spare part. Includes a clear bubble, mounted on o plastic dome cover and a separate smoked bubble.	\$ 29.00
SPR AXIS P3343-V DOME KIT	5700-311	Dome kit for AXIS P3343-V, AXIS P3344-V, AXIS P3363-V and AXIS P3364-V as spare part. Includes a clear bubble, mounted on an aluminium dome cover and a separate smoked bubble.	\$ 69.00
SPR DOME KIT AXIS P3343-VE	5700-341	Dome Kit for AXIS P3343-VE, P3344-VE, AXIS P3363-VE and AXIS P3364-VE as spare part. Includes a clear bubble, mounted on an aluminium dome cover and a separate smoked bubble.	\$ 69.00
SPR AXIS P3346-V DOME KIT	5700-911	Dome kit for AXIS P3346-V, P3367-V and AXIS P3384-V as spare part. Includes a clear bubble, mounted on a zinc alloy dome cover and a separate smoked bubble.	\$ 74.00
SPR AXIS P3346-VE DOME KIT	5700-921	Dome Kit for AXIS P3346-VE, P3367-VE, AXIS P3384-VE as spare part. Includes a clear bubble, mounted on an aluminium dome cover and a separate smoked bubble.	\$ 74.00
AXIS P3364-LV DOME KIT	5800-691	Dome kit for AXIS P3364-LV. The dome is pre-mounted in the standard white top cover casing.	\$ 74.00
AXIS P3364-LVE DOME KIT	5800-681	Dome kit for AXIS P3364-LVE. The dome is pre-mounted in a standard white top cover casing.	\$ 74.00
AXIS P33 SEMI-SMOKED DOME A 4PCS	01548-001	Semi-smoked dome with anti-scratch hard coating for indoor and outdoor AXIS P337X-LV/-LVE cameras. 4x domes per pack.	\$ 119.00
AXIS P33 CLEAR DOME A 4PCS	01549-001	Clear dome with anti-scratch hard coating for indoor and outdoor AXIS P337X-V/-VE cameras. 4x domes per pack.	\$ 119.00

AXIS P3707-PE CLEAR DOME KIT	5801-521	Dome kit for AXIS P3707-PE. The dome is pre-mounted in the standard white top cover casing.	\$ 99.00
AXIS P37 CLEAR DOME KIT A	01515-001	Dome kit for AXIS P3717-PLE and AXIS P3719-PLE. The dome is pre-mounted in the standard white top cover casing.	\$ 99.00
SPR TOP COVER AXIS P39-R 10 PCS	5801-111	Original top cover including dome and screws for AXIS P39-R Series. 10 pieces.	\$ 249.00
AXIS P54 CLEAR DOME	5800-771	Clear dome for AXIS P54-series.	\$ 49.00
AXIS P5512-E DOME KIT	5800-281	Dome kit for AXIS P5512-E, 5514-E, 5515-E. Clear-/smoked dome and dome cover included.	\$ 49.00
AXIS TP3809 DOME COVER WHITE 4P	02010-001	4 pack white dome cover for AXIS P3925-R. Replaces the standard white dome cover.	\$ 199.00
AXIS TQ6803 HARD-COATED CLEAR DOME	01814-001	Standard clear dome with anti-scratch hard coating. Compatible with selected AXIS Q61-LE cameras. Weather-resistant and chemical-resistant. Rubber gasket included. Single pack.	\$ 89.00
AXIS TQ6804 SMOKED DOME	01789-001	Accessory outdoor smoked dome compatible with selected AXIS Q60-E cameras. See axis.com for updated compatibility list.	\$ 79.00
AXIS TQ6804 CLEAR DOME	01790-001	Accessory outdoor clear dome compatible with selected AXIS Q60-E cameras. See axis.com for updated compatibility list.	\$ 79.00
AXIS TQ6806 HARD-COATED CLEAR DOME	01771-001	Hard coated clear dome spare part for Q6100-E.	\$ 79.00
AXIS TQ6807 CLEAR DOME COVER	01946-001	Clear dome cover including dome cover ring. Compatible with legacy AXIS Q60-E/-C cameras. See axis.com for updated compatibility list.	\$ 149.00
AXIS TQ9801 CLEAR DOME	02050-001	TQ9801 CLEAR DOME spare part for Q9216-SLV.	\$ 75.00
AXIS P553X CLEAR DOME	5800-251	Original clear dome for AXIS P5522/-E, AXIS P5532/-E, AXIS P5534/-E.	\$ 34.00
AXIS P553X SMOKED DOME	5800-191	Original smoked dome for AXIS P5522/-E, AXIS P5532/-E, AXIS P5534/-E.	\$ 34.00
AXIS DOME CLEAR P5544	5800-391	Sparepart dome for AXIS P5544. Note that this product does not contain the fisheye lens.	\$ 49.00
AXIS P5624-E/35-E CLEAR DOME	5506-141	Clear dome for AXIS P56 Series cameras.	\$ 49.00
AXIS TP5801-E Clear Dome	02280-001	Clear dome for AXIS P56 Series cameras. Hard-coated clear dome for harsh environments. It's weather-resistant and chemical-resistant.	\$ 49.00
AXIS Q3505-V CLEAR DOME 5P	5505-611	Standard clear domes for AXIS Q35-V Series, 5 pcs	\$ 179.00
AXIS Q35 CLEAR DOME A 5PCS	01180-001	Standard clear dome with anti-scratch hard coating. Compatible with AXIS Q3517-LV/-LVE. 5x domes per pack.	\$ 199.00
AXIS Q3505-VE CLEAR DOME 5P	5505-631	Standard clear dome for AXIS Q3505-VE. 5pcs	\$ 199.00
AXIS Q36-VE CLEAR DOME	5801-511	Standard clear dome with anti-scratch hard coating. Compatible with AXIS P38 and Q36 Series.	\$ 49.00
AXIS Q37 CLEAR DOME A	5507-311	Standard clear dome with anti-scratch hard coating. Compatible with AXIS Q3708-PVE and Q3709-PVE. Single pack.	\$ 49.00
AXIS Q6000-E CLEAR DOME	5506-641	Clear dome for AXIS Q6000-E	\$ 79.00
AXIS Q603X HD DOME KIT	5700-811	HD optimized dome kit for AXIS Q603X as spare part. Includes a clear bubble mounted on dome ring and a separate smoked bubble.	\$ 89.00
AXIS Q3517-SLVE CLEAR DOME 2P	01584-001	Original clear dome in polycarbonate with anti-scratch hard coating. IK10+ vandal-resistant and high chemical resistance. Compatible with AXIS Q3517-SLVE. 2x domes per pack.	\$ 89.00

AXIS Q60-E/C SMOKED DOME D	5503-961	Stand alone smoked dome for AXIS Q60XX-E/-C series	\$ 79.00
AXIS Q60-S CLEAR DOME A	5700-751	Original clear dome in a special nylon blend with superior stress and chemical resistance. Compatible with AXIS Q604x-S and Q6055-S cameras. Single-pack.	\$ 69.00
AXIS Q8414-LVS CLEAR DOME 5P	5506-331	Standard clear dome for AXIS Q8414-LVS. 5 pcs.	\$ 99.00
AXIS Q8414-LVS IR WINDOW A 5P	5506-341	Standard IR window with microphone hole and water-stop membrane for AXIS Q8414-LVS. 5 pcs.	\$ 149.00
AXIS A8105-E CLEAR DOME 5PCS	5801-471	AXIS A8105-E Clear Dome is sold as spare parts to the AXIS A8105-E Network Video Door Station and comes in packs of five clear dome covers. It enables easy on-site replacement in case the original dome cover has been damaged or vandalized.	\$ 35.00
AXIS TA8801 CLEAR DOME COVER 5P	01764-001	AXIS TA8801 Clear Dome Cover is sold as spare parts to the AXIS A8207-VE Network Video Door Station and comes in packs of five clear dome covers. It enables easy on-site replacement in case the original dome cover has been damaged or vandalized.	\$ 39.00
AXIS TP3801 WHITE CASING 4P	01799-001	Original white casing for selected AXIS P32 indoor cameras. 4pcs bulk pack.	\$ 79.00
AXIS TP3801-E WHITE CASING 4P	01800-001	Original white casing for selected AXIS M32 and P32 outdoor cameras. Pre-assembled with anti-loss screws. 4pcs bulk pack.	\$ 99.00
AXIS TP3802 CLEAR DOME 4P	01625-001	Standard clear dome with anti-scratch hard coating. Compatible with selected AXIS P32 indoor cameras. 4pcs bulk pack.	\$ 99.00
AXIS TP3802-E CLEAR DOME 4P	01629-001	Standard clear dome with anti-scratch hard coating. Compatible with selected AXIS M32 and P32 outdoor cameras. 4pcs bulk pack.	\$ 119.00
AXIS TP3807 DOME COVER WHITE 4P	02011-001	4 pack white dome cover for AXIS P3935-LR. Replaces the standard white dome cover.	\$ 199.00
AXIS TP3803-E CLEAR DOME	02197-001	This is a spare part clear dome for AXIS P3715-PLVE.	\$ 34.00
ACC ALLEN-KEY M3 TAMP PROOF 10PACK	5500-491	Allen-key for AXIS 209FD-R 10-pack	\$ 39.00
AXIS D20 MOUNT BRACKET KIT A	01439-001	Original stainless steel mounting bracket for AXIS D2050-VE. Includes two pipe adapters, anti-loss screws, two gray cable gaskets, three black cable gaskets, and an M20 cable gland.	\$ 59.00
AXIS M10 BRACKET KIT 5P	5901-211	Contains 5pcs wall-and-corner mount bracket and 5pcs table-top stand. Compatible with AXIS M10 Series.	\$ 39.00
AXIS Q604X RECESSED MOUNT	5505-161	Spare part indoor recessed mount for mounting AXIS Q60 indoor cameras in drop ceilings.	\$ 89.00
AXIS F82A06 ANGLED PINHOLE MT 5PCS	01198-001	Mounting bracket that allows AXIS FA1125 Sensor Unit to be mounted behind a thin metal/plastic/glass panel. 5 pcs.	\$ 29.00
P1214/P1214-E/P1224-E MOUNT BRACKET 5PCS	5503-991	Mount bracket for AXIS P1214, P1214-E and P1224-E. Allows to mount the sensor unit in different horizontal and vertical angles.	\$ 59.00
AXIS M501X MOUNTING KIT	5800-121	Original ceiling mount kit for both hard- and drop ceilings for the AXIS M501X.	\$ 15.00
AXIS Q8414-LVS BACK CHASSIS WHITE	5506-311	Spare part powder coated white stainless steel back chassis with gaskets for AXIS Q8414-LVS.	\$ 199.00
AXIS Q8414-LVS BACK CHASSIS METAL	5506-321	Spare part brushed stainless steel metal back chassis with gaskets for AXIS Q8414-LVS.	\$ 199.00

AXIS T98A MOUNTING BRACKET	5800-351	Original stainless steel mounting bracket for AXIS T98A-VE Surveillance Cabinet series.	\$ 59.00
AXIS STEEL STRAPS TX30 570MM 1PAIR	01472-001	1 pair marine-grade (SS316L) stainless steel straps with TX30 screw interface for ease-of-installation. Length 570mm (22.5"). Width 14.3mm (0.57"). Thickness 0.68mm (0.03"). Compatible with a wide range of Axis pole mounts. Pole diameter range 50-150mm (2"-6") when used with AXIS T91B47 Pole Mount.	\$ 29.00
AXIS STEEL STRAPS TX30 1450MM 1PAIR	01471-001	1 pair marine-grade (SS316L) stainless steel straps with TX30 screw interface for ease-of-installation. Length 1450mm (57"). Width 14.3mm (0.57"). Thickness 0.68mm (0.03"). Compatible with a wide range of Axis pole mounts. Pole diameter range 100-410mm (4"-16") when used with AXIS T91B47 Pole Mount.	\$ 39.00
STAINLESS STEEL STRAPS 1450MM 1 PAIR	5800-811	Original stainless steel straps for AXIS T91A47 110-400 mm. The straps also fit the AXIS T91A67. Mounting tool (P/N 21776) is required.	\$ 32.00
SPR AXIS P3343-VE SCREW KIT	5700-351	Screw Kit for AXIS P3343-VE and P3344-VE as spare part. Includes mounting screws, plugs and I/O connector.	\$ 5.00
SPR AXIS P3343/-V SCREW KIT	5700-301	Screw kit för AXIS P3343, P3343-V, P3344 and P3344-V as spare part. Includes mounting screws, plugs and I/O connector.	\$ 4.00
AXIS T94B02S MOUNTING BRACKET 5P	5901-281	Spare part mounting brackets for AXIS M20 Series, 5-pack. Includes 5x mounting brackets with 5x Gasket C M20.	\$ 59.00
AXIS T94F01S MOUNTING BRACKET	5505-171	Standard mount bracket for AXIS M3006-V, AXIS M3007-P/-PV, AXIS M3024-LVE/3025-VE/3026-VE	\$ 19.00
AXIS T94G01S MOUNTING PLATE	5506-081	Sparepart mounting bracket for AXIS Q1765-LE, Q1931-E, Q1932-E	\$ 29.00
AXIS T94K01S MOUNTING BRACKET 4P	5505-551	Sparepart mounting bracket for AXIS Q3505-V. 4 pcs	\$ 119.00
AXIS T94M01S MOUNTING BRACKET 4P	5505-561	Sparepart mounting bracket for AXIS Q3505-VE. 4 pcs	\$ 139.00
AXIS T94S01S MOUNTING BRACKET 4P	5506-061	Sparepart mounting bracket for AXIS P32-V Series. 4 pcs	\$ 69.00
AXIS T94T01S MOUNTING BRACKET 4P	5506-071	Sparepart mounting bracket for AXIS P32-VE Series. 4 pcs	\$ 89.00
AXIS T94T02S MOUNTING BRACKET	01566-001	Spare part mounting brackets for AXIS M3057/58-PLVE, single pack. Includes spring clips for ease-of-installation.	\$ 25.00
MOUNTING BRACKET AXIS P33XX-VE	5700-691	Original AXIS P33XX-VE mounting bracket for wall or hard ceiling.	\$ 29.00
AXIS T94V01S MOUNTING BRACKET	5801-911	Standard mounting bracket for AXIS Q36 Series Network Cameras.	\$ 39.00
AXIS 3/4" CONDUIT LOCKNUT A 4P	01512-001	4-pack of 3/4" conduit locknut. Suitable for AXIS T91B53 Telescopic Ceiling Mount.	\$ 15.00
AXIS T94U02S MOUNTING BRACKET	5506-671	Standard mounting bracket for AXIS Q3505-SVE made of stainless steel. Including gasket.	\$ 169.00
AXIS T94F02S MOUNTING BRACKET	5507-131	Standard plastic mounting bracket for AXIS P1405, P1425, P1427, P1428.	\$ 19.00
AXIS TP3001 MOUNTING BRACKET 4P	01806-001	Spare part mounting bracket for selected AXIS M32 and P32 cameras. Suitable for mounting cameras over junction boxes (4" octagon, single-gang, or double-gang), and other Axis mounting accessories. 4-piece bulk pack.	\$ 49.00

AXIS TP3001-E MOUNTING BRACKET 4P	01801-001	Spare part mounting bracket for selected AXIS P32 outdoor cameras. Suitable for mounting cameras over junction boxes (4" octagon, single-gang, or double-gang), and other Axis mounting accessories. 4-piece bulk pack.	\$ 89.00
AXIS P91 CLEAR DOME A 2P	01621-001	Standard clear dome with anti-scratch hard coating. Rubber gaskets included. Compatible with AXIS P9106-V. 2-piece bulk pack.	\$ 39.00
AXIS P91 SKIN COVER A BRUSHED STEEL	01622-001	Spare part skin cover for AXIS P9106-V. Brushed stainless steel finish. Easy to repaint. Magnetically attached. Suitable for both AXIS P9106-V White and Brushed Steel models.	\$ 59.00
AXIS P1214 SENSOR UNIT	5503-811	Original sensor unit for AXIS P1214 with premounted cable. Flush mount bracket included.	\$ 199.00
AXIS P1214-E SENSOR UNIT	5503-821	Original sensor unit for AXIS P1214-E with premounted cable. Flush mount bracket and sensor unit housing included.	\$ 199.00
SPR P1224-E SENSOR UNIT	5800-991	Original sensor unit for AXIS P1224-E with premounted cable. Flush mount bracket included.	\$ 199.00
RJ12 PLUG SHIELDED 10 PCS	01182-001	Shielded RJ12 connectors for use with AXIS modular cameras. 10-pack.	\$ 29.00
ACC MAINS ADAPTOR PS-P	5500-704	Power supply PS-P for AXIS 215 PTZ	\$ 39.00
AXIS MAINS ADAPTER 12V DC 40W	01509-001	Standard power supply for AXIS FA54. IEC-C13 mains cable is not included.	\$ 59.00
AXIS MAINS ADAPTER 48V DC 90W	01508-001	Standard power supply for AXIS Companion Recorder. IEC-C13 mains cable is not included.	\$ 99.00
ACC PS-RACK	22512	Power supply for the Axis Video Server Rack	\$ 499.00
ACC MALE RJ45 AXIS 209FD-R	5502-061	Vibration resistant male RJ-45 connector suitable for RJ-45 version of AXIS M31XX-R and AXIS 209FD-R/MFD-R Network Cameras.	\$ 15.00
MAINS CABLE IEC-C13	5800-201	Mains cable for AXIS One-Port Midspan, AXIS T8123/24, AXIS 291, AXIS Q7900, AXIS Video Server Rack, AXIS PoE Midspan 8-Port/16-Port, Power Supply AXIS T8412.	\$ 15.00
AXIS PATCH CABLE A 200MM 6PCS	5506-451	Set of patch cables for AXIS T8085 PS57 RACK MOUNT 500W 1U to connect AXIS T8646 POE+ OVER COAX BLADE	\$ 79.00
ACC MALE RJ45 AXIS 209FD-R 10PCS	5502-051	Vibration resistant male RJ-45 connector suitable for AXIS 209FD-R/MFD-R Network Camera. 10 pack	\$ 149.00
CABLE GLAND A M16 5PCS	5800-961	M16 cable gland for cable diameter of 4.5 to 10mm. IP68. 5 pcs.	\$ 19.00
AXIS P3367-VE CASING KIT	5800-601	The kit contains a complete AXIS P3367-VE enclosure, heater and cable cover. The kit could also be used for converting an indoor version of AXIS P3346, P3367, P3384 and P3365 to an outdoor VE version.	\$ 215.00
AXIS P54-SERIES WEATHER COVER	5505-151	Sparepart weather cover for Axis P54-Series.	\$ 39.00
CONN KIT AXIS P1311	5500-851	Kit for the AXIS P13XX-series. Content: one terminal connector 4P str 250mm BP LF and one 2P STR 3.81MM BP LF.	\$ 9.00
CONN KIT AXIS Q7404	5700-161	Terminal connectors for AXIS Q7404. Includes 8 pcs 2P 2.50MM, 4 pcs 4P 2.50MM and one 2P 3.81MM. In total 13 connectors.	\$ 35.00

AXIS TM3807 WHITE CASING 4P	02074-001	AXIS M3115/16-LVE WHITE CASING 4P sold as a spare part and comes in pack of four. It enables easy on-site replacement in case the original case has been damaged.	\$ 79.00
LENS M12 2.8-6MM 5PCS	5801-651	Varifocal lens 2.8-6MM, F2.0, M12 thread. Standard lens for AXIS F1015.	\$ 249.00
LENS M12 2.8MM F2.0 10PCS	5801-921	Standard lens for AXIS F4005-E, AXIS F1005-E and AXIS P1214-E.	\$ 199.00
LENS PINHOLE M12 3.7MM 10PCS	5801-661	Pinhole lens 3.7MM, F2.5, M12 thread. Standard lens for AXIS F1025. 10pcs	\$ 249.00
AXIS T93F TOP COVER	5505-891	Spare part top part of the housing including window.	\$ 59.00
ACC LENS CS VARIF 3-8MM DC-IR D/N	5500-061	CS mount Varifocal 3-8 mm DC-Iris for 221	\$ 125.00
ACC LENS CS VARIF 3-8MM DC-IR	5500-051	CS mount Varifocal 3-8 mm DC-Iris for 211	\$ 99.00
LENS CS 2.8-8MM F1.2 DC-I MP	5700-881	CS mounted Varifocal 2.8-8 mm DC-iris megapixel lens. Original lens for AXIS M1114.	\$ 149.00
LENS CS VF 2.8-8MM F1.2 P-IRIS	5800-671	Original CS mounted varifocal P-Iris lens 2.8-8mm for AXIS Q1604/14 and AXIS P1355/57	\$ 149.00
LENS CS VF 2.8-8MM F1.2 DC-IR	5800-661	Original CS mounted varifocal DC-Iris lens 2.8-8mm for AXIS Q1602/04 and AXIS P1354/55	\$ 149.00
AXIS LENS FUJINON CS 2.8-8MM P-IRIS	5506-721	Standard CS mounted varifocal P-Iris lens 2.8-8mm for AXIS Q1615.	\$ 149.00
LENS CS 2.8-8.5MM P-IRIS	5801-491	Standard CS mounted varifocal P-Iris lens 2.8-8.5mm for AXIS P1364.	\$ 159.00
LENS CS 2.9-8.2MM F1.4 DC SVGA	5700-871	Varifocal 2.9-8.2mm CS mounted SVGA DC-iris lens. Original lens for AXIS M1113	\$ 69.00
LENS CS 4-10MM P-IRIS	5801-011	Standard lens for AXIS Q1635-E.	\$ 249.00
LENS CS 6.0MM F1.8 MP	5700-861	CS mounted 6.0 mm megapixel lens. Original lens for AXIS M1103/4	\$ 49.00
AXIS LENS TAMRON C 4-13MM DC-IRIS	5506-731	Standard C mounted varifocal DC-Iris lens 4-13mm for AXIS Q1635.	\$ 399.00
TAMRON 5MP LENS P-IRIS 8-50 MM F1.6	01469-001	Varifocal 8-50 MM, 5 MP telephoto IR-corrected lens with P-Iris. Recommended for AXIS P1367 and AXIS P1367-E.	\$ 249.00
LENS CS 2.8 - 10 MM F1.2 P-IRIS 2MP	01949-001	Lens CS-mount 2.8 - 10 mm. F1.2 P-IRIS 2MP resolution Computer. Spare part for AXIS P1375 / -E	\$ 149.00
LENS M12 2.9MM F2.0 1P	02065-001	LENS M12 2.9MM F2.0 for Q6010-E and Q6100-E.	\$ 39.00
AXIS Q872x-E SUNSHIELD KIT	5800-321	Sunshield for AXIS Q872x-E as sparepart. Including screws and washer	\$ 299.00
SPR BRACKET KIT AXIS Q60XX/P55XX	5700-851	Bracket kit for surface mounting a camera on a hard ceiling. Compatible with Q603X and P553X. Content: Bracket, screws with washers and wave springs.	\$ 24.00
CONN KIT AXIS M7014	5800-621	Terminal connectors for AXIS M7014. Includes 2 pcs TERMINAL CONN 2P STR 2.50MM, rubber feet and mounting screws for the encoder.	\$ 9.00
SPR CONN KIT AXIS Q7401	5500-831	Connectors for AXIS Q7410 as spare parts. Includes two 2pin STR 2.50MM, one 6pin STR 2.50MM and one 2pin STR 3.81MM. In total 4 connectors.	\$ 19.00
CONN KIT AXIS P7214/Q7411	5800-611	Terminal connectors for AXIS P7214 and AXIS Q7411. Includes 1 pcs TERMINAL CONN 6P STR 2.50MM, 2 pcs TERMINAL CONN 2P STR 2.50MM, rubber feet and mounting screws for the encoder.	\$ 9.00

SPR CONN PUSH PULL PLUG IDC-8 IP67	5700-371	Spare RJ45 connector plug for AXIS Q603X-E & AXIS P55XX-E. IP67 rated.	\$ 49.00
NETWORK CABLE WITH GASKET 5M	5700-331	Shielded outdoor network cable 5 meter. Pre mounted rubber gasket and male RJ45 connectors. For use with AXIS M11-E series, AXIS P13-E series, AXIS Q16-E series, AXIS Q1755-E, AXIS Q19-E series, AXIS P33-VE series and AXIS T92/3-E housings.	\$ 10.00
AXIS Q60XX-C MULTI CONNECT CABLE 7M	5800-821	Cable between AXIS Q60XX-C and connection box AXIS T8605	\$ 179.00
AXIS T91G61/T91L61 SCREW KIT	5901-391	Screw kit for installing AXIS P55-E Series with either AXIS T91L61 or AXIS T91G61 Wall Mounts. Single-pack includes 3x bayonet screws, 3x securing screws, 3x springs and an installation guide.	\$ 10.00
AXIS P5544 LENS KIT	5800-401	Spare part lens kit for AXIS P5544	\$ 399.00
AXIS Q603X-E DOME COVER RING	5800-101	Dome cover ring for AXIS Q603X-E including screws.	\$ 18.00
AXIS T96B05 FRONT KIT 5 PCS	5506-851	Spare part window and window holder for AXIS T96B05 Outdoor Housing and AXIS P3905-RE. 5 Pcs. Includes screws.	\$ 169.00
AXIS Q60XX-C COOLING MODULE	5800-501	Peltier element, inside and outside fan for AXIS Q60XX-C	\$ 999.00
SPR ELECTRONIC KIT T95A00	5700-081	Electronic boards for replacement in AXIS T95A00 110-230 VAC. Includes 4 boards.	\$ 215.00
SPR HEATER/FAN KIT T95A10	5700-111	Replacement kit with 3 heaters and fans for AXIS T95A10	\$ 99.00
SPR SCREW AND GLAND KIT T95A	5700-151	Replacement cable gland plate, cable glands and screws for AXIS T95A	\$ 24.00
SPR MAINS ADAPTOR PS-V EUR	5700-221	Power supply PS-V for AXIS M10 series. White Sparepart	\$ 39.00
AXIS T8005 POWER SUPPLY 5V 5W USB	5901-191	Switching power supply, 5W with microUSB connector. Including interchangeable regional power plugs for world wide use.	\$ 39.00
SPR POWER SUPPLY 1U 310W FRONT	5700-071	Replacement power supply for AXIS Q7900 encoder rack	\$ 329.00
SPR POWER SUPPLY 1U 300W BL. FRONT	5800-861	Replacement power supply for AXIS Q7920 Video Encoder Chassis	\$ 329.00
AXIS T93G TOP COVER	5506-971	Spare part top part of the AXIS T93G housing including window.	\$ 49.00
AXIS T92G FRONT WINDOW KIT A	01578-001	Replacement front window assembly for AXIS T92G Outdoor Housing and AXIS Q16-LE Fixed Box Cameras. Includes front window, adjacent IR windows, mounting screws and sealing gasket.	\$ 99.00
AXIS T92G WEATHERSHIELD KIT A	01579-001	Original outdoor weathershield for AXIS T92G Outdoor Housing and AXIS Q16-LE cameras. The underside of the cover is specially coated with matte black anti-reflective coating to prevent reflections from IR LEDs and other light source. Mounting screws included.	\$ 59.00
AXIS T92G20 CAMERA HOLDER	01954-001	Spare Camera Holder for AXIS T92G20 Outdoor Housing and for AXIS Q1645/7-LE Network Cameras. The holder makes it possible to mount AXIS P13 Network Camera Series into AXIS T92G20 Outdoor Housing.	\$ 29.00
AXIS SUNSHIELD B	5800-971	Sunshield compatible with AXIS Q1765-LE, Q1931-E/32-E/41-E and Q2901-E	\$ 29.00
AXIS SUNSHIELD C	5800-981	Sunshield compatible with AXIS Q1765-LE PT Mount	\$ 29.00
AXIS P5512-E SUNSHIELD	5800-151	Sunshield for AXIS P5512-E.	\$ 24.00
SUNSHIELD KIT AXIS P553X-E	5700-961	Sunshield for AXIS P553X-E including mounting screws.	\$ 29.00

SUNSHIELD AXIS Q603X-E	5700-951	Sunshield for AXIS Q603X-E.	\$ 29.00
AXIS Q6010-E Solo kit	02221-001	Kit for making a stand-alone AXIS Q6010-E installation without PTZ camera inside. Includes a metal cover lid, IP66-rated RJ45 push-pull connector, and a connector plug. Use this kit together with an AXIS Q6010-E network camera (not included) and the AXIS T8133 Midspan 30 W 1-port (not included).	\$ 119.00
AXIS Q60XX-C SUNSHIELD	5800-471	Sunshield for AXIS Q60xx-C series	\$ 39.00
AXIS Q604X-S SUNSHIELD	5504-671	Stainless steel sunshield for AXIS Q604X-S	\$ 293.00
AXIS Q62 IMPACT PROTECTION BRACKET	01600-001	Protection of front window on AXIS Q62-LE camera. Provides IK10 rating on product. Includes bracket and mounting screws.	\$ 19.00
AXIS Q62 FRONT WINDOW KIT A	01601-001	Original front window assembly for AXIS Q62-LE, IK09 rated. Includes a complete front window glass assembly with mounting screws and sealing gasket; and a wiper arm (long-life, UV-resistant silicone rubber included). Note: IR window available separately.	\$ 149.00
AXIS Q62 WIPER KIT A 4P	01602-001	Bulk pack (4 pcs) of replacement wiper arms (rubber included) for AXIS Q62-LE. Made from long-life, UV-resistant silicone rubber.	\$ 49.00
AXIS Q62 IR WINDOW KIT A	01603-001	Original IR window assembly for AXIS Q62-LE. Includes a complete IR Window assembly with mounting screws and sealing gasket. Note: clear front window available separately.	\$ 49.00
SUNSHIELD KIT T92E	5700-941	Sunshield for AXIS P134X-E, AXIS Q1755-E and AXIS Q192X-E. Includes mounting screws and Torx key.	\$ 35.00
AXIS P33 WEATHERSHIELD KIT A	01701-001	Original weathershield with anti-loss screws for protecting AXIS P33 outdoor cameras from rain, snow and sun when wall mounted. The underside of the cover is specially coated with matte black anti-reflective coating to prevent reflections from IR LEDs and other light sources. This part is included with AXIS P3375-VE/-LVE Cameras.	\$ 25.00
AXIS P38 WEATHERSHIELD KIT A	01499-001	Original weathershield with anti-loss screws for protecting AXIS P3807-PVE from rain, snow and sun when wall mounted.	\$ 25.00
AXIS Q35 WEATHERSHIELD KIT A	01179-001	Original weathershield for AXIS Q35-LVE network camera series. Screws and gasket included.	\$ 24.00
AXIS WEATHERSHIELD KIT D	5506-761	Weathershield with screws for protecting the dome of an AXIS Q35-VE camera from rain, snow and sun.	\$ 20.00
AXIS WEATHERSHIELD KIT E	5506-751	Weathershield with screws for protecting the dome of an AXIS P32-VE camera from rain, snow and sun.	\$ 18.00
AXIS WEATHERSHIELD KIT M	5507-321	Standard weathershield for AXIS Q3709	\$ 34.00
AXIS WEATHERSHIELD KIT N	5801-851	Standard weather shield for AXIS M2025/26 and AXIS Companion Bullet	\$ 24.00
AXIS WEATHERSHIELD KIT Q	5801-451	Standard weather shield for Axis Q36 Series, protecting the dome from rain, snow and sun.	\$ 24.00
AXIS WEATHERSHIELD KIT R	01238-001	Weathershield for protecting wall mounted fixed dome cameras against rain, snow and sun. UV-resistant plastics and matte black anti-reflective coating on the underside to prevent reflection from IR illumination. Equipped with anti-loss screws for ease of installation. Compatible with AXIS P32-VE/-LVE fixed dome cameras.	\$ 39.00

WEATHERSHIELD KIT P3343/44-VE	5800-011	Original weathershield for AXIS P3343, AXIS P3344-VE, AXIS P3363-VE and AXIS P3364-VE. Screws included.	\$ 20.00
WEATHERSHIELD KIT P3346/67-VE	5800-021	Original weathershield for AXIS P3346, AXIS P3367-VE and AXIS P3384-VE. Screws included.	\$ 20.00
AXIS TP3805 WEATHERSHIELD 2P	01628-001	Outdoor weathershield for selected AXIS M32 and P32 cameras. The underside of the cover is specially coated with matte black anti-reflective coating to prevent reflections from external light sources. Anti-loss screws included. Bulk 2 pack.	\$ 69.00
FRONT GLASS KIT AXIS T92E20/21	5700-831	Complete Front Kit for AXIS T92E20/21. Content: Front Cover, Front Glass, Gasket & Screws.	\$ 20.00
ELECTRONIC KIT AXIS T92E20	5700-971	Sparepart including the electronics module of the AXIS T92E20 housing including fan and screws.	\$ 179.00
AXIS T92E EXTENSION KIT	5506-101	Extension front for AXIS T92E20 outdoor housing, allowing longer lenses than the standard housing. The kit includes aluminum front and extension part, window, gasket and screws.	\$ 39.00
AXIS M20 FRONT KIT A	5901-291	Replacement front window assembly for AXIS M2025-LE, M2026-LE. The kit comes with both a black and a white front cover ring. Includes one window and sealing gasket.	\$ 29.00
AXIS P13 WEATHERSHIELD KIT A	01693-001	Standard weather shield for selected AXIS P13 series. For protection from rain, snow and sun. The underside of the cover is coated with matte black anti-reflective coating, for suitable use near IR LEDs.	\$ 39.00
AXIS P13-E TOP COVER A	01694-001	Replacement top cover with front window for selected AXIS P13-E cameras. Original weathershield is not included but available separately.	\$ 79.00
AXIS P14 FRONT KIT A	5801-151	Standard front for AXIS P1405-E, P1405-LE, P1405-LE MKII, P1425-E, P1425-LE, P1425-LE MKII, P1427-E, P1427-LE, P1435-LE. Includes front ring, window and gasket.	\$ 29.00
AXIS P14 FRONT KIT B	5801-891	Standard front for AXIS P1428-E and AXIS P1435-E. Includes front ring, window and gasket.	\$ 29.00
AXIS P14 FRONT KIT C	01761-001	Standard front window kit for selected AXIS P144x-LE series. Abrasion and UV resistant for long service life. Includes cover ring, front window, and rubber gasket.	\$ 29.00
AXIS P14 WEATHERSHIELD A	01717-001	Standard weather shield for selected AXIS P14 series. For protection from rain, snow and sun. The underside of the cover is coated with matte black anti-reflective coating, for suitable use with camera's built-in IR LEDs.	\$ 25.00
AXIS Q17 FRONT WINDOW KIT A	01686-001	Original front glass window assembly for AXIS Q1785/86-LE, IK08 rated. Provides the clarity required for maximum utilization of the camera's zoom capacity.	\$ 79.00
AXIS Q17 FRONT WINDOW KIT C	01971-001	Original front glass window assembly for AXIS Q1700-LE, IK08 rated. Provides the clarity required for maximum utilization of the camera's zoom capacity.	\$ 99.00
AXIS Q1798-LE WEATHERSHIELD	01972-001	Original outdoor weathershield for AXIS Q1700-LE camera. Color: Black	\$ 49.00
AXIS Q1765-LE FRONT KIT	5801-101	Spare part front window for AXIS Q1765-LE	\$ 59.00

SPR FAN CASSETTE AXIS Q7900 E2	5800-271	Original spare part fan cassette for AXIS Q7900 E2.	\$ 199.00
SPR FAN CASSETTE AXIS Q7920	5800-851	Original spare part fan cassette for AXIS Q7920.	\$ 99.00
AXIS T98A05 CABINET DOOR	5800-521	Cabinet door for AXIS T98A Surveillance Cabinet. Stand alone. Used in T98A15-VE Cabinets.	\$ 129.00
AXIS T98A06 CABINET DOOR	5800-531	Cabinet door for AXIS T98A Surveillance Cabinet. Compatible cameras: AXIS M111X-E, AXIS P13XX-E, AXIS Q16XX-E, AXIS Q17XX-E, AXIS Q191X-E, AXIS Q192X-E. Used in T98A16-VE Cabinets.	\$ 129.00
AXIS T98A07 CABINET DOOR	5800-541	Cabinet door for AXIS T98A Surveillance Cabinet. Compatible cameras: AXIS P33-VE/-LVE and the outdoor bullet-style Q1765 and Q1931 cameras. Used in T98A17-VE Cabinets.	\$ 129.00
AXIS T98A08 CABINET DOOR	5800-551	Cabinet door for T98A. Compatible products: AXIS T91A61 Wall bracket for use with AXIS P55 and Q60-series or fixed dome pendant kits. Used in T98A18-VE Cabinets.	\$ 129.00
AXIS T98A09 CABINET DOOR	5800-871	Cabinet door for AXIS T98A. Compatible products: AXIS P54-Series. Used in T98A19-VE Cabinets.	\$ 129.00
AXIS P135X CONN KIT	5800-381	Terminal connectors for AXIS P135X-series. Includes 1 pcs TERMINAL CONNECTOR 4P STR 2.50MM, 1 pcs TERMINAL CONNECTOR 2P STR 3.81MM, 2 pcs TERMINAL CONNECTOR 2P STR 2.50MM	\$ 9.00
AXIS T8123/4-E MIDSPAN SPARE KIT	5800-371	2pcs RJ-45 waterproof plugs and 1pcs grounding wire for outdoor midspan T8123/4-E	\$ 29.00
FRONT KIT 60MM AXIS Q872X-E	5800-311	Frontkit for AXIS Q872X-E with 60mm lens as spare part.	\$ 1,499.00
FRONT KIT 35MM AXIS Q872X-E	5800-301	Frontkit for AXIS Q872X-E with 30mm lens as spare part	\$ 699.00
PT IR ILLUMINATOR KIT B	5800-921	Spare part illuminator kit for AXIS Q8665-LE. NOTE: it is not possible to upgrade a Q8665-E to become LE version	\$ 1,299.00
AXIS Q86 FRONT KIT A	01440-001	Replacement front window assembly for AXIS Q8685-E/-LE. Window in clear tempered glass. Includes built-in heater, wiper mechanism, and heat sink.	\$ 349.00
AXIS Q86 WIPER KIT A 5P	01441-001	Replacement wiper blades for selected AXIS Q86 and Q87 cameras. Made from long-life, UV-resistant silicone rubber. 5pcs per pack.	\$ 49.00
AXIS Q86-E LIGHT SENSOR BOX 120 V	5505-771	Light sensor box with integrated power supply for controlling IR illuminators and power AXIS Q8665-LE. Input power 120V AC.	\$ 640.00
AXIS Q8665-E BASE UNIT 24 V AC	5801-171	Spare part base unit for AXIS Q86-E 24 V AC.	\$ 1,199.00
AXIS Q8665-LE BASE UNIT 24V AC	5801-191	Spare part base unit for AXIS Q86-LE 24 V AC.	\$ 1,199.00
AXIS Q8665-E BASE UNIT 120 V AC	5801-181	Spare part base unit for AXIS Q86-E 120 V AC.	\$ 1,199.00
AXIS Q8631-E/32-E HOUSING TOP	5801-291	Spare part top housing with germanium window for AXIS Q8631-E/32-E.	\$ 599.00
AXIS Q8665 HOUSING TOP	5801-281	Spare part top housing with glass window for AXIS Q8665-E/-LE.	\$ 399.00
AXIS Q8665-LE ILLUMINATOR	5801-261	Spare part IR illuminator for AXIS Q8665-LE. Note. This is a single pack.	\$ 799.00
AXIS Q8665-LE ILLUMINATOR BRACKET	5801-271	Spare part IR illuminator bracket for AXIS Q8665-LE	\$ 299.00

AXIS Q8631/32/65 SUNSHIELD	5801-311	Spare parte sunshield for AXIS Q8631-E/32-E/65-E/65-LE	\$ 59.00
AXIS Q8665 WIPER	5801-201	Spare part wiper blade for AXIS Q8665-E/-LE including the stainless steel holder	\$ 59.00
AXIS Q8631/32/65 SEAL AND GASKET KIT	5801-231	Spare part kit for AXIS Q8631/32/65 consisting of mount bracket gasket, base unit cable glands, IR glands and housing gasket	\$ 79.00
AXIS Q8631/32/65 SCREW KIT	5801-211	Spare part screw kit for AXIS Q8631/32/65 consisting of all external screws and washers of the cameras	\$ 69.00
AXIS Q8721-E/22-E BASE	5800-951	Base assembly for the AXIS Q8721-E/22-E.	\$ 699.00
AXIS BISPECTRAL TOP COVER A	01497-001	Top cover for Axis bi-spectral cameras. Includes top housing, 38mm Germanium front window for thermal and glass window for visual camera, wiper etc.	\$ 1,199.00
AXIS BISPECTRAL TOP COVER B	01498-001	Top cover for Axis bi-spectral cameras. Includes top housing, 60mm Germanium front window for thermal and glass window for visual camera, wiper etc.	\$ 1,999.00
AXIS TM1802 TOP COVER KIT	01779-001	Replacement top cover with front window for selected AXIS M11-E cameras. Original weathershield included.	\$ 119.00
AXIS WEATHERSHIELD S	01496-001	Weathershield from UV-resistant plastics for protecting camera against rain, snow and sun.	\$ 59.00
AXIS WIPER KIT B	01688-001	Wiper arm with blade for easy replacement. Spare part.	\$ 59.00
AXIS CONNECTOR A 2P2.5 STR 10PCS	5505-261	Axis male connector for legacy IO port . Pitch: 2.50 mm. 2pos terminal block. 10pack.	\$ 19.00
AXIS CONNECTOR A 4P2.5 STR 10PCS	5800-891	Axis male connector for limited and full IO port . Pitch: 2.50 mm. 4pos terminal block. 10pack.	\$ 19.00
AXIS CONNECTOR A 6P2.5 STR 10PCS	5505-271	Axis male connector for extended IO port . Pitch: 2.50 mm. 6pos terminal block. 10pack	\$ 59.00
AXIS CONNECTOR A 2P3.81 STR 10PCS	5800-901	Axis male connector for low voltage power. Pitch: 3.81 mm. 2pos terminal block. 10pack	\$ 19.00
AXIS CONNECTOR A 3P3.81 STR 10PCS	5505-281	Axis male connector for low voltage power. Pitch: 3.81 mm. 3pos terminal block. 10pack	\$ 29.00
AXIS CONN A 4P3.81 STR IN/OUT 10P	5505-291	Axis male connector for audio. Pitch: 3.81 mm. 2+2pos terminal block. 10pack	\$ 39.00
AXIS CONNECTOR A 4P3.81 STR 10PCS	5505-251	Axis male connector for low voltage power. Pitch: 3.81 mm. 4pos terminal block. 10pack	\$ 29.00
AXIS CONNECTOR A 2P5.08 STR 10PCS	5505-301	Axis male connector for low voltage power. Pitch: 5.08 mm. 2pos terminal block. 10pack	\$ 29.00
SPR 5 PORT GB ETHERNET SWITCH KIT	5800-881	Spare part internal switch for the AXIS Q8721-E/22-E Dual cameras,including brackets.	\$ 599.00
AXIS Q1765 FOOT CHASSIS	5506-091	Sparepart foot chassis for AXIS Q1765-LE and AXIS Q193X-E. Note. This sales part does not include the mounting bracket (5506-081 AXIS T94G01S Mounting plate)	\$ 39.00
AXIS ADAPTER RJ45 MALE TO MALE	5506-891	Adapter for connecting Q6000-E to PTZ camera	\$ 15.00
AXIS ACI CONDUIT COVER A 10PCS	01175-001	Spare part plastic side covers for compatible AXIS T91- and AXIS T94- series of mounting accessories. 10 pcs per pack.	\$ 19.00

AXIS TQ1801 WEATHERSHIELD	01760-001	Original outdoor weathershield for AXIS Q1785/86-LE cameras. The underside of the cover is specially coated with matte black anti-reflective coating to prevent reflections from external light sources. Includes weathershield slider and anti-loss screw.	\$ 49.00
AXIS TQ1802 WEATHERSHIELD	02014-001	KIT WEATHER SHIELD spare part Q1700-LE E1.	\$ 99.00
AXIS TQ1803 FRONT WINDOW KIT	02015-001	Original front glass window assembly for AXIS Q1700-LE, IK08 rated. Provides the clarity required for maximum utilization of the camera's zoom capacity.	\$ 149.00
AXIS DEVICE MICROPHONE A	01575-001	AXIS Device Microphone A is an omnidirectional microphone to enable audio recording and/or audio analytics with AXIS devices that support audio but do not include a microphone. The product is compatible with devices that support 3.5 mm audio input, like AXIS indoor Q35 series or P33 series together with AXIS TP3201 Recessed Mount.	\$ 29.00
AXIS T8351 MK II MICROPHONE 3.5MM	01560-001	AXIS T8351 Mk II Microphone 3.5mm is an omnidirectional microphone with a 3.5mm connector, compatible with all Axis network video products supporting a 3.5mm jack for microphone input. Flexible to install, AXIS T8351 adapts to different installation scenarios thanks to a vast range of included accessories and to its dust-and-water proof casing.	\$ 99.00
AXIS T8355 DIGITAL MICROPHONE	01561-001	AXIS T8355 Digital Microphone is an omnidirectional microphone compatible with Axis network product with digital in and ring power supporting both a 3.5mm jack and audio terminal block for microphone input. Axis T8355 could be placed up to 100m (328 ft) away from Axis network products, generating flexibility for installation without deterioration of the audio signal.	\$ 129.00
AXIS TP3901 MICROPHONE KIT	01798-001	Casing with built-in microphone for selected AXIS P32-LV cameras. Color: Axis white.	\$ 49.00
AXIS DEVICE MICROPHONE B	01963-001	AXIS Device Microphone B is an omnidirectional microphone to enable audio recording and/or audio analytics with AXIS devices that support audio but do not include a microphone. The product includes a Terminal Block to 3.5 mm Audio Extension allowing it to be installed together with our latest AXIS P32 series.	\$ 35.00
POE SPLITTER 5V	02044-001	PoE Splitter 5 V can be used together with a network device that has no built-in support for Power over Ethernet (PoE). The product splits PoE into separate 5 V DC and data outputs. The product is IEEE 802.3af compliant.	\$ 59.00
AXIS POE MIDSPAN 8-PORT	5012-004	802.3af compliant power injector for standard Cat 5 network cables. Maximum cable length is 328ft/100m. Supporting up to eight Axis Network cameras/video servers. Metal casing.	\$ 599.00
AXIS POE MIDSPAN 16-PORT	5012-014	802.3af compliant power injector for standard Cat 5 network cables. Maximum cable length is 328ft/100m. Supporting up to sixteen Axis Network cameras/video servers. Metal casing.	\$ 799.00

AXIS T8120 15W MIDSPAN 1-PORT	5026-204	Provides power over Ethernet to Axis network video products with built-in PoE support. AXIS T8120 is IEEE 802.3af compliant, ensuring compatibility with all Axis PoE Class 1-3 products. The midspan can be installed on a wall or shelf.	\$ 59.00
AXIS T8120 15W MIDSPAN 10PCS	5026-224	Provides power over Ethernet to Axis network video products with built-in PoE support. AXIS T8120 is IEEE 802.3af compliant, ensuring compatibility with all Axis PoE Class 1-3 products. The midspan can be installed on a wall or shelf. 10 pcs.	\$ 529.00
AXIS T8607 MEDIA CONV SWITCH 24VDC	5901-271	Media converter switch . 2 RJ45 ports and 2 SFP slots for optical fiber connection (SFP modules not included). Two I/O ports and a combined communication and powering port for the camera. Temp spec. -40 °C to 75 °C (-40 °F to 167 °F). 12 V DC power input. Shelf or DIN-rail mount. 24 V DC power in.	\$ 449.00
AXIS T8123-E OUTDOOR MIDSPAN 30w	5030-234	Outdoor ready IP66-rated midspan compliant with IEEE802.3af and 802.3at. Built in surge protection and IP66-rated male RJ45 connector is included. Delivers up to 30W. Temperature specification: -40°C to 55°C (-40° to 131°F) for 30W and -40°C to 65°C (-40°F to 149°F) for 15.4W.	\$ 249.00
AXIS T8611 SFP MODULE LC.LX	5801-801	Small Form Factor Pluggable (SFP) transceiver module. Single mode 1310nm, 10km. Industrial grade.	\$ 99.00
AXIS 30W OUTDOOR MIDSPAN	01944-001	AXIS 30 W Outdoor Midspan is an outdoor ready IP66-/IP67-rated midspan compliant with IEEE802.3af and 802.3at. With built in 6kV surge protection. Delivers up to 30W. Temperature specification: 40°C to 65°C (-40°F to 149°F) for 30W.	\$ 249.00
AXIS T8612 SFP MODULE LC.SX	5801-811	Small Form Factor Pluggable (SFP) transceiver module. Multi mode 850nm, 550m. Industrial grade.	\$ 79.00
AXIS T8613 SFP MODULE 1000BASE-T	5801-821	Small Form Factor Pluggable (SFP) transceiver module. Ethernet RJ-45 . Industrial grade	\$ 99.00
AXIS T8133 30W MIDSPAN	5900-294	Single port midspan for Power over Ethernet Plus (PoE+) IEEE 802.3at Type 2 Class 4. Replaces AXIS T8123.	\$ 79.00
AXIS T8134 MIDSPAN 60W	5900-334	High PoE 1-port midspan 60W. Compliant with 802.3.at and PoE 802.3af.	\$ 149.00
AXIS T8144 60W INDUSTRIAL MIDSPAN	01154-001	Industrial midspan with extended temperature range, PoE 60W and dual DC 12/24 V DC power input for redundancy. Operating temperature -40 to +75 degC or -40 to +167 °F. DIN and wall mount included.	\$ 249.00
AXIS T8154 60W SFP MIDSPAN	5901-004	AXIS T8154 60 W SFP Midspan is a compact, plug-and-play media converter with PoE. With its integrated power supply, it minimizes the amount of cabling and facilitates installation. AXIS T8154 offers data input through SFP or RJ45, and delivers High PoE 60 W. It works with all Axis network products supporting Power over Ethernet	\$ 199.00
AXIS T8124-E OUTDOOR MIDSPAN 60W	5031-244	Outdoor ready IP66-rated midspan for AXIS Q60-E. Built in surge protection and IP66-rated male RJ45 connector is included. Delivers up to 60W. Temperature specification: -40°C to 50°C (-40° to 122°F).	\$ 319.00
AXIS T8125 AC 24V MIDSPAN 60W	5900-251	60W PoE midspan for 24V AC input.	\$ 159.00
POWER SUPPLY DIN CP-D 12/2.1 25W	5505-731	DIN power supply. 12V DC, 2.1 A. For use in T98A to power cameras, media converters etc.	\$ 99.00

POWER SUPPLY DIN CP-D 24/4.2 100 W	01169-001	DIN power supply. 24V DC, 4.2 A. For use in AXIS Surveillance Cabinets to power cameras, media converters etc.	\$ 149.00
POWER SUPPLY PS24 240 W	01170-001	24V DC power supply with 240 W output power.	\$ 229.00
SPR Q62 MIDSPAN 90W 1-PORT	01938-001	Spare part: 90W Midspan for devices like AXIS Q62 Series.	\$ 199.00
AXIS T8127 60 W SPLITTER 12/24 V DC	5500-001	PoE splitter. Can deliver both 12 and 24 V DC (user selectable) from High PoE 60W midspan. Useful to power and connect non-PoE devices like IP cameras, magnetic locks for access control systems, WiFi AP, thin clients etc.	\$ 89.00
POWER SUPPLY DIN PS24 480W	01677-001	Power supply for AXIS Q86, Q87 & T99A product lines. 480W 24V 20A for DIN rail mounting.	\$ 299.00
AXIS POWER SUPPLY DIN PS56 240W	01726-001	Power supply for AXIS T8504-R Industrial PoE Switch. 240W 56V 5A for DIN rail mounting.	\$ 249.00
AXIS T8129 PoE EXTENDER	5025-281	Power over Ethernet extender repeats the data signal and forward the PoE to the camera, PoE+ compliant it is compatible with all Axis cameras. No additional power supply is required. The maximum total distance between switch and camera depends on the power input and the power required by the camera, but all cameras can be at least extended to 200 meter connection.	\$ 199.00
AXIS T8129-E OUTDOOR POE EXTENDER	01148-001	AXIS T8129-E Outdoor PoE Extender repeats the data signal and PoE to the camera. AXIS T8129-E is PoE+ compliant with all Axis cameras and does not require an additional power supply. The maximum total distance between switch and camera depends on the power input and the power required by the camera, but all cameras can be at least extended to 200 meter connection.	\$ 299.00
ACC CABLE I/O AUDIO 5M P3343-VE	5502-331	Audio and I/O extension cable for AXIS P33 Series. Includes 4 pin terminal connector 2.5mm Female to Male, 2 x stereo plug 3.5mm Male to Female. 5 meter.	\$ 39.00
AXIS LONG RANGE POE EXTENDER KIT	01857-001	AXIS Long range PoE Extender kit offers a smart and easy-to-install solution for extending the range of your network and PoE up to 1000m (3280ft.). Connect the product in-line with the CAT5e or CAT6 cable and power and data are forwarded to your Axis network devices. AXIS Long range PoE Extender kit supports both IEEE 802.3af and IEEE 802.3at compliant devices and can withstand challenging temperatures. The product is NEMA TS2 compatible.	\$ 499.00
AXIS DIGITAL AUDIO EXTENSION KIT	01590-001	AXIS Digital Audio Extension Kit enables AXIS T8355 Digital Microphone to extend to distances up to 100m (328 ft).	\$ 19.00
AXIS T8508 POE+ NETWORK SWITCH	01191-004	PoE+ managed fanless gigabit network switch, optimized for Axis network products. 2 SFP/RJ45 uplink ports and 8 PoE+ ports with 130W power supply. Built in DCHP server for plug-and-play camera setup. Easy system configuration for effective installation of Axis network products	\$ 399.00
AXIS AUDIO EXTENSION CABLE B 5M	01589-001	Audio extension cable for Axis 3.5mm mono microphones. Length 5m (197 in).	\$ 19.00

AXIS T8516 PoE+ NETWORK SWITCH	5801-694	PoE+ managed gigabit network switch, optimized for Axis network products. 2 SFP/RJ45 uplink ports and 16 PoE+ ports with 250W power supply. Built in DHCP server for plug-and-play camera setup. Easy system configuration for effective installation of Axis network products.	\$ 699.00
AXIS AUDIO EXTENSION CABLE A 5M	5505-131	Audio extension cable for Axis 3.5mm mono microphones. Length 5m (197 in)	\$ 19.00
AXIS T8524 POE+ NETWORK SWITCH	01192-004	PoE+ managed gigabit network switch, optimized for Axis network products. 2 SFP/RJ45 uplink ports and 24 PoE+ ports with 370W power supply. Built in DHCP server for plug-and-play camera setup. Easy system configuration for effective installation of Axis network products.	\$ 899.00
TERMINAL BLOCK TO 3.5MM AUDIO EXT	01714-001	3.5mm audio jack extension for Axis Network Video products with terminal block audio connection.	\$ 10.00
AXIS MULTICABLE A I/O AUDIO PWR 1M	5505-031	Multi-connector cable for power (12VDC), audio and I/O port. 1m (40 in)	\$ 79.00
AXIS T8640 POE+ OVER COAX ADAP	5026-401	Pair of Ethernet over COAX adapters that enable use of COAX cables for PoE applications, supports IEEE802.3af/at. Powered by either PoE or power supply, dependent on power requirement at the device end. Diagnostics LEDs for power and link status in both base and device unit. Connectors: BNC and RJ45 connector and power input (for optional power supply). The package contains one base unit and one device unit.	\$ 414.00
AXIS MULTICABLE A I/O AUDIO PWR 5M	5505-021	Multi-connector cable for power (12VDC), audio and I/O port. 5m (197 in)	\$ 99.00
AXIS T8641 POE+ OVER COAX BASE	5028-411	Single Base unit of Ethernet over COAX adapter. The package contains one base unit.	\$ 207.00
AXIS MULTICABLE B I/O AUDIO PWR 2.5M	5505-511	Multi-connector cable for AC/DC power, audio in/out and I/O connectivity. 2.5m (8.2 ft)	\$ 79.00
AXIS T8642 POE+ OVER COAX DEVI	5027-421	Single Device unit of Ethernet over COAX adapter. The package contains one device unit.	\$ 207.00
AXIS MULTICABLE C I/O AUDIO PWR 1M	5506-201	Multi-connector cable for power, audio and I/O connectivity. 1m (3.3 ft)	\$ 109.00
AXIS T8643 POE+ OVER COAX COMPACT	01468-001	AXIS T8643 PoE+ over Coax Compact enables legacy coax cabling to be kept when converting an analog system to digital. The design allows for improved installation and cable management as it can easily be integrated in housings and backboxes. It delivers standard Power over Ethernet (PoE) and centrally-sourced power through existing coax cabling.	\$ 207.00
AXIS MULTICABLE C I/O AUDIO PWR 5M	5506-191	Multi-connector cable for power, audio and I/O connectivity. 5m (16.4 ft)	\$ 139.00

AXIS T8645 PoE+ COAX COMPACT KIT	01489-001	<p>AXIS T8645 PoE+ over Coax Compact Kit enables legacy coax cabling to be kept when converting an analog system to digital, and comprises AXIS T8641 PoE+ Over Coax Base and AXIS T8643 PoE+ over Coax Compact.</p> <p>It delivers standard Power over Ethernet (PoE) and centrally-sourced power through existing coax cabling. The compact design of the AXIS T8643 PoE+ over Coax Compact allows for improved installation and cable management as it can easily be integrated in housings and backboxes.</p>	\$ 414.00
AXIS T8646 POE+ OVER COAX BLADE	5026-461	<p>Ethernet over COAX blade (6ch) that enable use of COAX cables for PoE applications, supports IEEE802.3af/at. For use with Axis video encoder chassis together with our AXIS T8082 or AXIS T8085 power supplies.</p> <p>Requires one AXIS T8642 POE+ OVER COAX DEVICE for every channel at the camera end.</p>	\$ 699.00
AXIS T8646 POE+ OVER COAX BLADE KIT	5026-471	<p>A Kit that contains one (1) AXIS T8646 POE+ OVER COAX BLADE and six (6) AXIS T8642 POE+ OVER COAX DEVICE for a complete 6 channel solution.</p>	\$ 1,699.00
AXIS T8648 PoE+ COAX BLADE COMP KIT	01490-001	<p>AXIS T8648 PoE+ Coax Blade Compact Kit contains one (1) AXIS T8646 PoE+ over Coax Blade and six (6) AXIS T8643 POE+ over Coax Compact for a complete 6 channel solution with improved installation and cable management as it can easily be integrated in housings and backboxes.</p>	\$ 1,699.00
USB POWER CABLE 1M	5505-661	<p>USB power cable to power our M10 cameras. Perfekt to use with AXIS M1025 as PVM. Connect camera to a TV through HDMI and use this cable to the USB port on the TV to power the camera, no need for external power supply.</p> <p>DC plug 1.35x3.5mm. Length 1M (3.3 ft). White color.</p>	\$ 14.00
AXIS OUTDOOR RJ45 CABLE 5M	5502-731	<p>Outdoor CAT6 Ethernet cable for outdoor AXIS PTZ and panoramic cameras. IP66-rated male push pull connector on one end, IP20 rated male RJ45 connector on the other end. Length: 5m (16ft). Color: black.</p>	\$ 79.00
AXIS OUTDOOR RJ45 CABLE 15M	5504-731	<p>Outdoor CAT6 Ethernet cable for outdoor AXIS PTZ and panoramic cameras. IP66-rated male push pull connector on one end, IP20 rated male RJ45 connector on the other end. Length: 15m (50ft). Color: black.</p>	\$ 149.00
AXIS Q60XX-C MULTI CONNECT CABLE 12M	5504-651	<p>Cable between AXIS Q60XX-C and connection box AXIS T8605. Lenght: 12m (39ft).</p>	\$ 249.00
AXIS CABLE 24 VDC/24-240 VAC 22M	5801-741	<p>Heavy duty power cable, 22m (72ft) in length, 3-wire, 12AWG, jacket diameter 10mm (0.4in). Suitable for outdoor installation. UL20626 up to 90°C (194°F) ambient temperature. Designed for use with AXIS Positioning Cameras and Positioning Units, such as AXIS Q8685-E. Material: TPE insulation, copper wire, PVC-free and halogen-free. Color: Black.</p>	\$ 199.00
NETWORK CABLE COUPLER INDOOR	5503-771	<p>Female/female RJ45 coupler. For indoor use. Perfect when you need to extend a pre-terminated cable.</p>	\$ 11.00

NETWORK CABLE COUPLER INDOOR SLIM	5503-272	Female/female RJ45 coupler. Slim and compact size. For indoor use. Perfect when you need to extend a pre-terminated cable.	\$ 19.00
ELECTRICAL SAFETY KIT A 120VAC	5503-521	Electrical safety kit for AXIS T98A in countries where the mains power is 120 V DC. Included products: Surge protector class 2, Fuse/main switch, terminal blocks and an intrusion door switch.	\$ 199.00
AXIS T98A15-VE MEDIA CONVERTER CABINET A (120 V AC)	5505-351	Pre-assembled T98A Surveillance cabinet with following system components: (1) Breaker and surge protection, (2), 12 VDC DIN PSU, (3)AXIS T8604 Media Converter, (4) Internal cables and mounts. Tested and verified with Axis cameras.	\$ 899.00
AXIS T98A16-VE MEDIA CONVERTER CABINET A (120 V AC)	5505-361	Pre-assembled T98A Surveillance cabinet with following system components: (1) Breaker and surge protection, (2), 12 VDC DIN PSU, (3)AXIS T8604 Media Converter, (4) Internal cables and mounts. Tested and verified with Axis cameras.	\$ 899.00
AXIS T98A17-VE MEDIA CONVERTER CABINET A (120 V AC)	5505-371	Pre-assembled T98A Surveillance cabinet with following system components: (1) Breaker and surge protection, (2), 12 VDC DIN PSU, (3)AXIS T8604 Media Converter, (4) Internal cables and mounts. Tested and verified with Axis cameras.	\$ 899.00
AXIS T98A18-VE MEDIA CONVERTER CABINET A (120 V AC)	5505-381	Pre-assembled T98A18-VE Surveillance cabinet with following system components: (1) Breaker and surge protection, (2), 12 VDC DIN PSU, (3) AXIS T8604 Media Converter, (4) Power cable and DIN clip for midspan AXIS T8124, (5) Internal cables and mounts. Tested and verified with Axis cameras.	\$ 899.00
AXIS T98A19-VE MEDIA CONVERTER CABINET A (120 V AC)	5505-391	Pre-assembled T98A Surveillance cabinet with following system components: (1) Breaker and surge protection, (2), 12 VDC DIN PSU, (3)AXIS T8604 Media Converter, (4) Internal cables and mounts. Tested and verified with Axis cameras.	\$ 899.00
ACC MAINS ADAPTOR AXIS PS24	5000-001	24VAC power adapter for outdoor use. Output max 63VA.	\$ 149.00
AXIS T8008 PS24	5801-701	24V DC power supply 250W with extended temperature (-40 to +75C (-40 to 167F)).	\$ 399.00
AXIS T8051 Power Converter AC/DC to DC	5505-051	AC/DC to DC power converter for AXIS Q35-VE, 24 V AC or 12/24 V DC input. Backbox designed to match perfectly with camera.	\$ 199.00
AXIS T8061 ETHERNET SURGE PROTECTOR	5801-641	Protect your Ethernet networks device, i.e. cameras, switches, midspans, etc..., from lighting. Protects up to 10KV surge, IP66 and UL certified.	\$ 99.00
CONNECTOR M12 MALE 4P 10PCS	5502-131	Rugged, male D-coded M12 connector compatible with AXIS M31XX-R M12 and Connector M12 Female 4P . Field installable with screw-in contacts. 10 pcs	\$ 149.00
AXIS 10-PIN PUSH-PULL SYSTEM CONN	5506-251	10-pin system connector for power, audio and I/O.	\$ 39.00

RJ45 FIELD CONNECTOR 10 PCS	01996-001	RJ45 Field Connector (10 PCS) for easy assembly in the field without the need for special tools. Due to its compact size, it has a wide compatibility with Axis devices, like AXIS P32 Series or Network Cable Coupler IP66. Ready to be used with CAT6a ethernet cabling, AWG 26-22. Suitable for IEEE 802.3af, 802.3at, 802.3bt and Axis HighPoE solution.	\$ 129.00
AXIS STEREO-TO-MONO ADAPTER	5801-681	AXIS Stereo-to-mono Adapter. Spare part to AXIS F44 Dual Audio Input Main Unit. Allows two microphones or line inputs to be connected to AXIS F44 Dual Audio Input.	\$ 29.00
AXIS POWER CABLE 24 V 7m (23ft)	02198-001	AXIS Power Cable 24V 7m (23ft) helps extending the operating temperature of AXIS Q6010 / Q6100 -E up to -50° (-58°F) when installed in extreme cold environments. The power cable requires a 24V DC mains adapter (Not included).	\$ 39.00
AXIS 30W MIDSPAN	02172-004	Single port midspan for Power over Ethernet Plus (PoE+) IEEE 802.3at Type 2 Class 4 products	\$ 79.00
AXIS SURVEILLANCE CARD 64 GB	5801-951	AXIS Surveillance Card 64 GB is a high endurance microSDXC™ card optimized for video surveillance. It has support for health status monitoring with Axis cameras. The card enables flexible edge recording solutions with de-centralized video recording, eliminating the need of an onsite server, DVR or NVR. Optimizes bandwidth usage as video is recorded onboard each camera even when bandwidth is limited or absent. Combined with Axis Zipstream technology, even high quality video or longer retention times can be used effectively. Includes SD card adapter.	\$ 59.00
AXIS SURVEILLANCE CARD 64 GB 10P	5801-961	AXIS Surveillance Card 64 GB is a high endurance microSDXC™ card optimized for video surveillance. It has support for health status monitoring with Axis cameras. The card enables flexible edge recording solutions with de-centralized video recording, eliminating the need of an onsite server, DVR or NVR. Optimizes bandwidth usage as video is recorded onboard each camera even when bandwidth is limited or absent. Combined with Axis Zipstream technology, even high quality video or longer retention times can be used effectively. Includes SD card adapter. 10pack.	\$ 569.00
AXIS SURVEILLANCE CARD 128 GB	01491-001	AXIS Surveillance Card 128 GB is a high endurance microSDXC™ card optimized for video surveillance. It has support for health status monitoring with Axis cameras. The card enables flexible edge recording solutions with de-centralized video recording, eliminating the need of an onsite server, DVR or NVR. Optimizes bandwidth usage as video is recorded onboard each camera even when bandwidth is limited or absent. Combined with Axis Zipstream technology, even high quality video or longer retention times can be used effectively. Includes SD card adapter.	\$ 99.00
AXIS SURVEILLANCE CARD 128 GB 10P	01678-001	The 10 pack variant of the AXIS Surveillance Card 128 GB, a high endurance microSDXC™ card optimized for video surveillance. It has support for health status monitoring with Axis cameras.	\$ 959.00

AXIS SURVEILLANCE CARD 256GB	02021-001	AXIS Surveillance Card 256 GB is a high endurance microSDXC™ card optimized for video surveillance. It has support for health status monitoring with Axis cameras. The card enables flexible edge recording solutions with de-centralized video recording, eliminating the need of an onsite server, DVR or NVR. Optimizes bandwidth usage as video is recorded onboard each camera even when bandwidth is limited or absent. Combined with Axis Zipstream technology, even high quality video or longer retention times can be used effectively. Includes SD card adapter.	\$ 199.00
AXIS SURVEILLANCE CARD 256GB 10PCS	02021-021	AXIS Surveillance Card 256 GB (10pcs) are high endurance microSDXC™ cards optimized for video surveillance. They have support for health status monitoring with Axis cameras. The cards enable flexible edge recording solutions with de-centralized video recording, eliminating the need of an onsite server, DVR or NVR. Optimizes bandwidth usage as video is recorded onboard each camera even when bandwidth is limited or absent. Combined with Axis Zipstream technology, even high quality video or longer retention times can be used effectively. Includes SD card adapters.	\$ 1,930.00
SURVEILLANCE HARD DRIVE 4TB	01858-001	Surveillance Hard Drive 4TB is a 3.5-inch internal drive designed and tested for 24/7 reliable video surveillance. It is optimized for high-definition continuous or event triggered recordings and high write-cycle workloads. Suitable for storage expansion of compatible appliances, it enables for flexible storage solutions. Storage needs can be estimated with AXIS Site Designer 2 and appropriate recommendation will be provided.	\$ 239.00
SURVEILLANCE HARD DRIVE 6TB	01859-001	Surveillance Hard Drive 6TB is a 3.5-inch internal drive designed and tested for 24/7 reliable video surveillance. It is optimized for high-definition continuous or event triggered recordings and high write-cycle workloads. Suitable for storage expansion of compatible appliances, it enables for flexible storage solutions. Storage needs can be estimated with AXIS Site Designer 2 and appropriate recommendation will be provided.	\$ 359.00
AXIS T8310 CONTROL BOARD	5020-001	Modular control board for professional camera and video management. AXIS T8310 Control Board is a complete control board solution which includes AXIS T8311 Joystick, AXIS T8312 Keypad and AXIS T8313 Jog Dial. Includes required USB cables inter-connecting the units and a 2 meter USB cable to the workstation. AXIS T8310 Video Surveillance Control Board is supported in ACS ver. 3.3 or later.	\$ 1,149.00
AXIS T8311 JOYSTICK	5020-101	Professional joystick for accurate control of Axis pan/tilt/zoom and dome network cameras. Connects to the workstation over USB. Features a three-axis joystick with X/Y-axis for positioning and turning knob for zoom and 6 push-buttons. Includes a 2 meter USB cable for connection to the workstation. AXIS T8311 Joystick is supported in ACS ver. 3.3 or later.	\$ 399.00

AXIS T8312 KEYPAD	5020-201	Professional 22 button keypad for quick navigation between workspaces, camera views and PTZ. Connects to the workstation over USB. Includes a 2 meter USB cable for connection to the workstation. AXIS T8312 Keypad is supported in ACS ver. 3.3 or later.	\$ 449.00
AXIS T8313 JOG DIAL	5020-301	Professional video surveillance jog dial for high precision playback, facilitating functions such as play, pause, index, image steps and fast search. 6 built-in push buttons additionally simplifies video forensics. AXIS T8313 Jog Dial is supported in ACS ver. 3.3 or later.	\$ 399.00
AXIS T8604 MEDIA CONVERTER SWITCH	5027-041	Four port media converter switch with 2 RJ45 ports and 2 SFP slots for optical fiber connection (SFP modules not included). Shelf or DIN-rail mount. Temp spec: -40°C to +75°C (-40°F to 167°F).	\$ 399.00
AXIS T8606 MEDIA CONV SWITCH 24VDC	5901-261	Four port media converter switch with 2 RJ45 ports and 2 SFP slots for optical fiber connection (SFP modules not included). Shelf or DIN-rail mount. Temp spec: -40°C to +75°C (-40°F to 167°F). 24 V DC power in.	\$ 399.00
AXIS T8331 PIR MOTION DETECTOR	5506-931	Indoor PIR detector especially made for Axis cameras to enhance motion detection. Easy plug and play connectivity to Axis I/O camera port.	\$ 39.00
AXIS T8331-E PIR MOTION DETECTOR	5506-941	Outdoor PIR detector especially made for Axis cameras to enhance motion detection. Easy plug and play connectivity to Axis I/O camera port.	\$ 129.00
AXIS T8341 PIR MOTION SENSOR	01202-004	PIR Motion Sensor for Axis Wireless I/O using Z-wave technology.	\$ 49.00
AXIS T8342 DOOR/WINDOW SENSOR	01203-004	Door/window sensor for Axis Wireless I/O using Z-wave technology.	\$ 49.00
AXIS T8343 ALERT BUTTON	01204-004	Panic button for Axis Wireless I/O using Z-wave technology.	\$ 49.00
AXIS T8344 POWER ON/OFF PLUG	01205-004	Power on/off plug for Axis Wireless I/O using Z-wave technology.	\$ 49.00
AXIS T8353A MICROPHONE 3.5MM	5032-531	AXIS T8353A Microphone 3.5mm is an omnidirectional microphone with a 3.5mm adaptor, compatible with all Axis network video products supporting a 3.5mm jack for microphone input. AXIS T8353A Microphone offers great details and resolution, the capsule has a neutral sonic character and is very natural sounding. The discreet microphone is very reliable even in demanding environments.	\$ 449.00
AXIS T8353 MOUNT	5505-041	Mounting accessory for AXIS T8353 Microphones	\$ 19.00
AXIS T8415 WIRELESS INSTALLATION TOOL	5506-231	Camera installation made easy. Battery driven Wi-Fi access point with PoE+ to camera for use with AXIS Installation application on your iOS or Android device.	\$ 599.00
AXIS T8415 WIRELESS INST TOOL KIT	5506-881	Kit including AXIS T8415 Wireless Installation Tool, one extra AXIS Installation Tool Battery 12V3.4Ah and one AXIS Installation Bag.	\$ 699.00
AXIS P55/Q60 MULTI CONN CABLE 5M	5502-491	Multi-connector cable for power, audio and I/O. Used for Indoor AXIS P55-series and Indoor Q60-series PTZ Dome Network Camera.	\$ 109.00
AXIS T8415 INSTALLATION BAG	5506-871	Durable soft bag to carry the AXIS T8415 Wireless Installation Tool, with space for extra battery, charger, network cables etc.	\$ 49.00
AXIS INSTALLATION TOOL BATTERY 12V3.4Ah	5506-551	Additional battery for AXIS T8415 Wireless Installation Tool.	\$ 99.00

ACC MAINS ADAP PS-P T-C	5502-261	Power supply PS-P T-C for AXIS Q1755 and AXIS Q7404	\$ 39.00
AXIS INSTALLATION CHARGER ADAPTOR 12V1A	5506-561	Charging adaptor for AXIS T8415 Wireless Installation Tool.	\$ 49.00
AXIS P8221	0321-004	Network I/O and audio module. Eight digital ports configurable as inputs or outputs. Two-way audio configurable to simplex, half or full duplex. Built-in pre-amp, phantom power and gain control for a balanced microphone. Line and speaker output. Serial port RS-232/422/485. Power over Ethernet enabled. Includes power supply.	\$ 349.00
AXIS T8006 PS12	5030-064	Power supply with extended temperature specification -40°C to +75°C (-40°F to +167°F) providing 12 V DC to units such as AXIS T8604 and AXIS Q7424-R.	\$ 89.00
NETWORK CABLE COUPLER IP66	5503-431	Compact IP66-rated female/female RJ45 cable coupler. Perfect when you need to extend a pre-terminated outdoor cable.	\$ 29.00
ACC MAINS ADAP PS-K TERM-CONN	5503-681	Power supply for AXIS P1311/43/44 and AXIS Q7401 as a spare part.	\$ 39.00
AXIS T8003 PS57	5029-034	Power supply for the AXIS T8640 Coax Over Ethernet Adapter. If connected to the base end COAX adapter part, it powers up the connection, the device end unit and the PoE camera and thereby removes the need for a separate midspan. Can also be connected to the device end, to secure enough power (max 30W) to the connected PoE camera (COAX cable quality/long distance).	\$ 54.00
AXIS T8007 PS24	5503-104	Indoor mains power supply. Output 24V DC 1.5A. AXIS T8007 PS24 EU and UK versions are temporarily unavailable until April 1st 2021. Orders can still be placed however shipments will start again from April 1st 2021 AXIS T8007 PS24 US version is not subject to any delivery restrictions. Orders will be shipped as usual.	\$ 69.00
AXIS T8008 PS12	5503-661	Power supply for AXIS Q60XX-C series -40 to +75C (-40 to 167F). In 90-264V AC 47-63Hz. Out 12,5V DC 85W.	\$ 399.00
AXIS T8085 PS57 500W 1U	5504-864	Power supply 500W for use with AXIS T8646 POE+ OVER COAX BLADE in a 1U rack.	\$ 1,149.00
CONNECTOR M12 FEMALE 4P 10PCS	5502-141	Rugged, female D-coded M12 connector compatible with Connector M12 male 4P, 209FD-R M12 /209MFD-R M12. Field installable with screw-in contacts. 10 pcs	\$ 149.00
AXIS T90C10 FIXED DOME IR-LED	5024-101	IR-illuminator for AXIS P334X-VE cameras. 18-56 VDC input. Operating temperature -40 °C to 55 °C (-40 °F to 131 °F). IP66-, Nema 4X rated, vandal resistant. Premounted 5m power cable cable with gaskets.	\$ 349.00
AXIS T90C20 FIXED DOME IR-LED	5024-201	IR-illuminator for AXIS P334X-VE cameras. PoE IEEE802.3af compliant. Operating temperature -40 °C to 55 °C (-40 °F to 131 °F). IP66-, Nema 4X rated, vandal resistant. Premounted 5m network cable cable with gaskets.	\$ 349.00

AXIS T90D20 IR-LED	01210-001	IR LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 36m to 144m (118 ft to 472 ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F). 12/24 V DC or AC input.	\$ 449.00
AXIS T90D20 POE IR-LED	01211-001	PoE powered IR LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 36m to 144m (118 ft to 472 ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F). PoE+ IEEE 802.3at required.	\$ 449.00
AXIS T90D25 W-LED	01215-001	White LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 25 m to 110 m (80 ft to 360 ft). Made of IK09 impact resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F). 12/24 V DC or AC input	\$ 449.00
AXIS T90D25 POE W-LED	01216-001	PoE powered white LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 25 m to 110 m (80 ft to 360 ft). Made of IK09 impact resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F). PoE+ IEEE 802.3at required.	\$ 449.00
AXIS T90D30 IR-LED	01212-001	IR LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 70m to 350m (230ft to 1150 ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F). 12/24 V DC or AC input.	\$ 799.00
AXIS T90D30 POE IR-LED	01213-001	PoE powered IR LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 70m to 350m (230ft to 1150 ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F). PoE+ IEEE 802.3at required.	\$ 799.00
AXIS T90D35 W-LED	01217-001	White LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 35m to 180m (115ft to 590ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F). 12/24 V DC or AC input.	\$ 799.00

AXIS T90D35 POE W-LED	01218-001	PoE powered white LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 35m to 180m (115ft to 590ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F).PoE+ IEEE 802.3at required.	\$ 799.00
AXIS T90D40 IR-LED	01214-001	IR LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°-140° beam angles. Beam distance ranges 105m to 500m (345ft to 1640ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F). 12/24 V DC or AC input.	\$ 1,199.00
AXIS WL LENS A 120 DEG	5505-671	Accessory lens providing 120° beam angle, beam distance 10 m (33 ft). Compatible with AXIS T90B15 W-LED.	\$ 25.00
AXIS WL LENS B 120 DEG	5505-681	Accessory lens providing 120° beam angle, beam distance is 15 m (49 ft). Compatible with AXIS T90B25 W-LED.	\$ 29.00
AXIS IR LENS B 120 DEG	5505-701	Accessory lens providing 120° beam angle, beam distance 20 m (66 ft). Compatible with AXIS T90B20 IR-LED.	\$ 29.00
AXIS WL LENS C 120 DEG	5505-691	Accessory lens providing 120° beam angle, beam distance 20 m (66 ft). Compatible with AXIS T90B35 W-LED.	\$ 34.00
AXIS IR LENS C 120 DEG	5505-711	Accessory lens compatible with AXIS T90B30 IR-LED providing 120° beam angle, beam distance 30 m (98 ft). Also compatible with AXIS T90B40 IR-LED (two lenses are required as the illuminator has two panels). The beam angle can be adjusted between 120° and 180°, with a beam distance stretching from 65 m to 45 m (213 ft to 148 ft). This sales part includes one lens.	\$ 34.00
AXIS IR LENS D 120 DEG	01235-001	Accessory lens providing 120° beam angle	\$ 39.00
AXIS T90B REMOTE CONTROL	5800-931	The remote control is compatible with all Axis T90B illuminators and provides the possibility to adjust settings of light intensity, photocell sensitivity and more conveniently from the ground level. No lift or ladder required. The remote control feature can be disabled after the installation is finalized to avoid tampering.	\$ 39.00
AXIS T90 WALL-AND-POLE MOUNT	01219-001	Mounting bracket for AXIS T90 illuminators.	\$ 39.00
AXIS T90 SINGLE BRACKET	01220-001	Mounting bracket for AXIS T90 illuminators.	\$ 49.00
AXIS T90 MULTI BRACKET	01221-001	Mounting bracket for AXIS T90 illuminators.	\$ 69.00
AXIS DOOR SWITCH A	5503-841	Intrusion door switch for AXIS T98A, connection to I/O port.	\$ 29.00
AXIS DOME INTRUSION SWITCH C	01802-001	AXIS Dome Intrusion Switch C can be placed in compatible Axis dome cameras and devices to trigger an event upon removal of the casing. Connects directly to the I/O port.	\$ 19.00
MAINS CABLE ANGL C13-OPN 0.5M	5506-244	Angled C13 mains cable for use when limited space. Open ends for installation in terminal blocks etc. Use when installing midspan into AXIS T98A Surveillance cabinet.	\$ 14.00

AXIS FIXED BOX IR ILLUMINATOR KIT A	01534-001	AXIS Fixed Box IR Illuminator Kit A for AXIS P1375-E. For mounting on AXIS P13 Series camera. Range of reach 50 m (164 ft) or more depending on the scene. Powered by AXIS P13 Series camera. Requires Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 4 midspan power for AXIS P13 Series camera.	\$ 99.00
AXIS I/O INDICATION LED 4P	01765-001	AXIS I/O Indication LED is an easy to install signaling accessory for all AXIS devices that support 12 V I/O and can be setup through the event handling of the device to address desired deterrence or privacy concerns. The LED comes with IP44 rating. Up to three LEDs could be installed with AXIS devices that support 50 mA load on their I/O ports. This product comes in a 4-pack.	\$ 69.00
AXIS CAMERA HEATER POWER SUPPLY	02040-001	AXIS Camera Heater Power Supply helps extending the operating temperature of AXIS Q6010 / Q6100 -E up to -50°C (-58°F) when installed in extreme cold environments.	\$ 99.00
AXIS D2110-VE	01564-001	AXIS D2110-VE Security Radar, 24.05–24.25 GHz, FMCW, for wall mounting outdoor. Reliable 180 degrees horizontal field of detection 24/7 with built-in analytics including classification of humans and vehicles. Complement to video surveillance enables filtering on distance, customized detection zones, and auto-tracking for PTZ cameras. Trigger events to activate camera recording, audio notification or light source for deterrence. Open API for software integration, microSD/SDHC memory card slot for edge storage, 30W PoE out to power an additional device, 4 input/output ports, 24 V DC relay port. Powered by PoE+ (IEEE 802.3at, Type 2 Class 4) or DC 8-28V. IP66, IK08 and NEMA 4. Operating conditions -40°C to 60°C (-40°F to 140°F).	\$ 1,499.00
AXIS D2050-VE	01033-001	Phased array FMCW (Frequency Modulated Continuous Wave), 24 GHz outdoor radar motion detector. 120 degrees horizontal and 5-50 meter detection range (16-164 feet). Serves as a complement to video surveillance and enables filtering on distance, customizable detection zones, and autotracking for PTZ cameras. Trigger events to activate camera recording, audio notification or light for deterrence Open API for software integration, microSD/SDHC memory card slot for edge storage, 4 input/output ports, 24 V DC relay port. Wall mount. Powered by PoE+ (IEEE 802.3at, Type 2 Class 4), IP66, IK08 and NEMA 4X Operating conditions -40°C to 60°C (-40°F to 140°F). Midspan not included	\$ 1,299.00
AXIS D8004 UNMANAGED POE SWITCH	02101-004	AXIS D8004 Unmanged PoE Switch is a 4 channel 10/100 Mbps PoE+ switch with plug & play installation. The unmanaged switch comes with a 60 W power budget and is perfect as an entry-level switch for small systems with PoE requirements.	\$ 99.00

AXIS T8504-E OUTDOOR POE SWITCH	01449-001	Outdoor 4-port managed PoE switch for surveillance applications. 4 PoE ports with up to 60W PoE per port and one SFP port for uplink. Robust metal enclosure with wide temperature range , IP67 and surge protection for demanding installations. Managed switch for remote configuration and management.	\$ 1,199.00
AXIS T8504-R INDUSTRIAL POE SWITCH	01633-001	AXIS T8504-R Industrial PoE Switch is a 4-port managed industrial PoE++ Gigabit switch. In addition, the switch is equipped with 2 x RJ45 and 2x SFP data ports that allows for extra devices to be connected. The switch uses the same intuitive administrator interface as AXIS T85 PoE Network Switch Series, is ruggedized with a wide temperature range and NEMA TS2 compliant.	\$ 699.00
AXIS T6101 AUDIO AND I/O INTERFACE	01160-001	AXIS T6101 Audio and I/O Interface enabling two-way audio and configurable supervised inputs / digital outputs for Axis cameras that do not have such functionality built-in. Powered by standard Power over Ethernet, no midspan included. Allows the connected camera to provide one stream for audio and video, without the need for any additional IP address.	\$ 99.00
AXIS T6112 AUDIO AND I/O INTERFACE	01230-001	AXIS T6112 Audio and I/O Interface combines AXIS T6101 Audio and I/O Interface with an omnidirectional microphone in a discreet casing suitable for indoor installation on wall or ceiling. Powered by standard Power over Ethernet, no midspan included. Two-way audio and configurable supervised inputs / digital outputs for Axis cameras that do not have such functionality built-in. Allows the connected camera to provide one stream for audio and video, without the need for any additional IP address.	\$ 149.00
AXIS P8221 BULK 10PCS	0321-021	AXIS P8221 in 10-pack/bulk. Cannot be sold separately as single pack. NO midspans. Power supplies not included.	\$ 3,449.00
AXIS TW1100 Clip Mount 5P	02126-001	AXIS TW1100 Clip Mount 5P 5 pack mount for the Klick Fast adaptor on the AXIS W100 Body Worn Camera. The clip mount is an easy to use, versatile mount suitable for many types of clothing.	\$ 99.00
AXIS TW1101 MOLLE Mount 5P	02127-001	AXIS TW1101 MOLLE Mount 5P. 5 pack mount for the Klick Fast adaptor on the AXIS W100 Body Worn Camera. The MOLLE mount is especially suitable for the MOLLE system found on tactical equipment and such.	\$ 69.00
AXIS TW1102 Magnet Mount 5P	02128-001	AXIS TW1102 Magnet Mount 5P 5 pack mount for the Klick Fast adaptor on the AXIS W100 Body Worn Camera. The magnet mount is a rugged, versatile mount suitable for many types of clothing	\$ 429.00

AXIS TW1103 Chest Harness Mount 5P	02129-001	AXIS TW1103 Chest Harness Mount 5P 5 pack mount for the Klick Fast adaptor on the AXIS W100 Body Worn Camera. The chest harness mount holds the camera independent of choice of clothing.	\$ 169.00
AXIS TW1200 BW MINI BULLET SENSOR	01952-001	As an accessory to the W100 Body Worn Camera the AXIS TW1200 Body Worn Mini Bullet Sensor is designed to offer a flexible recording position. It supports the Picatinny mounting system, making it compatible with many kinds of available gear, and especially suitable for helmets. AXIS TW1200 offers the same optical performance as AXIS W100 with sharp images even in challenging conditions. Mounting options are included.	\$ 199.00
AXIS TW1900 ADHESIVE PICATINNY RAIL 5P	02031-001	5 pack adhesive picatinny rail to mount the AXIS TW1200 Body Worn Mini Bullet Sensor on general equipment.	\$ 59.00
AXIS TW1901 CABLE HOLDER 5P	02030-001	5 pack replacement cable holder to securely connect the AXIS TW1200 Body Worn Mini Bullet Sensor cable to the W100 Body Worn Camera.	\$ 29.00
AXIS TW1902 LENS PROTECTOR 5P	02032-001	5 pack replacement lens protector for AXIS TW1200 Body Worn Mini Bullet Sensor.	\$ 69.00
AXIS TW1904 Body Worn Mount Flight	02191-001	Demonstration kit consisting of 3 mounts, 1 of each AXIS TW1101, AXIS TW1102 and AXIS TW1103.	\$ 149.00
AXIS W100 BODY WORN CAMERA	01722-001	AXIS W100 Body Worn Camera is an easy-to-use, lightweight and robust body worn camera with an operating time of over 12 hours at 1080p. It delivers sharp images even in challenging conditions and has dual microphones for excellent audio and noise suppression. AXIS W100 features the Klick Fast System, making it compatible with most available mounting options, the TW1100 Clip Mount is included. In addition, Axis Zipstream technology allows users to store as much footage as they require without compromising image quality. The camera also features a GPS/GNSS receiver for location data, Bluetooth Low Energy 4.1, IEEE 802.11b/g/n, and a 6-axis gyro and accelerometer. Docking stations and system controller are sold separately.	\$ 649.00
AXIS W800 SYSTEM CONTROLLER	01964-004	AXIS W800 System Controller is the central integration and management point of the body worn solution. It ensures a high speed and supervised data offloading from the cameras and has built in temporary storage. A single AXIS W800 supports up to five docking stations and 40 cameras and larger body worn systems can easily be extended with additional system controllers. Power adaptor and mounting bracket are included.	\$ 1,099.00
AXIS W700 DOCKING STATION 1 BAY	01723-004	AXIS W700 Docking Station 1 Bay charges the battery and ensures easy data offloading of a single body worn camera. Power adaptor included.	\$ 99.00
AXIS W701 DOCKING STATION 8 BAY	01724-004	AXIS W701 Docking Station 8 Bay charges the batteries and ensures easy data offloading of up to eight body worn cameras. Power adaptor included.	\$ 549.00