



MV607 SBA

Sales Proposal For:
North Carolina Sherriffs Association

Presented By:
TRIPLE T PARTS & EQUIP

Prepared For:
North Carolina Sherriffs Association
Jason Bennett
PO Box 20049
Raleigh, NC 27619-0049
(919)743 - 7433
Reference ID: MV607

Presented By:
TRIPLE T PARTS & EQUIP
104 DAISY SCOTT ROAD
ROCKY POINT NC 28457 -

(910)675-0112

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.



Model Profile
2019 MV607 SBA (MV607)

AXLE CONFIG:	4X2
APPLICATION:	Dry Van
MISSION:	Requested GVWR: 19500. Calc. GVWR: 19500 Calc. Start / Grade Ability: 27.59% / 2.45% @ 55 MPH Calc. Geared Speed: 79.7 MPH
DIMENSION:	Wheelbase: 211.00, CA: 143.90, Axle to Frame: 75.00
ENGINE, DIESEL:	{Cummins B6.7 200} EPA 2017, 200HP @ 2400 RPM, 520 lb-ft Torque @ 1600 RPM, 2600 RPM Governed Speed, 200 Peak HP (Max)
TRANSMISSION, AUTOMATIC:	{Allison 1000 HS} 5th Generation Controls, Close Ratio, 5-Speed with Overdrive, Less PTO Provision, Less Retarder, Includes Park Pawl, with 19,500-lb GVW and 26,000-lb GCW Max Omit Item (Clutch & Control)
CLUTCH:	
AXLE, FRONT NON-DRIVING:	{Meritor MFS-08-153B} I-Beam Type, 8,000-lb Capacity
AXLE, REAR, SINGLE:	{Meritor MS-17-13X-3DFL} Single Reduction, 15,500-lb Capacity, 190 Wheel Ends Gear Ratio: 4.88
CAB:	Conventional
TIRE, FRONT:	(2) 255/70R22.5 Load Range H HSR2 SA (CONTINENTAL), 565 rev/mile, 75 MPH, All-Position
TIRE, REAR:	(4) 255/70R22.5 Load Range H HSR2 SA (CONTINENTAL), 565 rev/mile, 75 MPH, All-Position
SUSPENSION, RR, SPRING, SINGLE:	Vari-Rate; 15,500-lb Capacity, with 4500 lb Auxiliary Rubber Spring
PAINT:	Cab schematic 100WP Location 1: 9219, Winter White (Std) Chassis schematic N/A

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
MV60700	Base Chassis, Model MV607 SBA with 211.00 Wheelbase, 143.90 CA, and 75.00 Axle to Frame.	5474/2935	8409
1ANA	AXLE CONFIGURATION {Navistar} 4x2	0/0	0
	<u>Notes</u> : Pricing may change if axle configuration is changed.		
1CAC	FRAME RAILS High Strength Low Alloy Steel (50,000 PSI Yield); 10.125" x 3.062" x 0.312" (257.2mm x 77.8mm x 8.0mm); 480.1" (12195mm) Maximum OAL	66/242	308
1LLD	BUMPER, FRONT Full Width, Aerodynamic, Steel; 0.142" Material Thickness	0/0	0
1WEJ	WHEELBASE RANGE 199" (505cm) Through and Including 254" (645cm)	0/0	0
2ATK	AXLE, FRONT NON-DRIVING {Meritor MFS-08-153B} I-Beam Type, 8,000-lb Capacity	0/0	0
3ADA	SUSPENSION, FRONT, SPRING Parabolic, Taper Leaf; 8,000-lb Capacity; with Shock Absorbers	0/0	0
4100	BRAKE SYSTEM, HYDRAULIC {Wabco} Split System, with Automatic Adjustment and Four Channel ABS	0/0	0
4732	DRAIN VALVE {Berg} with Pull Chain, for Air Tank	0/0	0
4GAR	BRAKE, PARKING {Bosch} DSSA Type, 12" x 3"; for Hydraulic Brake Chassis; Activated by Lever in Cab; Differential Mounted	0/0	0
4JNP	BRAKES, FRONT, HYDRAULIC DISC Quadraulic; Four 70mm Diameter Pistons	0/0	0
4NNL	BRAKES, REAR, HYDRAULIC DISC Quadraulic; Four 70mm Diameter Pistons	0/0	0
4SPK	AIR COMPRESSOR {Cummins} 18.7 CFM Capacity, with Tank for Air Source on Hydraulic Chassis, without Gauge	56/18	74
4VKV	AIR TANK LOCATION (1) Mounted Inside Left Rail, Back of Cab	0/0	0
5AAA	STEERING COLUMN Stationary	0/0	0
5CAW	STEERING WHEEL 4-Spoke; 18" Dia., Black	0/0	0
5PRG	STEERING GEAR {TRW (Ross) TAS40} Power	0/0	0
7BKY	EXHAUST SYSTEM Single, Horizontal Aftertreatment Device, Frame Mounted Under Right Rail, Back of Cab, Includes Short Horizontal Tail Pipe	0/0	0
7SCP	ENGINE EXHAUST BRAKE for Cummins ISB/B6.7/ISL/L9 Engine with Variable Vane Turbo Charger	0/0	0
8000	ELECTRICAL SYSTEM 12-Volt, Standard Equipment	0/0	0
8GXD	ALTERNATOR {Leece-Neville AVI160P2013} Brush Type; 12 Volt 160 Amp. Capacity, Pad Mount, with Remote Sense	0/0	0
8MEP	BATTERY SYSTEM {International} Maintenance-Free, (2) 12-Volt 1300CCA Total	0/0	0
8RMS	SPEAKERS Omit	0/0	0
8RMX	RADIO Omit; Includes Wiring and Antenna	0/0	0
8TKD	STOP, TURN, TAIL & B/U LIGHTS Omit Item, Does Not Omit Cable to End of Frame, DOES NOT INCLUDE LICENSE PLATE LIGHT	0/-5	-5
8VAY	HORN, ELECTRIC Disc Style	0/0	0

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
8VUX	BATTERY BOX Steel, with Plastic Cover, 25" Wide, 2 or 3 Battery Capacity, Mounted Right Side Under Cab	0/0	0
8WWJ	INDICATOR, LOW COOLANT LEVEL with Audible Alarm	0/0	0
8WZK	HEADLIGHTS Halogen; Composite Aero Design for Two Light System	0/0	0
8XAH	CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses	0/0	0
8XKL	STARTING MOTOR {Mitsubishi Electric Automotive America 90P47} 12-Volt, with Soft-Start	0/0	0
9AAB	LOGOS EXTERIOR Badges	0/0	0
9AAE	LOGOS EXTERIOR, ENGINE Badges	0/0	0
9HAD	GRILLE Chrome	0/0	0
9WAY	FRONT END Tilting, Fiberglass, with Three Piece Construction	0/0	0
10060	PAINT SCHEMATIC, PT-1 Single Color, Design 100	0/0	0
	<u>Includes</u> : PAINT SCHEMATIC ID LETTERS "WP"		
10761	PAINT TYPE Base Coat/Clear Coat, 1-2 Tone	0/0	0
10WCY	SAFETY TRIANGLES	6/0	6
11001	CLUTCH Omit Item (Clutch & Control)	0/0	0
12703	ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection	0/0	0
12EJC	ENGINE, DIESEL {Cummins B6.7 200} EPA 2017, 200HP @ 2400 RPM, 520 lb-ft Torque @ 1600 RPM, 2600 RPM Governed Speed, 200 Peak HP (Max)	0/0	0
12TSY	FAN DRIVE {Borg-Warner SA85} Viscous Type, Screw On	0/0	0
12UYE	RADIATOR Aluminum; 2-Row, Cross Flow, Over Under System, 717 SqIn Louvered, with 313 SqIn Charge Air Cooler. with In-Tank Transmission Cooler	14/-1	13
12VBR	AIR CLEANER with Service Protection Element	0/0	0
12VGM	FEDERAL EMISSIONS {Cummins B6.7} EPA, OBD and GHG Certified for Calendar Year 2018	0/0	0
12VXT	THROTTLE, HAND CONTROL Engine Speed Control; Electronic, Stationary, Variable Speed; Mounted on Steering Wheel	0/0	0
12VYP	ENGINE CONTROL, REMOTE MOUNTED - No Provision Furnished for Remote Mounted Engine Control	0/0	0
12WPV	OIL PAN 15 Quart Capacity, For Cummins ISB/B6.7 Engines	0/0	0
12WZE	EMISSION COMPLIANCE Federal, Does Not Comply with California Clean Air Idle Regulations	0/0	0
13APZ	TRANSMISSION, AUTOMATIC {Allison 1000 HS} 5th Generation Controls, Close Ratio, 5-Speed with Overdrive, Less PTO Provision, Less Retarder, Includes Park Pawl, with 19,500-lb GVW and 26,000-lb GCW Max	0/0	0
13WLN	TRANSMISSION OIL Synthetic; 20 thru 28 Pints	0/0	0
13WVS	TRANSMISSION SHIFT CONTROL T-Handle Type	0/0	0

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
13WYY	SHIFT CONTROL PARAMETERS Allison 1000 or 2000 Series Transmissions, 5th Generation Controls, Performance Programming	0/0	0
14AKE	AXLE, REAR, SINGLE {Meritor MS-17-13X-3DFL} Single Reduction, 15,500-lb Capacity, 190 Wheel Ends . Gear Ratio: 4.88	0/0	0
14VAC	SUSPENSION, RR, SPRING, SINGLE Vari-Rate; 15,500-lb Capacity, with 4500 lb Auxiliary Rubber Spring	0/0	0
15LMR	FUEL/WATER SEPARATOR {Racor 400 Series,} with Primer Pump, Includes Water-in-Fuel Sensor	2/0	2
15LMU	LOCATION FUEL/WATER SEPARATOR Mounted Outside Left Rail, 8" Back of Cab	0/0	0
15SWU	FUEL TANK Top Draw, Non-Polished Aluminum, D-Style, 16" Tank Depth, 40 US Gal (151L), with Quick Connect Outlet, Mounted Left Side, Under Cab	0/0	0
15WDG	DEF TANK 7 U.S. Gal. 26.5L Capacity, Frame Mounted Outside Left Rail, Under Cab	0/0	0
16030	CAB Conventional	0/0	0
16400	SEAT, PASSENGER Omit Item	0/0	0
16BAM	AIR CONDITIONER with Integral Heater & Defroster	56/0	56
16GDK	GAUGE CLUSTER Base Level; English with English Speedometer and Tachometer, for Hydraulic Brake Chassis, Includes Engine Coolant Temperature, Fuel and DEF Gauges, Oil Pressure Gauge, Includes 3 Inch Monochromatic Text Display	0/0	0
16HKT	IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster	0/0	0
16JXG	SEAT, FRONT BENCH {National} Full Width; Vinyl, with Fixed Mid Back	0/0	0
16SNL	MIRRORS (2) Black Heads, Brackets and Arms, 7.55" x 14.1" Flat Glass, 7.48" x 6.77" Convex Glass Both Sides	0/0	0
16VKB	CAB INTERIOR TRIM Classic, for Day Cab	0/0	0
16VLM	CAB REAR SUSPENSION Rubber Suspension, for Low Cab Height	0/0	0
16XCK	WINDOW, MANUAL (2) and Manual Door Locks, Left and Right Doors	0/0	0
16XJN	INSTRUMENT PANEL Flat Panel	0/0	0
16ZBT	ACCESS, CAB Steel, Driver & Passenger Sides, Two Steps Per Door, for use with Regular and Extended Cabs	0/0	0
27DTU	WHEELS, FRONT {Accuride 29001} DISC; 22.5x7.50 Rims, Powder Coat Steel, 5-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs	0/0	0
28DTU	WHEELS, REAR {Accuride 29001} DUAL DISC; 22.5x7.50 Rims, Powder Coat Steel, 5-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs	0/0	0
29580	WHEEL SEALS, FRONT {International} Oil-Lubricated Wheel Bearings	0/0	0
7752525421	(2) TIRE, FRONT 255/70R22.5 Load Range H HSR2 SA (CONTINENTAL), 565 rev/mile, 75 MPH, All-Position	0/0	0
7752525421	(4) TIRE, REAR 255/70R22.5 Load Range H HSR2 SA (CONTINENTAL), 565 rev/mile, 75 MPH, All-Position	0/0	0

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
	Services Section:		
40129	WARRANTY Standard for MV Series, Effective with Vehicles Built July 1, 2017 or Later, CTS-2020A	0/0	0
	Total Component Weight:	5674/3189	8863
	Dealer Inservice	0/0	0
	Total Goods Purchased:	0/0	0

The weight calculations included in this proposal are an estimate of future vehicle weight. The actual weight as manufactured may be different from the estimated weight. Navistar, Inc. shall not be liable for any consequences resulting from any differences between the estimated weight of a vehicle and the actual weight.