

NAME OF VEHICLE: F-750 84 CA DIESEL BASE SUPERCAB (X7D)
NCSA SPECIFICATION NUMBER: 91
AWARDED DEALERSHIP: Capital Ford Inc

Option Code	Option Description	MSRP	NCSA Discount Provided	Discounted Price
99E	6.7L Power Stroke V8 Turbo Diesel - 300 HP @ 2500 RPM	1995	119.7	1875.3
99X	6.7L Power Stroke V8 Turbo Diesel - 330 HP @ 2600 RPM	3495	209.7	3285.3
41H	Engine Block Heater	60	3.6	56.4
98R	Active Regen Control	205	12.3	192.7
916	Speed Limit - 65mph	0	0	0
917	Speed Limit - 70mph	0	0	0
62G	Air Compressor	1175	70.5	1104.5
94A	Engine Idle Shutdown Timer - 5 Minutes	25	1.5	23.5
94B	Engine Idle Shutdown Timer - 10 Minutes	25	1.5	23.5
94C	Engine Idle Shutdown Timer - 15 Minutes	25	1.5	23.5
94D	Engine Idle Shutdown Timer - 20 Minutes	25	1.5	23.5
41A	Transmission Power Take-Off Provision	895	53.7	841.3
64H	Wheels, Front 22.5x8.25 Aluminum, 10- Hole Alcoa Bright Polished w/Dura- Bright Seal on Both Sides	735	44.1	690.9
649	Wheels, Front 22.5x8.25 Black Wheel	30	1.8	28.2
T2A	Tires, Front Two 11R22.5H Goodyear Fuel Max RSA (497 rev/mile)	45	2.7	42.3
T2E	Tires, Front Two 11R22.5H Michelin X Multi Energy Z (501 rev/mile)	240	14.4	225.6
TCH	Tires, Front Two 255/70R22.5H Goodyear Endurance RSA (566 rev/mile)	40	2.4	37.6
T2F	Tires, Front Two 275/80R22.5G Michelin X Multi Energy Z (515 rev/mile)	190	11.4	178.6
TFA	Tires, Front Two 275/80R22.5H Hankook AH22 (510 rev/mile)	100	6	94
TRA	Tires, Front Two 295/75R22.5H Continental HA3 (514 rev/mile)	130	7.8	122.2
TDG	Tires, Front Two 295/80R22.5H Continental HSR2 SA (514 rev/mile)	210	12.6	197.4
66H	Wheels, Rear 22.5x8.25 Aluminum, 10- Hole Alcoa Bright Polished w/Dura- Bright Seal on Both Sides	830	49.8	780.2
66C	Wheels, Rear 22.5x8.25 DRW Aluminum, 10-Hole Alcoa Bright Polished w/Dura-Bright Seal on Both Sides	1470	88.2	1381.8
669	Wheels, Rear 22.5x8.25 Black Wheel	120	7.2	112.8
60Z	Wheel, Spare 22.5x8.25 White Powder Coated Steel, 10-Hole - Quantity (One only)	145	8.7	136.3
R2A	Tires, Rear Four 11R22.5H Goodyear Fuel Max RSA (497 rev/mile)	95	5.7	89.3
R2G	Tires, Rear Four 11R22.5G Goodyear Fuel Max RTD (493 rev/mile)	140	8.4	131.6
R2H	Tires, Rear Four 11R22.5H Goodyear Fuel Max RTD (493 rev/mile)	175	10.5	164.5
R2E	Tires, Rear Four 11R22.5H Michelin X Multi Energy Z (501 rev/mile)	480	28.8	451.2
RMB	Tires, Rear Four 11R22.5H Michelin X Multi D (494 rev/mile)	405	24.3	380.7
R2K	Tires, Rear Four 255/70R22.5H	140	8.4	131.6

	Goodyear Fuel Max RTD (563 rev/mile)	170	5.7	101.0
RCH	Tires, Rear Four 255/70R22.5H Goodyear Fuel Max RSA (563 rev/mile)	80	4.8	75.2
R2J	Tires, Rear Four 275/80R22.5G Michelin X Multi Energy D (514 rev/mile)	265	15.9	249.1
R2F	Tires, Rear Four 275/80R22.5G Michelin X Multi Energy Z (515 rev/mile)	375	22.5	352.5
RFA	Tires, Rear Four 275/80R22.5H Hankook AH22 (510 rev/mile)	200	12	188
RDG	Tires, Rear Four 295/80R22.5H Continental HSR2 SA (500 rev/mile)	425	25.5	399.5
RRC	Tires, Rear Four 295/75R22.5H Continental HDR2 (514 rev/mile)	310	18.6	291.4
RRA	Tires, Rear Four 295/75R22.5H Continental HA3 (514 rev/mile)	260	15.6	244.4
152	Trailer Connection Socket - 7-Way, Wired for Turn Signals Combined with Stop	100	6	94
154	Trailer Connection Socket - 7-Way, Wired for Turn Signals, Separate of Stop	100	6	94
67A	Air Brakes - Straight Truck w/Traction Control	2180	130.8	2049.2
18H	Electronic Stability Control	0	0	0
98B	Special Build Requirement - Low - 38" to 48" Center of Gravity	0	0	0
98C	Special Build Requirement - Medium - 48" to 58" Center of Gravity	0	0	0
98E	Special Build Requirement - High - 58" to 68" Center of Gravity	0	0	0
98F	Special Build Requirement - Tanker High - 58" to 68" Center of Gravity	0	0	0
98J	Special Build Requirement - Tanker Medium - 48" to 58" Center of Gravity	0	0	0
62F	Brake Chamber Spring Relocated - Required	45	2.7	42.3
62D	Air Dryer, Bendix AD/IS w/Heater	460	27.6	432.4
158	Trailer Air Brake Package	365	21.9	343.1
159	Trailer Connection Socket - 7-Way, Wired for Turn Signals Combined with Stop	100	6	94
157	Trailer Connection Socket - 7-Way, Wired for Turn Signals, Separate of Stop	100	6	94
43P	12,000 lb. Cap. Non-Driving - Dana E- 12021 - I-Beam Type	525	31.5	493.5
43D	14,000 lb. Cap. Non-Driving - Dana	1280	76.8	1203.2
61D	Taper-Leaf Springs, Parabolic - 12,000	305	18.3	286.7
61E	Taper-Leaf Springs, Parabolic - 13,200	365	21.9	343.1
61F	Taper-Leaf Springs, Parabolic - 14,000	425	25.5	399.5
15S	Front Stabilizer Bar	490	29.4	460.6
60A	Lube, Front Axle, EmGard 50W, Synthetic Oil	50	3	47
476	21,000 lb. Single Reduction - Locking - Dana / Spicer 21060D	1830	109.8	1720.2
477	21,000 lb. Dual Reduction - Open - Dana / Spicer 21065T	1405	84.3	1320.7
479	23,000 lb. Single Reduction - Open - Dana / Spicer S23-172	2320	139.2	2180.8
47P	23,000 lb. Single Reduction - Locking - Dana / Spicer S23-172D	2100	126	1974
17Y	26,000 lb. Single Reduction - Open -	2445	146.7	2298.3

77A		477.0	170.7	220.0
	Dana / Spicer S26-190			
18P	Driveshaft Upgrade	185	11.1	173.9
68R	Multi-Leaf Springs - 23,000 lb. Cap	230	13.8	216.2
68T	Multi-Leaf Springs - 31,000 lb. Cap	490	29.4	460.6
68B	Air Suspension - 21,000 lb. Cap	1140	68.4	1071.6
68F	Air Suspension - 23,000 lb. Cap	1150	69	1081
68Z	Air Suspension Dump Valve	205	12.3	192.7
68Y	Air Suspension Leveling Valve, 1 Additional Valve Provides Dual Height	330	19.8	310.2
961	Shock Absorbers, Rear - Double Acting	165	9.9	155.1
607	Lube, Rear Axle, EmGard 75W-90, Synthetic Oil	100	6	94
X4E	4.63 Axle Ratio	0	0	0
X4F	4.78 Axle Ratio	0	0	0
X4G	4.88 Axle Ratio	0	0	0
X5F	5.25 Axle Ratio	0	0	0
X5B	5.29 Axle Ratio	0	0	0
X5D	5.57 Axle Ratio	0	0	0
X6A	6.14 Axle Ratio	0	0	0
X6B	6.17 Axle Ratio	0	0	0
X6D	6.50 Axle Ratio	0	0	0
X6E	6.83 Axle Ratio	0	0	0
X48	4.88/6.65 Two-Speed Axle Ratios	0	0	0
X52	5.29/7.21 Two-Speed Axle Ratios	0	0	0
X65	6.50/8.87 Two-Speed Axle Ratios	0	0	0
197WB	179" Wheelbase/84" CA/49" AF/267"	85	5.1	79.9
203 WB	203" Wheelbase/108" CA/70" AF/312"	165	9.9	155.1
215WB	215" Wheelbase/120" CA/75" AF/329"	320	19.2	300.8
221WB	221" Wheelbase/126" CA/75" AF/335"	375	22.5	352.5
233WB	233" Wheelbase/138" CA/81" AF/535"	390	23.4	366.6
239WB	239" Wheelbase/144" CA/81" AF/359"	580	34.8	545.2
245WB	245" Wheelbase/150" CA/87" AF/371"	775	46.5	728.5
251WB	251" Wheelbase/156" CA/87" AF/377"	770	46.2	723.8
263WB	263" Wheelbase/168" CA/100" AF/402"	780	46.8	733.2
281WB	281" Wheelbase/186" CA/120" AF/440"	885	53.1	831.9
536	Single Channel - Straight 'C' 14.18 SM, 120,000 PSI	365	21.9	343.1
538	Single Channel - Straight 'C' 16.98 SM, 120,000 PSI	650	39	611
539	Single Channel - Straight 'C' 20.11 SM, 120,000 PSI	1075	64.5	1010.5
41R	Outer "C" Channel Reinforcement - 120,000 PSI	1160	69.6	1090.4
532	Frame Extension, Front - Integral 20" In Front of Grille	490	29.4	460.6
765	Bumper, Front - Full Width, Chrome Plated Steel - (Included in (90E) Exterior Appearance Group)	490	29.4	460.6
767	Bumper, Front - Swept Back, Painted Steel	345	20.7	324.3
76X	Bumper, Front - Delete - Also Deletes Mounting Brackets	-135	-8.1	-126.9
76F	3" Front Bumper Extension	175	10.5	164.5
76Y	Tow Hooks - Delete	-70	-4.2	-65.8
18D	Special Rating GVWR - Limited to 25,999 lb. GVWR	120	7.2	112.8
18G	Special De-Rating GVWR - Limited to 33,000 lb. GVWR	120	7.2	112.8
86C	Chrome Grille Surround	245	14.7	230.3
86B	Grille, Fixed - Black/Gray	125	7.5	117.5
19D	Frame Rail Drill #3	50	3	47
91B	Back of Cab, Right Side Outlet, Torpedo-Style	0	0	0

91D	Under Cab, Vertical Outlet, Right Side, Switchback-Style - Intrudes 2" into clean CA	715	42.9	672.1
65F	Fuel Tank - 115 Gallon Rectangular - Aluminum - LH 65-gal, RH 50-gal	915	54.9	860.1
17D	Dual Heavy Duty Alternators - 357 Amp Capacity - 200 & 157 amp Denso SC5/SC2	855	51.3	803.7
17A	Extra Heavy Duty Alternator - 12-Volt, 240 Amps	410	24.6	385.4
55M	Jump Start Stud - Remote Mounted	90	5.4	84.6
63B	Battery - Two 900 CCA, 1800 Total, Includes Steel Battery Box	60	3.6	56.4
63D	Battery - Three 900 CCA, 2700 Total, Includes Steel Battery Box	250	15	235
63Y	Battery - Temporary Mount for Truck Chassis	235	14.1	220.9
164	Roof Marker/Clearance Lights - Clear Lenses, 5 Lights (Replaces Standard Amber Lenses)	30	1.8	28.2
16X	Roof Marker/Clearance Lights - Delete	0	0	0
59C	Body Builder Wiring - At End of Frame, Combined - (ILO Standard - Back of Cab Combined)	135	8.1	126.9
59D	Body Builder Wiring - At Back of Cab, Separate - (ILO Standard - Back of Cab Combined)	70	4.2	65.8
59E	Body Builder Wiring - At End of Frame, Separate - (ILO Standard - Back of Cab Combined)	135	8.1	126.9
17M	Back-Up Alarm - Electric, 102 dBA	110	6.6	103.4
962	Daytime Running Lamps	45	2.7	42.3
86M	Upfitter Interface Module	320	19.2	300.8
55X	Tail Light Delete	0	0	0
16V	Voltmeter	100	6	94
88B	30/0/30 Fixed Driver & Fixed Passenger w/Consolette - Cloth	125	7.5	117.5
881	30/70 Fixed Driver & Fixed 2- Passenger Bench - Vinyl	350	21	329
882	30/70 Fixed Driver & Fixed 2- Passenger Bench - Cloth	470	28.2	441.8
88C	30/0/0 Fixed Driver only - Vinyl	-120	-7.2	-112.8
88D	30/0/0 Fixed Driver only - Cloth	0	0	0
88Y	40/20/40 Fixed Driver & Fixed Passenger w/Unique 20% Fold-Down Console - Vinyl	420	25.2	394.8
88Z	40/20/40 Fixed Driver & Fixed Passenger w/Unique 20% Fold-Down Console - Cloth	545	32.7	512.3
87X	Rear Bench - Delete	-120	-7.2	
87H	Driver Assist Technology Package. Hydraulic Brake	1410	84.6	1325.4
87A	Driver Assist Technology Package (w/Bendix Wingman Advanced). Air Brake	3050	183	2867
90A	Appearance Group	735	44.1	690.9
90P	Power Equipment Group	470	28.2	441.8
92S	Window, Rear - Sliding	125	7.5	117.5
57N	Air Conditioning Delete	-100	-6	-94
86H	Rapid-Heat Supplemental Cab Heater	610	36.6	573.4
96C	Pull Out Cup Holder For Two Cups - Instrument Panel Mounted	30	1.8	28.2
55D	110 A/C Outlet - in Lower Center Finish	100	6	94

Code	Description	Price	Unit Price	Total Price
	Panel			
214	4 Speaker Option for 588 Radio	30	1.8	28.2
58P	Radio Prep Package	0	0	0
58B	Radio Delete Package	-60	-3.6	-56.4
85B	Keyed Alike - Not Available with Anti-Theft System, Requires Multiple-Unit Order	45	2.7	42.3
85L	Keyed Alike - Option 1 - Not Available with Anti-Theft System, Requires Multiple-Unit Order	45	2.7	42.3
85M	Keyed Alike - Option 2 - Not Available with Anti-Theft System, Requires Multiple-Unit Order	45	2.7	42.3
85N	Keyed Alike - Option 3 - Not Available with Anti-Theft System, Requires Multiple-Unit Order	45	2.7	42.3
85P	Keyed Alike - Option 4 - Not Available with Anti-Theft System, Requires Multiple-Unit Order	45	2.7	42.3
85A	SecuriLock Passive Anti-Theft System	120	7.2	112.8
85K	Remote Keyless Entry w/2 Key Fobs	195	11.7	183.3
90M	Interior Rear View Mirror	75	4.5	70.5
94T	Hidden Fuse for Odometer Tamper-Proofing	30	1.8	28.2
90E	Exterior Appearance Group	730	43.8	686.2
59A	Horn, Air - Black, Single Trumpet	90	5.4	84.6
54M	Mirrors, Dual - Heated Rectangular, XL2020 - 96" Width	85	5.1	79.9
54P	Mirrors, Dual - Heated & Motorized Rectangular, XL2020 - 96" Width	245	14.7	230.3
54B	Mirrors, Dual - Rectangular, XL2020 - 96" Width w/Chrome Cap	60	3.6	56.4
54N	Mirrors, Dual - Heated Rectangular, XL2020 - 96" Width w/Chrome Cap	120	7.2	112.8
54A	Mirrors, Dual - Heated & Motorized Rectangular, XL2020 - 96" Width w/Chrome Cap	305	18.3	286.7
54J	Mirrors, Dual - Rectangular, XL2020 - 102" Width	30	1.8	28.2
54C	Mirrors, Dual - Heated Rectangular, XL2020 - 102" Width	90	5.4	84.6
54R	Mirrors, Dual - Heated & Motorized Rectangular, XL2020 - 102" Width	275	16.5	258.5
54D	Mirrors, Dual - Rectangular, XL2020 - 102" Width w/Chrome Cap	90	5.4	84.6
54E	Mirrors, Dual - Heated Rectangular, XL2020 - 102" Width w/Chrome Cap	150	9	141
54K	Mirrors, Dual - Heated & Motorized Rectangular, XL2020 - 102" Width w/Chrome Cap	335	20.1	314.9
54F	Mirrors, Trailer Tow, Powered - Sail Mount - w/Power Telescoping & Power Folding	365	21.9	343.1
63F	Aux Spot Mirrors - Front Fender Mounted - (2) Driver Side and Passenger Side	225	13.5	211.5
63G	Aux Spot Mirror - Front Fender Mounted - (1) Passenger Side Only	120	7.2	112.8
165	Mud Flap Holder Without Flaps	95	5.7	89.3
166	Mud Flap Holder With Flaps	155	9.3	145.7
19A	Ambulance Prep Pkg w/Special Emissions	1285	77.1	1207.9
19E	Fire/Rescue Prep Pkg w/EPA Special	1285	77.1	1207.9

191	Emissions	1209	11.1	1207.9
19B	Beverage Delivery Package	60	3.6	56.4
SP101	Monotone Special Paint (Minimum Quantity 3)	814	48.84	765.16
SPF	Special Paint Formulation (Minimum Quantity 3)	1000	60	940
YCX	182 Wheelbase, 87 CA	662	39.72	622.28
YCZ	100 inch AF 200 inch WB	556	33.36	522.64
YDH	BlackTransmission Oil Cooler	122	7.32	114.68
YDM	FLO THRU VALVE TIRE	17	1.02	15.98